



Image shown may not reflect actual package.

PRIME

**320 e kW 400 kVA
60 Hz 1800 rpm 480 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

- Low Fuel consumption

UL 2200

- UL 2200 listed packages available. Certain restrictions may apply. Consult with your Cat® Dealer.

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

COMPLETE, READY-TO-RUN SYSTEM

- Fully configured generator set
- Full range of attachments and options available

ENCLOSURES (optional)

- Weather protective and sound attenuated

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

CAT® 3406C TA DIESEL ENGINE

- High efficiency, four-stroke-cycle engine designed for thousands of trouble-free hours of operation
- Field-proven in thousands of applications

CAT GENERATOR

- Matched to the performance and output characteristics of Cat engines
- Load adjustment module provides engine relief upon load impact and improves load acceptance and recovery time
- UL 1446 Recognized Class H insulation

CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

PRIME 320 kW 400 kVA

60 Hz 1800 rpm 480 Volts



FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> • Light duty air cleaner 	<input type="checkbox"/> Regular duty canister style, single stage with service indicator <input type="checkbox"/> Dual element <input type="checkbox"/> Heavy-duty and Muffler <input type="checkbox"/> Air Inlet Shut-off
Cooling	<ul style="list-style-type: none"> • Coolant drain line with valve • Fan and belt guards • Radiator with guard • Coolant drain line with valve • Fan and belt guards • Cat® Extended Life Coolant* • Coolant level sight gauge 	<input type="checkbox"/> Low coolant level shutdown <input type="checkbox"/> Duct flange
Exhaust	<ul style="list-style-type: none"> • Stainless steel exhaust flex • ANSI style outlet flange, gasket, bolts and mating weld flange; shipped loose 	<input type="checkbox"/> 10 DBA Industrial muffler <input type="checkbox"/> 25 DBA Residential muffler <input type="checkbox"/> Critical muffler <input type="checkbox"/> Flexible fitting <input type="checkbox"/> Elbow kit <input type="checkbox"/> Throughwall Installation kit <input type="checkbox"/> Manifold and Turbo Guard
Fuel	<ul style="list-style-type: none"> • Fuel priming pump • Fuel pressure gauge • Primary and secondary fuel filters • Flexible fuel lines 	<input type="checkbox"/> Water separator <input type="checkbox"/> Fuel level switch <input type="checkbox"/> Flexible fuel lines <input type="checkbox"/> Manual or auto fuel pumps <input type="checkbox"/> Single wall tank bases
Generator	<ul style="list-style-type: none"> • Three phase sensing • Class H insulation • VR6 3-phase sensing voltage regulator with load adjustment module • IP23 Protection • Circuit Breaker IEC, 3-pole • Segregated L.V. (AC/DC) wiring panel 	<input type="checkbox"/> Anti-condensation heater <input type="checkbox"/> Permanent Magnet excitation <input type="checkbox"/> RFI Filter <input type="checkbox"/> Coastal Protection <input type="checkbox"/> Terminal strip connection <input type="checkbox"/> Oversize generator <input type="checkbox"/> Circuit breaker, UL and IEC Listed, 3 & 4-pole with shunt trip <input type="checkbox"/> Multiple breaker capability <input type="checkbox"/> Digital Voltage Regulator
Governor	<ul style="list-style-type: none"> • Hydra-mechanical (3% speed regulation) 	<input type="checkbox"/> Electronic isochronous governor <input type="checkbox"/> Load sharing module
Control Panels	<ul style="list-style-type: none"> • EMCP 4.1 • User Interface panel (UIP) - rear mount (standard) • Emergency Stop Pushbutton 	<input type="checkbox"/> EMCP 4.2 <input type="checkbox"/> Local & remote annunciator modules <input type="checkbox"/> Load share module <input type="checkbox"/> Discrete I/O module <input type="checkbox"/> Generator temperature monitoring & protection
Lube	<ul style="list-style-type: none"> • Lubricating oil and filter • Oil drain line with valve piped to edge of base • Fumes disposal piped to front of radiator 	<input type="checkbox"/> Manual sump pump <input type="checkbox"/> Oil temperature sensor
Mounting	<ul style="list-style-type: none"> • Narrow integral fuel tank base (950L) • Linear vibration isolators between base and engine-generator 	<input type="checkbox"/> Narrow base <input type="checkbox"/> Wide Base <input type="checkbox"/> Lifting arch <input type="checkbox"/> Oil field skid base
Starting/Charging	<ul style="list-style-type: none"> • 45 amp charging alternator • 24 volt starting motor • Batteries with rack and cables • Safety shutoff protection 	<input type="checkbox"/> Battery chargers (5 or 10 amp) <input type="checkbox"/> Oversize batteries <input type="checkbox"/> Battery disconnect switch <input type="checkbox"/> Ether starting aid <input type="checkbox"/> Jacket water heater
General		<input type="checkbox"/> Enclosures - sound attenuated, weather protective <input type="checkbox"/> EU Certificate of Conformance (CE)

PRIME 320 kW 400 kVA

60 Hz 1800 rpm 480 Volts



SPECIFICATIONS

CAT GENERATOR

Frame size..... LC6114B
Excitation..... Self Excitation
Pitch..... 0.6667
Number of poles..... 4
Number of bearings..... Single bearing
Number of Leads..... 012
Insulation..... UL 1446 Recognized Class H with tropicalization and antiabrasion
- Consult your Caterpillar dealer for available voltages
IP Rating..... IP23
Alignment..... Pilot Shaft
Overspeed capability..... 125
Wave form Deviation (Line to Line)..... 002.00
Voltage regulator..... Three phase sensing
Voltage regulation..... Less than +/- 1/2% (steady state)
Less than +/- 1% (no load to full load)
Telephone influence factor..... Less than 50
Harmonic Distortion..... Less than 5%

CAT DIESEL ENGINE

3406C TA, I-6, 4-Stroke Water-cooled Diesel
Bore..... 137.20 mm (5.4 in)
Stroke..... 165.10 mm (6.5 in)
Displacement..... 14.64 L (893.39 in³)
Compression Ratio..... 14.5:1
Aspiration..... TA
Governor Type..... Hydra-mechanical

CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- kW, kVA, kVAR, kW-hr, %kW, PF (4.2 only)

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32) (4.2 only)
- Reverse reactive power (kVA) (32RV)
- Overcurrent (50/51)

Communications:

- Four digital inputs (4.1)
- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU) (4.2 only)
- Accessory module data link (4.2 only)
- Serial annunciator module data link (4.2 only)
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

PRIME 320 kW 400 kVA

60 Hz 1800 rpm 480 Volts



TECHNICAL DATA

Open Generator Set - - 1800 rpm/60 Hz/480 Volts	DM2270	
Low Fuel Consumption		
Generator Set Package Performance		
Genset Power rating @ 0.8 pf	400 kVA	
Genset Power rating with fan	320 kW	
Fuel Consumption		
100% load with fan	91.6 L/hr	24.2 Gal/hr
75% load with fan	69.8 L/hr	18.4 Gal/hr
50% load with fan	50.1 L/hr	13.2 Gal/hr
Cooling System¹		
Air flow restriction (system)	0.12 kPa	0.48 in. water
Air flow (max @ rated speed for radiator arrangement)	684 m ³ /min	24155 cfm
Engine Coolant capacity with radiator/exp. tank	57.8 L	15.3 gal
Engine coolant capacity	20.8 L	5.5 gal
Radiator coolant capacity	37.0 L	9.8 gal
Inlet Air		
Combustion air inlet flow rate	25.2 m ³ /min	889.9 cfm
Exhaust System		
Exhaust stack gas temperature	544.0 °C	1011.2 °F
Exhaust gas flow rate	72.1 m ³ /min	2546.2 cfm
Heat rejection to aftercooler	31 kW	1763 Btu/min
Exhaust flange size (internal diameter)	152.4 mm	6.0 in
Exhaust system backpressure (maximum allowable)	6.7 kPa	26.9 in. water
Heat rejection		
Heat rejection to coolant (total)	210 kW	11943 Btu/min
Heat rejection to exhaust (total)	341 kW	19393 Btu/min
Heat rejection to atmosphere from engine	73 kW	4152 Btu/min
Heat rejection to atmosphere from generator	21.9 kW	1245.5 Btu/min
Alternator²		
Motor starting capability @ 30% voltage dip	880 skVA	
Frame	LC6114B	
Temperature Rise	105 °C	189 °F
Lube System		
Sump refill with filter	38.0 L	10.0 gal
Emissions³		
NOx g/hp-hr	7.44 g/hp-hr	
CO g/hp-hr	2.35 g/hp-hr	
HC g/hp-hr	.08 g/hp-hr	
PM g/hp-hr	.654 g/hp-hr	

¹ For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

² UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40°C ambient per NEMA MG1-32.

³ Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

PRIME 320 kW 400 kVA

60 Hz 1800 rpm 480 Volts



RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC, 98/37/EC, 2004/108/EC

Prime - Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated kW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year. Prime power in accordance with ISO3046. Prime ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the alarm temperature.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions. **Fuel rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

PRIME 320 kW 400 kVA

60 Hz 1800 rpm 480 Volts



DIMENSIONS

Package Dimensions		
Length	4264.3 mm	167.89 in
Width	1110.0 mm	43.7 in
Height	2150.0 mm	84.65 in
Weight	3465 kg	7,639 lb

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #2923096).

Performance No.: DM2270

Feature Code: 406DEK8

Gen. Arr. Number: 2351203

Source: European Sourced

June 10 2011

17787935

www.Cat-ElectricPower.com

© 2011 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.