DIESEL GENERATOR SET





Image shown may not reflect actual package.

STANDBY 2500 ekW 3125 kVA 60 Hz 1800 rpm 12 470 Volts

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

 EPA Certified for Stationary Emergency Application (EPA Tier 2 emissions levels)

DESIGN CRITERIA

 The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

SINGLE-SOURCE SUPPLIER

 Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

CAT® 3516C-HD TA DIESEL ENGINE

- · Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

CAT HV GENERATOR

- Matched to the performance and output characteristics of Cat engines
- Single point access to accessory connections
- UL 1446 Recognized Class F insulation

CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

SEISMIC CERTIFICATION

- Seismic Certification available
- Anchoring details are site specific, and are dependent on many factors such as generator set size, weight, and concrete strength.
 IBC Certification requires that the anchoring system used is reviewed and approved by a Professional Engineer
- Seismic Certification per Applicable Building Codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, CBC 2007
- Pre-approved by OSHPD and carries an OSP-0084-10 for use in healthcare projects in California

60 Hz 1800 rpm 12 470 Volts



FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	Single element canister type air cleaner	[] Dual element & heavy duty air cleaners
	Service indicator	[] Air inlet adapters & shut-off
Cooling	Radiator with guard Coolant drain line with valve Fan and belt guards	[] Radiator duct flange
	Cat® Extended Life Coolant	
Exhaust	Dry exhaust manifold Flanged faced outlets	[] Mufflers and Silencers [] Stainless steel exhaust flex fittings [] Elbows, flanges, expanders & Y adapters
Fuel	Secondary fuel filters Fuel priming pump Flexible fuel lines Fuel cooler*	[] Water separator [] Duplex fuel filter
Generator	Cat digital voltage regulator (CDVR) with kVAR/PF control, 3-phase sensing Winding temperature detectors Anti-condensation heaters	[] Oversize & premium generators [] Bearing temperature detectors
Power Termination	Bus bar (NEMA mechanical lug holes) Right hand cable entry Top or bottom cable entry	[] Left hand cable entry
Governor	• ADEM™ 3	[] Load share module
Control Panels	• EMCP 4.2 Genset controller	[] Digital I/O Module [] Generator temperature monitoring & protection
Lube	Lubricating oil and filter Oil drain line with valves Fumes disposal Gear type lube oil pump	[] Oil level regulator [] Deep sump oil pan [] Electric & air prelube pumps [] Manual prelube with sump pump [] Duplex oil filter
Mounting	Rails - engine / generator / radiator mounting Rubber anti-vibration mounts (shipped loose)	[] Spring-type vibration isolator [] IBC Isolators
Starting/Charging	• 24 volt starting motor(s) • Batteries with rack and cables • Battery disconnect switch	[] Battery chargers [] Charging alternator [] Oversize batteries [] Ether starting aid [] Heavy duty starting motors [] Barring device (manual) [] Air starting motor with control & silencer [] Jacket water heater
General	Right-hand service Paint - Caterpillar Yellow except rails and radiators are gloss black SAE standard rotation Flywheel and flywheel housing - SAE No. 00	[] UL 2200 [] CSA certification [] CE Certificate of Conformance [] Seismic Certification per Applicable Building Codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, CBC 2007

60 Hz 1800 rpm 12 470 Volts



SPECIFICATIONS

CAT GENERATOR

Cat HV Generator Excitation......Permanent Magnet Number of poles.....4 Number of bearings......2 Number of Leads......006 Insulation..... Class H with tropicalization and antiabrasion - Consult your Caterpillar dealer for available voltages IP Rating.....IP23 Alignment......Closed Coupled Overspeed capability......125 Wave form Deviation (Line to Line)......002.00 Voltage regulator......3 Phase sensing with volts/Hz Voltage regulation.....Less than +/- 1/2% (steady state) Less than +/- 1/2% (w/3% speed change)

CAT DIESEL ENGINE

3516C-HD ATAAC, V-16, 4-5	Stroke Water-cooled Diesel
Bore	170.00 mm (6.69 in)
Stroke	215.00 mm (8.46 in)
Displacement	78.08 L (4764.73 in ³)
Compression Ratio	14.7:1
Aspiration	TA
Fuel System	Electronic unit injection
Governor Type	ADEM3

CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- ekW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32)
- Reverse reactive power (kVAr) (32RV)
- Overcurrent (50/51)

Communications:

- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

60 Hz 1800 rpm 12 470 Volts



TECHNICAL DATA

Open Generator Set 1800 rpm/60 Hz/12 470 Volts	DM8266	
EPA Certified for Stationary Emergency Application		
(EPA Tier 2 emissions levels)		
Generator Set Package Performance		
Genset Power rating @ 0.8 pf	3125 kVA	
Genset Power rating with fan	2500 ekW	
Fuel Consumption		
100% load with fan	656.8 L/hr	173.5 Gal/hr
75% load with fan	510.8 L/hr	134.9 Gal/hr
50% load with fan	372.4 L/hr	98.4 Gal/hr
Cooling System ¹		
Air flow restriction (system)	0.12 kPa	0.48 in. water
Air flow (max @ rated speed for radiator arrangement)	2800 m³/min	98881 cfm
Engine Coolant capacity with radiator/exp. tank	504.0 L	133.1 gal
Engine coolant capacity	233.0 L	61.6 gal
Radiator coolant capacity	271.0 L	71.6 gal
Inlet Air		<u> </u>
Combustion air inlet flow rate	204.2 m³/min	7211.3 cfm
Exhaust System		
Exhaust stack gas temperature	490.7 ° C	915.3 ° F
Exhaust gas flow rate	554.5 m³/min	19582.0 cfm
Exhaust flange size (internal diameter)	203.2 mm	8.0 in
Exhaust system backpressure (maximum allowable)	6.7 kPa	26.9 in. water
Heat Rejection		
Heat rejection to coolant (total)	826 kW	46975 Btu/min
Heat rejection to exhaust (total)	2502 kW	142288 Btu/min
Heat rejection to aftercooler	786 kW	44700 Btu/min
Heat rejection to atmosphere from engine	161 kW	9156 Btu/min
Heat rejection to atmosphere from generator	106.9 kW	6079.4 Btu/min
Alternator ²		
Motor starting capability @ 30% voltage dip	4478 skVA	
Frame	2770	
Temperature Rise	130 ° C	234 ° F
Lube System		
Sump refill with filter	466.0 L	123.1 gal
Emissions (Nominal) ³		
NOx g/hp-hr	5.32 g/hp-hr	
CO g/hp-hr	.42 g/hp-hr	
HC g/hp-hr	.1 g/hp-hr	
PM g/hp-hr	.037 g/hp-hr	

¹ For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

² Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics.

Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

60 Hz 1800 rpm 12 470 Volts



RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC, 98/37/EC, 2004/108/EC

Standby - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions. Fuel rates are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

60 Hz 1800 rpm 12 470 Volts



DIMENSIONS

Package Dimensions			
Length	Information not		
Width	available at this time.		
Height			

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #).

Performance No.: DM8266

Feature Code: 516DE6Q

Gen. Arr. Number: 3111156

Source: U.S. Sourced

November 06 2012

www.Cat-ElectricPower.com

2012 Caterpillar All rights reserved.

Materials and specifications are subject to change without notice. The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

6