



3508 Industrial Engine

578 bkW/775 bhp @ 1800 rpm




Image shown may not reflect
actual engine

CAT® ENGINE SPECIFICATIONS

V-8, 4-Stroke-Cycle Diesel

Bore..... 170.0 mm (6.69 in)
Stroke..... 190.0 mm (7.48 in)
Displacement..... 34.53 L (2,107.15 in³)
Aspiration..... Turbocharged / Aftercooled
Compression Ratio..... 13.0:1
Rotation (from flywheel end)..... Counterclockwise
Capacity for Liquids
Cooling System..... 102.7 L (27.1 gal)
Lube Oil System..... 424.0 L (112.0 gal)
Engine Weight, Net Dry (approximate).. 4,467 kg (9,848 lb)

FEATURES

EMISSIONS

Non-certified rating.

SINGLE SOURCE SUPPLIER

Caterpillar

- Casts engine blocks, heads, cylinder liners, and flywheel housings
- Machines critical components
- Assembles complete engine

Ownership of these manufacturing processes enables Caterpillar to produce high quality, dependable product.

Factory-designed systems built at Caterpillar ISO 9001:2000 certified facilities.

TESTING

- Prototype testing on every model
- proves computer design
 - verifies system torsional stability
 - functionality tests every model

Every Caterpillar engine is dynamometer tested under full load to ensure proper engine performance.

FULL RANGE OF ATTACHMENTS

Wide range of bolt-on system expansion attachments, factory designed and tested

UNMATCHED PRODUCT SUPPORT OFFERED THROUGH WORLDWIDE CATERPILLAR DEALER NETWORK

More than 1,500 dealer outlets.

Caterpillar factory-trained dealer technicians service every aspect of your industrial engine.

99.7% of parts orders filled within 24 hours worldwide.

Caterpillar parts and labor warranty.

Preventive maintenance agreements available for repair before failure options.

Scheduled Oil Sampling program matches your oil sample against Caterpillar set standards to determine:

- internal engine component condition
- presence of unwanted fluids
- presence of combustion by-products

WEB SITE

For all your industrial power requirements, visit www.cat-industrial.com.



STANDARD ENGINE EQUIPMENT

578 bkW/775 bhp @ 1800 rpm

Air Inlet System

Aftercooler core, corrosion resistant coated (air side), Air cleaner, regular duty with service indicators, Turbocharger, rear mounted, jacket water aftercooled

Control System

Governor, RH, 3161 with self contained synthetic oil sump, air-fuel ratio control, mechanical speed control, without torque control, Governor control, positive locking

Cooling System

Thermostats and housing for conventional core radiator, Jacket water pump, gear driven, centrifugal

Exhaust System

Exhaust manifold, dry

Flywheels and Flywheel Housings

Flywheel, SAE No. 0, 151 teeth, Flywheel housing, SAE No. 0, SAE standard rotation

Fuel System

Fuel filter, with service indicators, cartridge type with RH service, Fuel transfer pump

Instrumentation

Instrument Panel, RH, Engine oil pressure gauge, Fuel pressure gauge, Oil filter differential gauge, Jacket water temperature gauge, Service meter, electric, Tachometer

Lube System

Crankcase breather, top mounted, Oil cooler, Oil filler and dipstick, RH, Oil pump, Oil filter, cartridge type with RH service, Shallow oil pan, Fumes disposal (not installed)

Mounting System

Rails, mounting, engine length, 254 mm (10 in), industrial-type, C-channel. Included on selected top level engines.

Power Take-Offs

Accessory drive, upper RH, Front housing, single sided

Protection System

Junction box, Manual shutoff, RH, Safety shutoff protection, energized to shutdown, Low oil pressure, low idle 69 kPa (10 psi); high idle 207 kPa (30 psi), Water temperature, Overspeed, 3161 governor solenoid energized to shutdown

Starting System

Starting switch

General

Paint, Caterpillar Yellow,
Vibration damper and guard,
Lifting eyes




3508 Industrial Engine

PERFORMANCE CURVES

578 bkW/775 bhp @ 1800 rpm

IND - A (Continuous) - TM3519-09



Engine Speed rpm	Engine Power kW	Torque N·m	BSFC g/kW-hr	Fuel Rate L/hr
1800	578	3066	215.8	148.7
1700	552	3101	214.1	140.9
1600	525	3133	213.1	133.3
1500	497	3163	212.9	126.0
1400	466	3180	215.3	119.3
1300	432	3170	221.1	113.7




3508 Industrial Engine

PERFORMANCE CURVES

578 bkW/775 bhp @ 1800 rpm

IND - A (Continuous) - TM3519-09



English

Engine Speed rpm	Engine Power bhp	Engine Torque lb·ft	BSFC lb/bhp-hr	Fuel Rate gal/hr
1800	775	2261	.355	39.3
1700	740	2287	.352	37.2
1600	704	2311	.350	35.2
1500	666	2333	.350	33.3
1400	625	2345	.354	31.5
1300	579	2338	.363	30.0



RATINGS AND CONDITIONS


578 bkW/775 bhp @ 1800 rpm

IND - A (Continuous) Continuous heavy duty service where the engine is operated at maximum power and speed up to 100% of the time without interruption or load cycling. Time at full load can be up to 100% of the duty cycle. Typical service examples are: pumping, ventilation, customer specs.

Engine Performance Engine performance is corrected to inlet air standard conditions of 99 KPA (29.31 IN HG) dry barometer and 25 deg C (77 deg F) temperature. These values correspond to the standard atmospheric pressure and temperature as shown in SAE J1995.

Performance measured using a standard fuel with fuel gravity of 35 degrees API having a lower heating value of 42,780 KJ/KG (18,390 BTU/LB) when used at 29 DEG (84.2 DEG F) where the density is 838.9 G/L (7.001 LB/US GAL).

The corrected performance values shown for Caterpillar engines will approximate the values obtained when the observed performance data is corrected to SAE J1995, ISO 3046-2 and 8665 and 2288 and 9249 and 1585, EEC 80/1269 and DIN 70020 standard reference conditions.



Engine Dimensions

(1) Length	2135.8 mm (84.09 in)
(2) Width	1703.0 mm (67.05 in)
(3) Height	1715.8 mm (67.55 in)

Note: Do not use for installation design. See general dimension drawings for detail (Drawing # 1654034).

Performance Number: TM3519-09

Feature Code: 508DI01 Arr. Number: 4W0280

Materials and specifications are subject to change without notice.
16304934

© 2012 Caterpillar

All rights reserved.

The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.