CB534D, XW, CB564D

Vibratory Asphalt Compactors

"Heavy Hitter, Big Production"



Reliable Compaction Performance

- Exceptional Versatility
- Versa Vibe™ Vibratory System
 - 2 machines in 1, thick or thin lifts
 - 4 amplitudes, 2 frequencies
- Simple Setup
- Dual Amplitude/Dual Frequency Vibratory System
 - Automatically matches amplitude and frequency
 - Single amplitude w/each frequency
 - Controlled with switch on console
- Hardest hitting, widest range of amplitudes
- 5-Amp Vibratory System, versatile selection
 - Heavy hitter, easy selection
 - 5 amplitudes, 1 frequency
- 50/50 weight distribution, ensures consistent compaction coverage

Unmatched Machine Uptime


- Industry leading vibratory system reliability
- 3 year/3000 hour vibratory pod service interval, lowest lifetime operating cost
- Oil-bath lubrication for eccentric weight bearings, ensures long life
- Maintenance Free Hitch, no grease required
- Ground level service access, simplifies maintenance
- Long service intervals minimize costs



Exceptional Visibility and Control

- Automatic speed control (ASC), easily repeat desired speed and impact spacing
- · Heavy-duty isolation mounts, smooth ride
- Multi-position seating, controls remain in same position with operator
- Multi-function propel lever: speed, vibe on/off, water spray on/off, drum offset option
- Folded drum supports promote good visibility
- Tilting steering console conforms to operator

Dual Amplitude/Dual Frequency Vibratory System



Smooth Operating Powertrain

- Cat 3054C turbo-charged engine, 97 kW (130 hp) rated nower
- Pressure Override Valve (POR), balances power demand, remains responsive, less fuel usage
- Cooling system delivers clean air from above
- · Centered articulation delivers true drum tracking

Industry Leading Water Spray System

- Single high capacity tank, 1100 L (291 gal), quick refills
- Dual water pumps provide backup capability
- Triple filtration prevents clogs; fill point, before water pumps, and in nozzles
- Intermittent operation conserves water
- · Alternating pumps, extend life
- On/off control located on propel lever
- Freeze Protection Kit (option)



CB534D, CB534D XW, and CB564D Asphalt Compactor Specifications								
Dimensions	CB534D		CB534D XW		CI	CB564D		
Overall length		_	4934 mm	194 in		_		
Overall width	1883 mm	74 in	2183 mm	87 in	2310 mm	92 in		
Drum width	1700 mm	67 in	2000 mm	79 in	2130 mm	84 in		
Operating Weights								
Standard machine w/ROPS	10 380 kg	22,836 lb	11 300 kg	24,860 lb	12 600 kg	27,783 lb		
Static linear load (at drum)	29.4 kg/cm	164 lb/in	28.3 kg/cm	158 lb/in	29.6 kg/cm	165 lb/in		
Max. machine w/ROPS	11 297 kg	24,853 lb	12 217 kg	26,877 lb	13 507 kg	29,715 lb		
Standard machine w/ROPS ca	b 10 450 kg	23,038 lb	11 740 kg	25,882 lb	12 600 kg	27,783 lb		
Static linear load (at drum)	30.7 kg/cm	172 lb/in	29.4 kg/cm	165 lb/in	29.6 kg/cm	165 lb/in		
Max. machine w/ROPS cab	11 297 kg	24,853 lb	12 217 kg	26,877 lb	13 507 kg	29,715 lb		
Speed Ranges								
Speed: (low)		_	0 - 7.3 km/hr	0 - 4.5 mph		_		
(high)		_	0 - 13 km/hr	0 - 8 mph		_		
Vibratory System - Amplitude Ra	ange							
Five Amplitude System	0.33 mm -1.06 mm		0.30 mm (0.30 mm 0.30 mm		1.03 mm 0.41 mm		
	0.042 ir	- 0.013 in	0.034 in -	0.012 in	0.040 in	- 0.016 in		
Versa Vibe System	0.33 mm -0.86 mm		0.30 mm (0.30 mm 0.78 mm		0.67 mm 0.26 mm		
	0.013 ir	- 0.034 in	0.012 in -	0.031 in	0.010 in	- 0.026 in		
Dual Amplitude/Dual Frequency	0.34 mm -0.85 mm		0.27 mm (0.27 mm 0.77 mm		NA		
	0.013 ir	- 0.033 in	0.010 in -	0.030 in				

The Cat® Advantage - Single Source Provider							
	Cat Dealer	Competitive Dealer	Comment				
Convenient worldwide dealer locations	V		More than our 5 largest competitors combined				
Engine service	V		Cat machines feature Cat engines				
Machine service	V	V					
Service technician trained for paving equipment	V		Cat technicians trained on Cat machines				
24/7/365 parts availability on most service parts	V		Long lead times for competitive OEM parts				
New OEM parts	V		Competition offers inferior aftermarket parts				
Reconditioned OEM parts	V		Rebuilt to OEM spec by Cat Reman				
Available financing options	V		Available through Cat Financial				
Application expertise	~		Personnel understand the paving business				
Machine rental	V		Keeps your capital expense low				
Products with high resale value	V		Durable Cat machines built to last				

QEXQ1477 (11-10)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2010 Caterpillar All Rights Reserved Printed in U.S.A.

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

