



Image shown may not reflect actual package.

**STANDBY**  
**60 ekW 75 kVA**

**PRIME**  
**55 ekW 67 kVA**  
**60 Hz 1800 rpm 480 Volts**

**Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.**

---

## FEATURES

### FUEL/EMISSIONS STRATEGY

- EPA Certified for Stationary Emergency Application (Emits Equivalent U.S. EPA Tier 3 Nonroad Standards)

### DESIGN CRITERIA

- The generator set meets NFPA 110, ISO 8528-5 transient response and can accept 100% rated load in one step
- Cooling system designed to operate in 50 °C / 122 °F ambient temperatures with an air flow restriction of 0.5 in. water

### UL 2200 / CSA – Optional

- UL 2200 Listed
- CSA Certified

Certain restrictions may apply.

Consult with your Cat® Dealer.

### FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

### SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

### WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat S•O•S<sup>SM</sup> program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-product

### Cat® Model D60-6, Three Phase

#### CAT C4.4 DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic engine control

#### GENERATOR SET

- Complete system designed and built at ISO 9001 certified facilities
- Factory tested to design specifications at full load conditions

#### CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway
- Integrated Voltage Regulation

#### SEISMIC CERTIFICATION

- Seismic Certification available
- Anchoring details are site specific, and are dependent on many factors such as generator set size, weight, and concrete strength. IBC Certification requires that the anchoring system used is reviewed and approved by a Professional Engineer
- Seismic Certification per Applicable Building codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, IBC 2012 CBC 2007, CBC 2010

# STANDBY 60 ekW 75 kVA

## PRIME 55 ekW 67 kVA

60 Hz 1800 rpm 480 Volts



### FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> <li>• Dry replaceable paper element type with restriction indicator</li> </ul>	
Cooling	<ul style="list-style-type: none"> <li>• Radiator and cooling fan complete with protective guards</li> <li>• Standard ambient temperatures up to 50°C (122°F)</li> </ul>	<input type="checkbox"/> Radiator stone guard <input type="checkbox"/> Radiator transition flange
Exhaust		<input type="checkbox"/> Industrial <input type="checkbox"/> Residential <input type="checkbox"/> Critical mufflers <input type="checkbox"/> Overhead silencer mounting kit
Fuel	<ul style="list-style-type: none"> <li>• Flexible fuel lines to base with NPT connections</li> </ul>	<input type="checkbox"/> Sub-base dual wall UL listed fuel tanks <input type="checkbox"/> Emergency vent 12ft extension <input type="checkbox"/> 5 gallon spill containment
Generator	<ul style="list-style-type: none"> <li>• Class H insulation</li> <li>• Drip proof generator air intake (NEMA 2,IP23)</li> <li>• Electrical design in accordance with with BS5000 Part 99, EN61000-6, IEC60034-1, NEMA MG-1.33</li> <li>• IP23 Protection</li> </ul>	<input type="checkbox"/> Generator upgrade 1 size <input type="checkbox"/> Permanent magnet excitation <input type="checkbox"/> Internal excitation (IE) / AREP <input type="checkbox"/> Anti-condensation space heater
Power Termination	<ul style="list-style-type: none"> <li>• Circuit breakers, – 100% rated assembly, UL Listed</li> <li>• Power center houses EMCP controller and control terminations (CB)</li> <li>• Segregated low voltage wiring termination panel</li> <li>• NEMA 1 steel enclosure, vibration isolated</li> <li>• Electrical stub-up area directly below circuit breaker</li> </ul>	<input type="checkbox"/> Auxiliary contacts <input type="checkbox"/> Shunt trip <input type="checkbox"/> Overload shutdown via breaker
Governor	<ul style="list-style-type: none"> <li>• ADEM™ A4</li> </ul>	
Control Panels	<ul style="list-style-type: none"> <li>• EMCP 4.2 digital control panel</li> <li>• Vibration isolated NEMA 1 enclosure with lockable hinged door</li> <li>• DC and AC Wiring harnesses</li> </ul>	<input type="checkbox"/> NFPA110 upgrade <input type="checkbox"/> Control panel chassis
Lube		<input type="checkbox"/> Lube oil heater
Mounting	<ul style="list-style-type: none"> <li>• Heavy-duty fabricated steel base with lifting points</li> <li>• Anti-vibration pads to ensure vibration isolation</li> <li>• Complete OSHA guarding</li> <li>• Stub-up pipe ready for connection to silencer pipework</li> </ul>	<input type="checkbox"/> IBC Seismic and OSHPD certification per Applicable Building Codes: IBC2000, IBC2003, IBC2006, IBC 2009, IBC 2012, CBC 2007, CBC 2010
Starting/Charging	<ul style="list-style-type: none"> <li>• 12 volt starting motor</li> <li>• Batteries with rack and cables</li> </ul>	<input type="checkbox"/> Battery charger – UL 10 amp <input type="checkbox"/> Battery disconnect switch <input type="checkbox"/> Battery removal (does not remove rack and cables) <input type="checkbox"/> Coolant Heater
General	<ul style="list-style-type: none"> <li>• High gloss polyurethane paint, Caterpillar Yellow except rails and radiators gloss black</li> <li>• Anticorrosive paint protection</li> <li>• All electroplated hardware</li> </ul>	<input type="checkbox"/> CSA Certified <input type="checkbox"/> Weather protective enclosure <input type="checkbox"/> Sound attenuated protective enclosures <input type="checkbox"/> Caterpillar tool set <input type="checkbox"/> Caterpillar White paint

# STANDBY 60 ekW 75 kVA

## PRIME 55 ekW 67 kVA

60 Hz 1800 rpm 480 Volts



### SPECIFICATIONS

STANDARD CAT GENERATOR		
Frame size	LC2014H	
Excitation	Self excitation	
Pitch	0.6667	
Number of poles	4	
Number of bearings	Single bearing	
Number of leads	12	
Insulation	Class H	
IP Rating	IP23	
Overspeed capability (%)	125	
Wave form deviation (%)	2	
Voltage regulator	Three phase sensing	
Voltage regulation	+/- 0.25% (steady state)	
<b>Additional Voltage Information:</b>		
Three Phase	Prime	Standby
208V Temp Rise	125°C / 225°F	130°C / 234°F
240V Temp Rise	125°C / 225°F	130°C / 234°F
480V Temp Rise	105°C / 189°F	105°C / 189°F
600V Temp Rise	105°C / 189°F	105°C / 189°F
- Consult your Cat dealer for other available voltages		
<b>CAT DIESEL ENGINE</b>		
C4.4 In-line 4, 4-cycle diesel		
Bore	105.0 mm (4,13 in)	
Stroke	127.0 mm (5.0 in)	
Displacement	4.4 L (268.5 in <sup>3</sup> )	
Compression ratio	16.2:1	
Aspiration	Turbocharged	
Fuel system	Common rail	
Governor type	Electronic	

### CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 12 volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- ekW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under frequency (81 o/u)
- Reverse power (kW) (32)
- Reverse reactive power (kVAr) (32RV)
- Overcurrent (50/51)

Communications:

- Six digital inputs
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local annunciator
- Remote CAN annunciator
- Remote serial annunciator

# STANDBY 60 ekW 75 kVA

# PRIME 55 ekW 67 kVA

60 Hz 1800 rpm 480 Volts



## TECHNICAL DATA

Open Generator Set – 1800 rpm/60 Hz/480 Volts	P3468A		P3468B	
<b>EPA Certified for Stationary Emergency Application (Emits Equivalent U.S. EPA Tier 3 Nonroad Standards)</b>	<b>Standby</b>		<b>Prime</b>	
<b>Generator Set Package Performance</b> Genset power rating @ 0.8 pf Genset power rating with fan	75.0 kVA 60.0 ekW		68.8 kVA 55.0 ekW	
<b>Fuel Consumption</b> 100% load with fan 75% load with fan 50% load with fan	19.6 L/hr 17.0 L/hr 13.1 L/hr	5.2 gal/hr 4.5 gal/hr 3.5 gal/hr	18.9 L/hr 16.1 L/hr 12.4 L/hr	5.0 gal/hr 4.3 gal/hr 3.3 gal/hr
<b>Cooling System<sup>1</sup></b> Air flow restriction (system) Engine coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	0.12 kPa 16.5 L 9.5 L 7.0 L	0.48 in. water 4.4 gal 2.5 gal 1.8 gal	0.12 kPa 16.5 L 9.5 L 7.0 L	0.48 in. water 4.4 gal 2.5 gal 1.8 gal
<b>Inlet Air</b> Combustion air inlet flow rate	5.9 m <sup>3</sup> /min	208.4 cfm	5.9 m <sup>3</sup> /min	208.4 cfm
<b>Exhaust System</b> Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system back pressure (maximum)	547.0°C 14.7 m <sup>3</sup> /min 63.5 mm 15 kPa	1017 °F 519 cfm 2.5 in 60.2 in. water	525.0°C 14.4 m <sup>3</sup> /min 63.5 mm 15 kPa	977 °F 509 cfm 2.5 in 60.2 in. water
<b>Heat Rejection</b> Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	49.6 kW 66.9 kW 14.9 kW 6.1 kW	2821 Btu/min 3805 Btu/min 847.3 Btu/min 346.9 Btu/min	46.7 kW 65.9 kW 10.8 kW 5.4 kW	2656 Btu/min 3742 Btu/min 614.2 Btu/min 307.1 Btu/min
<b>Alternator<sup>2</sup></b> Motor starting capability @ 30% voltage dip Frame Insulation class Temperature rise	163 skV LC2014HF H 105°C	189°F	163 skV LC2014HF 105°C	189°F
<b>Lubrication System</b> Total oil capacity Oil pan	8.4 L 6.9 L	2.2 gal 1.8 gal	8.4 L 6.9 L	2.2 gal 1.8 gal
<b>Emissions (Nominal)<sup>3</sup></b> NOx + HC CO PM	4.33 g/kWhr 1.15 g/kWhr 0.18 g/kWhr			

<sup>1</sup>For ambient and altitude capabilities consult your Cat dealer. Airflow restriction (system) is added to existing restriction from factory.

<sup>2</sup>Generator temperature rise is based on a 40°C (104°F) ambient per NEMA MG1-32.

<sup>3</sup>The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load.

**STANDBY 60 ekW 75 kVA**

**PRIME 55 ekW 67 kVA**

60 Hz 1800 rpm 480 Volts



## **RATING DEFINITIONS AND CONDITIONS**

---

**Applicable Codes and Standards:** AS1359, CSA C22.2 No 100-04, UL142, UL489, UL601, UL869, UL2200, NFPA 37, NFPA 70, NFPA 99, NFPA 110, IBC, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, 72/23/EEC, 98/37/EC, 2004/108/EC.

**Standby** – Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

**Prime** – Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand of 100% of prime-rated ekW with 10% of overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions.

**Fuel rates** are based on fuel oil to specification EPA 2D 89.330-96 with a density of 0.845 – 0.850 kg/L (7.052 – 7.094 lbs/U.S. gal.) @ 15°C (59°F) and fuel inlet temperature 40°C (104°F).

**Additional ratings** may be available for specific customer requirements, contact your Cat representative for details.

**STANDBY 60 ekW 75 kVA**

**PRIME 55 ekW 67 kVA**

60 Hz 1800 rpm 480 Volts



## DIMENSIONS

---

Package Dimensions		
Length	1932 mm	76 in
Width	1110 mm	44 in
Height	1767 mm	46 in

**NOTE:** For reference only – do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #3989305).

Performance No.: P3468A/B

Feature Code: NAC133P

Gen. Arr. Number: 3932521

Source: U.S. Sourced

LEHE0420-02 (06/14)

[www.Cat-ElectricPower.com](http://www.Cat-ElectricPower.com)

2014 Caterpillar  
All rights reserved.

Materials and specifications are subject to change without notice.  
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.