



Image shown may not reflect actual package.

**STANDBY**  
**100 ekW 100 kVA**

**PRIME**  
**90 ekW 90 kVA**  
**60 Hz 1800 rpm 240/120 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

## FEATURES

### FUEL/EMISSIONS STRATEGY

- EPA Certified for Stationary Emergency Application (Emits Equivalent U.S. EPA Tier 3 Nonroad Standards)

### DESIGN CRITERIA

- The generator set meets NFPA 110, ISO 8528-5 transient response and can accept 100% rated load in one step
- Cooling system designed to operate in 50°C / 122°F ambient temperatures with an air flow restriction of 0.5 in. water

### UL 2200 / CSA – Optional

- UL 2200 Listed
- CSA Certified

Certain restrictions may apply.

Consult with your Cat® Dealer.

### FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

### SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

### WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat S•O•S<sup>SM</sup> program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-product

### Cat® Model D100-6S, Single Phase

#### CAT C4.4 DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic engine control

#### GENERATOR SET

- Complete system designed and built at ISO 9001 certified facilities
- Factory tested to design specifications at full load conditions

#### CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway
- Integrated Voltage Regulation

#### SEISMIC CERTIFICATION

- Seismic Certification available
- Anchoring details are site specific, and are dependent on many factors such as generator set size, weight, and concrete strength. IBC Certification requires that the anchoring system used is reviewed and approved by a Professional Engineer
- Seismic Certification per Applicable Building codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, IBC 2012 CBC 2007, CBC 2010

**STANDBY 100 ekW 100 kVA**

**PRIME 90 ekW 90 kVA**

60 Hz 1800 rpm 240/120 Volts



## FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"><li>• Dry replaceable paper element type with restriction indicator</li></ul>	
Cooling	<ul style="list-style-type: none"><li>• Radiator and cooling fan complete with protective guards</li><li>• Standard ambient temperatures up to 50°C (122°F)</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Radiator stone guard</li><li><input type="checkbox"/> Radiator transition flange</li></ul>
Exhaust		<ul style="list-style-type: none"><li><input type="checkbox"/> Industrial</li><li><input type="checkbox"/> Residential</li><li><input type="checkbox"/> Critical mufflers</li><li><input type="checkbox"/> Overhead silencer mounting kit</li></ul>
Fuel	<ul style="list-style-type: none"><li>• Flexible fuel lines to base with NPT connections</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Sub-base dual wall UL listed fuel tanks</li><li><input type="checkbox"/> Emergency vent 12 ft extension</li><li><input type="checkbox"/> 5 gallon spill containment</li></ul>
Generator	<ul style="list-style-type: none"><li>• Class H insulation</li><li>• Drip proof generator air intake (NEMA 2,IP23)</li><li>• Electrical design in accordance with BS5000 Part 99, EN61000-6, IEC60034-1, NEMA MG-1.33</li><li>• IP23 Protection</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Generator upgrade 1 size</li><li><input type="checkbox"/> Permanent magnet excitation</li><li><input type="checkbox"/> Internal excitation (IE) / AREP</li><li><input type="checkbox"/> Anti-condensation space heater</li></ul>
Power Termination	<ul style="list-style-type: none"><li>• Circuit breakers – 100% rated assembly, UL Listed</li><li>• Power center houses EMCP controller and control terminations (CB)</li><li>• Segregated low voltage wiring termination panel</li><li>• NEMA 1 steel enclosure, vibration isolated</li><li>• Electrical stub-up area directly below circuit breaker</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Auxiliary contacts</li><li><input type="checkbox"/> Shunt trip</li><li><input type="checkbox"/> Overload shutdown via breaker</li></ul>
Governor	<ul style="list-style-type: none"><li>• ADEM™ A4</li></ul>	
Control Panels	<ul style="list-style-type: none"><li>• EMCP 4.2 digital control panel</li><li>• Vibration isolated NEMA 1 enclosure with lockable hinged door</li><li>• DC and AC Wiring harnesses</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> NFPA110 upgrade</li><li><input type="checkbox"/> Control panel chassis</li></ul>
Lube		<ul style="list-style-type: none"><li><input type="checkbox"/> Lube oil heater</li></ul>
Mounting	<ul style="list-style-type: none"><li>• Heavy-duty fabricated steel base with lifting points</li><li>• Anti-vibration pads to ensure vibration isolation</li><li>• Complete OSHA guarding</li><li>• Stub-up pipe ready for connection to silencer pipework</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> IBC Seismic and OSHPD certification per Applicable Building Codes: IBC2000, IBC2003, IBC2006, IBC 2009, IBC 2012, CBC 2007, CBC 2010</li></ul>
Starting/Charging	<ul style="list-style-type: none"><li>• 12 volt starting motor</li><li>• Batteries with rack and cables</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Battery charger – UL 10 amp</li><li><input type="checkbox"/> Battery disconnect switch</li><li><input type="checkbox"/> Battery removal (does not remove rack and cables)</li><li><input type="checkbox"/> Coolant Heater</li></ul>
General	<ul style="list-style-type: none"><li>• High gloss polyurethane paint, Caterpillar Yellow except rails and radiators gloss black</li><li>• Anticorrosive paint protection</li><li>• All electroplated hardware</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> CSA Certified</li><li><input type="checkbox"/> Weather protective enclosure</li><li><input type="checkbox"/> Sound attenuated protective enclosures</li><li><input type="checkbox"/> Caterpillar tool set</li><li><input type="checkbox"/> Caterpillar White paint</li></ul>

**STANDBY 100 ekW 100 kVA**  
**PRIME 90 ekW 90 kVA**  
60 Hz 1800 rpm 240/120 Volts



## SPECIFICATIONS

STANDARD CAT GENERATOR	
Frame size	LCB3014D
Excitation	Self excitation
Pitch	0.6667
Number of poles	4
Number of bearings	Single bearing
Number of leads	4
Insulation	Class H
IP Rating	IP23
Overspeed capability (%)	125
Wave form deviation (%)	2
Voltage regulation	+/- 0.25% (steady state)
CAT DIESEL ENGINE	
C4.4 In-line 4, 4-cycle diesel	
Bore	105.0 mm (4,13 in)
Stroke	127.0 mm (5.0 in)
Displacement	4.4 L (268.5 in <sup>3</sup> )
Compression ratio	16.2:1
Aspiration	Turbocharged, Air-to-Air Aftercooled
Fuel system	Common rail
Governor type	Electronic

### CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 12 volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- ekW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under frequency (81 o/u)
- Reverse power (kW) (32)
- Reverse reactive power (kVAr) (32RV)
- Overcurrent (50/51)

Communications:

- Six digital inputs
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local annunciator
- Remote CAN annunciator
- Remote serial annunciator

**STANDBY 100 ekW 100 kVA**  
**PRIME 90 ekW 90 kVA**  
60 Hz 1800 rpm 240/120 Volts



**TECHNICAL DATA**

Open Generator Set – 1800 rpm/60 Hz/480 Volts	P3362A			
EPA Certified for Stationary Emergency Application (Emits Equivalent U.S. EPA Tier 3 Nonroad Standards)	Standby		Prime	
<b>Generator Set Package Performance</b> Genset power rating @ 1.0 pf Genset power rating with fan	100.0 kVA 100.0 ekW		90.0 kVA 90.0 ekW	
<b>Fuel Consumption</b> 100% load with fan 75% load with fan 50% load with fan	23.1 L/hr 18.5 L/hr 13.8 L/hr	6.1 gal/hr 4.9 gal/hr 3.6 gal/hr	27.4 L/hr 21.9 L/hr 16.4 L/hr	7.9 gal/hr 6.3 gal/hr 4.6 gal/hr
<b>Cooling System<sup>1</sup></b> Air flow restriction (system) Engine coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	0.12 kPa 17.0 L 7.0 L 10.0 L	0.48 in. water 4.5 Gal 1.8 Gal 2.6 Gal	0.12 kPa 17.0 L 7.0 L 10.0 L	0.48 in. water 4.5 Gal 1.8 Gal 2.6 Gal
<b>Inlet Air</b> Combustion air inlet flow rate	8.5 m³/min	300.2 cfm	8.4 m³/min	296.6 cfm
<b>Exhaust System</b> Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system back pressure (maximum)	506°C 20.0 m³/min 63.5 mm 15.0 kPa	943°F 706.3cfm 2.5 in 60.2 in. water	480°C 19.2 m³/min 63.5 mm 15.0 kPa	896°F 678.0 cfm 2.5 in 60.2 in. water
<b>Heat Rejection</b> Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	61.0 kW 87.0 kW 18.0 kW 18.0 kW 9.7 kW	3469 Btu/min 4948 Btu/min 1024 Btu/min 1023.6 Btu/min 551.6 Btu/min	57.0 kW 81.0 kW 17.0 kW 15.0 kW 8.4 kW	3242 Btu/min 4606 Btu/min 967 Btu/min 853 Btu/min 477.7Btu/min
<b>Alternator<sup>2</sup></b> Motor starting capability @ 30% voltage dip Frame Insulation class Rotor temperature rise	206 skV LC3014B H 130°C		206 skV LC3014B	189°F
<b>Lubrication System</b> Total oil capacity Oil pan	8.0 L 7.0 L	2.1 gal 1.8 gal	8.0 L 7.0 L	2.1 gal 1.8 gal
<b>Emissions (Nominal)<sup>3</sup></b> NOx + HC CO PM	3.73 g/kWhr 1.15 g/kWhr 0.21 g/kWhr			

<sup>1</sup>For ambient and altitude capabilities consult your Cat dealer. Airflow restriction (system) is added to existing restriction from factory.

<sup>2</sup>Generator temperature rise is based on a 40°C (104°F) ambient per NEMA MG1-32.

<sup>3</sup>The nominal emissions data shown is subject to instrumentation, easurement, facility and engine to engne variations. Emissions data is based on 100% load.

**STANDBY 100 ekW 100 kVA**

**PRIME 90 ekW 90 kVA**

60 Hz 1800 rpm 240/120 Volts



## **RATING DEFINITIONS AND CONDITIONS**

---

**Applicable Codes and Standards:** AS1359, CSA C22.2 No 100-04, UL142, UL489, UL601, UL869, UL2200, NFPA 37, NFPA 70, NFPA 99, NFPA 110, IBC, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, 72/23/EEC, 98/37/EC, 2004/108/EC.

**Standby** – Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

**Prime** – Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand of 100% of prime-rated ekW with 10% of overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions.

**Fuel rates** are based on fuel oil to specification EPA 2D 89.330-96 with a density of 0.845 – 0.850 kg/L (7.052 – 7.094 lbs/U.S. gal.) @ 15°C (59°F) and fuel inlet temperature 40°C (104°F).

**Additional ratings** may be available for specific customer requirements, contact your Cat representative for details.

**STANDBY 100 ekW 100 kVA**

**PRIME 90 ekW 90 kVA**

60 Hz 1800 rpm 240/120 Volts



## DIMENSIONS

---

Package Dimensions		
Length	2362 mm	93 in
Width	1110 mm	44 in
Height	1304 mm	51 in

**NOTE:** For reference only – do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #4190059).

Performance No.: P3362A

[www.Cat-ElectricPower.com](http://www.Cat-ElectricPower.com)

Feature Code: NAC143P

2014 Caterpillar  
All rights reserved.

Gen. Arr. Number: 3932540

Materials and specifications are subject to change without notice.  
The International System of Units (SI) is used in this publication.

Source: U.S. Sourced

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

LEHE0430-02 (06/14)