

# HOW LOW CAN YOU GO?

## HIGHEST PERFORMANCE IN LOW COAL

For coal seams with an average height under 1.8 m (70 in), plows are the system of choice for longwall mining.

Automated Cat® plow systems allow access to extended reserves in very low coal seams with a height of down to 0.6 meters —achieving high reserve recovery rates.

[mining.cat.com](http://mining.cat.com)

### Cat RHH800 Base-plate Plow

Installed Power  
2 x 400 kW (2 x 540 hp)



Cutting Height:  
**0.6 – 1.6 m (23.6 – 63 in)**

### Cat GH800B Gliding Plow

Installed Power  
2 x 400 kW (2 x 540 hp)



Cutting Height:  
**0.75 – 2.0 m (29.5 – 79 in)**

### Cat GH800 Gliding Plow

Installed Power  
2 x 400 kW (2 x 540 hp)



Cutting Height:  
**1.0 – 2.0 m (39 – 79 in)**

### Cat GH1600 Gliding Plow

Installed Power  
2 x 800 kW (2 x 1,080 hp)



Cutting Height:  
**1.1 – 2.3 m (43 – 90.5 in)**

**BUILT FOR IT.™**

© 2015 Caterpillar | All Rights Reserved. | AEXQ1707  
CAT, CATERPILLAR, BUILT FOR IT, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

**CAT**®