5 THINGS TO FIND IN EQUIPMENT FLUIDS

During $S \cdot O \cdot S^{SM}$ Services analysis, multiple tests are performed on engine, hydraulic and drive train oils—plus coolants, too. They can reveal a lot.

1

COMPONENT WEAR RATE

Why we do it: Each oil-washed system has a particular concentration of wear metals produced during normal operation. By evaluating wear inside the lubricated compartment, we can see if rates are normal or not. (For example, high levels of iron and chrome can stem from problems with your engine's cylinder liners and/or piston rings.)

What are we looking for?

- Wear metals including iron, lead, copper, aluminum & chrome
- Silicon can indicate dirt entry depending on local soil conditions
- Sodium potential indicator of water or coolant entry

2

OIL CONDITION

Why we do it: Wear occurs when oil depletes its additives and begins to deteriorate. This can damage components in oil-washed compartments. So it's important to know if the oil has reached the end of its useful life.

What are we looking for?

- Viscosity (how the oil flows) too low & wear can occur; too high & oil won't do its job
- Oxidation (oxygen molecules joining with lubricant molecules) in diesel engines, oxidation can trigger sticking piston rings; in hydraulics, oxidized lubricants will increase pump wear & damage valves
- Sulfation (sulfur combining with water during diesel fuel combustion) can corrode valves, cylinder liners & more
- Nitration (generally a problem in natural gas engines) may result in oil filter plugging, crankcase deposits & other issues

NOW, THAT'S SMALL!

When you're testing fluids, you've got to see what operators can't.

Concentration of elements is shown in parts per million (ppm).

For comparison:

1 PPM IS LIKE
ONE DROP
OF MILK IN...

QALLONS
OF COFFEE

3

OIL CONTAMINATION

Why we do it: This robust analysis involving several tests can determine if anything harmful has entered the oil.

What are we looking for?

- Soot (from partially burned fuel) can plug oil filters & cause engine wear
- Fuel can come from the combustion process & cause low viscosity
- · Water (such as from condensation, leaks, wet conditions) can cause wear, rust & sludge
- Coolant can contaminate engine oil



OIL IDENTIFICATION

Why we do it: The wrong fluid in the wrong compartment can affect performance and lube protection or even severely damage major components. To tell if it's the right fluid, it's important to take an accurate sample with the right labeling.

What are we looking for?

- Viscosity is it optimal for the geared compartment & your application?
- Additive chemistry is the oil appropriate based on its unique chemical makeup?

COOLANT ANALYSIS

Why we do it: Today's heavy-duty engines produce a lot of power from a small package, and cooling systems have to do more with less. Also, customers may be extending drain intervals or recycling to reduce disposal costs.

What are we looking for?

- Coolant type with so many on the market, they all have different chemistries
- Boil & freeze protection to monitor fluid's ability to provide adequate protection
- Condition to test health for pH, conductivity, nitrite, solids, odor, color & appearance
- Contamination has anything harmful entered?

KNOW YOUR FLEET, KNOW YOUR OPPORTUNITIES

Expert fluid analysis is a key part of good equipment management. It helps you maintain overall equipment health—so you can maximize uptime and avoid costly failures.

What can equipment management do for you? To get a leg up, take the quiz at KnowYourFleet.com.

- · Your strengths in managing jobs and equipment
- Opportunities to improve your decision-making
- · Recommendations for your personal challenges around cost, people, risk and operations

KNOW YOUR FLEET. TAKE THE QUIZ.



You'll discover:

