

Start-up & Shut Down Procedures: Front Shovel Excavators

SAFETY.CAT.COM™

Operator/Inspector Date	Time
Serial Number Machine Hours	
Was procedure step completed properly?	✓ Evaluator Comments
For more information, please refer to the Operation and Maintenance Manual or any other applicable manuals and instructions for this product. If you have questions, please contact your local Caterpillar dealer.	
Starting the machine	
Perform walk around inspection	
Mount the machine using 3 points of contact	
Turn the battery disconnect switch to ON	
Adjust seat, arm rests	
Fasten seat belt	
Confirm all implements are grounded	
Move hydraulic lock lever into the LOCKED position	
Make sure all personnel are clear of machine	
Turn the key start switch to ON	
Perform start-up test on the monitoring panel	
Turn the key start switch to START; Crank engine	
Machine warm-up	
Allow machine to warm-up for 5 minutes at low idle	
Engage and disengage hydraulic controls to help speed warm-up of hydraulic oil	
Cycle all controls to allow warm oil to circulate through all cylinders a lines	and
Check gauges and action lights frequently	
Moving the machine	
Make sure area is clear	
Move hydraulic lock lever into the RUN position	
Raise all lowered implements	
Move travel controls in the direction you want to go (check machine rotation: final drives are to rear)	
Machine shut-down	
Park machine on smooth, level area	
Ground all hydraulic implements	
Move Hydraulic lock lever into the LOCKED position	
Allow engine to run at LOW IDLE for 5 minutes	
Turn key start switch to OFF and remove key	
Turn battery disconnect switch to OFF	
Dismount machine using 3-point contact	
Conduct post-operation walk around inspection	

HTTP://SAFETY.CAT.COM V0810.1

