

# M316F

Wheeled Excavator



## Lift Capacity Specifications

# Table of Contents

## M316F Wheeled Excavator Lift Charts

### Variable Adjustable Boom – Counterweight: 3200 kg

Short Stick – 2100 mm . . . . .	3
Medium Stick – 2400 mm . . . . .	4
Long Stick – 2600 mm . . . . .	5
Industrial Stick – 3100 mm . . . . .	6

### Variable Adjustable Boom – Counterweight: 3700 kg

Short Stick – 2100 mm . . . . .	7
Medium Stick – 2400 mm . . . . .	8
Long Stick – 2600 mm . . . . .	9
Industrial Stick – 3100 mm . . . . .	10

### One-Piece Boom – Counterweight: 3200 kg

Short Stick – 2100 mm . . . . .	11
Medium Stick – 2400 mm . . . . .	12
Long Stick – 2600 mm . . . . .	13
Industrial Stick – 3100 mm . . . . .	14

### One-Piece Boom – Counterweight: 3700 kg

Short Stick – 2100 mm . . . . .	15
Medium Stick – 2400 mm . . . . .	16
Long Stick – 2600 mm . . . . .	17
Industrial Stick – 3100 mm . . . . .	18

### Offset Boom – Counterweight: 3700 kg

Short Stick – 2100 mm . . . . .	19
Medium Stick – 2400 mm . . . . .	20





















































For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

AEXQ1612 (01-2016)  
(Europe)

© 2016 Caterpillar  
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

