



Cat[®] 972M

Wheel Loader

*The new 972M Wheel Loader has an ACERT™ engine equipped with a combination of proven electronic, fuel, and air components. Applying proven technologies systematically and strategically lets us meet our customer's high expectations for productivity, fuel efficiency, reliability and service life. Deep system integration results in reduced emissions, improved performance and improved fuel economy without interrupting machine performance making it seamless to operators. Aggregate Handler and other optional configurations are available.***

RELIABILITY, PRODUCTIVITY AND FUEL EFFICIENCY

- 10% more fuel efficient than K Series*
- Up to 25% more efficient than H Series*

Linkage and Work Tools

- Performance Series buckets and range of work tools
- Fusion™ « zero-offset » coupler (option)

Engine and Aftertreatment Advancements

- Cat[®] C9.3 ACERT engine
- Meets U.S. EPA Tier 3/EU Stage IIIA equivalent emissions standards
- Productive economy mode

Transmission Advancements

- Powershift transmission with single clutch speed shifts and torque based down shifts
- Lock up clutch torque converter with lock-to-lock shifting
- Split flow oil system and multi-viscosity oil

Axle Advancements

- On-the-go disc-type front differential locks (front and rear fully automatic option)
- Caliper disc parking brake
- Bevel gear shrouds

Next Generation Hydraulic Systems

- Next generation main valve
- Next generation ride control system with dual accumulators
- Next generation implement pump with increased displacement
- Full flow and kidney loop filtration
- Load-sensing hydraulics with simultaneous hydraulic functions
- 3rd and 4th function (option)

EASE OF OPERATION

Best-in-class Operator Environment

- Optimized all-around visibility
- E-H joystick steering (steering wheel optional)
- Touch screen multifunction color display with integrated controls and rearview camera
- Stair-like ingress and egress
- New wider door and increased glass area
- Seat-mounted fingertip electro-hydraulic implement controls
- Large convex rearview mirrors with integrated spot mirror
- Remote door opening (option)
- Automatic climate control
- Viscous cab mounts
- Low operator sound levels

Advanced Technology with Cat Connect

- Link technologies, like Product Link™ to monitor equipment and manage production using online VisionLink[®] software
- Payload technologies, like Cat Production Measurement (option) to measure payloads and optimize productivity
- Detect technologies, like the rear vision camera to keep people safe and help the operator work more productively

SERVICE ACCESS

- One-piece tilting hood with side and rear doors
- Centralized service centers for hydraulic and electrical components
- Windshield cleaning platform and harness tie-off

*Fuel efficiency is measured in mass of material moved per volume of fuel burned. Average efficiency improvement as tested and analyzed for an average composite cycle and stand configuration with variations per comparable model with and without economy mode active. Factors influence result variation such as, but not limited to, machine configuration, operator technique, machine application, climate, etc.

**Optional configuration and equipment may vary from region to region. Consult your Caterpillar representative for further details.



Cat® 972M Wheel Loader

Engine

Engine Model	Cat C9.3 ACERT	
Max Gross Power @ 1,800 rpm – SAE J1995	246 kW	330 hp
Max Gross Power @ 1,800 rpm – SAE J1995 (metric)	334 hp	
Max Gross Power @ 1,800 rpm – ISO 14396	242 kW	325 hp
Max Gross Power @ 1,800 rpm – ISO 14396 (metric)	329 hp	
Max Net Power @ 1,700 rpm – SAE J1349	222 kW	298 hp
Max Net Power @ 1,700 rpm – SAE J1349 (metric)	302 hp	
Max Net Power @ 1,700 rpm – ISO 9249	222 kW	298 hp
Max Net Power @ 1,700 rpm – ISO 9249 (metric)	302 hp	
Peak Gross Torque (1,200 rpm) – SAE J1995	1728 N·m	1,275 lbf·ft
Peak Gross Torque (1,200 rpm) – ISO 14396	1710 N·m	1,261 lbf·ft
Maximum Net Torque (1,000 rpm)	1632 N·m	1,204 lbf·ft
Displacement	9.3 L	568 in ³

Weights

Operating Weight	24 897 kg	54,871 lb
------------------	-----------	-----------

- Weight based on a machine configuration with Michelin 26.5R25 XHA2 L3 radial tires, full fluids, operator, standard counterweight, cold start, roading fenders, Product Link, manual diff lock/open axles (front/rear), power train guard, secondary steering, sound suppression and a 4.8 m³ (6.28 yd³) general purpose bucket with BOCE.

Bucket Capacities

Bucket Range	2.90- 9.90 m ³	3.8- 13.0 yd ³
--------------	------------------------------	------------------------------

Operating Specifications

Static Tipping Load – Full 37° Turn – with Tire Deflection	16 164 kg	35,626 lb
Static Tipping Load – Full 37° Turn – No Tire Deflection	17 421 kg	38,396 lb
Breakout Force	196 kN	44,075 lbf

- For a machine configuration as defined under “Weight.”
- Full compliance to ISO 143971:2007 Sections 1 thru 6, which requires 2% verification between calculations and testing.

Sound

With Cooling Fan Speed at Maximum Value:	
Operator Sound Pressure Level (ISO 6396:2008)	70 dB(A)
Exterior Sound Power Level (ISO 6395:2008)	109 dB(A)
Exterior Sound Pressure Level (SAE J88:2013)	76 dB(A)*
*Distance of 15 m (49.2 ft), moving forward in second gear ratio.	
With Cooling Fan Speed at 70% of Maximum Value:**	
Operator Sound Pressure Level (ISO 6396:2008)	69 dB(A)
Exterior Sound Power Level (ISO 6395:2008)	108 L _{WA} ***
**For machines in countries that adopt the “EU Directives.”	
***European Union Directive “2000/14/EC” as amended by “2005/88/EC.”	

Transmission

Forward 1	6.7 km/h	4.2 mph
Forward 2	13.1 km/h	8.1 mph
Forward 3	23.2 km/h	14.4 mph
Forward 4	39.5 km/h	24.5 mph
Reverse 1	7.6 km/h	4.7 mph
Reverse 2	15.0 km/h	9.3 mph
Reverse 3	26.5 km/h	16.5 mph
Reverse 4	39.5 km/h	24.5 mph

- Maximum travel speed in standard vehicle with empty bucket and standard L3 tires with 826 mm (32.5 in) roll radius.

Service Refill Capacities

Fuel Tank	313 L	82.7 gal
Cooling System	71.6 L	18.9 gal
Crankcase	24.5 L	6.5 gal
Transmission	58.5 L	15.5 gal
Differentials and Final Drives – Front	57 L	15.1 gal
Differentials and Final Drives – Rear	57 L	15.1 gal
Hydraulic Tank	125 L	33 gal

Hydraulic System

Implement Pump Type	Variable Displacement Piston
Implement System:	
Maximum Pump Output (2,200 rpm)	360 L/min 95 gal/min
Maximum Operating Pressure	31 000 kPa 4,496 psi
Hydraulic Cycle Time – Total	10.7 Seconds

Dimensions

	Standard Lift		High Lift	
Height to Top of Hood	2818 mm	9'3"	2818 mm	9'3"
Height to Top of Exhaust Pipe	3522 mm	11'7"	3522 mm	11'7"
Height to Top of ROPS	3587 mm	11'9"	3587 mm	11'9"
Ground Clearance	434 mm	1'5"	434 mm	1'5"
Center Line of Rear Axle to Edge of Counterweight	2500 mm	8'2"	2500 mm	8'2"
Center Line of Rear Axle to Hitch	1775 mm	5'10"	1775 mm	5'10"
Wheelbase	3550 mm	11'8"	3550 mm	11'8"
Overall Length (without bucket)	7774 mm	25'7"	8109 mm	26'8"
Hinge Pin Height at Maximum Lift	4458 mm	14'8"	4793 mm	15'9"
Hinge Pin Height at Carry	680 mm	2'3"	778 mm	2'7"
Lift Arm Clearance at Maximum Lift	3843 mm	12'7"	4140 mm	13'6"
Rack Back at Maximum Lift	56 degrees		71 degrees	
Rack Back at Carry Height	50 degrees		49 degrees	
Rack Back at Ground	41 degrees		39 degrees	
Maximum Width over Tires	3009 mm	9'11"	3009 mm	9'11"
Tread Width	2230 mm	7'4"	2230 mm	7'4"

- All dimensions are approximate and based on L3 XHA2 tires.

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2016 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, “Caterpillar Yellow” and the “Power Edge” trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

AEXQ1748 (03-2016)
(Canada, LACD, ANZ)

