



**C7 ACERT™**  
**Industrial Power Unit**  
Tier 3/Stage IIIA  
168 bkW/225 bhp @ 2200 rpm

**CATERPILLAR ENGINE  
SPECIFICATIONS**




Image shown may not reflect actual engine

**I-6, 4-Stroke-Cycle Diesel**

Bore.....	110.0 mm (4.33 in)
Stroke.....	127.0 mm (5.0 in)
Displacement.....	7.2 L (442 in <sup>3</sup> )
Aspiration.....	Turbocharged ATAAC
Compression Ratio.....	17:1
Rotation (from flywheel end).....	Counterclockwise
Lube Oil System (refill).....	28 L (7.4 U.S. gal)
Weight, Net Dry (approximate kg, lb).....	588 kg (1296 lbs)

**FEATURES**

**Emissions**

Meets U.S. EPA Tier 3, EU Stage IIIA emission requirements.

**Worldwide Supplier Capability**

Caterpillar  
- Casts engine blocks and heads  
- Machines critical components  
- Assembles complete engine  
- Factory-designed systems built at Caterpillar ISO 9001:2000 certified facilities  
- Ownership of these manufacturing processes enables Caterpillar to produce high quality, dependable product.

**Testing**

Prototype testing on every model:  
- proves computer design  
- verifies system torsional stability  
- functionality tests every model  
  
Every Caterpillar engine is dynamometer tested under full load to ensure proper engine performance.

**Full Range of Attachments**

Wide range of bolt-on system expansion attachments, factory designed and tested.

**Unmatched Product Support Offered Through Worldwide Caterpillar Dealer Network**

More than 1,500 dealer outlets  
Caterpillar factory-trained dealer technicians service every aspect of your industrial engine  
99.7% of parts orders filled within 24 hours worldwide  
Caterpillar parts and labor warranty  
Preventive maintenance agreements available for repair before failure options

Scheduled Oil Sampling program matches your oil sample against Caterpillar set standards to determine:

- internal engine component condition
- presence of unwanted fluids
- presence of combustion by-products

**Web Site**

For all your industrial power requirements, visit [www.cat-industrial.com](http://www.cat-industrial.com).

**STANDARD ENGINE EQUIPMENT**

---

**Air Inlet System**

Air to air aftercooled (ATAAC)  
Turbocharged

**Control System**

Electronic governing, PTO speed control  
Programmable ratings  
Cold mode start strategy  
Automatic altitude compensation  
Power compensation for fuel temperature  
Programmable low and high idle and total engine limit  
Electronic diagnostics and fault logging  
Engine monitoring system  
J1939 Broadcast (diagnostic and engine status)  
ADEM™ A4 Electronic Control Unit (ECU)

**Cooling System**

Thermostats and housing, vertical outlet  
Jacket water pump, centrifugal  
Water pump, inlet

**Exhaust System**

Exhaust manifold, dry  
Optional exhaust outlet

**Flywheels and Flywheel Housing**

SAE No. 1 Flywheel housing

**Fuel System**

HEUI™ injection  
Fuel filter, secondary (2 micron high performance)  
Fuel transfer pump  
Fuel priming pump  
ACERT™ Technology

**Lube System**


Crankcase breather  
Oil cooler  
Oil filler  
Oil filter  
Oil pan front sump  
Oil dipstick  
Oil pump (gear driven)

**General**

Paint, Caterpillar Yellow  
Vibration damper  
Lifting eyes

## PERFORMANCE CURVES


IND - B - DM8170-00



Engine Speed rpm	Engine Power kW	Torque N·m	BSFC g/kW-hr	Fuel Rate L/hr
2200	168	729	233	46.7
2100	168	764	232.1	46.5
2000	168	802	230	46.1
1900	168	844	226.9	45.4
1800	168	891	223.6	44.8
1700	166	934	221.1	43.8
1600	163	970	220.6	42.8
1500	157	1001	220.7	41.4
1400	151	1028	221.1	39.7
1300	138	1013	221.7	36.4

## PERFORMANCE CURVES

IND - B - DM8170-00




Engine Speed rpm	Engine Power bhp	Engine Torque lb-ft	BSFC lb/bhp-hr	Fuel Rate gal/hr
2200	225	538	.383	12.3
2100	225	563	.382	12.3
2000	225	592	.378	12.2
1900	225	623	.373	12.0
1800	225	657	.368	11.8
1700	223	689	.363	11.6
1600	218	715	.363	11.3
1500	211	738	.363	10.9
1400	202	758	.363	10.5
1300	185	747	.364	9.6

## RATINGS AND CONDITIONS

**IND - B** For service where power and/or speed are cyclic (time at full load not to exceed 80%).

**Engine Performance Diesel Engines** — 7 liter and higher All rating conditions are based on SAE J1995, inlet air standard conditions of 99 kPa (29.31 in. Hg) dry barometer and 25°C (77°F) temperature. Performance measured using a standard fuel with fuel gravity of 35° API having a lower heating value of 42,780 kJ/kg (18,390 btu/lb) when used at 29° C (84.2° F) with a density of 838.9 g/L.



### Engine Dimensions

(1) Length	2029.5 mm (79.9 in)
(2) Width	974.8 mm (38.38 in)
(3) Height	1986.3 mm (78.2 in)

Note: Do not use for installation design. See general dimension drawings for detail (Drawing # 3380381).

Performance Number: DM8170-00

Feature Code: C07DI04 Arr. Number: 2707235

Materials and specifications are subject to change without notice.

16292533

© 2011 Caterpillar

All rights reserved.

The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, SAFETY.CAT.COM their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.