

AP555E

Mobil-trac™ Asphalt Paver

"Smoothness Built-in"



Leading-Edge Technology

- Advisor display, visual reference
- Automatic engine speed control, fuel savings
- Cruise control feature, match paving train
- Integrated Cat® Grade and Slope Control
- Screed lock, prevents screed settling
- Friction steer, holds steering direction in turns
- Power Management, maintains engine speed under load

Unmatched Versatility


- Independent control of each auger and each conveyor, consistent head of material
- 2 or 4 feed sensor capability (sonic or mechanical)
- Ratio control dials, automatically adjusts for width changes
- Hydraulic mainframe extensions
- Reversible augers and conveyors
- Rigid electric creeper, excellent stability



Ventilation System



Mobil-trac™ Belt



Advisor Display

Exceptional Visibility and Comfort

- Front-mounted cooling system:
 - directs hot engine air away from crew
 - re-directs asphalt fumes cloud that occurs when truck dumping
- Quiet operation, easy communication
- Ventilation system, cleaner working environment

Durable Mobil-trac™ Undercarriage

- Oscillating bogies, minimize tow-point movement for smoother results
- Long-belt life, 4000-7000 hour belt life
- Excellent traction, soft/hard base capability
- Smooth-belt, less base disturbance and minimizes handwork
- Tread-bar belt, ultimate traction in any condition
- Speed of wheeled pavers

Excellent Serviceability

- Advisor display, lists service codes
- Manual overrides on hydraulics
- Visual indicators for routine service checks
- Electronic Control Modules monitor system performance
- Long service intervals, minimize costs



AP555E Asphalt Paver Specifications

Operating Weights*

Tractor	13 305 kg	29,335 lb
with AS2252C	16 005 kg	35,290 lb
with AS3251C	16 240 kg	35,810 lb

Machine Dimensions (operating)

Tractor length with push roller	4.38 m	(14' 4")
Overall machine length w/screed		
AS2252C (walkway deployed)	5.80 m	(19' 0")
AS3251C	6.11 m	(20' 0")
Tractor operating width (hopper lowered)	3.31 m	(10' 10")

Transport Dimensions

Transport height (exhaust, seat lowered)	2.82 m	(9' 3")
Transport width with screed end gates (hopper raised)	2.72 m	(8' 11")
Transport width w/o screed end gates (hopper raised)	2.50 m	(8' 2")

Screed Paving Width

AS2252C, maximum range	2.50 m - 5.60 m	8' 2" - 18' 5"
AS3251C, maximum range	2.44 m - 6.15 m	8' - 20' 2"
Maximum paving depth	305 mm	12"

Optional Equipment

- Auger and Mainframe Extensions
- Auxiliary Power Panel
- Cut-Off Shoe
- Decelerator Pedals
- Ecological Washdown System and Hose Reel
- Feeder Sensor (Mechanical or Sonic)
- Friction Steering
- Fumes Extraction
- Grade and Slope Controls (Cat/Topcon)
- Leveling Devices
- Lights (Working or Rooding)
- Mobil-trac Belt (Smooth or Treadbar)
- Oscillating Push Roller
- Power Folding Front Apron
- Power Mainframe Extensions
- Product Link
- Screed Extensions
- Tow-point Indicators (Upper)
- Track Plow
- Truck Hitch
- Umbrella
- Up-time Kit
- Warning Beacon
- Wide Width Paving Packages

Optional equipment may vary per region, contact your local Cat Dealer for more information.

The Cat® Advantage - Single Source Provider

	Cat Dealer	Competitive Dealer	Comment
Convenient worldwide dealer locations	✓		More than our 5 largest competitors combined
Engine service	✓		Cat machines feature Cat engines
Machine service	✓	✓	
Service technician trained for paving equipment	✓		Cat technicians trained on Cat machines
24/7/365 parts availability on most service parts	✓		Long lead times for competitive OEM parts
New OEM parts	✓		Competition offers inferior aftermarket parts
Reconditioned OEM parts	✓		Rebuilt to OEM spec by Cat Reman
Available financing options	✓		Available through Cat Financial
Application expertise	✓		Personnel understand the paving business
Machine rental	✓		Keeps your capital expense low
Products with high resale value	✓		Durable Cat machines built to last

QEXQ1476 (11-10)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2010 Caterpillar
All Rights Reserved
Printed in U.S.A.

Materials and specifications are subject to change without notice.
Featured machines in photos may include additional equipment.
See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

