AP1000E

Asphalt Paver

"High Production, Smooth Results"



Leading-Edge Technology

- Cat® C7.1 engine meets Tier 4 Interim/Stage IIIB emissions standards
- Advisor display, visual reference
- Self diagnostics from multiple ECMs displayed through Advisor
- Automatic engine speed control, fuel savings
- ECO-mode (1650 engine rpm) conserves fuel
- Cruise control feature, match paving train
- Screed lock, prevents screed settling
- Power Management, maintains engine speed under load

Award Winning Smoothness Features

- Independent control of each auger and each conveyor, consistent head of material
- 2 or 4 sensor mix delivery system, automatically adjusts for width changes
- Hydraulic mainframe extensions
- Reversible augers and conveyors4-position adjustable push roller
- Rigid electric screeds, excellent stability

Excellent Serviceability

- · Advisor display, lists service codes
- Electronic Control Modules monitor system performance and provide self diagnostics
- Manual overrides on hydraulics
- Visual indicators for routine service checks
- Long service intervals, minimize costs

Cat® Grade and Slope Control

- True Averaging, continuously through ECM
- Factory integrated system, single source supplier
- Single or dual displays
- Single display can control one or both sides of the screed
- Text-based menus, with multiple languages
- Durable enclosure with swivel capability
- Sonic or contacting grade sensors
- Sonic averaging beam; utilizes up to 3 sonic sensors

Wheel Undercarriage

- Best in class turning radius of 0.5 m (1.5 ft)
- Travel speeds of 0-20 km/hr (0-12 mph)
- Position sensor helps maintain travel speeds when making turns by adjusting the drive speed according to the steering angle of the front wheels, limits wear produces better mat
- Front wheel assist or all-wheel drive options



Cat Grade and Slope Control



Advisor Display



| AP1000E Asphalt Paver Specifications | | | Optional Equipment | |
|--|-------------------|--------------|---|--|
| Operating Weights* | • All-Wheel Drive | | | |
| Tractor | 15 160 kg | 33,352 lb | Auger and Mainframe Extensions | |
| w/AS2302C | 18 245 kg | 40,223 lb | • Auxiliary Power Panel • Cut-Off Shoe • Decelerator Pedals | |
| w/AS3301C | 18 427 kg | 40,625 lb | | |
| w/AS3301C and C6.6 engine | 18 660 kg | 41,138 lb | Ecological Washdown System and | |
| w/AS4251C | 19 508 kg | 43,008 lb | Hose Reel | |
| w/AS4251C and C6.6 engine | 19 742 kg | 43,524 lb | • Feeder Sensor (Mechanical or Sonic) | |
| w/AS4252C | 18 561 kg | 40,920 lb | | |
| w/AS452C and C6.6 engine | 18 795 kg | 41,436 lb | • Front Wheel Assist | |
| Note: C6.6 engine utilized in Tier 3/Stage IIIA markets. | | | • Fumes Extraction | |
| | | | • Grade and Slope Controls | |
| Machine Dimensions (operating) | | 4 51 9 11 | (Cat/Topcon) - • Hard Top Canopy - • Leveling Devices | |
| Tractor length with push roller | 4.95 m | 16' 3" | | |
| Overall machine length w/screed | | | Lights (Working or Roading) | |
| AS2302C (walkway deployed) | 5.46 m | 17' 11" | Oscillating Push Roller | |
| AS3301C | 6.61 m | 21' 7" | Power Folding Front Apron | |
| AS4251C | 6.52 m | 21' 4" | Power Mainframe Extensions | |
| AS4252C | 6.63 m | 21' 8" | Product Link | |
| Tractor operating width (hopper lowered) | 3.52 m | 11' 7" | Screed Extensions | |
| | | | • Tow-point Indicators (Upper) | |
| Transport Dimensions | | | Truck Hitch | |
| Transport height (fumes stack, seat lowered) | 2.85 m | 9' 4" | • Umbrella | |
| Transport width with screed end gates (hopper raised) | 3.24 m | 10' 8" | • Up-time Kit | |
| Transport width w/o screed end gates (hopper raised) | 3.00 m | 9' 10" | Warning BeaconWide Width Paving Packages | |
| Screed Paving Width | | | _ Optional equipment may vary per | |
| AS2302C, maximum range | 3.05 m - 6.70 m | 10' - 22' | _ region, contact your local Cat Dealer | |
| AS3301C, maximum range | 3.05 m - 7.38 m | 10' - 24' 2" | for more information. | |
| AS4251C, AS4252C, maximum range | 3.05 m - 8.00 m | 10' - 26' 4" | | |
| Maximum paving depth | 305 mm | 12" | _ | |

| The Cat® | Advantage | - Single | e Source | Provider |
|----------|-----------|----------|----------|----------|
|----------|-----------|----------|----------|----------|

| | Cat Dealer | Competitive Dealer | Comment |
|---|---------------|-----------------------|---|
| Convenient worldwide dealer locations | V | | More than our 5 largest competitors combined |
| Engine service | V | | Cat machines feature Cat engines |
| Machine service | V | ✓ | |
| Service technician trained for paving equipment | V | | Cat technicians trained on Cat machines |
| 24/7/365 parts availability on most service parts | ✓ | | Long lead times for competitive OEM parts |
| New OEM parts | ✓ | | Competition offers inferior aftermarket parts |
| Reconditioned OEM parts | ✓ | | Rebuilt to OEM spec by Cat Reman |
| Available financing options | ✓ | | Available through Cat Financial |
| Application expertise | ✓ | | Personnel understand the paving business |
| Machine rental | V | | Keeps your capital expense low |
| Products with high resale value | V | | Durable Cat machines built to last |

QEXQ1485 (4-11)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com $\,$

© 2011 Caterpillar All Rights Reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

