



# Cat<sup>®</sup> CST45 M

## GEARBOX

### Specifications

#### Typical Application

Chain Type Longwall Machinery like Armored Face Conveyors (AFC) and Plow Systems

#### Maximum Output Torque (for 3 sec) $T_{max}$ [N·m]

**P-45 M CST** 450 000 N·m 331,858 lb/ft

#### Rated Power P

Ratio i [-]

16  
21  
28  
33  
39  
45  
50

Rated Power P  
(n = 1,485 rpm)

800 kW  
800 kW  
800 kW  
800 kW  
700 kW  
540 kW  
500 kW

Rated Power P  
(n = 1,782 rpm)

1,305 hp  
1,305 hp  
1,305 hp  
1,305 hp  
1,142 hp  
881 hp  
816 hp

#### Dimensions

Length	1697 mm	66.8 in
Width	1120 mm	44.1 in
Height	1060 mm	41.7 in

#### Capacity


Oil Quantity	320 L	85 gal
Gearbox Weight (without oil)	7200 kg	15,873 lb

#### Requirements of Cooling Water

Required Cooling Water Quantity	30 L/min	7.9 gal/min
Maximum Water Inlet Temperature	25° C/298.15 K	77° F/298.15 K

#### Shaft Design

Input Shaft (cylindrical)	DIN 5480-W 120×4
Output Shaft with Internal Tothing	DIN 5480-N 260×10×30×24



#### GEARBOX RATIO i [-]

Rated Power P [hp] @ 60 Hz  
Rated Power P [kW] @ 50 Hz

# CST45 M Gearbox

---

For more complete information on Cat® products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

© 2017 Caterpillar  
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

AEHQ6877-01 (01-2017)  
Replaces AEHQ6877

