

DIESEL GENERATOR SET



DE165E3

EU stage IIIA emissions compliant.
Suitable for Mobile Applications in the European Community.

Image shown may not reflect actual package

Output Ratings		
Generator Set Model - 3 Phase	Prime*	Standby*
400/230V, 50 Hz	150.0 kVA 120.0 kW	165.0 kVA 132.0 kW
	-	-
	-	-

* Refer to ratings definitions on page 4.
Ratings at 0.8 power factor.

Technical Data		
Engine Make & Model:	Cat® C7.1	
Generator Model:	R2453L4	
Control Panel:	EMCP 4.1	
Base Frame Type:	Heavy Duty Fabricated Steel	
Circuit Breaker Type:	3 Pole MCCB	
Frequency:	50 Hz	60 Hz
Engine Speed: RPM	1500	-
Fuel Tank Capacity: litres (US gal)	327 (86.4)	
Fuel Consumption, Prime: l/hr (US gal/hr)	35.2 (9.3)	-
Fuel Consumption, Standby : l/hr (US gal/hr)	37.8 (10.0)	-

DIESEL GENERATOR SET



Engine Technical Data

Physical Data	
Manufacturer:	Caterpillar
Model:	C7.1
No. of Cylinders/Alignment:	6 / In Line
Cycle:	4 Stroke
Induction:	Turbocharged Air To Air Charge Cooled
Cooling Method:	Water
Governing Type:	Electronic
Governing Class:	ISO 8528 G2
Compression Ratio:	16.8:1
Displacement: l (cu.in)	7.0 (427.8)
Bore/Stroke: mm (in)	105.0 (4.1)/135.0 (5.3)
Moment of Inertia: kg m² (lb. in²)	1.53 (5228)
Engine Electrical System:	
-Voltage/Ground:	12/Negative
-Battery Charger Amps:	65
Weight: kg (lb) - Dry:	788 (1737)
- Wet:	822 (1812)

Air System	50 Hz	60 Hz
Air Filter Type:	Replaceable Element	
Combustion Air Flow:		
m ³ /min (cfm)	-Standby: 11.0 (388)	-
	-Prime: 10.6 (374)	-
Max. Combustion Air Intake		
Restriction: kPa (in H₂O)	8.0 (32.1)	-
Radiator Cooling Air Flow:		
m ³ /min (cfm)	276.0 (9747)	-
External Restriction to		
Cooling Air Flow: Pa (in H₂O)	125 (0.5)	-

Cooling System	50 Hz	60 Hz
Cooling System Capacity:		
l (US gal)	21.0 (5.5)	-
Water Pump Type:	Centrifugal	
Heat Rejected to Water & Lube Oil: kW (Btu/min)		
-Standby:	72.5 (4123)	-
-Prime:	64.0 (3640)	-
Heat Radiation to Room: Heat radiated from engine and alternator		
kW (Btu/min)	-Standby: 35.5 (2019)	-
	-Prime: 33.0 (1877)	-
Radiator Fan Load: kW (hp)	4.5 (6.0)	-
Cooling system designed to operate in ambient conditions up to 50°C (122°F). Contact your local Cat dealer for power ratings at specific site conditions.		

Lubrication System	
Oil Filter Type:	Spin-On, Full Flow
Total Oil Capacity l (US gal):	17.5 (4.6)
Oil Pan l (US gal):	15.5 (4.1)
Oil Type:	API CH4 / CI4 15W-40
Cooling Method:	Water

Performance	50 Hz	60 Hz
Engine Speed: RPM	1500	-
Gross Engine Power: kW (hp)		
-Standby:	149.7 (201.0)	-
-Prime:	135.9 (182.0)	-
BMEP: kPa (psi)		
-Standby:	1708.0 (247.7)	-
-Prime:	1550.0 (224.8)	-
Regenerative Power: kW	11.5	-

Fuel System				
Fuel Filter Type:	Replaceable Element			
Recommended Fuel:	Class A2 Diesel or BSEN590			
Fuel Consumption: l/hr (US gal/hr)				
	110% Load	100% Load	75% Load	50% Load
Prime				
50 Hz	37.8 (10.0)	35.2 (9.3)	28.2 (7.4)	20.0 (5.3)
60 Hz	-	-	-	-
Standby				
50 Hz		37.8 (10.0)	30.4 (8.0)	21.7 (5.7)
60 Hz		-	-	-
(based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)				

Exhaust System	50 Hz	60 Hz
Silencer Type:	Industrial	
Silencer Model & Quantity:	EXSY1 (1)	
Pressure Drop Across		
Silencer System: kPa (in Hg)	0.15 (0.044)	-
Silencer Noise Reduction		
Level: dB	10	-
Max. Allowable Back		
Pressure: kPa (in. Hg)	15.0 (4.4)	-
Exhaust Gas Flow:		
m ³ /min (cfm)	-Standby: 25.0 (883)	-
	-Prime: 24.0 (848)	-
Exhaust Gas Temperature: °C (°F)		
-Standby:	513 (955)	-
-Prime:	513 (955)	-

DIESEL GENERATOR SET



Technical Data


Voltage 50 Hz	Prime		Standby	
	kVA	kW	kVA	kW
415/240V	149.9	119.9	165.0	132.0
400/230V	150.0	120.0	165.0	132.0
380/220V	149.5	119.6	165.0	132.0

Voltage 60 Hz	Prime		Standby	
	kVA	kW	kVA	kW

Weights & Dimensions

Weights: kg (lb)	
Net (+ lube oil)	1590 (3505)
Wet (+ lube oil & coolant)	1611 (3552)
Fuel, lube oil & coolant	1889 (4165)

Dimensions: mm (in)	
Length	2450 (96.5)
Width	1010 (39.8)
Height	1554 (61.2)



Note: General configuration not to be used for installation. See general dimension drawings for detail.

Definitions

Standby Rating

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

Prime Rating

Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated kW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Standard Reference Conditions

Note: Standard reference conditions 25°C (77°F) air inlet temp, 100m (328ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

General Data

Documents

A full set of operation and maintenance manuals and circuit wiring diagrams.

Quality Standards

The equipment meets the following standards: **IEC60034-1, IEC60034-22, ISO3046, ISO8528, NEMA MG 1-32, NEMA MG 1-33, 2004/108/EC, 2006/42/EC, 2006/95/EC.**

Price List: C7.1PGBI, C7.1PGBT

Gen. Arr. Number:502-7328

Source: European or China

LEHE1165-00 (08/16)

www.Cat-ElectricPower.com

© 2016 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice. The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.