

DEMAND THE BEST.

CAT[®] AGRICULTURE PRODUCT LINEUP



CONTENTS

- > COMPACT WHEEL LOADERS 4-5
- > SMALL WHEEL LOADERS 6-7
- > TELEHANDLERS 8-9
- > SKID STEER LOADERS 10-11
- > COMPACT TRACK LOADERS 12-13
- > MINI EXCAVATORS 14-15



Farming's a demanding business. Cat[®] agricultural products are built to meet those demands.

Engineered to be tough and built to be reliable, Caterpillar's range addresses both the diversity of modern farming as well as the needs of the progressive farmer. So whether you're looking for something to cope with the rigours of livestock enterprises, or to meet the heavy-duty expectations of a large arable operation, Cat equipment provides the reassurance, dependability and capability that says you made the right choice.

Join thousands of other farmers around the world whose businesses rely on Caterpillar to keep them running strong.





Turn your hand to anything and everything with this well-engineered design. On-the-go adjustability, using the Cat onboard computer, gives you access to as much or as little power as you need, making handling and manoeuvrability a breeze. Meanwhile, Caterpillar's hallmark ground level serviceability means maintenance won't be a chore.



COMPACT WHEEL LOADERS

A PERFORMANCE LIFT



	906M Ag Handler	907M Ag Handler	908M Ag Handler	910M	914M	918M
Loader Arm Arrangement	Standard Lift	Standard Lift	Standard Lift	Standard Lift/High Lift	Standard Lift/High Lift	Standard Lift
Gross Engine Power	74 hp (55 kW)	74 hp (55 kW)	74 hp (55 kW)	100 hp (74 kW)	100 hp (74 kW)	117 hp (87 kW)
Operating Weight	5,987 kg	6,078 kg	6,853 kg	8,297/8,821 kg	8,754/9,095 kg	9,565 kg
Tipping Load (Full Turn)	3,482 kg	3,571 kg	4,185 kg	5,042/4,688 kg	5,254/4,619 kg	5,863 kg
Bucket Pin Height	3,212 mm	3,212 mm	3,333 mm	3,673mm/4,030mm	3,701/4,055 mm	3,818 mm
Height: Ground to Cab	2,911 mm	3,034 mm	3,098 mm	3,020 mm	3,093 mm	3,110 mm
Length: Overall	5,552 mm	5,550 mm	5,759 mm	6,373/6,825 mm	6,489/6,962 mm	6,768 mm
Width: Over Tyres	1,840 mm	1,840 mm	1,990 mm	2,259 mm	2,259 mm	2,259 mm

MORE THAN JUST A LOADING SHOVEL

Stable, fast and versatile, this is a machine characterised by its exceptional loading and fork performance. Maximise that versatility by choosing from the comprehensive range of Cat Attachments to ensure you can get the most from your Compact Wheel Loader.

A CAB THAT KEEPS YOU WORKING

As soon as you get in the cab, you'll know it was designed by an operator. Spacious, comfortable and quiet, you'll tire of the job long before you tire of the cab, thanks to a redesigned pedal layout, improved console and joystick, and pillar-less rear glass plus a rearview camera for complete confidence in your surroundings.

INTUITIVE CONTROLS

Whether you're on yard duty or hauling between farms, each model in the Compact Wheel Loader range is simple and easy to control, reducing operator fatigue and improving work rates.

Power, economy and comfort are the hallmarks of the Cat Small Wheel Loader range – so much so that we believe they'll become the benchmark by which other similar farm machines are judged. At the heart of the machine is our Cat C7.1 ACERT™ engine, providing high torque at low speed. Couple that to its intelligent hystat power train and the scene is set for an outstanding combination: power as you need it, industry-leading fuel economy and a quiet, spacious cab that puts you in complete control.



SMALL WHEEL LOADERS POWER. YOU CHOOSE.



	926M	926M Ag Handler	930M	938M
Loader Arm Arrangement	Standard Lift/High Lift	Standard Lift/High Lift	Standard Lift/High Lift	Standard Lift/High Lift
Gross Engine Power	155 hp (114 kW)	166 hp (122 kW)	166 hp (122 kW)	190 hp (140 kW)
Operating Weight	12,696/12,974 kg	12,994/13,272 kg	13,627/13,859 kg	16,001/16,168 kg
Tipping Load (Full Turn)	8,873/6,402 kg	7,460/5,575 kg	8,873/6,402 kg	10,517/7,448 kg
Bucket Pin Height	3,907/4,400 mm	3,982/4,475 mm	3,907/4,500 mm	3,969/5,853 mm
Height: Ground to Cab	3,340 mm	3,415 mm	3,340 mm	3,340 mm
Length: Overall	7,451/8,093 mm	7,460/8,117 mm	7,530/8,324 mm	7,656/8,397 mm
Width: Over Tyres	2,540 mm	2,787 mm	2,540 mm	2,693 mm



POWER. YOU CHOOSE.

A choice of power modes means you can choose between maximum fuel efficiency, or boosted power to get the job done more quickly. And a flexible power train, with electronically controlled transmission, means you always feel in control, no matter what the task at hand.

MAKE WORK EASY

Drive, lift and steer simultaneously with smooth and predictable control – the machine does exactly what you ask of it. Programmable controls can be set on-the-go, ideal for situations where the work cycle is repeatable, or in areas with limited manoeuvrability or clearance. And Machine Application Profiles allow the operator to set up the machine in the way that's most suited to the job being done.

STAY COMFORTABLE, STAY IN CONTROL

In the cab, you're not only in charge but also in comfort. Seat-mounted controls. All-round visibility including a rearview camera. Large, at-a-glance displays. Filtration that's designed for agriculture, keeping out smells and improving cab air quality. And a whisper-quiet standard cab sound level of just 64dB(A). This is the best seat on the farm.



From our most compact model to the most powerful, there's a Cat Telehandler to suit your farm. Our range boasts superior design and no compromise on features, plus unrivalled lift and reach capabilities. New engines meet the latest EU emission standards and deliver remarkable fuel efficiency. And of course there's the Cat cab, where you can spend the day in comfort while maximising productivity with the machine's superb appetite for work.



TELEHANDLERS EXTEND YOUR CAPABILITY



TH357D



TH408D



TH3510D

Gross Engine Power	111 /124 hp (83/92.6 kW)	111 /124 /142 hp (83/92.6/106 kW)	111 /124 /142 hp (83/92.6/106 kW)
Operating Weight	7,785 kg	8,526 kg	9,149 kg
Maximum Lift Capacity	3,500 kg	4,000 kg	3,500 kg
Maximum Lift Height	7,000 mm	7,600 mm	9,800 mm
Travel Speed*	40 km/h	40 km/h	40 km/h
Transmission	Autoshift 6 Speed	Autoshift 6 Speed	Autoshift 6 Speed
Height: Ground to Cab	2,475 mm	2,475 mm	2,475 mm
Length: Overall	5,000 mm	5,286 mm	5,260 mm
Width: Over Tyres	2,382 mm	2,382 mm	2,382 mm

* Maximum travel speed may vary dependent on machine configuration



LIMITED SPACE? THIS ONE'S FOR YOU.

Thought your shed was too small for a telehandler? Our most compact model is just 1.8 m wide and 1.9 m tall, but will still lift 2,500 kg to 5.6 m. Three steering modes ensure maximum manoeuvrability in the tightest of spots. And a low boom pivot point lends outstanding right-hand and rear visibility.

WHAT YOU NEED, AS YOU NEED IT, WHEN YOU NEED IT

Cat Telehandlers' fast-response, multi-function hydraulics make our farm telehandlers some of the simplest to operate. Fast boom cycle times, small turning circles and a single-level joystick boasting simultaneous capability all combine to speed up jobs and get them completed more quickly, giving you more time for those other jobs around the farm. Meanwhile, a choice of transmission options and limited slip differential gives you flexibility and confidence, even on those toughest farm tasks.

AN ALL-ROUND MULTITASKER

One Cat machine, multiple uses. Quick-coupling attachments make light work of many tasks. With the renowned comfort of our cabs, including an air-suspension seat and powerful heating and ventilation units, you'll soon be wondering what other jobs you can turn to with your Cat Telehandler.



For all-round operability, versatility and comfort, you can't go wrong with a Cat Skid Steer Loader. Fingertip manoeuvrability, high work rates and the high performance hydraulics and power train you've come to expect from Caterpillar make this a machine that's eminently suitable for numerous tasks around the farm, thanks to its rugged durability.



SKID STEER LOADERS CAPABILITY REDEFINED



216B3 **226D** **236D** **246D** **232D** **242D** **262D (XPS)** **272D2 (XPS)**

	216B3	226D	236D	246D	232D	242D	262D (XPS)	272D2 (XPS)
Loader Arm Arrangement	Radial	Radial	Radial	Radial	Vertical	Vertical	Vertical	Vertical
Gross Engine Power	51 hp (38 kW)	67 hp (50 kW)	74 hp (55.4 kW)	74 hp (55.4 kW)	67 hp (50 kW)	74 hp (55.4 kW)	74 hp (55.4 kW)	98 hp (73 kW)
Operating Weight	2,581 kg	2,588 kg	2,975 kg	3,368 kg	2,818 kg	3,166 kg	3,634 kg	3,977 kg
Rated Operating Capacity*	680 kg	749 kg	900 kg	1,088 kg	885 kg	1,066 kg	1,338 kg	1,656 kg
Maximum Bucket Pin Height	2,854mm	2,818 mm	3,122 mm	3,154 mm	3,001 mm	3,076 mm	3,172 mm	3,265 mm
Hydraulic Flow (Standard Flow / High Flow) (L/min)	61/ -	69/99	76/112	86/121	69/99	76/112	86/121	86/121
Height: Ground to Cab	1,950 mm	2,028 mm	2,082 mm	2,110 mm	2,029 mm	2,111 mm	2,110 mm	2,094 mm
Length: Overall	3,233 mm	3,234 mm	3,487 mm	3,708 mm	3,233 mm	3,487 mm	3,714 mm	3,945 mm
Width: Over Tyres	1,525 mm	1,497 mm	1,676 mm	1,676 mm	1,497 mm	1,676 mm	1,676 mm	1,829 mm

*With additional counterweight

CAB COMFORT

Industry-leading sealed and pressurized cab option provides a cleaner and quieter operating environment with excellent work tool visibility. Available high-back, heated, air ride seat with seat mounted adjustable joystick controls make Cat Skid Steer Loaders the industry leader in operator comfort.

CONTROL AS YOU LIKE IT

Hand or foot controls? With the Cat Skid Steer, you can choose between the two. Tight space? You can turn within the machine's own footprint. Difficult terrain? Choose from a range of undercarriages suitable to take on any ground conditions – including traditional wheeled skid steer loaders. If you require lower ground pressure, opt for our compact track loaders.

OPERATIONAL FLEXIBILITY

Make the most of your machine's versatility and put it to even more uses around the farm with the comprehensive range of Cat Work Tools and Attachments. Forks, brooms, augers, buckets, brushcutters and many more, make the Cat Skid Steer the true Swiss Army knife of farm machinery. Choose between the standard quick coupling system for rapid tool change, or for even greater ease there's a hydraulic option – so you don't even have to leave the cab.



Experience the difference with our Cat Compact Track Loaders, which help you get more work done. Our spacious operator stations feature intuitive controls and an array of time-saving features. They're built for outstanding performance, comfort and versatility. Delivering incredibly low ground pressure, it's almost as though these machines glide over the ground. Partner them with our range of Cat Attachments and this is the Swiss Army knife of farm machinery.

COMPACT TRACK LOADERS

UNMATCHED MANOEUVRABILITY



239D **249D** **259D** **279D (XPS)** **299D2 (XPS)**

	239D	249D	259D	279D (XPS)	299D2 (XPS)
Loader Arm Arrangement	Radial	Vertical	Vertical	Vertical	Vertical
Gross Engine Power	67 hp (50 kW)	67 hp (50 kW)	74 hp (55.4 kW)	74 hp (55.4 kW)	98 hp (73 kW)
Operating Weight	3,306 kg	3,486 kg	4,013 kg	4,487 kg	5,114 kg
Rated Operating Capacity*	1,021 kg	1,134 kg	1,406 kg	1,444 kg	2,204 kg
Maximum Bucket Pin Height	2,825 mm	3,002 mm	3,075 mm	3,173 mm	3,208 mm
Hydraulic Flow (Standard Flow / High Flow) (L/min)	69/99	69/99	76/112	86 (121)	86 (121)
Height: Ground to Cab	2,034 mm	2,039 mm	2,111 mm	2,113 mm	2,125 mm
Length: Overall	3,234 mm	3,233 mm	3,486 mm	3,714 mm	3,931 mm
Width: Over Tracks**	1,676 mm	1,676 mm	1,676 mm	1,931 mm***	1,931 mm***

*With additional counterweight **320 mm track option ***400 mm track option



POWERFUL PERFORMANCE

The high-performance power train provides maximum performance and production capability through the Electronic Torque Management system and an electronic hand/foot throttle with decel pedal capability. A High Flow hydraulic system is available for applications that demand maximum hydraulic work tool performance. An electronically controlled Cat C2.2 engine delivers high horsepower and torque while meeting EU Stage IIIB (U.S. EPA Tier 4 Final) emission standards.

SUSPENDED UNDERCARRIAGE

The standard fully independent torsion axle suspension combined with the optional Speed Sensitive Ride Control system improves operation on rough terrain, enabling better load retention, increased productivity and greater operator comfort. You can work in a broader range of applications with an optional wide bar-tread track that delivers better traction in snow, more flotation and less ground disturbance.



Simple. Safe. And the most comfortable to operate. The Cat Mini Excavator range works in the toughest of environments, because it's been designed that way. The compact radius design allows you to reach the tightest of places, while the class-leading cab provides for easy operation – all day long. So when you're after a tool for all jobs, you'll find the Cat Mini Excavator fits the bill, with its hydraulic quick hitch, impressive array of attachments and customary Caterpillar quality. You'll never look back on your purchase.



MINI EXCAVATORS

THINK BIG. BUY SMALL.



OPERATING WEIGHT

 300.9D 1,020 kg	 301.4C 1,710 kg	 301.7D 1,980 kg	 301.7D CR 1,690 kg	 302.4D 2,320 kg
 302.7D CR 2,670 kg	 303E CR 3,530 kg	 303.5ECR 3,692 kg	 304E2 CR 4,039 kg	 304.5E2 XTC 4,080 kg
 305E2 CR 5,185 kg	 305.5E2 CR 5,423 kg	 307E2 7,270 kg	 308E2 CR 8,400 kg	

PERFORMANCE. IT'S SUPERIOR.

With outstanding specifications across the range, from the 300.9D right up to the advanced 308E2 CR, you won't be disappointed with the Cat Mini Excavator. Whether you need a compact radius, a 200 degree bucket rotation or just good old-fashioned digging power, Cat excavators deliver. Add in highly attractive lifetime operating and owning costs and Caterpillar's ever-present focus on safety and security, you've got a machine that's head and shoulders above the competition.

EVERYTHING YOU NEED, AND MORE

Whether it's the cab or the canopy version you choose, there's an impressive list of standard equipment on the Cat Mini Excavator. Auxiliary hydraulics with one and two-way flow. A full suspension seat. Onboard diagnostics monitor. The blade float function to improve productivity and efficiency. They're all features designed to deliver benefits.

