



Cat[®] 316F L

Hydraulic Excavator

2017

The Cat[®] 316F L is a perfect choice for customers who value versatility, reliability, durability, and maximum efficiency.

Performance

- The C4.4 ACERT[™] Japan 2014 (Tier 4 Final) engine is powerful and efficient.
- Advanced control automatically manages pump and engine speed for maximum efficiency.
- Two power modes, standard and eco mode, help you actively manage fuel consumption.
- Engine idle shutdown saves fuel, reduces emissions, and extends service intervals.

Versatility

- Site prep and finishing work are quick and easy with a wide range of Cat work tools.
- Utility work is fast and flawless with a Cat bucket.
- See the whole more profitable attachment line for your machine at www.cat.com/attachments.

Comfort

- The roll-over protective structure (ROPS) certified cab is quiet and comfortable.
- Automatic climate control helps maintain consistent cab temperature.
- Joystick consoles and armrests are adjustable.
- The LCD monitor is easy to navigate and programmable in 42 languages.

Serviceability

- Many routine service and maintenance points can be accessed from ground level reducing the time taken to check and service your machine.
- Wide service doors make for easy access.
- Filters are grouped to reduce service time.
- The cooling package is designed to prevent plugging, make blowing off debris easy.

Technology

- Cat Connect technology improves job site efficiency.
- Product Link[™]/VisionLink[®] connects owners to the machine, providing access to location, hours, fuel consumption, idle time, events, and diagnostic codes.

Durability

- The large swing bearing is secured with elongated bolts to help handle the most swing-intensive work.
- Robot welded, Caterpillar designed boom and sticks are built for long service.
- Greased track link between pins and bushings increases undercarriage life and reduces noise.

Safety

- The hydraulic activation lever locks out all hydraulic functions.
- Handrails, anti-skid plating, and countersunk bolts reduce slipping and tripping.
- A ground-level engine shutoff switch shuts down the engine in case of emergency.
- Standard rearview camera and mirrors enhance visibility.



オフロード法2014年
基準適合

Cat® 316F L Hydraulic Excavator

Engine	
Engine Model	Cat C4.4 ACERT
Net Power – SAE J1349/ISO 9249	87.5 kW
Engine Power – ISO 14396	91.0 kW
Bore	105 mm
Stroke	127 mm
Displacement	4.4 L

Hydraulic System	
Main System – Maximum Flow (total)	300 L/min
Maximum Pressure – Equipment	35 000 kPa
Maximum Pressure – Travel	35 000 kPa
Maximum Pressure – Swing	25 000 kPa
Pilot System – Maximum Flow	23 L/min
Pilot System – Maximum Pressure	4120 kPa

Drive	
Maximum Travel Speed	5.3 km/h
Maximum Drawbar Pull	156 kN

Machine Weights	
Operating Weight*	17 100 kg
*5.1 m reach boom, 2.6 m stick and 500 mm track shoes, with 0.65 m³ bucket.	

Swing	
Swing Speed	8.9 rpm
Swing Torque	49.6 kN-m

Service Refill Capacities	
Fuel Tank Capacity	290 L
DEF Tank Capacity	20 L
Cooling System	26 L
Engine Oil (with filter)	13.5 L
Swing Drive	2.4 L
Final Drive (each)	6 L
Hydraulic System (including tank)	190 L
Hydraulic Tank	120 L

Dimensions*	
Reach Boom – 5.1 m	
Stick	R2.6 m
Shipping Height	3050 mm
Shipping Length	8570 mm
Tail Swing Radius	2500 mm
Length to Center of Rollers	3170 mm
Track Length	3970 mm
Ground Clearance	440 mm
Track Gauge	1990 mm
Transport Width – 500 mm Shoes	2520 mm
Cab Height	2890 mm
Cab Height with Top Guard	3100 mm
Counterweight Clearance	1010 mm

Working Ranges*	
Reach Boom – 5.1 m	
Stick	R2.6 m
Maximum Digging Depth	6070 mm
Maximum Reach at Ground Level	8750 mm
Maximum Cutting Height	8890 mm
Maximum Loading Height	6300 mm
Minimum Loading Height	2330 mm
Maximum Vertical Wall Digging Depth	5260 mm

Bucket & Stick Forces*	
Reach Boom – 5.1 m	
Stick	R2.6 m
General Duty Bucket	
Bucket Digging Force (ISO)	114 kN
Stick Digging Force (ISO)	80 kN

*With a 0.65 m³, 1100 mm bucket.

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2017 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

Based on the Labor, Safety and Health Laws in Japan, employer of small construction equipment are required to provide specific training for all operators on machines with ship weight less than 3 metric ton. For machines greater than 3 metric ton, operator needs to obtain operator license certification from a Government approved registered training school.

AEXQ2165
(Japan)

