



CAT[®] HAMMERS

Break through Barriers

EASY TO MAINTAIN AND OPERATE • LOW OWNING AND OPERATING COSTS • LASTING EQUIPMENT VALUE

MAXIMIZING YOUR ROI

3,000-5,000 operating hours, fully rebuildable for another 3,000+ with the best resale value on the market.

GUARANTEED RELIABILITY AND POWER

Ultimate consistent, hard-hitting performance through a seamless hydraulic connection that allows faster job completion and 24/7 operation.

COMPLETELY CAT

Machine → Hammer → Parts → Dealer Support

Part of a total system solution, leveraging the machine's power and protecting your investment from damage.

PREMIUM FEATURES

- Silenced models have fully enclosed housing for quieter operation
- Automatic shut off prevents blank firing and protects the hammer from damage
- High blow rate for greater productivity
- Unique suspension system improves recoil and protects machine
- Standing level grease point for easier maintenance
- Self-contained accumulator allows immediate access for recharging
- Internal buffering reduces vibration



NOTES:

CONTACT INFORMATION:

Dealer _____ Name _____ Phone _____

CAT MACHINE MATCHING GUIDE

Machine Weight		H25D	H35E H35Es	H45E H45Es	H55E Pin-on	H55E H55Es Flat Top	H65E Pin-on	H65E H65Es Flat Top	H75Es	H95Es	H110Es	H115Es	H120Es	H130Es	H140Es	H160Es	H180Es
Minimum	t (lb)	0.8 (1,760)	1.1 (2,430)	1.5 (3,310)	2.5 (5,500)	2.5 (5,500)	3.0 (6,610)	3.0 (6,610)	6.0 (13,200)	7.0 (15,400)	11.0 (24,300)	12.0 (26,500)	16.0 (35,300)	18.0 (39,700)	24.0 (52,920)	32.0 (70,600)	42.0 (92,600)
Maximum	t (lb)	1.1 (2,430)	2.4 (5,300)	3.2 (7,060)	6.0 (13,200)	6.0 (13,200)	9.0 (19,800)	9.0 (19,800)	10.0 (22,100)	14.0 (30,900)	18.0 (39,700)	20.0 (44,100)	27.0 (59,500)	36.0 (79,400)	42.0 (92,600)	55.0 (121,300)	76.0 (167,600)
Tracked Excavators																	
300.9D		•															
301.4C			•														
301.7D CR-302.4D			•	•													
302.5C-302.7DCR				•	•	• *											
303.5D CR-306E					•	•	•										
307D-308E2 CR SB								• **	•	•							
311D RR / 311F RR										•	•						
312D-313FL GC										•	•	•					
314D CR-314F											•	•					
315D L-316F											•	•	•				
318D2-320D GC												•	•	•			
321D LCR													•	•			
323D / 323D2													•	•	•		
323F													•	•			
324D-324E													•	•	•		
325F LCR													•	•			
326D2-326F													•	•	•		
328D LCR-335F LCR														•	•		
336D-340F															•	•	
345D-352F																•	•
365C-374F																	•
Wheeled Excavators																	
M313C / M313D / M315D2											•	•					
M315C-M318F											•	•	•				
M318C-M322D2												•	•	•			
Compact Track, Multi-Terrain and Skid Steer Loaders																	
216B2-299D XHP					•	•	•	•									
Backhoe Attachments																	
BH30 / BH30W					•	•											
BH150 / BH160					•	•	•										
Backhoe Loaders																	
416D-420F2								• **	•	•							
422E-428F2								• **	•								
430E-444F2								• **	•	•							
446D-450F										•	•						

* Installation of add-on optional counterweight to machine is required.

** Hydraulic flows and pressures must be checked to verify they match the requirements for the hammer being installed.

Note 1: Caterpillar recommends the use of a suitable shield/guard system to ensure operator has adequate protection from flying debris.

Note 2: These matches are for general reference purposes for Cat machines only. When special boom and quick coupler arrangements are used, these matches may not apply.

Contact your dealer for more information about special arrangements or matching to a machine other than Cat.

BUILT FOR IT.™

Learn more at catattachmentsolutions.com

GEK00227-01 October 2016

© 2016 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, BUILT FOR IT, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

