



Progress Rail's Maintenance-of-Way (MOW) division was born out of the movement toward mechanization in the railroad industry and introduced the first Kershaw Ballast Regulator in 1945.

As a global supplier of Kershaw MOW, utility and vegetation management equipment, we provide a comprehensive line of machines to help maintain rail infrastructure and right-of-ways around the world.

The Kershaw Model 32-10 Brushcutter clears brush and overhanging tree branches from railroad right-of-ways. The Model 32-10 Brushcutter has two independently controlled booms attached to each side. A 10-foot wide cutter head is attached to the end of each boom, and can extend from zero to 90 degrees and lift up to 45 degrees from a horizontal position, or 40 degrees below. The machine is capable of cutting a 10-foot swath up to 30-feet from the track center on each side and leaves behind biodegradable mulch.

Progress Rail
A Caterpillar Company

800-633-5766

progressrail.com

▼ @Progress_Rail

KERSHAW 32-10 BRUSHCUTTER

Frame: Welded construction, lower frame is structural steel and 1-in. (25.4 mm) thick steel plate for the slewing ring support. Upper deck is structural steel and formed deck plates. Frame covered by a five (5) year warranty. Oversize 46 7/8 -inch diameter slewing ring rated for 80,000 ft-lb. Remote grease fittings for slewing ring and axle bearings. Eight-channel 6,000 psi hydraulic swivel is accessible from upper deck.


Engine: Cat C4.4, Tier III, 127 HP @ 2200 rpm.

Transmission and Axles: 3" (76 mm) diameter solid axles with chain drive from separate hydraulic motors driving both axles. Travel speed: 20 mph (32 km/hr). Two (2) propel drive motors for quicker response in work mode. #100 drive chain with hardened tooth sprockets.

Hydraulic System: Pressure compensated piston type pump direct coupled to engine. Deck rotation by hydraulic motor through gearbox. Hydraulic oil is filtered through a 100 mesh (145 micron) suction screen and 10 micron return line filter. Manifold-type stack valves for improved serviceability. Remote oil cooler accessible from ground level with dual electric cooling fans. Electric emergency pump.

Electrical System: 12 volt DC negative ground, 100 amp alternator, color coded and numbered wiring.

Air System: A 12 cfm (.34 m³/min) @1,250 rpm air compressor, engine oil lubricated, air-cooled; pressure - 110-120 psi (758-927 kPa), 613 cubic inches (10 liter) air tank. Because of Progress Rail's continuous desire to improve products, specifications and design are subject to change at any time and without notice and without incurring any obligation to incorporate these changes in previous models.



Illustrations and photographs may include optional equipment and may not include standard equipment.

Cab: Large enclosed cab with 99.5 cubic foot capacity. Ergonomically designed seat. Large front windshield with unobstructed view of boom operation through full range of motion. Hydraulic pilot-pressure bottom-ported joystick controls on operator seat with heat shields. Self-contained hydraulically driven air conditioner/heater/pressurizer unit mounted on rear wall of cab (roof mount optional). Remote controlled boom travel lock. Rubber suspension ladder steps. No service items located on cab roof on standard machine.

Wheels and Brakes: 16-in. (406 mm) cast steel wheels. External, individual composite brake shoes applied directly on the vertical centerline of wheel tread. Service brakes are air applied, spring released. Emergency/parking brakes are spring applied, air released.

Capacities - Fuel: 75 gal. (284 liters), **Hydraulic:** 70 gal. (265 liters). **Weight:** 18,000 lbs (8164.8 kg).

Boom: Ultra-wide 32 inch (813 mm) spread base root boom mount. GV-12 grapple rotator. Single tie grapple.

Optional Equipment: Basket grapple; two tie grapple; timber grapple; concrete tie grapple; rail clamps; bridge crane package; timber crane package; boom winch; two-speed propel; boom-mounted flail mower.

Progress Rail
A Caterpillar Company

800-633-5766

progressrail.com

▼ @Progress_Rail