

PRO Rental Product Range

PRO60-2

(R96 EUIIIa Equivalent)

50/60 Hz Switchable Rating

Prime Product

60 kVA / 48 kW



KEY FEATURES

Rental Ready Features

- 24 hour dual wall tankbase
- Forklift pockets
- Fully certified single point lifting eye
- Integrated heavy duty drag bar with robust skid plate
- Coolant & oil drains piped to baseframe
- EMC certified
- Fully certified spark arresting silencer
- 50/60 Hz switchable frequency
- Optimized cable entry for easy hook-up
- Sound isolated control panel with integrated power distribution access
- Robust hook-up point for lugged cable connection
- AC protected by limit switch on distribution door
- Emergency stop on control panel and enclosure
- Inboard mounted 3 way fuel valve connection for external fuel connection

Engine

- Perkins four-stroke diesel engine
- Electronic governor, mechanical actuator
- R96 EUIIIa equivalent

Single-Source Supplier

- Factory designed and fully prototype tested with certified torsion vibration analysis available
- ISO 9001:2000 compliant facility

DSE7320 Control Panel

- Fully featured power metering, protective relaying, and engine/generator control and monitoring
- Simple user friendly interface and navigation

Alternator

- Leroy Somer Alternator
- Coastal insulation protection
- Self (SHUNT) excitation

Enclosure

- Galvanized sheet steel construction with two coat polyester powder-coated finish
- Six lockable (padlock / keylock) access doors for ease of maintenance
- Safety glass control panel viewing window with key lock
- Fuel fill and battery can only be reached through lockable access doors

Reduced Environmental Impact

- R96 EUIIIa equivalent
- Dual wall base tank with 110% spill containment
- CE labelling
- Bund Level alarm
- Exceptional noise performance Meets (TBC) LWA 50 Hz (EUIIIa) Sound Power Limits (EU Machinery Directive)



PRO Rental Product Range

STANDARD EQUIPMENT

Air Inlet

- Air cleaner with dust cup and service indicator
- Turbocharger and air-to-air aftercooler

Alternator

- LL1514P frame, three-phase, random wound, 12-lead design, self-excited, 2/3 pitch
- Coastal insulation protection

Charging System

- Charging alternator; 12V, heavy duty with integral regulator and belt guards

Control Panel

- DeepSea 7320 genset mounted digital controller
- Panel mounted Emergency stop switch
- Fully featured power metering, protective relaying and engine/generator control and monitoring

Cooling System

- Cooling package mounted radiator with high ambient capability
- Pusher fan with guards
- Coolant drain line with internal brass ball control valve piped to base-frame
- Low coolant level shutdown
- 50% coolant antifreeze with corrosion inhibitor

Distribution System

- Robust steel enclosure, separate hinged, lockable door with rust resistant pinned hinges
- Main circuit breaker 4-pole, 125A with 12V DC shunt trip wired to distribution door safety switch
- Two wire remote start/stop terminals and 120-240 VAC auxiliary power connection for rapid starting
- Cable support

Enclosure

- Sound attenuating, galvanized sheet metal enclosure with exceptional noise performance
- External emergency stop switch on enclosure
- Modular panel construction with a welded roof design
- Interior walls, ceilings and ducts insulated with precision cut noise insulating materials
- Sealed quarter turn compression door latches with key and padlock capabilities
- Front and rear access provided through hinged doors
- External single point lifting
- Enclosure is protected by powder coated white paint

Engine

- Perkins 1104D heavy duty diesel engine
- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight
- ECM electronic engine control

Exhaust System

- Integrated spark arresting silencer with flexible connectors, in separate compartment



PRO Rental Product Range

Fuel System

- 301L double wall fuel tank, internal fuel fill. 24 hour based on 75% prime rating
- Engine mounted primary fuel filter (30 micron) with integral water separator and Water in Fuel sensor
- Manual Push Button priming pump
- Auxiliary connections for customer supplied fuel transfer with 3 way fuel transfer system, internally mounted within the bunded area
- Mechanical fuel gauge
- Electronic Fuel gauge with control panel display. Low level fuel warning & shutdown
- Bund level sensor. Low level warning & high level warning / shutdown

Lube System

- On engine primary & secondary oil filters, filler and dipstick
- Open crankcase breather with a fumes disposal container
- Oil drain piped to edge of baseframe with internally mounted ball valve
- 500 hour oil change intervals

Mounting System

- Generator set soft mounted using captive vibration mounts
- Heavy duty steel base frame contains integral fuel tank
- Provides 110% spill containment of all engine fluids
- Forklift pockets and heavy duty drag bar with skid plates

Starting System

- Single electric starting motor, 12V
- 12V 950CCA maintenance free battery, with single pole battery isolator switch
- 120/240 Volt single phase jacket water heater with thermostat and shut off valves

General

- Factory testing of standard generator set
- Full manufacturer's warranty, O&M manuals

AVAILABLE OPTIONS

- CE socket box with integrated MCB and RCBO protection
- Clipsal socket box with integrated MCB and RCBO protection
- Anti-condensation heater 110 or 230 VAC
- Coolant heater 110 or 230 VAC
- 12V battery charger
- UL/CSA listed 120 V, 20 Amp battery charger, shock mounted and enclosed in dust proof housing
- Permanent Magnet Generator (PMG)
- Earth Leakage
- CE labelling
- Lube oil sump pump

PRO Rental Product Range


Power Ratings

Frequency	Voltage	Prime kW (kVA)	Output Amps (A)	Breaker Rating (A)
50 Hz	415/240V	48 (60)	83	125
	400/230V	48 (60)	86	
	380/220V	48 (60)	91	
60 Hz	480/277V	54.2 (60)	82	200
	440/254V	54.4 (60)	89	
	380/220V	47.2 (60)	90	
	240/139V	54.2 (60)	164	
	220/127V	54.2 (60)	178	

Ratings at 0.8 power factor.

Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Power available at variable load with a load factor not exceeding 80% of the prime power rating in a 24 hour period.



Weights & Dimensions

Length - A (mm)	2610				
Width - B (mm)	1120				
Height - C (mm)	1776.5				
Weight - Lube Oil & Coolant (kg)	1715				
Weight - Lube Oil, Coolant & Fuel (kg)	2029				

Sockets	15A	16A	32A	50A	63A
Clipsal	2x 1ph+N+E	-	1x 3ph+N+E	-	-
Sockets (CEE Form)	-	2x 1ph+N+E	1x 3ph+N+E	-	1 x 3ph+N+E



PRO Rental Product Range

PRO60-2 Technical Data

Generator Set Technical Data

	UNITS	50 Hz	60 Hz
Power rating	kW (kVA)	48 (60)	68 (54)
Oil pan capacity	L	7	7
Fuel consumption			
100% load	L/hr	16.5	18.8
75% load		12.4	14.4
50% load		8.3	9.8
Fuel tank capacity	L	301	301
Running time (75% load)	Hrs	24	21
Ambient capability	°C	48	49
Engine & radiator coolant capacity	L	13	13
Engine coolant capacity	L	7	7
Combustion airflow	m ³ /min	4.7	5.8
Exhaust flow at rated – dry exhaust	m ³ /min	11.5	13.5
Exhaust temperature at rated kW	°C	540	542
Noise rating			
Sound power*		93	95
1m at 100% load	dB(A)	74.4	77.4
7m at 100% load		64.6	67.4
1m at 75% load		73.3	76.4
7m at 75% load		63.2	66.5

*Guaranteed sound power as per 2000/14/EC



PRO Rental Product Range

Perkins 1104D Engine Data

Engine	Perkins 1104D-44TG2
Bore – mm (in)	105 mm (4.13 in)
Stroke – mm (in)	127 mm (50 in)
Displacement – L (cu in)	4.4 L (268 in ³)
Compression ratio	18.23:1
Engine RPM	1500 / 1800
Aspiration	Turbocharged
Aftercooler type	N/A
Turbocharger	Single
Fuel system	Direct Injection
Governor type	Mechanical Actuator
Fuel	Class A2 Diesel or BS-EN590

Alternator Data

Frame Size	LL1514P
Pitch	2/3
No of Poles	4
Excitation	Static regulated, brushless, self-excited
No of Bearings	Single bearing, close coupled
Insulation Class	H
Temperature rise	125/40°C
Enclosure IP Rating	IP23
Overspeed Capability (% of rated)	25%
Voltage regulator	Single phase sensing
Voltage regulation	Less than $\pm 0.5\%$
Telephone Harmonic Factor (THF)	Less than 2%
Harmonic Distortion (THD)	Less than 2%

* Materials and specifications are subject to change without notice.

Caterpillar (NI) Limited is the manufacturer of FG Wilson brand diesel generating sets, and our facilities manufacture products in the following locations:
Brazil • China • India
With headquarters in Northern Ireland, FG Wilson products are distributed through a Global Dealer Network.
To contact your local Sales Office, please visit the FG Wilson website at www.fgwilson.com.

In line with our policy of continuous product development, we reserve the right to change specification without notice.