

AEI tag reading is mandatory for any sophisticated Asset Protection Systems. Our ability to capture data via TransCore's RFID products ensures seamless integration in transit visibility, maintenance, repair yard and inventory management in the industry.



COMMUNICATIONS

Frequency Range

- 902 to 928 MHz

Typical Working Range

- 5 to 10 ft (1.5 to 3 m)
- Range depends on system parameters.

Polarization

- Parallel with longer side

MEMORY

SeGo Mode

- Total:
 - 32 Pages
 - 256 bytes
 - 2,048 bits
- Unique ID:
 - 1 Pages
 - 8 bytes
 - 64 bits

- User Data, General Use:
 - 20 Pages
 - 168 bytes
 - 1,344 bits
- User Data, AAR:
 - 17 Pages
 - 136 bytes
 - 1,088 bits

- Reserved for security authentication:

- 11 Pages
- 88 bytes
- 704 bits

EGO Mode

- Total:
 - 128 bytes
 - 1,024 bits
- Unique ID:
 - 8 bytes
 - 64 bits
- User Data:
 - 110 bytes
 - 880 bits

ATA Mode

- Up to 20 six-bit alphanumeric characters (120 available bits)

Security

- The AT5118 Harsh Environment Transportation Tag provides data encryption and authentication

POWER REQUIREMENTS

Power Source

- Beam powered

LIFE EXPECTANCY

Service Life

- Unlimited

PHYSICAL

Dimensions

- Length: 9.3 (23.6 cm)
- Width: 2.38 (6 cm)
- Depth: 0.69 in (1.75 cm)
- Weight: 5.3 oz (150.2 g)

PHYSICAL

Operating Temperature

- -40° F to +185° F (-40° C to +85° C)

Storage Temperature

- -67° F to +212° F (-55° C to +100° C)

Progress Rail
A Caterpillar Company

800-476-8769 • progressrail.com

@progressrail • @Progress_Rail