



Buckets

for Hydraulic Excavators

Technical Specifications

Capacity based on ISO 7451.

Bucket weights do not include tips, unless otherwise indicated.

Bucket part numbers shown include adapters, tips ordered separately unless otherwise indicated.

Not all attachments available in all regions. Consult your Cat® dealer for specific configurations available in your region.

Table of Contents

Pin-on/Cat® Pin Grabber Buckets	2
313D2 GC, 313D2	2
M315D2, M317D2	2
M320D2	2
318D2	2
M322D2, M322D2 MH, M324D2 MH	3
A-Family (320 SLR, 326D2 SLR)	3
B-Family (320 GC, 320, 323, 336D2 SLR)	3
CB-Family (326D2, 330D2)	4
DB-Family (326D2 ME, 330D2 ME, 336 GC, 336D2, 340D2)	4
TB-Family (336D2 ME, 340D2 ME, 349D2)	4
UB-Family (349D2 ME)	4
VB-Family (374F, 390F)	5
WB-Family (374F ME)	5
HB-Family (390F)	5
JC-Family (390F ME)	5
Pin Grabber Performance Buckets	6
M315D2, M317D2	6
B-Family (320 GC, 320, 323, 336D2 SLR)	6
Dedicated Coupler Buckets	6
313D2 GC, 313D2	6
318D2	6
B-Family (320 GC, 320, 323, 336D2 SLR)	6
CB-Family (326D2, 330D2)	6
DB-Family (326D2 ME, 330D2 ME, 336 GC, 336D2, 340D2)	6
CW Dedicated Coupler Buckets	7
CW20 (313D2 GC, 313D2)	7
CW45 (326D2 ME, 330D2 ME, 336 GC, 336D2)	7
CW45S (326D2 ME, 330D2 ME, 336 GC, 336D2)	7
CW55 (340D2, 349D2)	7
CW70 (374F, 390F)	7
Connecting Lines for Ditch Cleaning Tilt Buckets	8
Ground Engaging Tools	9
Cat Advansys™ Tips	9
K Series Tips	9
J Series Tips	9
Sidecutters and Protectors	9

Buckets for Hydraulic Excavators Technical Specifications

Pin-on/Cat® Pin Grabber Buckets

Can be used pinned on to the machine or with a Cat Pin Grabber Coupler.

313D2 GC, 313D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
358-8612	600	24	0.31	0.40	J250	4	313	690
358-8616	900	36	0.53	0.69	J250	6	403	888
358-8615	900	36	0.53	0.69	J250	5	394	869
432-8367*	900	36	0.53	0.69	J250	6	440	970
370-3249*	1050	42	0.65	0.85	J250	6	493	1087
358-8621	1200	48	0.76	1.00	J250	7	487	1074
473-4633*	1200	48	0.76	1.00	J250	7	535	1179
Severe Duty								
358-8640	900	36	0.53	0.69	J300	5	456	1005
385-6080*	1050	42	0.65	0.84	J300	5	546	1203
396-8956*	1050	42	0.65	0.85	J300	5	559	1233
358-8641	1050	42	0.65	0.84	J300	5	502	1106
Ditch Cleaning								
439-7299	1200	48	0.57	0.74	BOCE Included		388	855
439-7300	1500	60	0.74	0.97	BOCE Included		455	1003
Ditch Cleaning Tilt								
509-9130	1200	48	0.48	0.63	BOCE Included		563	1240

*Tips included

BOCE – Bolt-on Cutting Edge

M315D2, M317D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
385-5644	450	18	0.20	0.27	J250	3	292	644
353-1575	600	24	0.35	0.46	K80	3	429	945
387-5718	750	30	0.49	0.64	K80	3	466	1027
353-1576	750	30	0.49	0.64	K80	4	481	1060
353-1577	900	36	0.62	0.81	K80	5	552	1150
385-5647	1000	39	0.60	0.79	J250	5	440	970
353-1578	1050	42	0.76	1.00	K80	5	584	1287
385-5648	1100	43	0.68	0.89	J250	6	471	1038
387-5719	1100	43	0.80	1.04	K80	4	580	1279
387-5720	1200	48	0.91	1.19	K80	5	625	1378
353-1579	1200	48	0.91	1.19	K80	6	640	1411
385-5649	1210	48	0.76	1.00	J250	6	500	1102

M315D2, M317D2 (continued)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
353-1585	600	24	0.35	0.46	K90	3	480	1058
353-1586	750	30	0.49	0.64	K90	4	543	1197
353-1587	900	36	0.62	0.81	K90	5	618	1341
353-1588	1050	42	0.76	1.00	K90	5	663	1462
353-1590	1200	48	0.91	1.19	K90	6	730	1609
Clean-up								
439-7303	1500	60	1.24	1.62	BOCE Included		770	1698
Ditch Cleaning								
456-2087	1500	60	0.93	1.22	BOCE Included		579	1277
456-2088	1800	72	1.14	1.49	BOCE Included		661	1458
Ditch Cleaning Tilt								
516-2840	2000	79	0.86	1.12	BOCE Included		1043	2299

BOCE – Bolt-on Cutting Edge

M320D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
388-9586	600	24	0.39	0.50	K80	3	458	1010
388-9587	750	30	0.53	0.69	K80	3	506	1116
388-9588	900	36	0.68	0.88	K80	4	562	1239
388-9589	1050	42	0.83	1.09	K80	4	611	1347
466-8140*	1200	48	1.00	1.31	J300	5	692	1526
388-9590	1200	48	0.98	1.29	K80	5	669	1475
389-0254	1300	51	1.07	1.41	K80	5	698	1539
388-9591	1400	55	1.18	1.54	K80	5	730	1609
Heavy Duty								
417-2671	900	36	0.68	0.88	K80	4	605	1335
417-2672	1050	42	0.83	1.09	K80	4	648	1429
417-2673	1200	48	0.98	1.29	K80	5	707	1559

*Tips included

318D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
394-8509	1050	42	0.76	1.00	K80	5	603	1329
394-8508	900	36	0.62	0.81	K80	4	538	1186

(continued on next page)

Buckets for Hydraulic Excavators Technical Specifications

Pin-on/Cat® Pin Grabber Buckets (continued)

Can be used pinned on to the machine or with a Cat Pin Grabber Coupler.

M322D2, M322D2 MH, M324D2 MH

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
422-6976	1200	48	1.19	1.56	K80	5	768	1693
422-6978	1400	55	1.43	1.87	K80	5	808	1781

MH – for use with Material Handling configuration

A-Family (320 SLR, 326D2 SLR)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Ditch Cleaning								
452-6069	1200	48	0.57	0.74			326	718
441-6077	1200	48	0.57	0.74	BOCE Included		386	852

BOCE – Bolt-on Cutting Edge

SLR – for use with Super Long Reach configuration

B-Family (320 GC, 320, 323, 336D2 SLR)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
347-6795	600	24	0.55	0.72	K80	3	601	1324
347-6796	750	30	0.75	0.98	K80	4	687	1516
347-6797	900	36	0.95	1.24	K80	5	758	1671
469-4896*	1050	42	1.00	1.31	K80	5	771	1699
347-6798	1050	42	1.16	1.52	K80	5	819	1805
347-6799	1200	48	1.38	1.80	K80	6	891	1964
347-6800	1350	54	1.59	2.08	K80	7	963	2124
General Duty – Wide Tip								
396-4653*	600	24	0.55	0.72	K80	3	615	1356
396-4654*	750	30	0.75	0.98	K80	4	708	1561
396-4655*	900	36	0.95	1.24	K80	5	784	1728
396-4656*	1050	42	1.16	1.52	K80	6	860	1896
396-4657*	1200	48	1.38	1.80	K80	7	938	2068
396-4658*	1350	54	1.59	2.08	K80	8	1016	2240

*Tips included

SLR – for use with Super Long Reach configuration

B-Family (320 GC, 320, 323, 336D2 SLR) (continued)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Heavy Duty								
347-6727	600	24	0.46	0.61	K90	3	628	1385
347-6728	750	30	0.64	0.84	K90	4	721	1590
347-6729	900	36	0.81	1.06	K90	5	791	1744
347-6730	1050	42	1.00	1.31	K90	5	845	1863
347-6852	1200	48	1.19	1.56	K90	4	891	1965
511-3073*	1200	48	1.19	1.56	K90	4	967	2133
347-6731	1200	48	1.19	1.56	K90	6	930	2050
511-3074*	1350	54	1.40	1.83	K90	5	1061	2339
347-6853	1350	54	1.40	1.83	K90	5	978	2156
347-6732	1350	54	1.38	1.81	K90	7	1006	2217
Heavy Duty Power								
347-6807	900	36	0.79	1.03	K90	5	808	1781
347-6808	1050	42	0.96	1.26	K90	5	873	1925
347-6809	1200	48	1.14	1.49	K90	6	952	2099
Severe Duty								
347-6747	600	24	0.46	0.61	K90	3	674	1486
347-6748	750	30	0.64	0.84	K90	4	775	1709
347-6749	900	36	0.81	1.06	K90	5	855	1885
347-6750	1050	42	1.00	1.31	K90	5	930	2050
347-6751	1200	48	1.19	1.56	K90	6	1012	2231
563-9004	1350	54	1.56	2.04	K90	5	1166	2571
Severe Duty Power								
347-6813	900	36	0.79	1.03	K90	5	874	1927
Clean-up								
439-7308	1800	72	1.60	2.09	BOCE Included		979	2157
Ditch Cleaning								
441-6074	1500	60	1.01	1.32	BOCE Included		651	1436
441-6075	1800	72	1.24	1.62	BOCE Included		740	1630
Ditch Cleaning Tilt								
511-5334	1500	60	0.90	1.18	BOCE Included		948	2090
511-5337	1800	72	1.40	1.83	BOCE Included		1105	2436
511-5335	1800	72	1.11	1.45	BOCE Included		1063	2344
516-6671	2000	79	1.23	1.61	BOCE Included		1132	2496

*Tips included

BOCE – Bolt-on Cutting Edge

SLR – for use with Super Long Reach configuration

(continued on next page)

Buckets for Hydraulic Excavators Technical Specifications

Pin-on/Cat® Pin Grabber Buckets (continued)

Can be used pinned on to the machine or with a Cat Pin Grabber Coupler.

CB-Family (326D2, 330D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
346-0837	600	24	0.63	0.83	K90	3	704	1552
346-0838	750	30	0.86	1.13	K90	4	784	1728
346-0839	900	36	1.09	1.43	K90	5	874	1927
346-0840	1050	42	1.34	1.75	K90	5	946	2086
346-0841	1200	48	1.58	2.07	K90	6	1031	2273
346-0842	1350	54	1.83	2.40	K90	7	1118	2464
General Duty – Wide Tip								
396-4659*	600	24	0.63	0.83	K90	3	729	1607
396-4660*	750	30	0.86	1.13	K90	4	818	1803
396-4661*	900	36	1.09	1.43	K90	5	908	2002
396-4662*	1050	42	1.34	1.75	K90	5	988	2178
396-4664*	1200	48	1.58	2.07	K90	6	1082	2385
396-4665*	1350	54	1.83	2.40	K90	7	1176	2593
Heavy Duty								
540-4092*	1500	60	1.76	2.30	100	5	1245	2745
Severe Duty Power								
550-2252	1350	54	1.56	2.04	100	4	1235	2723
Clean-up								
439-7314	1800	72	1.81	2.37	BOCE Included		1146	2526
Ditch Cleaning								
439-7315	1500	60	1.23	1.61	BOCE Included		839	1850
439-7316	1800	72	1.52	1.99	BOCE Included		950	2094
Ditch Cleaning Tilt								
277-4044	1829	72	1.14	1.50	BOCE Included		1069	2357

*Tips included

BOCE – Bolt-on Cutting Edge

DB-Family (326D2 ME, 330D2 ME, 336 GC, 336D2, 340D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
540-4108	1650	65	2.12	2.77	100	5	1303	2873
Heavy Duty								
528-4564*	1650	66	2.12	2.77	110	5	1690	3726
Severe Duty								
528-4645	1500	59	1.91	2.50	110	4	1610	3549
528-4585*	1650	66	2.15	2.81	110	5	1887	4160
Clean-up								
439-7323	1800	72	2.48	3.24	BOCE Included		1444	3183
Ditch Cleaning								
439-7324	1800	72	1.96	2.56	BOCE Included		1147	2529

*Tips included

BOCE – Bolt-on Cutting Edge

ME – for use with Mass Excavation configuration

TB-Family (336D2 ME, 340D2 ME, 349D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
528-2166	2050	80	3.82	5.00	110	7	2454	5410
Heavy Duty								
528-2177	1500	60	2.14	2.80	110	6	2059	4539
528-4551	1650	66	2.41	3.15	110	7	2209	4870
528-4660	1850	72	2.69	3.52	110	5	2317	5108
Severe Duty								
528-2192	1050	42	1.34	1.75	110	4	1719	3790
528-2193	1200	48	1.60	2.09	110	5	1875	4134
518-9314	1400	55	1.87	2.44	130	4	2089	4605
518-9327	1550	61	2.14	2.80	130	4	2246	4951
518-9315	1550	61	2.14	2.80	130	5	2268	5000
518-9316	1700	67	2.41	3.15	130	5	2408	5309
528-8133*	1750	69	2.40	3.14	130	4	2640	5820
518-9317	1850	74	2.69	3.52	130	6	2588	5705
518-9330	1900	75	2.78	3.64	130	5	2622	5780
Extreme Duty								
518-9318	1250	49	1.60	2.09	130	4	2113	4658
518-9319	1400	55	1.87	2.44	130	4	2253	4967
525-4053	1550	61	2.00	2.59	130	4	2481	5470
Clean-up								
439-7330	2000	78	2.80	3.66	BOCE Included		2187	4822

*Tips included

BOCE – Bolt-on Cutting Edge

ME – for use with Mass Excavation configuration

UB-Family (349D2 ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Heavy Duty								
518-9320	1650	65	2.77	3.62	130	4	2492	5494
518-9322	1850	73	3.21	4.20	130	4	2677	5902
518-9324	1950	77	3.43	4.49	130	5	2811	6197
Severe Duty								
518-9326	1750	69	2.40	3.14	130	4	2463	5430
518-9325	1850	73	3.21	4.20	130	4	2871	6329
Extreme Duty								
518-9339	1600	63	2.61	3.41	130	4	3025	6669
528-8157	1600	63	2.66	3.48	130	4	3136	6914

ME – for use with Mass Excavation configuration

(continued on next page)

Buckets for Hydraulic Excavators Technical Specifications

Pin-on/Cat® Pin Grabber Buckets (continued)

Can be used pinned on to the machine or with a Cat Pin Grabber Coupler.

VB-Family (374F, 390F)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
519-5280	2000	79	3.80	4.97	150	5	3576	7884
519-5281	2050	82	4.60	6.02	150	5	3817	8415
Heavy Duty								
519-5282	1300	52	2.20	2.88	150	3	2811	6197
519-5283	1750	70	3.30	4.32	150	4	3417	7533
519-5284	2000	79	3.80	4.97	150	5	3737	8239
Severe Duty								
519-5285	1150	47	1.90	2.49	150	3	2740	6041
519-5286	1600	64	2.90	3.79	150	4	3313	7303
519-5287	1750	70	3.30	4.32	150	4	3509	7736
519-5288	2000	79	3.80	4.97	150	5	3837	8459
Extreme Duty								
519-5289	2000	79	3.84	5.02	150	4	4330	9546

WB-Family (374F ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
519-5399	1950	77	4.10	5.36	170	4	4631	10210
519-5400	2050	81	4.40	5.75	170	4	4787	10554
519-5405	2150	85	4.60	6.02	170	4	4944	10900
Extreme Duty								
519-5409	2050	81	4.40	5.75	170	4	5578	12297
519-5412	2150	85	4.60	6.02	170	4	6044	13325
519-5411	2150	85	4.60	6.02	170	4	5765	12710

ME – for use with Mass Excavation configuration

HB-Family (390F)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
519-5303	1150	45	2.20	2.88	150	3	2770	6107
519-5304	1450	57	2.90	3.79	150	3	3100	6834
519-5305	1750	69	3.70	4.84	150	4	3531	7785
519-5290	1750	69	3.90	5.10	150	4	3679	8111
519-5291	2000	79	4.60	6.02	150	5	4009	8838
519-5292	2050	81	5.30	6.93	150	5	4254	9378
519-5307	2050	81	4.60	6.02	150	4	3913	8627
Severe Duty								
519-5294	1150	45	2.30	3.00	150	3	3179	7008
519-5295	1450	57	3.00	3.92	150	4	3596	7928
519-5296	1750	69	3.90	5.10	150	4	4017	8856
519-5298	2000	79	4.60	6.02	150	5	4371	9636

JC-Family (390F ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
519-5401	2350	93	5.70	7.45	170	6	5572	12284
519-5402	2450	96	6.00	7.84	170	6	5754	12685
528-8163	2600	102	6.50	8.50	170	6	5985	13195
Heavy Duty								
528-8164	1800	71	4.10	5.36	170	4	4754	10481
Severe Duty								
519-5465	2000	79	4.60	6.02	200	4	5818	12826
519-5466	2300	91	5.40	7.06	200	4	6396	14101
519-5474	2400	94	5.70	7.46	200	4	6601	14553
519-5467	2500	98	6.00	7.85	200	5	6835	15069
Extreme Duty								
519-5476	2200	87	5.00	6.54	200	4	6948	15318
519-5468	2200	87	5.00	6.54	200	5	7428	16376
519-5477	2350	93	5.40	7.06	200	4	7291	16074

ME – for use with Mass Excavation configuration

Buckets for Hydraulic Excavators Technical Specifications

Pin Grabber Performance Buckets

For use with Cat Pin Grabber Coupler only.

M315D2, M317D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
376-9106	1072	42	0.70	0.92	K90	5	664	1464
376-9107	1224	48	0.83	1.09	K90	6	731	1612

B-Family (320 GC, 320, 323, 336D2 SLR)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Heavy Duty								
347-6817	600	24	0.44	0.57	K90	3	656	1446
347-6818	750	30	0.60	0.79	K90	4	751	1656
347-6819	900	36	0.76	1.00	K90	5	830	1830
347-6820	1050	42	0.93	1.22	K90	5	894	1972
347-6821	1200	48	1.11	1.45	K90	6	975	2150
347-6822	1350	54	1.28	1.67	K90	7	1056	2328

SLR – for use with Super Long Reach configuration

Dedicated Coupler Buckets

For use with Dedicated Coupler.

313D2 GC, 313D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Heavy Duty								
267-6224	610	24	0.30	0.39	J300	3	368	831
281-2174	914	36	0.52	0.68	J300	5	471	1037
283-9842	1067	42	0.63	0.82	J300	5	515	1134

Ditch Cleaning

439-7301	1500	60	0.74	0.97	BOCE Included		465	1024
----------	------	----	------	------	---------------	--	-----	------

BOCE – Bolt-on Cutting Edge

318D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
267-6227	610	24	0.42	0.55	K80	3	406	896
267-6228	914	36	0.73	0.95	K80	5	522	1151
267-6229	1067	42	0.92	1.20	K80	5	570	1256

Heavy Duty

267-6231	610	24	0.42	0.55	K90	3	515	1136
267-6232	914	36	0.73	0.95	K90	5	656	1446
268-3478	1067	42	0.88	1.15	K90	5	713	1572

Ditch Cleaning

439-7306	1800	72	1.14	1.49	BOCE Included		662	1460
----------	------	----	------	------	---------------	--	-----	------

BOCE – Bolt-on Cutting Edge

B-Family (320 GC, 320, 323, 336D2 SLR)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Heavy Duty								
267-1551	676	27	0.54	0.71	K90	3	701	1545
Ditch Cleaning								
441-6076	1500	60	1.01	1.32	BOCE Included		686	1511

BOCE – Bolt-on Cutting Edge

SLR – for use with Super Long Reach configuration

CB-Family (326D2, 330D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Ditch Cleaning								
439-7317	1800	72	1.52	1.99	BOCE Included		954	2102

BOCE – Bolt-on Cutting Edge

DB-Family (326D2 ME, 330D2 ME, 336 GC, 336D2, 340D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Clean-up								
439-7326	1800	72	2.49	3.26	BOCE Included		1415	3120
439-7325	2100	83	2.91	3.81	BOCE Included		1568	3457
Ditch Cleaning								
439-7327	1800	72	1.96	2.56	BOCE Included		1122	2474

BOCE – Bolt-on Cutting Edge

ME – for use with Mass Excavation configuration

Buckets for Hydraulic Excavators Technical Specifications

CW Dedicated Coupler Buckets

For use with CW Dedicated Coupler.

CW20 (313D2 GC, 313D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
358-8652	1100	43	0.68	0.89	J250	6	462	1019
358-8653	1200	48	0.76	1.00	J250	6	490	1081

CW45 (326D2 ME, 330D2 ME, 336 GC, 336D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
528-4668	1500	59	1.91	2.50	110	4	1581	3486
528-4663	1650	66	2.41	3.15	110	5	2197	4844

ME – for use with Mass Excavation configuration

CW45S (326D2 ME, 330D2 ME, 336 GC, 336D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Heavy Duty								
554-3118*	1650	66	1.97	2.58	100	5	1316	2901

*Tips included

ME – for use with Mass Excavation configuration

CW55 (340D2, 349D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
518-9336	1650	65	2.77	3.62	130	4	2579	5686
Extreme Duty								
518-9340	1550	61	2.61	3.41	130	4	2962	6530

CW70 (374F, 390F)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
519-5403	1950	77	4.00	5.23	170	4	4605	10152
519-5404	2050	81	4.40	5.75	170	4	4760	10494
519-5471	2300	91	5.40	7.06	200	4	6151	13561
Extreme Duty								
519-5410	2050	81	4.40	5.75	170	4	5551	12238

Buckets for Hydraulic Excavators Technical Specifications

Connecting Lines for Ditch Cleaning Tilt Buckets

Connecting Lines must be ordered in addition to the Bucket.

Choose Connecting Lines to match Carrier Stick Lines.

Flow Control Valve is required for Carriers with High Pressure Lines without Tool Control.

Quick Disconnect Fittings are optional.

Carrier	Linkage	Interface	Connecting Lines		Flow Control Valve for HP	OPTIONAL
			High Pressure (HP)	Medium Pressure (MP)		Quick Disconnect
313D2 GC 313D2		Pin-on	513-7230	513-7231	492-1555	499-3172
		Pin Grabber				499-3172
318D2		Pin-on	513-7230	513-7231	492-1555	499-3172
		Pin Grabber				499-3172
320 GC 320 323	B	Pin-on	513-7232	513-7231	492-1555	499-3172
		Pin Grabber	513-7228	513-7229	492-1555	499-3172
M315D2 M317D2 M320D2		Pin-on	513-7232	513-7234	492-1555	
		Pin Grabber	513-7228	513-7233	492-1555	
M322D2		Pin-on	513-7232	513-7234	492-1555	
		Pin Grabber	513-7228	513-7233	492-1555	

Buckets for Hydraulic Excavators Technical Specifications

Ground Engaging Tools

Part numbers include tip and retainer unless otherwise indicated.

Cat Advansys™ Tips

	100	110	130	150	170	200
Double Spike	505-4105	505-4115	381-4092	368-3788	368-3871	
General Duty	505-4106	505-4116	381-4088	368-3789	368-3872	385-4811
Heavy Duty	505-4002	505-4012	368-3791	368-3786	368-3867	385-4814
Heavy Duty Long Life (ARM)	505-4003	505-4013	368-3857	368-3861	387-6856	387-6867
Leveling Edge Conversion (LEC)	505-4005					
Penetration	505-4101	505-4111	381-4093	368-3785	368-3868	368-3877
Penetration Long Life (ARM)	505-4102	505-4112	368-3858	368-3874	387-6866	387-6868
Penetration Plus	505-4103	505-4113	381-4089	368-3783	368-3869	368-3878
Spike	505-4104	505-4114	381-4090	368-3787	368-3870	
Wide	505-4100	505-4110	381-4091	368-3790	368-3866	

K Series Tips

	K80	K90
Double Spike	229-6968	217-4895
Extra Duty	229-6964	217-4891
General Duty	229-6969	217-4896
Penetration	229-6965	217-4892
Penetration Plus	229-6966	217-4893
Spike	229-6967	217-4894
Wide	229-6963	217-4890

J Series Tips

	J250	J300
Long	9J-3169	9J-3167
Long, Heavy Duty	8E-3750	8E-3751
Wide	101-2927	4T-2215
Short	9J-3178	9J-3175
Abrasion, Heavy Duty	8E-3755	8E-3756
Penetration	100-6462	3G-3237
Penetration Plus		195-9180
Twin Sharp	229-7137	

Sidcutters and Protectors

Machine Model or Linkage Family	Sidebar Protectors	Sidcutters		
	4 Piece Set	GD	HD	SD
311, 312, 313, 314		380-1203		380-1203
315, 316, M313-M318		380-1204	380-1204	380-1204
318		380-1204	380-1204	380-1204
B, CB, DB	357-2691	7Y-0366	357-2698	357-2698
M320, M322	195-7216	380-1204	380-1204	
TB, UB, VB, HB	357-2687		357-2685	357-2685
VB2, WB2, HB2	329-5956		357-2686	357-2686
JC	357-2688		357-2686	357-2686

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2018 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

GEJQ2367-00 (10-2018)
Replaces GEJQ2500
(S Am)

