



Buckets

for Hydraulic Excavators

Technical Specifications

Capacity based on ISO 7451.

Bucket weights do not include tips, unless otherwise indicated.

Bucket part numbers shown include adapters, tips ordered separately unless otherwise indicated.

Not all attachments available in all regions. Consult your Cat® dealer for specific configurations available in your region.

Table of Contents

Pin-on/Cat® Pin Grabber Buckets	2
313F GC, 313F2
315F, 318D22
M322D2, M322D2 MH, M324D2 MH2
A-Family (320 SLR, 326D2 SLR, 330D2 SLR)2
B-Family (320 GC, 320, 336D2 SLR)2
CB-Family (326D2, 330D2)3
DB-Family (326D2 ME, 330D2 ME, 336D2, 340D2)3
TB-Family (336D2 ME, 340D2 ME, 349D2)3
UB-Family (349D2 ME)3
WB-Family (374F ME)4
JC-Family (390F ME)4
CW Dedicated Coupler Buckets	4
CW55 (349D2)4
CW70 (374F, 390F)4
Connecting Lines for Ditch Cleaning Tilt Buckets	5
Ground Engaging Tools	5
Cat Advansys™ Tips5
K Series Tips5
J Series Tips6
Sidecutters and Protectors6

Buckets for Hydraulic Excavators Technical Specifications

Pin-on/Cat® Pin Grabber Buckets

Can be used pinned on to the machine or with a Cat Pin Grabber Coupler.

313F GC, 313F

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Utility Duty								
441-6080*	900	36	0.53	0.69	J250	5	411	906
General Duty								
392-1128*	450	18	0.20	0.26	J250	3	316	696
392-1130*	600	24	0.31	0.40	J250	3	359	791
392-1131*	750	30	0.41	0.54	J250	4	407	896
520-6181*	772	30	0.41	0.54	K80	4	440	969
438-9799*	900	36	0.53	0.69	J250	5	411	905
392-1132*	900	36	0.53	0.69	J250	5	455	1004
427-5991	900	36	0.53	0.69	K80	4	423	933
432-8367*	900	36	0.53	0.69	J250	6	440	970
484-0191*	900	36	0.53	0.69	J250	5	428	942
518-1023*	900	36	0.53	0.69	K80	4	484	1066
507-0131*	1000	39	0.60	0.78	J250	5	452	996
392-1133*	1050	42	0.65	0.84	J250	6	503	1109
370-3249*	1050	42	0.65	0.85	J250	6	493	1087
420-3377*	1050	42	0.65	0.85	J250	6	497	1097
527-1253*	1100	43	0.70	0.92	J250	6	501	1105
Severe Duty								
396-8956*	1050	42	0.65	0.85	J300	5	559	1233
Clean-up								
449-8618	1500	60	1.02	1.33	BOCE Included		651	1434
449-8617	1800	72	1.25	1.63	BOCE Included		748	1649
Ditch Cleaning Tilt								
482-0843	1800	72	0.90	1.18	BOCE Included		784	1728

*Tips included

BOCE – Bolt-on Cutting Edge

315F, 318D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
381-7185*	600	24	0.35	0.46	K80	3	488	1076
381-7186*	750	30	0.49	0.64	K80	3	531	1171
381-7187*	900	36	0.62	0.81	K80	4	593	1307
381-7188*	1050	42	0.76	1.00	K80	4	641	1413
418-5278*	1100	43	0.80	1.04	J300	5	657	1448
433-0313*	1200	47	0.80	1.05	J300	6	677	1492
381-7189*	1200	48	0.91	1.19	K80	5	702	1547

*Tips included

315F, 318D2 (continued)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Clean-up								
449-8620	1500	60	1.24	1.62	BOCE Included		799	1762
449-8619	1800	72	1.53	2.00	BOCE Included		911	2008
Ditch Cleaning Tilt								
484-0188	1800	72	0.78	1.02	BOCE Included		969	2136
Severe Duty								
394-2345*	1050	42	0.76	1.00	J350	5	730	1609

*Tips included

BOCE – Bolt-on Cutting Edge

M322D2, M322D2 MH, M324D2 MH

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
422-6976	1200	48	1.19	1.56	K80	5	768	1693
422-6978	1400	55	1.43	1.87	K80	5	808	1781

MH – for use with Material Handling configuration

A-Family (320 SLR, 326D2 SLR, 330D2 SLR)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Ditch Cleaning								
441-6077	1200	48	0.57	0.74	BOCE Included		386	852

BOCE – Bolt-on Cutting Edge

SLR – for use with Super Long Reach configuration

B-Family (320 GC, 320, 336D2 SLR)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
377-5391*	600	24	0.46	0.61	K80	3	628	1385
469-4896*	1050	42	1.00	1.31	K80	5	771	1699
377-5393*	1200	48	1.19	1.56	K80	5	881	1942
377-5395*	1400	56	1.14	1.49	J350	6	882	1945

*Tips included

SLR – for use with Super Long Reach configuration

(continued on next page)

Buckets for Hydraulic Excavators Technical Specifications

Pin-on/Cat® Pin Grabber Buckets (continued)

Can be used pinned on to the machine or with a Cat Pin Grabber Coupler.

B-Family (320 GC, 320, 336D2 SLR) (continued)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Heavy Duty								
347-6823*	600	24	0.46	0.61	K90	3	711	1568
347-6824*	750	30	0.64	0.84	K90	4	810	1786
347-6825*	900	36	0.81	1.06	K90	5	888	1958
347-6835	1200	48	1.19	1.56	K90	6	898	1980
347-6827*	1200	48	1.19	1.56	K90	6	998	2200
347-6829*	1350	54	1.38	1.81	K90	7	1100	4850
347-6828*	1350	54	1.38	1.81	K90	7	1100	4850
377-5392*	1350	54	1.40	1.83	K90	4	813	1792
Severe Duty								
347-6830*	900	36	0.81	1.06	K90	5	983	2167
347-6838	900	36	0.81	1.06	K90	5	834	1839
540-4105*	1100	43	1.00	1.31	100	4	1042	2297
Clean-up								
449-8622	1800	72	1.60	2.09	BOCE Included		1021	2251
449-8621	2000	78	1.76	2.31	BOCE Included		1088	2399
Ditch Cleaning Tilt								
511-5338	1800	72	1.40	1.83	BOCE Included		1114	2456

*Tips included

BOCE – Bolt-on Cutting Edge

SLR – for use with Super Long Reach configuration

CB-Family (326D2, 330D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
370-5861*	600	24	0.52	0.68	K90	3	699	1540
370-5862*	1350	53	1.54	2.01	K90	5	1106	2438
370-5863*	1500	60	1.76	2.30	K90	5	1170	2579
346-0831	1500	59	1.76	2.30	K90	5	1041	2294
Heavy Duty								
554-3119*	1200	48	1.33	1.74	100	5	1197	2639
540-4098*	1350	55	1.54	2.02	100	6	1312	2892
554-3120*	1350	54	1.54	2.02	100	6	1297	2859
540-4095*	1450	57	1.57	2.05	100	6	1329	2930
528-4595*	1550	60	1.76	2.30	110	5	1440	3175
Severe Duty								
528-4598*	1400	56	1.54	2.01	110	5	1496	3298
Clean-up								
449-8624	1800	72	1.81	2.37	BOCE Included		1207	2661
449-8623	2000	78	2.00	2.61	BOCE Included		1285	2833

*Tips included

BOCE – Bolt-on Cutting Edge

DB-Family (326D2 ME, 330D2 ME, 336D2, 340D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
General Duty								
540-4078*	1650	65	2.12	2.77	100	5	1470	3241
Heavy Duty								
528-4570*	750	30	0.73	0.95	110	3	1131	2493
528-4571*	1050	42	1.17	1.53	110	4	1372	3025
528-4572*	1200	48	1.40	1.83	110	5	1506	3320
528-4573*	1350	54	1.64	2.14	110	5	1602	3532
528-4574*	1500	59	1.88	2.46	110	6	1737	3829
528-4575*	1650	66	2.12	2.77	110	7	1872	4127
528-4576*	1850	72	2.36	3.09	110	7	1969	4341
Severe Duty								
528-4588*	1200	48	1.40	1.83	110	5	1614	3558
Clean-up								
449-8626	1800	72	2.48	3.24	BOCE Included		1521	3353
449-8625	2000	78	2.74	3.58	BOCE Included		1618	3567

*Tips included

BOCE – Bolt-on Cutting Edge

ME – for use with Mass Excavation configuration

TB-Family (336D2 ME, 340D2 ME, 349D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Heavy Duty								
528-4554*	1650	66	2.41	3.15	110	7	2486	5481
528-4555*	1850	72	2.69	3.52	110	7	2615	5765
Severe Duty								
519-2235*	1650	65	2.41	3.15	130	5	2584	5697
Clean-up								
449-8628	2000	78	2.80	3.66	BOCE Included		2288	5044
449-8627	2400	94	3.38	4.42	BOCE Included		2721	5999

*Tips included

BOCE – Bolt-on Cutting Edge

ME – for use with Mass Excavation configuration

UB-Family (349D2 ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
519-2236*	1550	61	2.61	3.41	130	4	2740	6041
519-2237*	1850	73	3.21	4.20	130	5	3078	6786

*Tips included

ME – for use with Mass Excavation configuration

(continued on next page)

Buckets for Hydraulic Excavators Technical Specifications

Pin-on/Cat® Pin Grabber Buckets (continued)

Can be used pinned on to the machine or with a Cat Pin Grabber Coupler.

WB-Family (374F ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
519-5393*	2150	85	4.60	6.02	170	4	5216	11499
519-5405	2150	85	4.60	6.02	170	4	4944	10900
Extreme Duty								
519-5396*	2050	81	4.40	5.75	170	4	5762	12703
519-5397*	2150	85	4.60	6.02	170	4	5949	13115
519-5411	2150	85	4.60	6.02	170	4	5765	12710

*Tips included

ME – for use with Mass Excavation configuration

JC-Family (390F ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
519-5460*	2300	91	5.40	7.06	200	4	6780	14947
519-5467	2500	98	6.00	7.85	200	5	6835	15069

*Tips included

ME – for use with Mass Excavation configuration

CW Dedicated Coupler Buckets

For use with CW Dedicated Coupler.

CW55 (349D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
518-9334	1550	61	2.61	3.41	130	4	2499	5509
518-9336	1650	65	2.77	3.62	130	4	2579	5686
Extreme Duty								
518-9340	1550	61	2.61	3.41	130	4	2962	6530

CW70 (374F, 390F)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m ³	yd ³	GET	Qty.	kg	lb
Severe Duty								
519-5403	1950	77	4.00	5.23	170	4	4605	10152
519-5404	2050	81	4.40	5.75	170	4	4760	10494
519-5471	2300	91	5.40	7.06	200	4	6151	13561
519-5472	2400	94	5.70	7.46	200	4	6355	14010

Buckets for Hydraulic Excavators Technical Specifications

Connecting Lines for Ditch Cleaning Tilt Buckets

Connecting Lines must be ordered in addition to the Bucket.

Choose Connecting Lines to match Carrier Stick Lines.

Flow Control Valve is required for Carriers with High Pressure Lines without Tool Control.

Quick Disconnect Fittings are optional.

Carrier	Linkage	Interface	Connecting Lines		Flow Control Valve for HP	OPTIONAL
			High Pressure (HP)	Medium Pressure (MP)		Quick Disconnect
313F GC 313F		Pin-on	513-7230	513-7231	492-1555	499-3172
		Pin Grabber				
315F 318D2		Pin-on	513-7230	513-7231	492-1555	499-3172
		Pin Grabber				
320 GC 320	B	Pin-on	513-7232	513-7231	492-1555	499-3172
		Pin Grabber	513-7228	513-7229	492-1555	499-3172
M322D2		Pin-on	513-7232	513-7234	492-1555	
		Pin Grabber	513-7228	513-7233	492-1555	

Ground Engaging Tools

Part numbers include tip and retainer unless otherwise indicated.

Cat Advansys™ Tips

	100	110	130	170	200
Double Spike	505-4105	505-4115	381-4092	368-3871	
General Duty	505-4106	505-4116	381-4088	368-3872	385-4811
Heavy Duty	505-4002	505-4012	368-3791	368-3867	385-4814
Heavy Duty Long Life (ARM)	505-4003	505-4013	368-3857	387-6856	387-6867
Leveling Edge Conversion (LEC)	505-4005				
Penetration	505-4101	505-4111	381-4093	368-3868	368-3877
Penetration Long Life (ARM)	505-4102	505-4112	368-3858	387-6866	387-6868
Penetration Plus	505-4103	505-4113	381-4089	368-3869	368-3878
Spike	505-4104	505-4114	381-4090	368-3870	
Wide	505-4100	505-4110	381-4091	368-3866	

K Series Tips

	K80	K90
Double Spike	229-6968	217-4895
Extra Duty	229-6964	217-4891
General Duty	229-6969	217-4896
Penetration	229-6965	217-4892
Penetration Plus	229-6966	217-4893
Spike	229-6967	217-4894
Wide	229-6963	217-4890

(continued on next page)

Buckets for Hydraulic Excavators Technical Specifications

Ground Engaging Tools *(continued)*

Part numbers include tip and retainer unless otherwise indicated.

J Series Tips

	J250	J300	J350
Abrasion, Heavy Duty	8E-3755	8E-3756	
Double Spike			135-9357
General Duty			1U-3352
Long	9J-3169	9J-3167	
Long, Heavy Duty	8E-3750	8E-3751	
Penetration	100-6462	3G-3237	9J-4359
Penetration Long Life (ARM)			119-9359
Penetration Plus		195-9180	168-1359
Short	9J-3178	9J-3175	
Spike			168-1350
Twin Sharp	229-7137		
Wide	101-2927	4T-2215	107-3350

Sidecutters and Protectors

Machine Model or Linkage Family	Sidebar Protectors	Sidecutters		
	4 Piece Set	GD	HD	SD
311, 312, 313, 314		380-1203		380-1203
315, 316, M313-M318		380-1204	380-1204	380-1204
318		380-1204	380-1204	380-1204
B, CB, DB	357-2691	7Y-0366	357-2698	357-2698
M320, M322	195-7216	380-1204	380-1204	
TB, UB, VB, HB	357-2687		357-2685	357-2685
VB2, WB2, HB2	329-5956		357-2686	357-2686
JC	357-2688		357-2686	357-2686

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

GEJQ0371-00 (10-2018)
(Pacific Islands)

© 2018 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

