



# Buckets

for Hydraulic Excavators

## Technical Specifications

Capacity based on ISO 7451.

Bucket weights do not include tips, unless otherwise indicated.

Bucket part numbers shown include adapters, tips ordered separately unless otherwise indicated.

**Not all attachments available in all regions. Consult your Cat® dealer for specific configurations available in your region.**

### Table of Contents

<b>Pin-on/Cat® Pin Grabber Buckets</b> .....	<b>2</b>
313D2 GC, 313D2 .....	2
M315D2, M317D2 .....	2
318D2 .....	2
M320D2 .....	2
M322D2, M322D2 MH, M324D2 MH .....	2
A-Family (320 SLR, 326D2 SLR, 330 SLR) .....	2
B-Family (320 GC, 320, 323, 326D2, 336 SLR) .....	2
CB-Family (326D2, 330 GC, 330) .....	2
DB-Family (326D2 ME, 330 ME, 336 GC, 336, 340D2) .....	3
TB-Family (336 GC ME, 336 ME, 340D2 ME, 349D2 ME) .....	3
UB-Family (349D2 ME) .....	3
WB2-Family (374F ME) .....	3
JC-Family (390F ME) .....	3
<b>Ground Engaging Tools</b> .....	<b>3</b>
Cat Advansys™ Tips .....	3
K Series Tips .....	4
J Series Tips .....	4
Sidecutters and Protectors .....	4

# Buckets for Hydraulic Excavators Technical Specifications

## Pin-on/Cat® Pin Grabber Buckets

Can be used pinned on to the machine or with a Cat Pin Grabber Coupler.

### 313D2 GC, 313D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Utility Duty</b>								
441-6080*	900	36	0.53	0.69	J250	5	411	906
<b>General Duty</b>								
484-0191*	900	36	0.53	0.69	J250	5	428	942
438-9799*	900	36	0.53	0.69	J250	5	411	905
507-0131*	1000	39	0.60	0.78	J250	5	452	996
370-3249*	1050	42	0.65	0.85	J250	6	493	1087
527-1253*	1100	43	0.70	0.92	J250	6	501	1105
<b>Severe Duty</b>								
396-8956*	1050	42	0.65	0.85	J300	5	559	1233

\*Tips included

### M315D2, M317D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
385-5644	450	18	0.20	0.27	J250	3	292	644
387-5718	750	30	0.49	0.64	K80	3	466	1027
423-0430*	1000	39	0.60	0.79	J250	5	474	1044
387-5720	1200	48	0.91	1.19	K80	5	625	1378
385-5649	1210	48	0.76	1.00	J250	6	500	1102

\*Tips included

### 318D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
433-0313*	1200	47	0.80	1.05	J300	6	677	1492
<b>Severe Duty</b>								
394-2345*	1050	42	0.76	1.00	J350	5	730	1609

\*Tips included

### M320D2

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
388-9586	600	24	0.39	0.50	K80	3	458	1010
466-8140*	1200	48	1.00	1.31	J300	5	692	1526
388-9590	1200	48	0.98	1.29	K80	5	669	1475
389-0254	1300	51	1.07	1.41	K80	5	698	1539
388-9591	1400	55	1.18	1.54	K80	5	730	1609

\*Tips included

### M322D2, M322D2 MH, M324D2 MH

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
422-6976	1200	48	1.19	1.56	K80	5	768	1693
422-6978	1400	55	1.43	1.87	K80	5	808	1781

MH – for use with Material Handling configuration

### A-Family (320 SLR, 326D2 SLR, 330 SLR)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Ditch Cleaning</b>								
441-6077	1200	48	0.57	0.74	BOCE Included		386	852

BOCE – Bolt-on Cutting Edge

SLR – for use with Super Long Reach configuration

### B-Family (320 GC, 320, 323, 326D2, 336 SLR)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Utility Duty</b>								
355-7211*	1124	44	0.80	1.05	J350	5	736	1623
442-8268*	1150	46	0.90	1.18	J350	5	750	1653
<b>General Duty</b>								
377-5394*	1250	50	1.00	1.31	J350	5	816	1800
377-5395*	1400	56	1.14	1.49	J350	6	882	1945
<b>Severe Duty</b>								
540-4105*	1100	43	1.00	1.31	100	4	1042	2297
540-4106*	1250	49	1.19	1.56	100	5	1140	2513

\*Tips included

SLR – for use with Super Long Reach configuration

### CB-Family (326D2, 330 GC, 330)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
370-5824*	1400	55	1.54	2.02	J400	6	1165	2568
<b>Heavy Duty</b>								
540-4094*	1300	53	1.45	1.90	100	5	1243	2740
540-4095*	1450	57	1.57	2.05	100	6	1329	2930
556-2168*	1500	60	1.76	2.30	100	7	1404	3095
<b>Severe Duty</b>								
528-4596*	1300	51	1.36	1.78	110	4	1395	3075
528-4598*	1400	56	1.54	2.01	110	5	1496	3298

\*Tips included

(continued on next page)

# Buckets for Hydraulic Excavators Technical Specifications

## Pin-on/Cat® Pin Grabber Buckets (continued)

Can be used pinned on to the machine or with a Cat Pin Grabber Coupler.

### DB-Family (326D2 ME, 330 ME, 336 GC, 336, 340D2)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
509-4276*	1500	60	1.88	2.45	J400	5	1339	2952
<b>Heavy Duty</b>								
528-4565*	1350	55	1.64	2.14	110	5	1572	3466
563-2888*	1450	58	1.76	2.30	110	5	1619	3569
528-4566*	1500	61	1.88	2.46	110	5	1670	3682
528-4567*	1650	67	2.12	2.77	110	5	1768	3898
<b>Severe Duty</b>								
525-4049*	1400	55	1.64	2.14	130	4	1805	3979
525-4050*	1550	61	1.90	2.48	130	4	1948	4295
528-8130*	1700	67	2.12	2.77	130	5	2094	4616
563-2899*	1850	73	2.31	3.02	130	5	2191	4830

\*Tips included

ME – for use with Mass Excavation configuration

### TB-Family (336 GC ME, 336 ME, 340D2 ME, 349D2 ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
374-6710*	1500	60	2.14	2.80	J550	4	2092	4612
<b>Heavy Duty</b>								
519-2233*	1650	65	2.41	3.15	130	5	2488	5485
<b>Severe Duty</b>								
519-2234*	1550	61	2.14	2.80	130	4	2338	5154
519-2235*	1650	65	2.41	3.15	130	5	2584	5697
542-5967*	1700	67	2.41	3.16	J550	5	2683	5915

\*Tips included

ME – for use with Mass Excavation configuration

### UB-Family (349D2 ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Severe Duty</b>								
519-2236*	1550	61	2.61	3.41	130	4	2740	6041
519-2237*	1850	73	3.21	4.20	130	5	3078	6786

\*Tips included

ME – for use with Mass Excavation configuration

### WB2-Family (374F ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Severe Duty</b>								
519-5394*	2200	87	4.60	6.02	170	4	5248	11570

\*Tips included

ME – for use with Mass Excavation configuration

### JC-Family (390F ME)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
391-0826*	2500	98	6.00	7.90	J700	6	6079	13402
<b>Severe Duty</b>								
519-5462*	2300	91	5.26	6.88	200	4	6896	15203
519-5461*	2500	95	6.00	7.85	200	5	7282	16054

\*Tips included

ME – for use with Mass Excavation configuration

## Ground Engaging Tools

Part numbers include tip and retainer unless otherwise indicated.

### Cat Advansys™ Tips

	100	110	130	170	200
<b>Double Spike</b>	505-4105	505-4115	381-4092	368-3871	
<b>General Duty</b>	505-4106	505-4116	381-4088	368-3872	385-4811
<b>Heavy Duty</b>	505-4002	505-4012	368-3791	368-3867	385-4814
<b>Heavy Duty Long Life (ARM)</b>	505-4003	505-4013	368-3857	387-6856	387-6867
<b>Leveling Edge Conversion (LEC)</b>	505-4005				
<b>Penetration</b>	505-4101	505-4111	381-4093	368-3868	368-3877
<b>Penetration Long Life (ARM)</b>	505-4102	505-4112	368-3858	387-6866	387-6868
<b>Penetration Plus</b>	505-4103	505-4113	381-4089	368-3869	368-3878
<b>Spike</b>	505-4104	505-4114	381-4090	368-3870	
<b>Wide</b>	505-4100	505-4110	381-4091	368-3866	

(continued on next page)

# Buckets for Hydraulic Excavators Technical Specifications

## Ground Engaging Tools *(continued)*

Part numbers include tip and retainer unless otherwise indicated.

### K Series Tips

	<b>K80</b>
<b>Double Spike</b>	229-6968
<b>Extra Duty</b>	229-6964
<b>General Duty</b>	229-6969
<b>Penetration</b>	229-6965
<b>Penetration Plus</b>	229-6966
<b>Spike</b>	229-6967
<b>Wide</b>	229-6963

### J Series Tips

	<b>J250</b>	<b>J300</b>	<b>J350</b>	<b>J400</b>	<b>J550</b>	<b>J700</b>
<b>Abrasion, Heavy Duty</b>	8E-3755	8E-3756			198-8486	455-1027
<b>Double Spike</b>			135-9357	135-9408		
<b>Extra Duty</b>						455-1031
<b>General Duty</b>			1U-3352	7T-3402		
<b>Long</b>	9J-3169	9J-3167			198-8478	
<b>Long, Heavy Duty</b>	8E-3750	8E-3751			198-8479	
<b>Penetration</b>	100-6462	3G-3237	9J-4359	6Y-7409	198-8487	
<b>Penetration Long Life (ARM)</b>			119-9359	124-7409		
<b>Penetration Plus</b>		195-9180	168-1359	168-1409	195-9185	455-1024
<b>Short</b>	9J-3178	9J-3175			198-8485	
<b>Spike</b>			168-1350	159-0400		136-8700
<b>Twin Sharp</b>	229-7137				169-4150	
<b>Wide</b>	101-2927	4T-2215	107-3350	107-3400	8J-9840	

### Sidecutters and Protectors

Machine Model or Linkage Family	Sidebar Protectors	Sidecutters		
	4 Piece Set	GD	HD	SD
<b>311, 312, 313, 314</b>		380-1203		380-1203
<b>315, 316, M313-M318</b>		380-1204	380-1204	380-1204
<b>318</b>		380-1204	380-1204	380-1204
<b>B, CB, DB</b>	357-2691	7Y-0366	357-2698	357-2698
<b>M320, M322</b>	195-7216	380-1204	380-1204	
<b>TB, UB, VB, HB</b>	357-2687		357-2685	357-2685
<b>VB2, WB2, HB2</b>	329-5956		357-2686	357-2686
<b>JC</b>	357-2688		357-2686	357-2686

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

GEJQ2368-00 (10-2018)  
(China)

© 2018 Caterpillar  
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

