



Cat[®] 140 GC

Motor Grader

The Cat[®] 140 GC motor grader is easy to own and operate. It's easy on your wallet too. A demand fan and standard ECO mode reduces fuel consumption while open access to maintenance points makes service quick and simple. Control the blade with consistent precision using lever controls from the comfort of the cab. Not all features available in all regions. Consult your Cat dealer for specific configurations available in your region.

Productive and Economical

- Increase your fuel economy up to five percent with the standard ECO mode.
- The on-demand fan reduces fuel consumption and under-hood heat for longer component life.
- Improve productivity with the Electronic Throttle Control which matches engine power and torque to application requirements.
- The powershift transmission and machine balanced design ensures that you get full drawbar power to the ground with the Cat C7.1 engine.
- The hydraulic system makes the machines more precise and predictable for a consistent grade.
- The Digital Blade Slope Meter option shows you the grade without relying on manual grade checkers.
- Product Link™ provides location, machine hours, fuel usage, productivity, idle time, diagnostic codes, and other machine data on demand through the VisionLink® online interface, which helps you improve job site efficiency with lower operating costs.

Cab Keeps You Comfortable All Day Long

- Choose your comfort level in the cab with standard, mechanical suspension or air suspension seat.
- Easily adjust the control console and steering wheel.
- The high capacity Heating, Ventilation and Air Conditioning (HVAC) system option circulates fresh air, prevents dust entry and keeps windows from fogging.
- Easily add a radio to the cab using the built-in mounting location option.

Reliability

- The drawbar circle moldboard stays factory tight providing precision grading pass after pass.
- The machine structure is built for a long life. It's designed to use several types of work tools, such as a front blade.
- A slip clutch option protects the circle drive if the machine strikes an immovable object.
- The front axle maximizes bearing life while also minimizing maintenance.
- Reduce daily greasing requirements and costly repairs to your circle and pinion with the Circle Saver option.



Cat® 140 GC Motor Grader

Safety

- See what's behind you with the rear camera option. The dedicated display can always be on to ensure a safe work environment.
 - The heated lens keeps the rearview camera clear in cold and wet conditions.
- In the event of an engine stall, count on the secondary steering system option to help stop the machine safely.
- Use three points of contact when entering and exiting the machine with strategically placed walk ways and grab rails.
- Ground level engine shut-off switch stops all fuel to the engine when activated and shuts down the machine.
- See the rear of your machine with side and rearview mirrors.
- Work past sundown using the strategically placed lights for night time visibility.
- Keep your work site safer with Cat GRADE Digital Blade Slope Meter to reduce the need for manual grade checking with working machines.

Maintenance

- Filters, such as fuel, engine air, and oil filters, are grouped together for easy access and preventative maintenance.
- The standard drawbar circle moldboard increases durability using hardened circle teeth and replaceable wear inserts to help sustain factory tightness.
- Hydraulic brakes are well oiled to keep them maintenance free.
- The standard bottom guard shields the transmission and filter. Optional guarding protects your machine from damage in demanding applications.

Versatility

- Improve the performance and efficiency of your machine with the counterweight or push block option.
- Ripper and scarifier options are available to assist with grading hard ground.
- The front lift group option is ready for attachments like the straight or angle front blade.
- For more road coverage, add a moldboard extension to add 605 mm (24 in).

Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
CAB			DRAWBAR CIRCLE MOLDBOARD		
Standard Seat	✓		Standard	✓	
Mechanical Suspension Seat		✓	Circle Drive Slip Clutch		✓
Air Suspension Seat		✓	Circle Saver		✓
Steering Wheel/Lever Controls	✓		SAFETY		
ROPS		✓	Parking brake	✓	
Heating/Cooling Cab System		✓	Signaling/warning horn	✓	
Rear Wiper		✓	Rearview mirror	✓	
Base Cab	✓		Rearview camera		✓
Canopy		✓	Hydraulic brakes	✓	
Cab Plus		✓	Secondary steering system		✓
Information Display Screen	✓		Side view mirrors	✓	
Halogen Lighting	✓		Walkways and Grab Rails	✓	
Entertainment Radio Ready	✓		VERSATILITY		
Rear Window Screen		✓	Counterweight		✓
Front Wipers		✓	Push Block		✓
Digital Blade Slope Meter		✓	Ripper		✓
Product Link	✓		Scarifier		✓
ENGINE			Front Lift Group		✓
Cat C7.1	✓		Front Blade		✓
ECO Mode	✓				
On-Demand Fan	✓				

Cat® 140 GC Motor Grader

Technical Specifications

Engine

Engine Model	Cat 7.1	
Emissions	China Nonroad Stage III and Brazil MAR-1 emission standards, equivalent to U.S. EPA Tier 3/EU Stage IIIA	
Net Power Range (Tier 3)	131 kW-147 kW	176 hp-196 hp
Engine RPM	2,200 rpm	
Displacement	7.01 L	427.8 in ³
Bore	105 mm	4.1 in
Stroke	135 mm	5.3 in
Torque Rise ISO 9249	40%	
Maximum Torque ISO 9249	889 N·m	656 lbf·ft
Number of Cylinders	6	
Derating Altitude	4500 m	14,764 ft
Standard Capability	43° C	109° F
<ul style="list-style-type: none"> • Net power is tested per ISO 9249, SAE J1349, and EEC 80/1269 Standards in effect at the time of manufacture. • Net power advertised is the power available at rated speed of 2,200 rpm, measured at the flywheel when engine is equipped with fan, air cleaner, muffler and alternator. • Power as declared per ISO 14396. 		

Air Conditioning System

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 2.0 kg of refrigerant which has a CO₂ equivalent of 2.86 metric tonnes.

Machine Weight

Weight*	16 620 kg	36,640 lb
*Typically equipped includes tires, push block, ripper, bottom guard, operator, and full fluids and fuel.		

Dimensions

Length of Machine*	10 332 mm	406.7 in
Maximum Height	3777 mm	148.7 in
Width	2428 mm	95.6 in
*Typically equipped with push block and ripper.		

Moldboard

Blade Width	3.7 m	12 ft
Blade Height	509 mm	20 in
Arc Radius	413 mm	16.3 in
Throat Clearance	112 mm	4.4 in
End Bit Width	152 mm	6 in
Cutting Edge Width	152 mm	6 in

Blade Range

Circle Center Shift		
Right	728 mm	28.7 in
Left	752 mm	29.6 in
Moldboard Side Shift		
Right	512 mm	20.2 in
Left	663 mm	26.1 in
Blade Tip Range		
Forward	40°	
Backward	5°	
Maximum Shoulder Reach		
Right	1928 mm	76 in
Left	1764 mm	69.4 in
Maximum Lift Above Ground	480 mm	18.9 in
Maximum Depth of Cut	735 mm	29 in

Service Refill Capacities

Fuel Tank	295 L	78 gal
Circle Drive with Slip Clutch	7 L	1.8 gal
Circle Drive without Slip Clutch	1.5 L	0.4 gal
Engine Crankcase	19 L	5 gal
Cooling System	57 L	15.1 gal
Hydraulic System	55 L	14.5 gal
Transmission	18 L	4.8 gal



For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2018 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Yellow", the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

AEXQ2479 (10-2018)
Build Number: 01A
(Afr-ME, Aus-NZ, CIS, China, India,
Indonesia, S Am, SE Asia, Turkey)

