

# CAT® GROUND ENGAGING TOOLS



FOR CONSTRUCTION



# MADE FOR YOUR APPLICATION.

**Protect expensive machine components. Reduce your operating costs. And get the most out of your machine's performance.**

The most important part of any machine is its work tool. Buckets or blades, tips or edges, rippers or side cutters—no matter the size, worktools and Ground Engaging Tools (G.E.T.) are the main reason the machine exists. G.E.T. have a direct effect on the machine's ability to produce. Improper selection affects not only your productivity, but also your fuel consumption, maintenance costs and possibly the longevity of your equipment.

Caterpillar offers "off-the-shelf" and custom G.E.T. systems that maximize machine productivity, and your Cat® dealer can help you establish an effective management program that minimizes preventable problems—working to reduce your operating and maintenance costs.

Use this catalog to learn more about what's available for your equipment, then work with your Cat dealer's G.E.T. specialist or PSSR to select the components built for your industry and jobsite conditions. We'll make sure you get the rugged durability, solid protection and lowest cost-per-ton production system you need.





**Dozers**..... 4  
 Cutting Edges & End Bits ..... 6  
 Ripper Systems..... 16

**Motor Graders**..... 25  
 Cutting Edges..... 27  
 Grader Bit System 2™ ..... 35  
 Mining Bit System..... 41  
 End Bit System..... 42  
 Ripper-Scarifier System..... 43

**Hydraulic Excavators**..... 47  
 Tip & Adapter Systems  
     Cat Advansys Tip & Adapter System ..... 50  
     K Series Tip & Adapter System..... 55  
     J Series Tip & Adapter System..... 60  
     Hammerless Tip & Adapter System ..... 64  
 Base Edge Systems ..... 67  
 Side & Edge Protection..... 71  
 Rip & Load System..... 80

**Wheel Loaders**..... 82  
 Tip & Adapter Systems  
     Cat Advansys Tip & Adapter System ..... 84  
     K Series Tip & Adapter System..... 90  
     J Series Tip & Adapter System..... 96  
     Hammerless Series Tip &  
     Adapter System..... 100  
 Base Edge Systems ..... 104  
 Cutting Edges..... 114  
 Side & Edge Protection..... 120  
 Bucket Selection Guide ..... 125  
**Wear Parts & A.R.M.**..... 131

Part number reference can be found in Appendix (PEBJ0079)

\*Note: Please send all feedback to <https://dealer.cat.com/en/ps/parts/parts-mktg/get/c/form.html>

# DOZERS

No other manufacturer in the world has more experience moving material than Caterpillar. We invented the dozer over 100 years ago—and we've been the market leader ever since. There are more Cat dozers at work in the world than any other brand.

Dozers work in dozens of different industries, applications, climates and environments and can be customized for specific jobs—just like the G.E.T. that protect their blade or ripper system. From parts availability to expert support and service, Cat customers can count on one reliable source—Caterpillar and Cat dealers.



# SYSTEM OVERVIEW

Dozers move ground at mines, construction sites, residential developments and hundreds of other places. A dozer's main work tools are a blade and a ripper. The universal blade is curved, wide and tall so that it can carry material. Other blades are flat or shorter, but they all do a similar job: leveling the ground. The ripper loosens the rocky or compact earth, which makes dozing or loading easier.

Both the blade and ripper have to balance ground penetration with wear life. Excessive worktool or G.E.T. wear material can make the machine less effective. Cat dozer cutting edges and end bits are designed as a balanced system to move more material over a longer period with less downtime—which translates into a lower cost per hour for you. Select from dozens of ripping system configurations or have your Cat dealer help you choose the best option for your application.



# CUTTING EDGES & END BITS

BALANCED EDGE SYSTEMS FOR EVERY APPLICATION.

Matching your cutting edge wear rates with your end bit selection is easy with our broad portfolio of options. You achieve a balanced system, which helps reduce both maintenance intervals and operating costs, leading to more productivity.

Cat end bits and cutting edges can be custom ordered with Cat Abrasion Resistant Material (A.R.M.), which is recommended for applications where sand, gravel or other abrasive materials severely diminish wear life. Hard tungsten carbide particles are bonded to critical wear areas, providing up to five times greater wear life than similar end bits and cutting edges without A.R.M. See your Cat dealer for details.

## SAFER, SIMPLER INSTALLATION

Threaded holes allow easier handling of edges at first install or during rotation to wear opposite edge.

## MINIMAL THROW AWAY

Multiple edge sections allow you to rotate or replace only the worn areas.

## IMPROVED PRODUCTIVITY

Broad offerings allow you to have both end bit penetration and long cutting edge life, resulting in less maintenance.



# CUTTING EDGE & END BIT OPTIONS

We have G.E.T. for your blade, no matter the application or environment. As machines grow larger, their jobs become tougher, and so do Cat G.E.T. Maximum wear life and breakage resistance is possible with our steel alloy that can endure 2 times the heat and pressure of traditional blade steel products. Consult your local Cat dealer to help determine the best cutting edge system for your application to give you the lowest cost per hour.



# D3 - D5 END BIT OPTIONS



## LEVEL CUT/ FINISH (FACTORY FIRST FIT)

- » Recommended for finish and semi-finish dozing
- » Matches cutting edge's depth of cut
- » Low-impact, low-abrasion materials only

**A.R.M.**  
OPTION  
AVAILABLE



## LEVEL CUT REVERSIBLE

- » Reversible finish and semi-finish dozing end bits
- » Used in applications where curbing is not a requirement



## LEVEL CUT EXTENDED REVERSIBLE

- » Longer reversible finish and semi-finish dozing end bits used to extend the length of the blade
- » Used in applications where curbing is not a requirement



# D6 END BIT OPTIONS



## LEVEL CUT/ FINISH (FACTORY FIRST FIT)

- » Recommended for finish and semi-finish dozing
- » Matches cutting edge's depth of cut
- » Low-impact, low-abrasion materials only

**A.R.M.**  
OPTION  
AVAILABLE



## LEVEL CUT REVERSIBLE

- » Reversible finish and semi-finish dozing end bits
- » Used in applications where curbing is not a requirement




## HOT CUPPED

- » Forward protruding profile for better penetration than flat plate



## GENERAL PURPOSE

- » Sharpened, forward protruding profile for excellent penetration
- » For fast blade loading, high productivity applications



## UTILITY

- » Thick cross-section for high face wear applications
- » Recommended for high-impact, high-abrasion applications




## EXTENDED WEAR LIFE (EWL)

- » 25% more usable wear material than General Purpose
- » Prolonged life and excellent penetration in abrasive conditions

**A.R.M.**  
OPTION  
AVAILABLE


# D7 - D9 END BIT OPTIONS



## LEVEL CUT/ FINISH

- » Recommended for finish and semi-finish dozing
- » Matches cutting edge's depth of cut
- » Low-impact, low-abrasion materials only


**A.R.M.**  
OPTION  
AVAILABLE



## UTILITY

- » Thick cross-section for high face wear applications
- » Acceptable in high-impact, high-abrasion applications

**A.R.M.**  
OPTION  
AVAILABLE



## HOT CUPPED

- » Forward protruding profile for better penetration than flat plate

**A.R.M.**  
OPTION  
AVAILABLE



## GENERAL PURPOSE (FACTORY FIRST FIT)

- » Sharpened, forward protruding profile for excellent penetration
- » For fast blade loading, high productivity applications

**A.R.M.**  
OPTION  
AVAILABLE



## EXTENDED WEAR LIFE (EWL)

- » 25% more usable wear material than General Purpose
- » Prolonged life and excellent penetration in abrasive conditions

**A.R.M.**  
OPTION  
AVAILABLE

*See page 188 for more details on Abrasion Resistant Material (A.R.M.).*

# D10 - D11 END BIT OPTIONS



## LEVEL CUT/ FINISH

- » Recommended for finish and semi-finish dozing
- » Matches cutting edge's depth of cut
- » Low-impact, low-abrasion materials only



## UTILITY

- » Thick cross-section for high face wear applications
- » Acceptable in high-impact, high-abrasion applications



## HOT CUPPED

- » Forward protruding profile for better penetration than flat plate



## GENERAL PURPOSE

- » Sharpened, forward protruding profile for excellent penetration
- » For fast blade loading, high productivity applications



## EXTENDED WEAR LIFE (EWL: FACTORY FIRST FIT)

- » 25% more usable wear material than General Purpose
- » Prolonged life and excellent penetration in abrasive conditions

**A.R.M.**  
OPTION  
AVAILABLE



## EXTREME EXTENDED WEAR LIFE (EEWL)

- » 25% more usable wear material than General Purpose
- » Prolonged life and excellent penetration in abrasive conditions

**A.R.M.**  
OPTION  
AVAILABLE



## HIGH ABRASION

- » New cast edges and end bits provide up to 40% longer wear life than Extended Wear Life (EWL)
- » Optimized material placement

# HIGH-ABRASION CAST CUTTING EDGE SYSTEM

MAXIMIZE MACHINE UPTIME IN THE MOST ABRASIVE APPLICATIONS.

Designed to fit Cat D10 and D11 universal and semi-universal blades, this cast cutting-edge system delivers reduced machine downtime and maximum productivity in low to moderate impact pushing applications. The new high-abrasion end bits are now married up with complementary cast high-abrasion cutting edges, an offering that Cat has never had in the past.

## MAXIMUM WEAR LIFE

New cast edges and end bits provide up to 40% longer wear life than Extended Wear Life (EWL).

## LESS THROW AWAY

Optimized material placement results in more wear material and less throwaway weight.



## A COUPLE MINUTES CAN SAVE YOU HOURS.

Ensuring a long life for your blade and the G.E.T. that protects it involves three simple steps. Clean surfaces, new hardware and proper installation technique are shared as tips and tricks below. Always follow the specific instructions for your machine. Your local Cat dealer is only a phone call away if you need assistance.

### 1) Clean and Pristine

- » Surfaces, bolts and nut threads must be clean to ensure maximum clamping force
- » When installing, use new hardware as old bolts may have suffered metal fatigue

### 2) Center Out

- » Cutting edge bolts are installed from the center outward—do not install from both ends toward the center
- » End bit bolts are installed first from the center outward, then from the center inward

### 3) Torque, Bang, Torque

- » Tighten all bolts to the required torque
- » Wearing safety goggles, seat bolt heads in the countersinks with a heavy hammer
- » Tighten the bolts again to required torque



# BLADE PROTECTION

PUSH BACK ON COSTLY REPAIRS.

Protect your blades from impact and aggressive wear with the line of Cat blade protection for dozers. All Cat blade products are manufactured to the factory contour, making fit and installation fast and efficient.

## REDUCE BLADE DAMAGE


Push plates distribute the high forces created when pushing scrapers.

## EXTEND BLADE SERVICE LIFE

Wear plates extend the service life of the blade "skin" in highly abrasive conditions.


## SIMPLIFY INSTALLATION

Cat wear bars are 450 BHN and beveled to accept weld bead—a fast way to add strength and protection.



## BLADE MAINTENANCE & REPAIR

Only a Cat cutting edge support will guarantee dimensional accuracy like the factory originals. Cutting edges and end bits are fastened to your cutting edge support. This bolted connection requires a perfectly flat and smooth surface the full length of the blade to ensure your G.E.T. stays secure. When millimeters matter, count on Cat quality and your Cat dealer's capabilities.



# SIDEBAR PROTECTOR


Dozers need sidebar protection, too. Large dozers, like large loaders, work in high-impact and extreme abrasion. Increase carrying capacity and simplify your blade maintenance with hammerless protection. Simply weld in the protector adapter once and save hours each time you replace the sidebar protection.

## LOW MAINTENANCE

Protects the blade edge and extends sidebar reach to reduce maintenance cost and increase capacity.

## HAMMERLESS

Fast, easy removal and installation. Reduces risk of injury.



# RIPPER SYSTEMS

CAUSE A DISTURBANCE, GAIN PRODUCTIVITY.

Selecting the proper ripping tools can make the difference between just being able to rip a material and being able to reach optimum efficiency and maximum production (lowest cost/yd<sup>3</sup>). Production ripping (>20% of operation) usually requires a single shank ripper, as do very hard or tightly compacted materials. The more varied the job conditions, the greater the need for the multishank ripper. The multishank is especially useful in pre-ripping for scrapers or other loading tools.

## LOWER OPERATING COSTS

Hammerless design allows pin re-use on R style adapters.

## HAMMERLESS DESIGN

Fast, easy removal and installation. Reduces risk of injury.



*For more information on ripper systems, please reference [The Handbook of Ripping \(AEDK0752\)](#).*

# RIPPER SYSTEM AVAILABILITY

Tooth penetration can be the key to ripping success. That's why we offer a variety of tip styles and profiles. Our alloy steel tips withstand higher operating temperatures and are also self-sharpening. Shank protection helps you cut the material and extend your maintenance intervals. The products below are readily available, or you can consult your Cat dealer for custom options.

TIP OPTIONS	R350		R450		R500		R550	
	Side Pin	CapSure						
Centerline - Short								
Centerline - Intermediate								
Centerline - Intermediate A.R.M.								
Centerline - Long								
Centerline - Sharp Limestone								
Centerline - Sharp A.R.M.								
Penetration - Short								
Penetration - Intermediate								
Penetration - Intermediate A.R.M.								
Penetration - Long								
Penetration - Sharp								

SHANK PROTECTOR	R350		R450		R500		R550	
	Side Pin	CapSure						
Protector - Long (110mm Shank)								
Protector - Std (110mm Shank)								
Protector - Long (100mm Shank)								
Multi pc Sharp & Guard (100mm Shank)								
Protector - Std (100mm Shank)								
Protector - Long (90mm Shank)								
Protector - Std 1 pin (90mm Shank)								
Protector - Std 2 pin (90mm Shank)								
Protector - Long (75mm Shank)								
Protector - Sharp (75mm Shank)								
Protector - Std (75mm Shank)								
Protector - Std (73mm Shank)								

# HAMMERLESS RIPPER TIPS

## CAPSURE RETENTION

Always use the longest tip without excessive breakage. Centerline tips have equal wear material on both sides and can be reversed, which can extend the life and help maintain sharpness. Cat penetration ripper tips have an aggressive angle to break through even the hardest surfaces and dig into the ground more effectively. Both hammerless options feature a topside deflector, which creates a smooth transition with the shank protector.



### SHORT CENTERLINE

- » Used in extreme impact conditions
- » Sacrifices some wear material



### INTERMEDIATE CENTERLINE

- » Used for moderate impact and abrasion conditions
- » 33% longer than Short Centerline



### INTERMEDIATE PENETRATION

- » Used for moderate impact and abrasion conditions



### LONG PENETRATION

- » Designed for low-impact, highly abrasive conditions where breakage is not a problem
- » 20% longer than Intermediate Penetration

## INSTALLATION & REMOVAL

Hammerless removal and installation is possible with your current side pin shank/adapter system. CapSure™ retention is built into each tip, so you only need to insert a pin to experience faster, safer, easier tip change out.

**1** Insert pin into adapter hole.




**2** Insert washer into adapter hole.



**3** Slide the tip onto adapter.



**4** Turn retainer 180° to lock/unlock.



Removal and installation animation is available at [www.youtube.com/watch?v=UW6\\_jjqa\\_eA](http://www.youtube.com/watch?v=UW6_jjqa_eA) or by scanning the QR code to the right.



# R SERIES RIPPER TIP OPTIONS

Always use the longest tip without excessive breakage. Centerline tips have equal wear material on both sides and can be reversed, which can extend the life and help maintain sharpness. Cat penetration ripper tips have an aggressive angle to break through even the hardest surfaces and dig into the ground more effectively.



## SHORT CENTERLINE

- » Used in extreme impact conditions
- » Sacrifices some wear material



## INTERMEDIATE CENTERLINE

- » Used for moderate impact and abrasion conditions
- » 17% more wear material than Short Centerline

**A.R.M.**  
OPTION  
AVAILABLE



## LONG CENTERLINE

- » Used in low-impact, high-abrasion conditions where breakage is not a problem
- » 30% more wear material than Intermediate Centerline



## SHARP CENTERLINE A.R.M.

- » Intermediate Centerline tip, which is tapered to a pick-like point on the end
- » A.R.M. strip on one side enhances sharpening action
- » Offers best penetration and 13% more wear material than Short Centerline

**A.R.M.**  
OPTION  
AVAILABLE



## SHARP LIMESTONE

- » Used in limestone or caliche applications
- » Chisel point penetrates in hard-to-penetrate materials
- » 16% more wear material than Short Centerline and 10mm shorter than Intermediate Centerline



## SHORT PENETRATION

- » Used in extreme impact conditions
- » Sacrifices some wear material



## INTERMEDIATE PENETRATION

- » 17% more wear material and 50mm longer than Short Penetration
- » Used for moderate impact and abrasion conditions



## LONG PENETRATION

- » Used in low-impact, high-abrasion conditions where breakage is not a problem
- » 4% more wear material and 47mm longer than Intermediate

**A.R.M.**  
OPTION  
AVAILABLE



## SHARP PENETRATION

- » Intermediate Penetration length tip
- » Factory sharpened to ensure maximum penetration

## INSTALLATION & REMOVAL

The R Series Tooth and Adapter system uses the standard pin and retainer system. The Tooth Pin Remover tool is available to make removal easier.

- 1** Place the tool on the tip and align the extractor with the pin.



- 2** Strike the tool with a hammer until the pin is removed.



*Single shank machine*

# RIPPER SHANK PROTECTOR

WANT BETTER PRODUCTIVITY WITH LESS COST? WE'VE GOT YOU COVERED.

Shank protectors cut through material with sharp edges, lowering the ripping effort. Minimize the wear, and required maintenance, on the more expensive shank body when you guard it with a protector. Never rip without Cat G.E.T. Our hammerless options offer fast, easy removal and installation without specialty tools.

## SHARPENED PROFILE

Cuts through tough and compact materials, causing lower ripping resistance and less horsepower loss.

## EXTENDED PROTECTORS

60% more coverage.

## FULL LENGTH

Triangle-shaped guard-bar integrates with sharp lower protector for maximum ripping protection.



# RIPPER SHANK PROTECTOR OPTIONS

Four different protection options align with the tractor's ripping system and the most common applications.



**PIN ON**

## GENERAL PURPOSE

- » Baseline protector R350 and R450 only



**ONE PIN**



**HAMMERLESS**

## SHARP

- » Penetrates compact material better than standard design
- » Hammerless option has 40% more wear material than side pin version



**PIN ON**



**HAMMERLESS**

## EXTENDED PROTECTOR

- » 60% more shank protection than Sharp



**THREE-PIECE SHANK PROTECTOR**



**PIN ON**

## INTEGRATED SHARP

- » Works with triangle-shaped bar to provide complete shank protection

## INSTALLATION & REMOVAL

Hammerless retention made simple. The CapSure™ locking system allows for safer and easier removal/installation in four steps.

1

Insert pins and washer into shank hole.



2

Place shank protector over lower pin.




3

Position retainer over upper pin.



4

Turn retainer 180° to lock/unlock.



Removal and installation animation is available at [www.youtube.com/watch?v=UW6\\_jjqa\\_eA](http://www.youtube.com/watch?v=UW6_jjqa_eA) or by scanning the QR code to the right.



# MOTOR GRADERS

We offer hundreds of cutting edge options available on the shelf, plus the ability to customize through our Made as Order (MAO) program. Unique offerings like the Cat GraderBits™ system meet the toughest application needs and are complemented by multiple End Bit options. Trust your Cat dealer to offer you solutions that focus on total machine productivity.



# CHOOSING AN EDGE

Edge selection is critical for enhancing production and keeping cost to a minimum. Application affects the cutting edge shape, metallurgy and style. Impact, penetration and abrasion define your application environment. An edge has to penetrate the material and not break during operation. Edge life then becomes a matter of metallurgy and thickness.



## WHAT IS YOUR APPLICATION?



### DEVELOPING A ROAD OR PERFORMING HEAVY MAINTENANCE

» A flat edge is best suited for this application. A better penetrating option is a flat serrated edge. A flat edge has limited ability to carry material forward.



### GRADING HARD-PACKED GRAVEL, FROZEN EARTH AND ICE

» A serrated edge penetrates better than a continuous edge because it exerts more down pressure. A curved serrated edge penetrates better than a flat serrated edge with a forward mold board.



### RECONDITIONING OR FINISH GRADING AN EXISTING ROAD SURFACE

» Curved edges penetrate the roadway while carrying existing material forward to leave a smooth flat surface. A better penetrating option is a curved serrated edge. A serrated edge will not leave as clean a roadway surface as a continuous edge.

# MOTOR GRADER CUTTING EDGE OPTIONS

PARTNER WITH CATERPILLAR, EDGE OUT THE COMPETITION.

Caterpillar offers a wide range of cutting edges for motor graders. Each provides certain benefits when used in the appropriate application. Using the right edge is critical for enhancing production and keeping total costs to a minimum. The three factors to consider in choosing a cutting edge are shape, width and thickness.

There are two basic edge shapes—flat and curved—with serrated edges available in both configurations. In addition, the Cat GraderBits system dramatically expands the range of edge shape options. Cat offers two types of grader edges and three edge thicknesses for the 16M and 24M motor graders.

---

## SUPERIOR DURABILITY, MORE OPTIONS

Cat DH-2 through-hardened steel edges are available in a variety of shapes and thicknesses to fit every application.

---

## EXTENDED EDGE LIFE

Maximize your edge life with tungsten carbide edges.

---

## MAXIMUM PENETRATION, MINIMUM WASTE

Cutting bit systems.

---



# THROUGH-HARDENED CUTTING EDGES

Most Cat edges are through-hardened steel, which offers high-impact resistance. High-carbon edges have good surface hardness and perform well in high-abrasion, low-impact applications such as finish work. High-carbon edges will not withstand the impact level of a through-hardened edge.



## FLAT

- » Heavy road maintenance and pioneering
- » Maximum strength and available wear material
- » Best option for abrasion and impact resistance




## FLAT SERRATED

- » Better penetration than a continuous edge (greater down pressure per inch of edge contact)
- » Designed to penetrate packed gravel, frozen earth and ice
- » For severe impact conditions, install over a 6" (152 mm) edge to reduce tooth breakage



## CURVED

- » Provides superior penetration and rolling action necessary for fine grading and finish work
- » Finishing tolerances less than 1/4" (6 mm)—the best value may be in selecting a narrow and thin cutting edge



## CURVED SERRATED

- » A curved serrated edge penetrates better than a straight serrated edge with a forward mold board



## EDGE WIDTH EQUALS WEAR MATERIAL

- » An 8" (203 mm) edge provides twice the wear material as a 6" (152 mm) edge at about 35% more cost
- » Hardware cost and R&I downtime are reduced by 50%

# TUNGSTEN CARBIDE TILE CUTTING EDGES

Cat Tungsten Carbide Cutting Edges combine through-hardened steel with the wear resistance of tungsten carbide. When used in high-abrasion, low-impact applications, they can provide up to 20 times the life of a standard through-hardened edge. Fewer edge changes means less downtime and lower hardware costs.



## TUNGSTEN CARBIDE EDGES

- » Tungsten carbide edges have a continuous row of trapezoid-shaped carbide “tiles.” This patented shape forms a leading / cutting edge
- » Carbide tile bottom must be flat to the ground. 20° maximum tilt
- » Max 5 mph/8kph
- » Do not use on roads with large embedded rocks



## FLAT EDGES

- » Maximum strength and available wear material
- » Longest wearing edge available in high abrasion and low impact



## CURVED EDGES

- » Curved-edge design improves penetration and rolling action
- » Trapezoid-shaped tungsten carbide tile on leading edge stays sharp as it wears
- » Shorter edge sections speed rotation and reduce “throw-away” due to edge crowning



## SERRATED EDGES

- » Better penetration than a continuous edge (greater down pressure per in<sup>2</sup> of edge contact)
- » No cast angle restrictions

# TUNGSTEN CARBIDE INSERT CUTTING EDGES

Cat carbide insert edges offer long wear life in higher speed applications like state/county road snow removal. The tungsten carbide is brazed into a milled groove in the center of the edge. The design offers impact resistance and minimizes edge “crowning” in applications that require a level grading operation.



# ROTATING BIT SYSTEM

The rotating bit system outperforms steel blades in high-production road reconditioning applications. Individual cutting bits have tungsten carbide tips and form a serrated edge to penetrate and lift material to the surface immediately. As a result, most road maintenance jobs can be accomplished in a single pass.

## MORE PRODUCTION, LESS WASTE


Material is brought to the surface for reuse, reducing the expense of spreading new gravel.

## NO RESTRICTIONS

No cast angle restriction.

## EASY INSTALLATION & MAINTENANCE

Bits changed individually with no special tools.



# ROTATING BIT SYSTEM

Rotating Scarifier Bits are self-sharpening for more uniform wear and long life. Cutting height is maintained as cutting tools may be rotated from position to position. Carbide bits can last as long as 5 -10 sets of conventional grader blades.

Rotating Scarifier Bits are made for applications such as dirt and gravel reclamation, oil road reclamation, and snow and ice removal.




## 1" SHANK

- » Smooth design


## 7/8" SHANK

- » Engineered with flat sides that aid in bit rotation



## ADAPTER BOARDS

- » Either 5/8" or 3/4" bolt hole punch
- » 3' (914mm)-21 bits
- » 4' (1219mm)-28 bits
- » Standard Board uses 7/8" bit
- » Heavy Duty board uses 1" bit



## OPERATING TIPS


- » 20° Board Angle
- » Moldboard may vibrate and bits may not turn if angle is not correct

## INSTALLATION & REMOVAL

Improve safety and simplify edge change-out. Cat cutting edges allow you to use a threaded bolt and link to remove and install sections. Even worn edges can be removed, because the threads are located in the back half of the hole.

**1**

Drilled and tapped holes.



**2**

Attach approved lifting device.



**3**

Lift.



## OPERATING TECHNIQUES FOR REDUCED COST.

Through better management of the interface between machine and materials, operators can maximize productivity, lower machine operating costs and reduce cab vibration, improving operator comfort.



### MOLDBOARD POSITION

- » Start with moldboard 2" (4" for 24M) ahead of the edge
- » Grade with cutting edge 90° to the road
- » Maintain fixed angle to ensure constant edge thickness
- » Laid back reduces penetration and can wear moldboard
- » Frequent angle changes will shorten the edge life




### SPEED AND EXCESSIVE DOWN PRESSURE

- » Use accumulator to absorb shocks
- » < 6mph/8kph speed
- » Excess speed can cause edge slivering
- » Need penetration? Choose a thinner edge, a serrated edge or the Cat GraderBits system for the most compacted materials



### CROWNING

- » Occurs when the cutting edge conforms to the material being graded
- » A narrow and thin edge reduces the "throw away" material
- » Extreme crowning may require a bit system



### STANDARDIZE YOUR HARDWARE

- » Moldboard bushings reduce 3/4" holes to 5/8"
- » Simplify inventory and lower cost

# GRADERBIT2™ SYSTEM

SMOOTH OUT THE TOUGHEST ROADWAYS IN A SINGLE PASS.

GraderBit2 System is ideal for finish grading, maintaining roadways or reconditioning haul roads. Tungsten carbide cutting bits deliver up to 20x wear life of through-hardened cutting edges. 7 different bit designs can form a continuous edge or 10 serration patterns that allow pass-through of 15 to 60mm aggregate.

**LOWEST  
OPERATING COST**

20% CPH SAVINGS VS THROUGH  
HARDENED EDGES

**APPLICATION  
ADAPTABLE**

2 CONTINUOUS EDGE SYSTEMS & 10  
SERRATED OPTIONS RECONDITION ANY  
SURFACE


**BUILT TO BE REBUILT**

OVERLAY CHANNELS AND REPLACEABLE  
BUSHINGS EXTEND BOARD LIFE

# GRADERBIT2™ SYSTEM

BIT BOARDS THAT ARE BUILT TO PERFORM IN YOUR APPLICATION

Grooves cast into the boards accept weld overlay or material packing in order to extend board wear life, while installing and removing the boards is made easier through pre-drilled lifting eye holes. Adapter boards feature an off-set design that ensures optimal bolted joint strength and consistent bit placement.




Bushings reduce board damage during extreme operations and can be replaced to extend board life



# GRADERBIT2™ SYSTEM

RETENTION THAT INSTALLS WITHOUT TOOLS AND ADJUSTS TO YOUR GRADING CONDITIONS

Bits are installed effortlessly with no tools thanks to pull-ring pin that inserts into the bit shaft and locks over the bit. Bit life is optimized at any cast angle thanks to Angling plates that always keep the bits facing the direction of travel.



The pull-ring pin makes bit installation / removal easy without the need for tools.

The bit shaft fits into the angling plate to prevent the bits from rotating. 7 plate options allow for a 0° to 30° Blade cast angle in 5° increments.



Angle plates keep the carbide facing the direction of travel to reduce erosion of the bit body, which can reduce bit life.





7 different bit designs can form a continuous edge or 10 serration patterns that allow pass-through of 15 to 60mm aggregate. Serration patterns remove holes and ridges from compacted surfaces. Wide or SnowBit™ create a continuous edge the system can be used for finish grading.



#### WIDE

At 63mm wide this bit can be configured as a continuous edge or placed in every other hole for a 2.5" serration pattern.



#### WIDE MINING

63mm wide & 12mm taller. Imbedded carbide layer adds 72% more carbide to extend bit life.



#### STANDARD

30mm, this bit offers a serration pattern that will allow aggregate up to 30mm to pass through.



#### STANDARD MINING

30mm wide & 12mm taller. Imbedded carbide layer adds 72% more carbide to extend bit life.



#### SHARP

23mm wide, this bit will help break into hard ground while allowing aggregate size to 37mm to pass through.



#### SNOW BIT™

63mm wide bull nose carbide insert & steel face. This continuous edge system is impact resistant & designed for paved road snow removal.



#### PENETRATION

Specially design carbide shape that comes to point and a width of 15mm this bit will help break into any surface.



#### BORE SAVER™

Used to protect adapter board bore holes when not in use.

Aggregate (mm) Pass-Through	Bit Configuration	Bit Width
0	Wide bits across the board	63 mm
15	Alternate Wide and Standard bits	63 and 30 mm
20	Alternate Wide and Sharp bits	63 and 23 mm
25	Alternate Wide and Penetration bits	63 and 15.5 mm
32	Standard bits across the board	30 mm
34	Alternated Standard and Sharp bits	30 and 23 mm
38	Sharp bits across the board	23 mm
38	Alternate Standard and Penetration bits	30 and 15.5 mm
42	Alternate Sharp and Penetration bits	23 and 15.5 mm
46	Penetration bits across the board	15.5 mm
64	Wide bit every other space	63 mm

WIDE – 64 mm SERRATION




SHARP – 38 mm SERRATION




WIDE/PENETRATION – 25 mm SERRATION



WIDE – CONTINUOUS EDGE



SNOWBIT – CONTINUOUS EDGE



# GRADERBIT2™ SYSTEM

## REMOVAL AND INSTALLATION

- 1** Insert bit into board, carbide facing direction of travel



- 2** Place desired Angle Bracket over bit shaft



- 3** Insert pin into Bit pin hole



- 4** Fold ring over Bit shaft



- 5** Insert remaining Bits & Pins



# END BIT SYSTEM

PUT AN END TO MOLDBOARD WEAR.

Made of through-hardened DH-2 steel for added strength and service life, Cat end bits protect moldboard edges from wear.



# END BIT SYSTEM

Maximize moldboard life and lower repair costs. Use Cat end bits, overlays, repair plates and hardware to protect and repair your moldboards and working edges.




## MOLDBOARD END BITS

- » Recommended for all applications
- » Made of through-hardened DH-2 steel for added strength and service life



## OVERLAY END BITS

- » Fit over existing end bit
- » Recommended for applications such as ditching
- » Add strength and limit corner wear
- » When worn on one side, overlay end bits can be rotated for a second wear life



## MOLDBOARD REPAIR PLATES

- » Extend moldboard life with Cat Moldboard Repair Plates
- » Routine monitoring and timely edge replacement can prevent damage
- » When repair is needed, repair plates provide a way to extend moldboard life



## HARDWARE

- » When replacing ground engaging tools, always use Cat hardware regardless of the application
- » Cat Grade 8 hardware is performance-matched to Cat G.E.T. in both strength and durability

# RIPPER-SCARIFIER SYSTEM

GET MORE OUT OF YOUR GRADER.

Scarifier and ripper systems on motor graders can be used to improve road surfaces by lifting material from compacted and worn areas or by removing the “crowning” that causes excessive wear on cutting edges.

---

## ENHANCE PRODUCTION

Loosen material to reduce grading time and fill voids while saving on edge wear.

---

## EXTEND VERSATILITY

Reduce need for dozer ripping or cutting bit systems.

---



# RIPPER-SCARIFIER COMPONENTS

Scarifiers can be mounted before the blade (V-Block design) or behind the machine (Straight Block design). Rear-mounted ripper-scarifiers are more versatile than forward-mounted configurations. Rip or scarify by changing shank position.



## V-BLOCK

- » Loosen compacted surfaces, rocky subgrades and frozen ground
- » Fit ahead of the blade (mid mount)
- » Holds up to 11 shanks and scarifies up to 46" (1168 mm) wide



## STRAIGHT BLOCK

- » Low-impact applications and shallow scarifying
- » Higher allowable speed (up to 3rd gear) in shallow
- » Holds up to 17 shanks and scarifies up to 72" (1828 mm) wide
- » May be used as a mid-mount scarifier



## SCARIFIER TIPS

- » We offer three types of scarifier tips for surface reconditioning.
  - Tip has a tapered design that secures it to the shank
- » Through-hardened tips for general purpose scarifying
- » Heavy-Duty for deep penetration and extended distances
- » A.R.M. for high-abrasion/low-impact conditions extends tip life 3 to 5 times over through-hardened



## SCARIFIER SHANKS

- » Through-hardened and tempered to resist wear, bending and breakage
- » Front or rear notch for V-Block or Straight Block
- » Standard or extended lengths

# R SERIES RIPPER TIP OPTIONS

Caterpillar offers three options for the R350 ripper tip size class for 16M and 24M motor graders. Due to the extreme nature of maintaining haul roads, scarifiers are not offered on 16M and 24M.



**CENTERLINE** tips have equal wear material on both sides and can be reversed, which can extend the life and help maintain sharpness.

**A.R.M.**  
OPTION  
AVAILABLE



**PENETRATION** ripper tips have an aggressive angle to break through even the hardest surfaces and dig into the ground more effectively.

**A.R.M.**  
OPTION  
AVAILABLE



**PENETRATION - SHARP** tips are an intermediate length. They come factory sharpened to ensure maximum penetration.



## INSTALLATION & REMOVAL

The R Series Tooth system uses the standard pin and retainer system. The Tooth Pin Remover tool is available to make removal easier.

- 1** Place the tool on the tip and align the extractor with the pin.



- 2** Strike the tool with a hammer until the pin is removed.



# HYDRAULIC EXCAVATORS

Cat Hydraulic Excavators are the most versatile machines on the jobsite, working in applications ranging from small landscaping projects to large surface extraction mines—and everywhere in between. Together, Cat buckets and G.E.T. make up the only bucket system designed and developed to optimize hydraulic excavator performance and your productivity. Rely on your Cat dealer for expert support and service for your specific application.



# SYSTEM OVERVIEW

Hydraulic excavators are extremely versatile machines used for a variety of purposes, from grading to mass excavation to demolition work. A hydraulic excavator's main work tool is a bucket, but these machines can also be equipped with hydraulic couplers to pick up a variety of tools.

Balancing your desired productivity/penetration with the wear life of your system is critical. Excessive wear material can reduce productivity and increase fuel burn. Cat hydraulic excavator buckets and G.E.T. are designed as a balanced system to increase life while minimizing drag.



# TIP SELECTION GUIDE

Even though bucket tips come in many shapes and sizes, you don't have to be an expert to choose the right ones. Use the chart below to determine if the material you're digging in is high, medium or low impact and abrasion—then find the balance you need among these three factors:

## 1 STRENGTH

The ability to withstand digging and penetrating shocks and high breakout forces

## 2 PENETRATION

The ability to penetrate tough material when it's tightly compacted, rocky or frozen

## 3 WEAR LIFE

The ability to withstand wearing, scouring and abrasive action of the material being handled

	IMPACT (material size)			ABRASION (tip life)
	SMALL HEX (311-319)	MEDIUM HEX (320-329)	LARGE HEX (336-390)	
LOW	 0 - 1"   0 - 25 mm	 0 - 3"   0 - 75 mm	 0 - 6"   0 - 150 mm	> 1,000 hours
MEDIUM	 1 - 3"   25 - 75 mm	 3 - 8"   75 - 200 mm	 6 - 12"   150 - 300 mm	250 - 1,000 hours
HIGH	 3+ "   75 mm+	 8+ "   200 mm+	 12+ "   300 mm+	< 250 hours

# CAT ADVANSYS™ TIP & ADAPTER SYSTEM

BUILT TO DELIVER MAXIMUM PRODUCTIVITY AND THE LOWEST BUCKET LIFECYCLE COST IN THE TOUGHEST APPLICATIONS.

Cat Advansys is built for machine productivity, balancing tip wear material and penetration requirements. Integrated hammerless retention ensures you are back to work in minutes without a separate retainer.

## PERFORMANCE & PRODUCTIVITY

Wider top surface reduces drag on the tip and adapter side as the tip moves through the material. Reduced side drag results in less force required to move the hex bucket through the material.

## EXTEND BUCKET LIFECYCLE

Adapter design directs material flow over adapter strap, which can extend adapter service life and bucket lifecycle.

## ENHANCE JOBSITE SAFETY

Hammerless system. A 3/4 inch retainer lock requires no special tools for installation and removal.

**CAT ADVANSYS IS BUILT BY CATERPILLAR AND READILY ADAPTED TO FIT ANY BUCKET IN THE INDUSTRY.**

Available for 950 through 994 Wheel Loaders and 311 through 390 Hydraulic Excavators.

# CAT ADVANSYS TIP OPTIONS

Below are the tip shapes best suited for the wide range of jobsite conditions performed by the hydraulic excavators. We also offer additional Cat Advansys tips more commonly used with wheel loaders. Your Cat dealer can help you choose the one that offers the right balance of penetration and wear life for your application.

<p style="writing-mode: vertical-rl; transform: rotate(180deg);">ABRASION</p> <p style="writing-mode: vertical-rl; transform: rotate(180deg);">IMPACT</p>	<p><b>HEAVY DUTY</b></p> 	<p><b>Heavy Duty and Heavy Duty A.R.M.*</b> tips include approximately 60 percent more wear material in the tip body. The A.R.M. wears around the profile to increase penetration.</p>
	<p><b>GENERAL PURPOSE</b></p> 	<p><b>General Purpose</b> tips are symmetrical and the baseline for other tip styles. All wear comparisons are to the General Purpose tip unless otherwise noted.</p>
	<p><b>WIDE</b></p> 	<p><b>Wide</b> tips are used to maintain smooth trench floors and in low-abrasion, easy-to-penetrate material.</p>
	<p><b>PENETRATION PLUS</b></p> 	<p><b>Penetration Plus</b> tips feature 25 percent more wear material and a leading edge with 25 percent less cross-sectional area. They self-sharpen as they wear.</p>
	<p><b>PENETRATION</b></p> 	<p><b>Penetration</b> tips are ideal for densely compacted materials. They feature a leading edge with 60 percent less cross-sectional area—allowing for maximum penetration—and a single center rib that self-sharpens as it wears. These tips are available with A.R.M.*</p>
	<p><b>SPIKE</b></p> 	<p><b>Spike</b> tips are used to achieve maximum penetration. They are typically used in cohesive material and stay sharp during the life of the tip.</p>
	<p><b>DOUBLE SPIKE</b></p> 	<p><b>Double Spike</b> tips are used in the corner positions with the spike tips for hard-to-penetrate, fracturable materials.</p>

\*Abrasion Resistant Material (A.R.M.) is a welding process that bonds very hard tungsten carbide particles to Cat G.E.T. to create a protective shield over the component. Typically, the A.R.M. process doubles wear life and can last even longer in some applications.

# CAT ADVANSYS HAMMERLESS TIP & ADAPTER SYSTEM

Cast retention pin means no separate retention pin to buy or lose during tip replacements. The tip loads on the adapter nose, never putting the cast retention lugs under stress or wear.



**Integrated Retaining Lug**



**Hammerless Fast Installation and Removal**



## NOSE GEOMETRY DESIGN FEATURES

- Asymmetrical nose geometry reduces sliding wear on adapter nose surfaces, extending the life of the adapter.
- The asymmetrical design ensures a reliable fit even when the adapter surface becomes worn.

## CHANGE OUT TIPS QUICKLY & EASILY

CapSure hammerless retention requires no special tools. Just turn the retainer 180° to install or remove the tips.

Scan the QR Code to the right to watch the installation video.



- 1** Turn retainer 180° clockwise to lock.




- 2** Turn retainer 180° counter clockwise to unlock.



# CAT ADVANSYS ADAPTER DESIGN

The tip system design naturally shields the adapter strap even without a wear cap. This allows up to a 25% increase in wear life when compared to K series or other low profile systems.



Cat Advansys improves adapter to tip wear life ratio, and the resulting extension on the bucket life cycle.


Heavy Abrasion and Heavy Penetration tips both have a longer usable wear life, while staying sharper throughout the useful life of the entire tip.



**X220 Heavy Abrasion Tip<sup>1</sup>**  
72% Available Wear Material



**X220 Heavy Penetration Tip<sup>1</sup>**  
60% Available Wear Material



Wider top surface reduces drag on the tip and adapter side as the tip moves through the material. Reduced side drag results in less force required to move the hex bucket through the material.

The asymmetrical design ensures a reliable fit even when the adapter surface becomes worn.

<sup>1</sup> This is representative of one customer's wear rates and wear rates may vary by application

## MACHINE COMPATIBILITY

EXCAVATOR	LINKAGE	SIZE CLASS
315	N/A	Cat Advansys 80, Cat Advansys 90
318	N/A	Cat Advansys 80, Cat Advansys 90
320	Reach	Cat Advansys 80, Cat Advansys 90
	Mass Excavation	Cat Advansys 90, Cat Advansys 100
324	Reach	Cat Advansys 90, Cat Advansys 100
	Mass Excavation	Cat Advansys 100, Cat Advansys 110
329	Reach	Cat Advansys 90, Cat Advansys 100
	Mass Excavation	Cat Advansys 100, Cat Advansys 110
336	Reach	Cat Advansys 100, Cat Advansys 110
	Mass Excavation	Cat Advansys 110, Cat Advansys 130
349	Reach	Cat Advansys 110, Cat Advansys 130
	Mass Excavation	Cat Advansys 130
374	Reach	Cat Advansys 150
	Mass Excavation	Cat Advansys 170
390	Reach	Cat Advansys 150
	Mass Excavation	Cat Advansys 170, Cat Advansys 200



# K SERIES TIP & ADAPTER SYSTEM

EXCELLENT PENETRATION THROUGH VERTICAL RETENTION AND COMPACT PROFILE.

K Series delivers digging performance throughout the life of the tip with its elliptical adapter nose and vertical retention design. The twist-on fit of the tip and adapter makes installation easier.

---

## IMPROVE YOUR PRODUCTIVITY

Low-profile shape provides optimal sharpness, penetration, and digging ability throughout the tip life.

---

## STAY SAFE & REDUCE MAINTENANCE COSTS

One-piece vertical retainer allows for easy installation and removal.

---

## SIMPLIFY INSTALLATION

Rails on both sides of the adapter and a twist-on design hold the tip in place, allowing for quicker installation.

---

# K SERIES DRIVE-THROUGH TIP & ADAPTER SYSTEM

The drive-through system is for K80-K100 adapters and tips.

Lower-profile tip



Twist-on design



No hole in adapter



Drive-through retainer

## INSTALLATION & REMOVAL

It's safe and easy—just use a standard pry tool and follow this three-step process:

Scan the QR code to the right to watch the installation video.



**1** INSERT  
RETAINER



**2** HAMMER  
RETAINER



**3** SECURE  
RETAINER



# K SERIES HAMMERLESS TIP & ADAPTER SYSTEM

The hammerless system is for K110-K170 adapters and tips.



Twist-on design



Standard hammerless retainer

Lower-profile tip



No hole in adapter



Retainer - bolt drive

\* Additional offering only for extreme packing and slag applications.

Scan the QR code to the right to watch the installation video.



## INSTALLATION & REMOVAL

It's safe and easy—just use a standard pry tool and follow this three-step hammerless process:

**1** INSERT RETAINER



**2** PRESS DOWN RETAINER



**3** REMOVE RETAINER



## K SERIES TIP OPTIONS

Below are the tip shapes best suited for the wide range of jobsite conditions performed by hydraulic excavators. We also offer additional K Series tips more commonly used with wheel loaders. Your Cat dealer can help you choose the one that offers the right balance of penetration and wear life for your application.

ABRASION ↑

### EXTRA DUTY



- » **Extra Duty** and **Extra Duty Abrasion Resistant Material (A.R.M.)\*** tips include approximately 60% more wear material in the tip body. The A.R.M. wears around the profile to increase penetration.

**A.R.M.**  
OPTION  
AVAILABLE

### GENERAL PURPOSE



- » **General Purpose** tips are symmetrical and the baseline for other tip styles. All wear comparisons are to the General Purpose tip unless otherwise noted.



- » **Wide** tips are used to maintain smooth trench floors and in low-abrasion, easy-to-penetrate material.

### PENETRATION PLUS



- » **Penetration Plus** tips feature 25% more wear material and a leading edge with 25% less cross-sectional area. They self-sharpen as they wear.

### PENETRATION



- » **Penetration** tips are ideal for densely compacted materials. They feature a leading edge with 60% less cross-sectional area—allowing for maximum penetration—and a single center rib that self-sharpens as it wears. These tips are available with A.R.M.\*

**A.R.M.**  
OPTION  
AVAILABLE



- » **Spike** tips are used to achieve maximum penetration. They are typically used in cohesive material and stay sharp during the life of the tip.

### DOUBLE SPIKE



- » **Double Spike** tips are used in the corner positions with the spike tips for hard-to-penetrate, fracturable materials.

↓ IMPACT

\*Abrasion Resistant Material (A.R.M.) is a welding process that bonds very hard tungsten carbide particles to Cat G.E.T. to create a protective shield over the component. Typically, the A.R.M. process doubles wear life—and can last even longer in some applications.

## K SERIES ADAPTER OPTIONS

All K Series adapters feature rails on both sides of the nose for a twist-on design that stays in place during installation.

## MACHINE COMPATIBILITY

EXCAVATOR	LINKAGE	SIZE CLASS
315	N/A	K80, K90
318	N/A	K80, K90
320	Reach	K80, K90
	Mass Excavation	K90, K100
324	Reach	K90, K100
	Mass Excavation	K100, K110
329	Reach	K90, K100
	Mass Excavation	K100, K110
336	Reach	K100, K110
	Mass Excavation	K110, K130
349	Reach	K110, K130
	Mass Excavation	K130
374	Reach	K150
	Mass Excavation	K170
390	Reach	K150
	Mass Excavation	K170





# J SERIES TIP & ADAPTER SYSTEM

SIDE-PIN SECURITY WHEN YOUR APPLICATION DEMANDS IT.

Great performance and proven reliability over time—that's what you get with this classic horizontal retention system, a staple in the construction and mining industries.

---

## BOOST YOUR VERSATILITY

Industry-standard side-pinned design performs across a variety of applications.

---

## ENHANCE YOUR RELIABILITY

Weld-on adapters offer excellent retention.

---

## IMPROVE SAFETY & MAINTENANCE TIME

Ability to retrofit means you can use the hammerless CapSure™ system.

---

# J SERIES TIP & ADAPTER SYSTEM



Rock Chisel Tip

## INSTALLATION & REMOVAL

Simply use the standard pin and retainer system—and make removal even easier with our Tip Pin Remover tool.\*

- 1** Place the tool on the tip and align the extractor with the pin.



- 2** Strike the tool with a hammer until the pin is removed.



- 3** Place the tool over the tip (A), locate the pin in the hole of the holder (B) and strike the tool (C).



\*J550 and smaller use the pin removal tool. Consult your dealer for larger systems.

## J SERIES TIP OPTIONS

Below are the tip shapes best suited for the wide range of jobsite conditions performed by hydraulic excavators. We also offer additional J Series tips more commonly used with wheel loaders. Your Cat dealer can help you choose the one that offers the right balance of penetration and wear life for your application.

<p style="writing-mode: vertical-rl; transform: rotate(180deg);">ABRASION</p> <p style="writing-mode: vertical-rl; transform: rotate(180deg);">IMPACT</p>	<p><b>HEAVY DUTY LONG</b></p> 	<p>» <b>Heavy Duty Long</b> and <b>Heavy Duty Abrasion Resistant Material (A.R.M.)*</b> tips include approximately 60% more wear material in the tip body. The A.R.M. wears around the profile to increase penetration.</p>	<p><b>A.R.M.</b> OPTION AVAILABLE</p>
	<p><b>LONG (GENERAL PURPOSE)</b></p> 	<p>» <b>Long</b> tips are symmetrical and the baseline for other tip styles. All wear comparisons are to the Long tip unless otherwise noted.</p>	
	<p><b>WIDE</b></p> 	<p>» <b>Wide</b> tips are used to maintain smooth trench floors and in low-abrasion, easy-to-penetrate material.</p>	
	<p><b>PENETRATION PLUS</b></p> 	<p>» <b>Penetration Plus</b> tips feature 30% more wear material and 25% less cross-sectional area. They self-sharpen as they wear.</p>	
	<p><b>PENETRATION</b></p> 	<p>» <b>Penetration</b> and <b>Penetration A.R.M.*</b> tips are ideal for densely compacted materials. They feature a leading edge with approximately 50% less cross-sectional area and a single center rib for strength—allowing for maximum penetration.</p>	<p><b>A.R.M.</b> OPTION AVAILABLE</p>
	<p><b>SPIKE</b></p> 	<p>» <b>Spike</b> tips are used to achieve maximum penetration. They are typically used in cohesive material and stay sharp during the life of the tip.</p>	
	<p><b>SPIKE CORNER</b></p> 	<p>» <b>Spike Corner</b> tips can be used in the corner position with sharp center tips.</p>	
	<p><b>DOUBLE SPIKE</b></p> 	<p>» <b>Double Spike</b> tips are used in the corner positions with the spike tips for hard-to-penetrate, fracturable materials.</p>	

\*Abrasion Resistant Material (A.R.M.) is a welding process that bonds very hard tungsten carbide particles to Cat G.E.T. to create a protective shield over the component. Typically, the A.R.M. process doubles wear life—and can last even longer in some applications.

## GENERAL DUTY TIPS

General Duty tips offer a reliable, competitively priced parts option for small to medium-sized excavators operating in low to medium impact conditions. Tips are available in the J250-J460 size range.

General Duty tips are:

- » A match if you require quality and long wear
- » Designed to fit J Series adapters, reducing risky fit-ups
- » Backed by the standard Caterpillar warranty against breakage under normal, recommended operation in low to medium impact applications

### LONG



- » Most versatile shape with good balance of penetration, strength and abrasion resistance. Standard shape for most applications.

### HEAVY DUTY LONG



- » Use on larger machines where greater strength is required. More wear material for higher abrasion environments.

### PENETRATION PLUS



- » Enhanced penetration in densely compacted material, such as clay. Resists blunting and is self-sharpening. Ideal for tough trenching applications.

## J SERIES MACHINE COMPATIBILITY

EXCAVATOR	LINKAGE	SIZE CLASS
312	N/A	J250, J300
315	N/A	J300, J350
318	N/A	J300, J350
320	Reach	J300, J350, J400
	Mass Excavation	J400, J460
324	Reach	J400, J460
	Mass Excavation	J460, J550
329	Reach	J400, J460
	Mass Excavation	J460, J550
336	Reach	J460, J550
	Mass Excavation	J550
349	Reach	J550
	Mass Excavation	J550
374	Reach	J600
	Mass Excavation	J700
390	Reach	J600
	Mass Excavation	J700, J800

# HAMMERLESS TIP & ADAPTER SYSTEM FEATURING CAPSURE RETENTION

LOSE THE HAMMER, NOT THE FLEXIBILITY.

Simplify bucket tip replacement with hammerless CapSure retention. These tips are matched to side-pin adapters, allowing the flexibility to use our conventional pin retention if your application demands it.

---

## LOWER OPERATING COSTS

Side-pin retrofit design used on J-style adapters means the pin is reusable.

---

## ENHANCE JOBSITE SAFETY & MAINTENANCE TIME

A ¾-inch retainer lock requires no special tools and allows for hammerless installation and removal.

---

## CHANGE OUT TIPS QUICKLY & EASILY

Positive stop is cast into the tip to prevent over-rotation—just turn 180 degrees to lock or unlock.

---

## SPEED UP YOUR INSTALLATION TIME

Tip and retainer are one system, so there's no special assembly or extra pieces.

---



# HAMMERLESS TIP & ADAPTER SYSTEM FEATURING CAPSURE RETENTION



## INSTALLATION & REMOVAL

It's fast, easy and safe with the CapSure locking system—just follow these four simple steps:

Scan the QR code to the right to watch the installation video.



- 1** Insert pin and washer into the adapter hole.



- 2** Slide the tip onto the adapter.



- 3** Tighten 180° into the locked position with a 3/4" ratchet.



- 4** Remove by loosening 180° to the unlocked position.



## CAPSURE TIP OPTIONS

We offer four CapSure tip options designed for a range of jobsite conditions. Your Cat dealer can help you choose the one that offers the right balance of penetration and wear life for your application.

ABRASION ↑

IMPACT ↓

### HEAVY DUTY ABRASION



» **Heavy Duty Abrasion** tips are ideal for high-abrasion applications like sand, gravel and shot rock. They have the maximum amount of wear material—approximately 145% more—and the tip base features 35% more surface area than Heavy Penetration tips.

### HEAVY PENETRATION



» **Heavy Penetration** tips are ideal for high-impact, hard-to-penetrate materials. They feature approximately 120% more material in the high wear area as well as a sharp spade design with 70% less cross-sectional area on the leading edge than Heavy Duty Abrasion tips.

### HEAVY DUTY



» **Heavy Duty** tips are the baseline for other tips. All wear comparisons are to the Heavy Duty tip unless otherwise noted.

### PENETRATION PLUS



» **Penetration Plus** tips feature 30% more wear material and 25% less cross-sectional area. They self-sharpen as they wear.

## MACHINE COMPATIBILITY

EXCAVATOR	LINKAGE	SIZE CLASS
336	Reach	N/A
	Mass Excavation	J550 (Retrofit)
349	Reach	J550 (Retrofit)
	Mass Excavation	J550 (Retrofit)
374	Reach	J600 (Retrofit)
	Mass Excavation	J700 (Retrofit)
390	Reach	J600 (Retrofit)
	Mass Excavation	J700 (Retrofit), J800 (Retrofit)

# BASE EDGE SYSTEMS

FASTEST INSTALLATION TIMES IN THE INDUSTRY.

Cat base edge systems go through a series of carefully controlled manufacturing processes to deliver maximum strength, durability and long life. They come completely welded and assembled, dramatically shortening your installation and replacement time.

## INCREASE DURABILITY

A consistent heat-treat process maximizes strength and resists abrasion. Shot blasting removes impurities that can cause inclusions on a weld, and controlled cooling reduces the chance of stress points.

## SAVE INSTALLATION & REPLACEMENT TIME

Butterbead is applied to the back side of the base edge and the top strap of the corner adapter, so you can weld the edge onto the bucket without preheating.

## OPTIMIZE MACHINE PERFORMANCE

Base edges are designed by Caterpillar engineers for optimal performance on specific machines.




## BASE EDGE SYSTEMS

Base edge replacement involves replacing a base edge assembly, which includes adapters welded in from the factory, or replacing a bolt-on cutting edge (BOCE) base edge, which comes with factory-drilled holes for bolt-on G.E.T. Choose from three shapes (base edge for BOCE, straight and spade base edge assemblies) to get the right protection for your application.

### GET MORE ACCURACY

Lasers place the adapters within 0.1 mm of specifications.



BOLT-ON CUTTING EDGE



STRAIGHT



SPADE



# BUTTERBEAD BASE EDGE ASSEMBLY

DURABLE PROTECTION COMBINED WITH SHORTER INSTALLATION TIMES.

The protection you need, with no preheating required—that's what you get with butterbead weld prep. This technique, which involves applying a layer of weld to a heat-treated, higher hardness part, makes it possible to weld a base edge to a bucket without preheating the hardened part. Choose from two shapes (straight and spade) on cutting edges thicker than 50mm and three levels of build to get the right protection for your application.

## SPEED UP YOUR INSTALLATION TIME

Weld prep eliminates the need for preheating, shortening edge installation time by 30-50%.

## GET MORE DURABILITY

Base edges have the proper butterbead weld because it is applied in the factory.



# BASE EDGE END PROTECTION (BEEP)

PROTECT YOUR CORNERS—WITHOUT CUTTING THEM.

Reduce base edge end wear and subsequent corner adapter weld erosion with our BEEP design. It makes adapter replacement on the edge much easier when it's time to rebuild the base edge assembly. BEEPs are available in a wide array of thicknesses and angles to fit 336-390 hydraulic excavators.

## BOOST YOUR UPTIME

Through-hardened Rc ~45 (Br ~3.0) weldable steel is easily installed in the shop or the field.

## EXTEND LIFE

Extended base edge end protects adapter corner welds.

## SPEED UP INSTALLATION

Height and bevel are matched to the base edge, so there's no additional fabrication.



Plug Weld



# SIDE & EDGE PROTECTION

## MAINTAIN YOUR PERFORMANCE EDGE.

Protect your bucket's structural integrity with sidebar protectors and shear blocks or increase penetration and performance with side cutters.

- » Sidebar Protectors
- » Side Cutters
- » Half Arrows
- » Top Covers
- » Cutting Edges
- » Weld-On Edge Shrouds



# SIDEBAR PROTECTORS

Protect your bucket's structural integrity with sidebars and shear blocks.


## INCREASE YOUR UPTIME

Shear block protects the pin from extreme loads and breakage, helping ensure sidebar protector retention.

## CUT YOUR MAINTENANCE COSTS


Sidebar protector protects the bucket edge.

Shear block bears the loads instead of the pins.




# SIDECUTTERS

Improve your bucket's performance while protecting your sidebars.




## GENERAL PURPOSE SIDECUTTER

- › Effective in moderate-impact conditions.
- › Suitable for most soil conditions.
- › Provides a strong, wear-resistant surface to help protect bucket sides.
- › Extends bucket side width to match the teeth bite.



## HEAVY DUTY SIDECUTTER

- » For tough digging conditions.
- » More wear material.
- » Covers more of the sidebar for enhanced protection of the bucket.
- » Scalloped profile improves bucket penetration and machine performance.



## STRIKEOFF SIDECUTTER

- » Half arrow shape to provide better penetration than bare bucket.
- » Protects the lower bucket sides and corners.
- » For use in moderate-to-light conditions.
- » Can be stacked for more protection.

# BOLT-ON HALF ARROWS, TOP COVERS, CUTTING EDGES & WELD-ON SHROUDS

Protect your investment in buckets and base edges with these flexible components. Half arrows allow for a smooth transition of material over the base edge to protect the leading edge. Top covers complement the half arrows to protect the base edge fully. Modular edge shrouds are designed to fit any bucket configuration and extend the life of your excavator bucket edge assembly.

## SIMPLIFY MAINTENANCE

Individual pieces that protect the edge can be changed independently.

## ENHANCE DURABILITY

Half arrows cover the leading edge for smooth material transition.


## BOOST YOUR UPTIME

Top cover reduces wear on weld joints.



# BUCKET SELECTION GUIDE

We offer four standard bucket durability categories suitable for any application. Each category is based on the bucket's intended durability when used in the recommended application and material.



## GENERAL DUTY

- » For digging in low-impact, lower-abrasion materials such as dirt, loam and mixed compositions of dirt and fine gravel. Example: Digging conditions in which General Duty tip life exceeds 800 hours.



## HEAVY DUTY

- » For a wide range of impact and abrasion conditions including mixed dirt, clay and rock. Example: Digging conditions where Penetration Plus tip life ranges from 400 to 800 hours.
- » HD buckets are a good "center line" choice, or starting point, when application conditions are not well known.



### SEVERE DUTY

- » For higher abrasion conditions such as well-shot granite and caliche. Example: Digging conditions where tip life ranges from 200 to 400 hours with Penetration Plus tips.



Typical 336-349 bucket

### EXTREME DUTY


- » For very high-abrasion conditions including high quartzite granite. Example: Digging conditions where tip life is less than or equal to 200 hours with Extra Duty tips.



Typical 374-390 bucket

## CHOOSING THE RIGHT DURABILITY.

Choosing the wrong bucket can easily reduce production and increase operating costs by 10-20% or more. It can also cause unnecessary wear and fatigue for both machine and bucket. Contact your local Cat dealer for more detailed information on choosing the right excavator, bucket and work tool attachment combinations to meet your application needs.



# ADDITIONAL BUCKET STYLES

Several different bucket styles are available—each with a special purpose:



## DITCH CLEANING

These buckets are designed for cleaning ditches, sloping, grading and other finish work. Their shallow depth and compact size make working in confined areas easier. Drainage holes allow liquid to empty so material dumps more easily. Ditch Cleaning Buckets are available for 311-336 excavators.

Tilt Buckets feature a full 45° of tilt in each direction, powered by two double-acting cylinders. Tilt Buckets are available for 311-329 excavators.



## CENTER-LOCK™ PIN GRABBER PERFORMANCE

This bucket is designed with a patented recessed pin to provide maximum digging performance while keeping the versatility and convenience of a coupler. Tip radius is reduced and allows up to 10% improvement in breakout force when compared to a conventional pin-on bucket and coupler combination.

Center-Lock Pin Grabber Performance Buckets are available for 315-349 excavators in General Purpose and Severe Duty durability.



## POWER

Power Buckets are for use in abrasive applications where breakout force and cycle times are critical—and for use in materials such as tightly compacted mixed dirt and rock. (Not recommended for clay.) Breakout force is maximized due to decreased tip radius and increased pin spread. Machine cycle times in most material are improved over a standard bucket in a similar application.

Heavy Duty Power Buckets are available for 320-336 excavators.



## WIDE TIP

Wide Tip Buckets are intended to perform best in low-impact materials such as dirt and loam where leaving a smoother floor and minimal spillage is necessary. The bucket is engineered to be used exclusively with Cat Wide Tips. Corner adapters face straight forward to create a smooth edge.

General Duty Wide Tip Buckets are available in widths from 24" to 78" for 311-349 excavators.



## HIGH CAPACITY

High Capacity Buckets are designed and built for use in high-production truck-loading applications. With proper application and set up, these buckets will move more material in a minimal amount of passes—maximizing production.

High Capacity Buckets are available for 336-390 excavators in General Duty durability.

# CAT DEALER & BUCKET MANAGEMENT

CHOOSING CAT G.E.T. IS EASY.

Your Cat dealer makes it easy to choose the right G.E.T. for your machines and applications. In addition to a broad portfolio of products, your dealer offers the sales, service and technical support you need to keep productivity high and operating costs low. Trust your Cat dealer to:

## MAXIMIZE PRODUCTIVITY

Buckets and G.E.T. products are designed to meet your application requirements, rather than simply fit onto your machine.

## IMPROVE PERFORMANCE

Get the most out of your bucket and G.E.T. with expert advice that helps you lower costs and reduce unscheduled maintenance.

## SIMPLIFY MAINTENANCE

Tailored G.E.T. systems simplify your maintenance. We develop solutions that fit your expectations, including custom products.

## MANAGE WEAR

Intuitive Cat Inspect bucket inspection programs help you monitor how your G.E.T. system is wearing so you can adapt to changes in application and operation.



Talk to your Product Support Representative or G.E.T. specialist today to learn how they can help you simplify your bucket management by using Cat Inspect.

# HYDRAULIC EXCAVATOR (HEX) RIP AND LOAD

Using rippers mounted on large hex is a cost-effective alternative to blasting in quarries and site development. In site development, rippers on smaller excavators and backhoe loaders can readily deal with asphalt, caliche and frozen ground.

## IMPROVE YOUR PRODUCTIVITY

Increase productivity by adding efficiency and flexibility to your operation.

## EXTEND LIFE

A through-hardened hammerless wear tip and shank protector extend wear life.

## INCREASE DURABILITY

Upsized, hammerless adapters and tips accommodate higher loads and abrasion, while edge segments and top covers protect your base edge.



RIPPER-TO-BUCKET CHANGES ARE MADE HYDRAULICALLY IN LESS THAN 35 SECONDS.  
This gives the operator complete flexibility to continually adjust ripping, sorting and loading work.

## SIMPLE CHANGES

Pull material down and change bucket quickly and easily.

## BLAST FREE

Ripper allows you to work without blasting in areas with unstable land or sound regulations.

1



2



3



4



5



6



# WHEEL LOADERS (950-994)

STRENGTH. DURABILITY. LONG LIFE. PLUS EVERYTHING YOU NEED TO BOOST UPTIME ON YOUR JOB.

For wheel loaders, you can choose from Cat Advansys, K Series, J Series and Hammerless Tip & Adapter Systems, each available with multiple tip options for a range of jobsite conditions. Optimize your machine's productivity in every jobsite condition with the wide range of G.E.T. products available. Cat buckets and G.E.T. make up the only bucket system designed and developed to maximize the performance and productivity of your Cat wheel loader.



# TIP SELECTION GUIDE

Even though bucket tips come in many shapes and sizes, you don't have to be an expert to choose the right ones. Use the chart below to determine if the material you're digging in is high, medium or low impact and abrasion—then find the balance you need among these three factors:

## 1 STRENGTH

The ability to withstand digging and penetrating shocks and high breakout forces

## 2 PENETRATION

The ability to penetrate tough material when it's tightly compacted, rocky or frozen

## 3 WEAR LIFE

The ability to withstand wearing, scouring and abrasive action of the material being handled

	988-994 WHEEL LOADERS IMPACT (material size)	950-982 WHEEL LOADERS IMPACT (material size)	950-994 WHEEL LOADERS ABRASION (tip life)
LOW	 0-6"   0-152mm	 0-4"   0-102mm	> 1,000 hours
MEDIUM	 6-18"   152-457mm	 4-12"   102-305mm	250-1,000 hours
HIGH	 18"+   457mm+	 12"+   305mm+	< 250 hours

# CAT ADVANSYS TIP & ADAPTER SYSTEM

BUILT TO DELIVER MAXIMUM PRODUCTIVITY AND THE LOWEST BUCKET LIFECYCLE COST IN THE TOUGHEST APPLICATIONS.

Cat Advansys is built for machine productivity, balancing tip wear material and penetration requirements. Integrated hammerless retention ensures you are back to work in minutes without a separate retainer.

## PERFORMANCE & PRODUCTIVITY

Heavy Abrasion and Heavy Penetration designs have more usable wear material while maintaining profile during the full life of the tip.

## EXTEND BUCKET LIFECYCLE

Adapter design directs material flow over adapter strap, which can extend adapter service life and bucket lifecycle.

## ENHANCE JOBSITE SAFETY

Hammerless system. A 3/4 inch retainer lock requires no special tools for installation and removal.

# CAT ADVANSYS TIP OPTIONS

Below are the tip shapes best suited for the wide range of jobsite conditions performed by large wheel loaders. We also offer additional Cat Advansys tips more commonly used with excavators. Your Cat dealer can help you choose the one that offers the right balance of penetration and wear life for your application.

ABRASION ↑

## HEAVY ABRASION



» **Heavy Abrasion** tips feature a redesign for the Cat Advansys system that results in 11 percent more usable wear material than K Series and a tip shape that stays sharp through the life of the tip. These tips are available with Abrasion Resistant Material (A.R.M.)\*.

**A.R.M.**  
OPTION  
AVAILABLE

## HEAVY PENETRATION



» **Heavy Penetration** tips feature a redesign for the Cat Advansys system that results in 6 percent more usable wear material than K Series and a tip shape that stays sharp through the life of the tip in the most severe applications.

## HEAVY DUTY



» **Heavy Duty** and **Heavy Duty A.R.M.\*** tips include approximately 60 percent more wear material in the tip body. The A.R.M. wears around the profile to increase penetration.

**A.R.M.**  
OPTION  
AVAILABLE

## GENERAL PURPOSE



» **General Purpose** tips are symmetrical and the baseline for other tip styles. All wear comparisons are to the General Purpose tip unless otherwise noted.

## COAL



» **Coal** tips have a reduced amount of wear material to maximize bucket payload and a smooth underside to maintain a flat floor.

## PENETRATION PLUS



» **Penetration Plus** tips feature 25 percent more wear material and a leading edge with 25 percent less cross-sectional area. They self-sharpen as they wear.

## PENETRATION



» **Penetration** tips are ideal for densely compacted materials. They feature a leading edge with 60 percent less cross-sectional area—allowing for maximum penetration—and a single center rib that self-sharpens as it wears. These tips are available with A.R.M.\*


**A.R.M.**  
OPTION  
AVAILABLE

↓ IMPACT


\*Abrasion Resistant Material (A.R.M.) is a welding process that bonds very hard tungsten carbide particles to Cat G.E.T. to create a protective shield over the component. Typically, the A.R.M. process doubles wear life and can last even longer in some applications.

# CAT ADVANSYS HAMMERLESS TIP & ADAPTER SYSTEM

Cast retention pin means no separate retention pin to buy or lose during tip replacements. The tip loads on the adapter nose, never putting the cast retention lugs under stress or wear.



Integrated Retaining Lug



Hammerless Fast Installation and Removal

## CHANGE OUT TIPS QUICKLY & EASILY

CapSure hammerless retention requires no special tools. Just turn the retainer 180° to install or remove the tips.

Scan the QR Code to the right to watch the installation video.



1

Turn retainer 180° clockwise to lock.



2

Turn retainer 180° counter clockwise to unlock.




# CAT ADVANSYS ADAPTER SYSTEM



## NOSE GEOMETRY DESIGN FEATURES

- Asymmetrical nose geometry reduces sliding wear on adapter nose surfaces, extending the life of the adapter.
- The asymmetrical design ensures a reliable fit even when the adapter surface becomes worn.

Four adapter styles cover the entire wheel loader product range.



## 994/994K ADAPTER WEAR CAP SYSTEM

- » Adapter cover protects the adapter and welds in high-abrasion applications like granite and iron ore.
- » Allows for more penetration.



## FLUSH-MOUNT (SHOWN WITH OPTIONAL COVER)

- » 360-degree weld around the adapter provides 20 percent more weld strength than a two-strap system.
- » Adapter cover and half-arrow segment create a flush surface to keep the quarry floor clean, reducing potential tire damage.
- » Adapter cover protects the adapter and welds in high-abrasion applications like granite and iron ore.
- » Features a higher profile, which can affect penetration.



## TWO-STRAP

- » Features a lower profile than the flush-mount adapter.
- » Allows for more penetration.
- » Available with Abrasion Resistant Material (A.R.M.).

**A.R.M.**  
OPTION  
AVAILABLE




## BOLT-ON

- » Gives you the flexibility to switch between cutting edge or teeth when you need more penetration (such as a frozen pile).

# CAT ADVANSYS TIP SYSTEM DESIGN

The tip system design naturally shields the adapter strap even without a wear cap. This allows up to a 25% increase in wear life when compared to K series or other low profile systems.



Cat Advansys can improve tip to adapter wear life ratio. Extending your adapter life can mean fewer replacements during the bucket life cycle.

Heavy Abrasion and Heavy Penetration tips both have a longer usable wear life, while staying sharper throughout the useful life of the entire tip.



**X220 Heavy Abrasion Tip<sup>1</sup>**  
72% Available Wear Material



**X220 Heavy Penetration Tip<sup>1</sup>**  
60% Available Wear Material

<sup>1</sup> This is representative of one customer's and wear rates may vary by application

## MACHINE COMPATIBILITY

WHEEL LOADER	SIZE CLASS	ADAPTERS AVAILABLE
950, 962	Cat Advansys 80, 90 Cat Advansys 90	Bolt-on, Flush-Mount with Adapter Cover, Two-Strap with Top Cover
966, 972	Cat Advansys 90	Bolt-on, Flush-Mount with Adapter Cover, Two-Strap with Top Cover
980, 982	Cat Advansys 100	Bolt-on, Flush-Mount with Adapter Cover, Two-Strap with Top Cover
986, 988	Cat Advansys 110	Bolt-on, Flush-Mount with Adapter Cover, Two-Strap with Top Cover
988, 992	Cat Advansys 130	Flush-Mount with Adapter Cover, Two-Strap with Top Cover
992, 993, 994	Cat Advansys 150	Flush-Mount with Adapter Cover, Two-Strap with Top Cover
994	Cat Advansys 200	Two-Strap with Wear Cap System
994K	Cat Advansys 220	Two-Strap with Wear Cap System



# K SERIES TIP & ADAPTER SYSTEM

EXCELLENT PENETRATION THROUGH VERTICAL RETENTION AND COMPACT PROFILE.

K Series delivers digging performance throughout the life of the tip with its elliptical adapter nose and vertical retention design. The twist-on fit of the tip and adapter makes installation easier.

---

## IMPROVE YOUR PRODUCTIVITY

Low-profile shape provides optimal sharpness, penetration, and digging ability throughout the tip life.

---

## STAY SAFE & REDUCE MAINTENANCE COSTS

One-piece vertical retainer allows for easy installation and removal.

---

## SIMPLIFY INSTALLATION

Rails on both sides of the adapter and a twist-on design hold the tip in place, allowing for quicker installation.

---



## K SERIES TIP OPTIONS

Below are the tip shapes best suited for the wide range of jobsite conditions performed by large wheel loaders. We also offer additional K Series tips more commonly used with excavators. Your Cat dealer can help you choose the one that offers the right balance of penetration and wear life for your application.

ABRASION ↑  
 IMPACT ↓

### HEAVY ABRASION



» **Heavy Abrasion** tips are ideal for high-abrasion applications like sand, gravel and shot rock. They feature the maximum amount of wear material—approximately 145 percent more—and a tip base with 35 percent more surface area than Heavy Duty Penetration tips.

### HEAVY PENETRATION



» **Heavy Penetration** tips are ideal for high-impact, hard-to-penetrate materials. They feature approximately 120 percent more material in the high wear area as well as a spade design that has 60 percent less cross-sectional area on the leading edge than Heavy Abrasion tips.

### HEAVY DUTY



» **Heavy Duty** and **Heavy Duty Abrasion Resistant Material (A.R.M.)\*** tips include approximately 60 percent more wear material in the tip body. The A.R.M. wears around the profile to increase penetration.

**A.R.M.**  
OPTION  
AVAILABLE

### GENERAL PURPOSE



» **General Purpose** tips are symmetrical and the baseline for other tip styles. All wear comparisons are to the General Purpose tip unless otherwise noted.

### PENETRATION PLUS



» **Penetration Plus** tips feature 25 percent more wear material and a leading edge with 25 percent less cross-sectional area. They self-sharpen as they wear.

### PENETRATION



» **Penetration** tips are ideal for densely compacted materials. They feature a leading edge with 60 percent less cross-sectional area—allowing for maximum penetration—and a single center rib that self-sharpens as it wears. These tips are available with A.R.M.\*

**A.R.M.**  
OPTION  
AVAILABLE

\*Abrasion Resistant Material (A.R.M.) is a welding process that bonds very hard tungsten carbide particles to Cat G.E.T. to create a protective shield over the component. Typically, the A.R.M. process doubles wear life—and can last even longer in some applications.

# K SERIES DRIVE-THROUGH TIP & ADAPTER SYSTEM

The drive-through system is for K80-K100 adapters and tips.

Lower-profile tip



Twist-on design



No hole in adapter



Drive-through retainer

## INSTALLATION & REMOVAL

It's safe and easy—just use a standard pry tool and follow this three-step process:

Scan the QR code to the right to watch the installation video.



**1** INSERT  
RETAINER



**2** HAMMER  
RETAINER



**3** SECURE  
RETAINER



# K SERIES TIP HAMMERLESS TIP & ADAPTER SYSTEM

The hammerless system is for K110-K170 adapters and tips.



Lower-profile tip

Twist-on design



No hole in adapter



Retainer - Bolt Drive

- » Extreme Packing
- » Slag Operations

## INSTALLATION & REMOVAL

It's safe and easy—just use a standard pry tool and follow this three-step hammerless process:

To watch the installation video go to [www.youtube.com/watch?v=xKWEdWjV6nl](http://www.youtube.com/watch?v=xKWEdWjV6nl) or by scanning the QR code to the right.



**1** INSERT  
RETAINER



**2** PRESS DOWN  
RETAINER



**3** REMOVE  
RETAINER



## K SERIES ADAPTER OPTIONS

All K Series adapters feature rails on both sides of the nose for a twist-on design that stays in place during installation.



### FLUSH-MOUNT (SHOWN WITH OPTIONAL COVER)

- » 360-degree weld around the adapter provides 20 percent more weld strength than a two-strap system.
- » Adapter cover and half-arrow segment create a flush surface to keep the quarry floor clean, reducing potential tire damage.
- » Adapter cover protects the adapter and welds in high-abrasion applications like granite and iron ore.
- » Features a higher profile, which can affect penetration.



### TWO-STRAP

- » Features a lower profile than the flush-mount adapter.
- » Allows for more penetration and higher productivity.
- » Available with Abrasion Resistant Material.

**A.R.M.**  
OPTION  
AVAILABLE



### BOLT-ON

- » Gives you the flexibility to switch between cutting edge or teeth when you need more penetration (such as a frozen pile).

## K SERIES

WHEEL LOADER	SIZE CLASS	BUCKET TYPE / ADAPTERS AVAILABLE
950, 962	K80	Material handling,GD
	K90	Rock
966, 972	K90	Material handling,GD, rock, HD rock
972	K100	Slag
980, 982	K100	Material handling,GD, rock
	K110	HD quarry rock
980	K130	Slag
988	K110	Flush-Mount, Two-Strap, Bolt
988, 990	K130	Flush-Mount, Two-Strap
990, 992	K150	Flush-Mount, Two-Strap
992, 993, 994	K170	Two-Strap

## J SERIES

WHEEL LOADER	SIZE CLASS	BUCKET TYPE / ADAPTERS AVAILABLE
950, 962	J300	Material handling,GD
	J350	Rock
966	J350	Material handling,GD, rock, HD rock
972	J350	Material handling,GD, rock, HD rock
	J400	Slag
980	J400	Material handling, GD, rock
980, 982	J460	HD quarry rock
980	J550	Slag
982	J400	Material handling, GD, rock
988	J550	Flush-Mount, Two-Strap, Bolt
990	J600	Flush-Mount, Two-Strap
992	J700	Flush-Mount, Two-Strap
994	J800	Flush-Mount, Two-Strap, Mechanically Attached Adapter

# J SERIES TIP & ADAPTER SYSTEM

SIDE-PIN SECURITY WHEN YOUR APPLICATION DEMANDS IT.

Great performance and proven reliability over time—that's what you get with this classic horizontal retention system, a staple in the mining industry.

---

## BOOST YOUR VERSATILITY

Industry-standard side-pinned design performs across a variety of applications.

---

## ENHANCE YOUR RELIABILITY

Weld-on adapters offer excellent retention.

---

## IMPROVE SAFETY & MAINTENANCE TIME

Ability to retrofit means you can use the hammerless CapSure™ system.

---



# J SERIES TIP & ADAPTER SYSTEM



Rock Chisel Tip

## INSTALLATION & REMOVAL

Simply use the standard pin and retainer system—and make removal even easier with our Tip Pin Remover tool.\*

**1** Place the tool on the tip and align the extractor with the pin.



**2** Strike the tool with a hammer until the pin is removed.



**3** Place the tool over the tip (A), locate the pin in the hole of the holder (B) and strike the tool (C).



\*Models 992 and down use Tip Pin Remover tool. Consult your dealer for larger machines.

## J SERIES TIP OPTIONS

Below are the tip shapes best suited for the wide range of jobsite conditions performed by large wheel loaders. We offer additional J Series tips more commonly used with excavators. Your Cat dealer can help you choose the one that offers the right balance of penetration and wear life for your application.

ABRASION

### HEAVY DUTY ABRASION



- » **Heavy Duty Abrasion** tips are ideal for high-abrasion applications like sand, gravel and shot rock. They feature the maximum amount of wear material—approximately 145 percent more—and the tip base has 35 percent more surface area than Heavy Duty Penetration tips.

### HEAVY PENETRATION



- » **Heavy Penetration** tips are ideal for high-impact, hard-to-penetrate materials. They feature approximately 120 percent more material in the high wear area, and the spade design has 70 percent less edge area than Heavy Duty Abrasion tips.

### HEAVY DUTY LONG



- » **Heavy Duty Long** and **Heavy Duty Abrasion Resistant Material (A.R.M.)\*** tips include approximately 60 percent more wear material in the tip body. The A.R.M. wears around the profile to increase penetration.

**A.R.M.**  
OPTION  
AVAILABLE

### LONG



- » **Long** tips are symmetrical and the baseline for other tip styles. All wear comparisons are to the Long tip unless otherwise noted.

### PENETRATION PLUS



- » **Penetration Plus** tips feature 30 percent more wear material and 25 percent less cross-sectional area. They self-sharpen as they wear.

### PENETRATION



- » **Penetration** and **Penetration A.R.M.\*** tips are ideal for densely compacted materials. They feature a leading edge with approximately 50 percent less cross-sectional area and a single center rib for strength—allowing for maximum penetration.

**A.R.M.**  
OPTION  
AVAILABLE

### ROCK CHISEL



- » **Rock Chisel** tips are Heavy Duty Long tips ideal for high-impact and high-abrasion applications, such as granite. Additional length and wear material in the body helps retain the chisel shape throughout tip life.

IMPACT

\*Abrasion Resistant Material (A.R.M.) is a welding process that bonds very hard tungsten carbide particles to Cat G.E.T. to create a protective shield over the component. Typically, the A.R.M. process doubles wear life—and can last even longer in some applications.

## J SERIES ADAPTER OPTIONS

J Series adapters use a classic side-pinned retention system for proven, reliable performance.



### FLUSH-MOUNT WITH TOP COVER

- » 360-degree weld around the adapter provides 20 percent more weld strength than a two-strap system.
- » Adapter cover and half-arrow segment create a flush surface to keep the quarry floor clean, reducing potential tire damage.
- » Adapter cover protects the adapter and welds in high-abrasion applications like granite and iron ore.



### TWO-STRAP

- » Offers a lower profile than flush-mount adapters.
- » Allows for more penetration and higher productivity.
- » Available with Abrasion Resistant Material.

**A.R.M.**  
OPTION  
AVAILABLE



### TWO-STRAP BOLT-ON

- » Used on 988 wheel loaders for surge or stock piles.
- » Gives you the flexibility to switch between cutting edge or teeth when you need more penetration (such as a frozen pile).



### MECHANICALLY ATTACHED ADAPTER

- » Used on 994 wheel loader for mechanically attached edges.
- » Requires a C-clamp retainer.

WHEEL LOADER	SIZE CLASS	ADAPTERS AVAILABLE
988	J550	Flush-Mount, Two-Strap
990	J600	Flush-Mount, Two-Strap
992	J700	Flush-Mount, Two-Strap
994	J800	Two-Strap

# HAMMERLESS SERIES TIP & ADAPTER SYSTEM FEATURING CAPSURE RETENTION

LOSE THE HAMMER, NOT THE FLEXIBILITY.

Simplify bucket tip replacement with hammerless CapSure retention. These tips are matched to side-pin adapters, allowing the flexibility to use our conventional pin retention if your application demands it.

## LOWER OPERATING COSTS

Side-pin retrofit design used on J-style adapters means the pin is reusable.

## ENHANCE JOBSITE SAFETY & MAINTENANCE TIME

A ¾-inch retainer lock requires no special tools and allows for hammerless installation and removal.

## CHANGE OUT TIPS QUICKLY & EASILY

Positive stop is cast into the tip to prevent over-rotation—just turn 180 degrees to lock or unlock.

## SPEED UP YOUR INSTALLATION TIME

Tip and retainer are one system, so there's no special assembly or extra pieces.



# HAMMERLESS SERIES TIP & ADAPTER SYSTEM FEATURING CAPSURE RETENTION



Scan the QR Code to the right to watch the installation video.



## INSTALLATION & REMOVAL

It's fast, easy and safe with the CapSure locking system—just follow these four simple steps:

- 1** Insert pin and washer into the adapter hole.



- 2** Slide the tip onto the adapter.



- 3** Tighten 180° into the locked position with a 3/4" ratchet.



- 4** Remove by loosening 180° to the unlocked position.



## CAPSURE TIP OPTIONS

We offer four CapSure tip options designed for a range of jobsite conditions. Your Cat dealer can help you choose the one that offers the right balance of penetration and wear life for your application.

ABRASION ↑  
↓ IMPACT

### HEAVY DUTY ABRASION



- » **Heavy Duty Abrasion** tips are ideal for high-abrasion applications like sand, gravel and shot rock. They have the maximum amount of wear material—approximately 145 percent more—and the tip base features 35 percent more surface area than Heavy Penetration tips.

### HEAVY PENETRATION



- » **Heavy Penetration** tips are ideal for high-impact, hard-to-penetrate materials. They feature approximately 120 percent more material in the high wear area as well as a sharp spade design with 70 percent less cross-sectional area on the leading edge than Heavy Duty Abrasion tips.

### HEAVY DUTY



- » **Heavy Duty** tips are the baseline for other tips. All wear comparisons are to the Heavy Duty tip unless otherwise noted.

### PENETRATION PLUS



- » **Penetration Plus** tips feature 30 percent more wear material and 25 percent less cross-sectional area. They self-sharpen as they wear.

## OUR J SERIES ADAPTERS ARE MATCHED WITH HAMMERLESS SERIES TIPS

You can choose hammerless or positive pin systems—giving you the flexibility you need when you need it. Full details about J Series adapters can be found on page 18.



FLUSH-MOUNT WITH TOP COVER



TWO-STRAP BOLT-ON



TWO-STRAP



MECHANICALLY ATTACHED ADAPTER



# BASE EDGE SYSTEMS

FASTEST INSTALLATION TIMES IN THE INDUSTRY.

Cat base edge systems go through a series of carefully controlled manufacturing processes to deliver maximum strength, durability and long life. They come completely welded and assembled with no need for preheating, dramatically shortening your installation and replacement time.

## INCREASE DURABILITY

A consistent heat-treat process maximizes strength and resists abrasion. Shot blasting removes impurities that can cause inclusions on a weld, and controlled cooling reduces the chance of stress points.

## SAVE INSTALLATION & REPLACEMENT TIME

Butterbead is applied to the back side of the base edge and the top strap of the corner adapter, so you can weld the edge onto the bucket without preheating.

## OPTIMIZE MACHINE PERFORMANCE

Base edges are designed by Caterpillar engineers for optimal performance on specific machines.




# BASE EDGE SYSTEMS

Base edge replacement for 988-994 wheel loaders usually involves a base edge assembly, which is a base edge with adapters welded in place at the factory. Choose from three shapes (straight, spade and stepped spade) and three levels of build to get the right protection for your application.

## GET MORE ACCURACY

Lasers place the adapters within 0.1mm of specifications.



STRAIGHT




SPADE



Angled Adapter

STEPPED SPADE



Standard Adapter

# BUTTERBEAD BASE EDGE ASSEMBLY

DURABLE PROTECTION COMBINED WITH SHORTER INSTALLATION TIMES.

The protection you need, with no preheating required—that's what you get with butterbead weld prep. This technique, which involves applying a layer of weld to a heat-treated, higher hardness part, makes it possible to weld a base edge to a bucket without preheating the hardened part. Choose from three shapes (straight, spade and stepped spade) and three levels of build to get the right protection for your application.

## SPEED UP YOUR INSTALLATION TIME

Weld prep eliminates the need for preheating, shortening edge installation time by 30-50 percent.

## GET MORE DURABILITY

Base edges have the proper butterbead weld because it is applied in the factory.



## BUTTERBEAD BASE EDGE ASSEMBLY

The chart below shows how much time and money you can save by using Cat base edges prepared with butterbead weld. All 988-994 large wheel loaders have butterbead base edge offerings.

BASE EDGE THICKNESS (mm)	TIME SAVED (hours)
< 40	3 to 6
40 - 50	8 to 12
50 - 60	12 to 16
> 65	16 to 20



# MECHANICALLY ATTACHED ADAPTER SYSTEM (MAA)

ADAPTER RETENTION WITH NO HAMMERS OR WELDING.

Featuring side-pin adapters and CapSure G.E.T. components, our MAA system uses a bolt-in wedge method to tighten a C-clamp, which locks the adapter securely in place every time.

## CHANGE ADAPTERS FASTER


Hammerless system reduces change time to less than 60 minutes—70 percent quicker than welded systems.

## IMPROVE SAFETY ON YOUR JOBSITE

Bolt-in design eliminates the need for welding and sledgehammers.

## LOWER YOUR OPERATING COSTS

Full base edge protection reduces wear.



Side-pin nose designed for CapSure hammerless retention.


# MECHANICALLY ATTACHED ADAPTER SYSTEM (MAA)



C-clamp secures MAA to the base edge.



C-clamp uses a wedge system to adjust tension.



# FLUSH-MOUNT ADAPTER SYSTEM

MORE UPTIME AND PRODUCTIVITY ON YOUR JOB.

Our flush-mount adapter system is ideal for high-impact, high-abrasion applications. The larger adapter and cover offer greater durability and more wear protection than a traditional two-strap system.

## GET IMPROVED ADAPTER LIFE

Upsized adapter resists impact better than a two-strap system.

## ENHANCE DURABILITY

A 35-degree bevel on the adapter and base edge provides a thicker edge section to reduce cracks and breakage.

## BOOST UPTIME

Complete weld-around design provides 20 percent more weld strength than a two-strap system.

## SPEED UP CHANGE-OUT TIMES

Cover protects the adapter and welds.

## INCREASE PRODUCTION

Adapter cover matches half arrow thickness, providing a flat, clean floor.




# FLUSH-MOUNT ADAPTER SYSTEM

**NOTE:** Investing in additional protection up front provides lower G.E.T. cost during production. Reduced maintenance intervals usually outweigh any penetration differences.

Adapter cover protects the weld bead.



Strap is welded, even under the adapter.



Flush-mount adapter base edge assembly is shown with adapter covers.

# SERRATED EDGE SYSTEM

PENETRATES LIKE A TIP, WITH NO ADAPTER REQUIRED.

The serrated cutting edge increases the penetration capabilities of wheel loaders in highly compacted soil or in applications that have higher impact loading requirements. This lends greater versatility to the machine without requiring bucket changes or the addition of other G.E.T. to the existing bucket.

## SHORTEN YOUR DIGGING CYCLES

Self-sharpening chamfers provide the best possible penetration.

## SIMPLIFY MAINTENANCE

Flat floor offers easy cleanup on your jobsite.

## REDUCE YOUR REPAIR COSTS


Bolt-on segments mean no welding, so you only need to replace worn sections (988H and 990H only). \*See page 32 for example bucket.

## ENHANCE DURABILITY

One-piece edge means no loose parts or parts falling into crushers (988H, 990H and 992G only). \*See image below for example bucket.



## SERRATED EDGE SYSTEM



# BOLT-ON CUTTING EDGES (BOCE)

BALANCED EDGE SYSTEMS FOR EVERY APPLICATION.

Finding the best solution for your bucket and application is easy with Cat's broad portfolio of edge options. Increase your machine's productivity by reducing operating costs and maintenance interval costs.

Cat bolt-on cutting edge options are available in standard and heavy-duty thicknesses, Cat Abrasion Resistant Material (A.R.M.) and half arrow options. Cat A.R.M. is recommended for applications where sand, gravel or other abrasive materials severely diminish wear life. Hard tungsten carbide particles are bonded to critical wear areas, providing up to five times greater wear life. See your Cat dealer for details.

We have G.E.T. for your bucket, no matter the application or environment. Maximum wear life and breakage resistance is possible with our steel alloy that can endure 2 times the heat and pressure of traditional cutting edge steel products. Consult your local Cat dealer to help determine the best cutting edge system for your application to give you the lowest cost per hour.

## STANDARD BOCE



- » This is the baseline for all other bolt-on edge systems.
- » Lower initial price.
- » Low- to medium-impact, low-abrasion materials only.

---

## HEAVY DUTY BOCE



- » 5mm thicker edge thickness delivering increased wear life.
- » Medium- to high-impact, medium-abrasion materials.

## ABRASION RESISTANT BOCE



- » Lighter weight than the HD edge.
- » Up to 5 times the wear life of a standard BOCE.
- » For use in high-abrasion, low-impact materials only.

---

## HALF ARROW BOCE



- » Protects the front of your base edge as well as the bottom.
- » For use in high-abrasion, high-impact materials.

---


## TOP COVER



- » Protects the bevel and top of your base edge.
- » Use with half arrows to fully protect your base edge investment.

---

## SERRATED BOCE



- » Increases the penetration of your bolt-on edge system.
- » For use in packed or frozen materials.
- » Maintains smooth floor.

# CAPSURE SHROUDS

Shorten change-out time without sacrificing base edge protection with these easy-to-install shrouds, available in a range of thicknesses and angles. Hammerless CapSure retention shrouds were designed for high-abrasion bucket systems. Most shrouds fit to base edges that have a 35-degree bevel angle and are equipped with flush-mount adapters. Shrouds can be matched with J or K Series adapters.

## SPEED UP YOUR CHANGE-OUT TIME

It's easier to install a single casting than two-piece protection.

## SIMPLIFY REMOVAL & INSTALLATION

Hammerless system is fast and easy and reduces the risk of injury.

## BOOST YOUR UPTIME

Wear indicator holes signal change-out time, so you can plan maintenance.

## LOWER YOUR OWNING & OPERATING COSTS

Pin lug is reusable.



Base Edge Pin



# TOP COVERS, SEGMENTS & HALF ARROW SEGMENTS

Protect your investment in buckets and base edges with these flexible components. Half arrow segments allow for a smooth transition of material over the base edge to protect the leading edge. Top covers complement the half arrow segments to protect the base edge fully. And segments are ideal for moving re-handled materials with medium impact and medium abrasion.

## SIMPLIFY MAINTENANCE

Individual pieces that protect the edge can be changed independently.

## ENHANCE DURABILITY

Half arrow segments cover the leading edge for smooth material transition.

## BOOST YOUR UPTIME

Top cover reduces wear on weld joints.

## SAVE ON INVENTORY COSTS

Reversible segment creates more leading edge wear material, reducing piece parts.

Segments



Half Arrow Segments



Top Covers



# BASE EDGE END PROTECTION (BEEP)

PROTECT YOUR CORNERS—WITHOUT CUTTING THEM.

Reduce base edge end wear and subsequent corner adapter weld erosion with our BEEP design. It makes adapter replacement on the edge much easier when it's time to rebuild the base edge assembly.

## BOOST YOUR UPTIME

Through-hardened Rc ~45 (Br ~3.0) weldable steel is easily installed in the shop or the field.

## EXTEND LIFE

Extended base edge end protects adapter corner welds.

## SPEED UP INSTALLATION


Height and bevel are matched to the base edge, so there's no additional fabrication.



# BASE EDGE END PROTECTION SYSTEM (BEEP)

BEEPs are available in a wide array of thicknesses and angles to fit 988-994 wheel loaders. Use this height, length and bevel angle chart to determine which BEEP best matches your base edge end profile.

HEIGHT (H)	LENGTH (L)	BEVEL (Bv)	BLUNT HEIGHT (Hb)	THICKNESS (T)
50	355	22.5	15	25
63.5	336	22.5	22	30
63.5	355	22.5	22	30
63.5	331	35	33	30
70	325	22.5	30	30
70	384	35	35	30
70	456	35	35	30
70	370	35	35	30
76	308	22.5	24	30
76	384	35	35	30
90	400	35	35	40
90	369	35	35	40



# SIDE & EDGE PROTECTION

## MAINTAIN YOUR PERFORMANCE EDGE.

Protect your bucket's structural integrity and enhance penetration with sidebar protection and shear blocks.

- » Sidebar Protectors (CapSure and traditional locking system)
- » Half Arrows
- » Top Covers
- » Segments
- » CapSure Shrouds



# SIDEBAR PROTECTORS

Protect your bucket's structural integrity and enhance penetration with sidebars and shear blocks.


## INCREASE YOUR UPTIME

Shear block protects the pin from extreme loads and breakage, helping ensure sidebar protector retention.

## CUT YOUR MAINTENANCE COSTS

Sidebar protector protects the bucket edge.

Shear block bears the loads instead of the pins.



Side-pinned design protects the bucket edge.

## CAPSURE SIDEBAR PROTECTORS

Get all the benefits of the sidebar protector without the hammer. CapSure sidebar protectors use hammerless locks for fast, easy installation and reduce the risk of injury.



990, 992 and 993 SBP



994 SBP



Shear Block

# PERFORMANCE SERIES SIDEBAR PROTECTORS

## INSTALLATION & REMOVAL

Get all the benefits of the sidebar protector without the hammer. Performance Series Mechanically Attached sidebar protectors use proven hammerless spring retainers for fast, easy installation and reduce the risk of injury.

- 1** Insert the protector into the dove tail base plate.



- 2** Mechanically attached wear plate compression retainer.



- 3** Install one end of the compression retainer.



- 4** Install the other end of the compression retainer in place using a small pry bar.



Scan the QR code to the right to watch the installation video.



# CORNER GUARD SYSTEM

Reduce your bucket's maintenance costs and increase bucket performance with the Cat Corner Guard system. Cat corner guards are an easily replaced bolt-on system to fit your 950-982 wheel loader buckets. These corner guards are available with and without adapters to fit your application needs.

**1** Slide the corner guard into place.



**2** Torque, Bang, Torque bolts to the proper bolt torque.



# BUCKET SELECTION GUIDE

We offer four standard bucket durability categories suitable for any application. Each category is based on the bucket's intended durability when used in the recommended application and material.

## GENERAL PURPOSE



- » Good all around performance for stockpiling, re-handling, excavating and bank loading.
- » Intended for use in low-impact materials.

## MATERIAL HANDLING



- » For stockpile loading loose materials such as gravel, sand and dirt in load-and-carry applications.
- » Intended for use in low-impact materials.
- » These are the best performers for production loading.
- » Flat bottom bucket.

## ROCK BUCKETS



- » For use in applications such as face loading limestone and other unprocessed rock. Also used in truck and hopper loading for a wide range of quarry materials.
- » Intended for use in moderate- to high-abrasion applications.
- » Balances the need for high production in more abrasive applications.

## HEAVY DUTY QUARRY ROCK BUCKET




- » For use where maximum abrasion resistance is required.
- » Intended for use in high-abrasion, high-impact applications.

## CHOOSING THE RIGHT DURABILITY.


Choosing the wrong bucket can easily reduce production and increase operating costs by 10-20% or more. It can also cause unnecessary wear and fatigue for both machine and bucket.

Contact your local Cat dealer for more detailed information on choosing the right wheel loader, bucket and work tool attachment combinations to meet your application needs.



# ADDITIONAL BUCKET STYLES

Several different bucket styles are available—each with a special purpose:



**COAL:** Coal Buckets are high-volume material movers for loading and stockpiling coal and other materials of similar density.



**GRAPPLE:** Grapple Buckets clamp loose material with dual ladder-style grapple tines. These are key producers in transfer stations, landfills or wherever loose, lightweight material needs to be moved.



**HIGH DUMP:** High Dump Buckets utilize dedicated dumping cylinders and a bottom hinge to “roll out” material. Higher than ordinary bucket types, they are ideal for transfer stations or loading high-sided trucks.



**MULTI-PURPOSE:** Multi-Purpose Buckets have a unique action that can load, bulldoze, clamp and perform many other tasks. A versatile design for site cleanup, demolition or similar situations.



**SIDE DUMP:** Side Dump Buckets dump both to the front and to the side of the machine, an advantage when working in tight quarters such as street work, tunnel construction and building levees.

# ADDITIONAL BUCKET STYLES (CONT.)



**SLAG:** Cat Slag Buckets are heavy duty and specifically constructed to handle extreme conditions that come with handling hot slag.




**WASTE HANDLING:** Waste Handling Buckets move large volumes of low-density waste in transfer stations, landfills and recycling yards. Large capacities give maximum production when loading conveyors, trucks or hoppers.



**WASTE LOAD & CARRY:** Load & Carry Buckets are primarily designed to load and carry lightweight material, minimizing contact with the floor for less bucket and floor wear.



**WASTE DOZING:** Dozing Buckets are designed to push waste loads along the floor to a hole or hopper in the floor for below-grade truck loading.




**WOODCHIP:** As the name suggests, Woodchip Buckets are optimized for moving large volumes of wood chips. The flat floor and straight edge work to scoop the bucket full and help heap the load high.

# CAT WEAR MANAGEMENT SYSTEM INTRODUCES...

## BUCKET PRO



You may be familiar with CTS Pro for Cat Undercarriage Inspections. Now, the Cat Wear Management System is launching the second module to help you manage G.E.T. on your bucket fleet.




**Your Cat dealer offers sales, service and technical support you need to keep your bucket at maximum productivity.**

- » Work with your Cat Dealer to set up your site and bucket fleet within the Bucket Pro App.
- » Use smart phone, iPad, or tablet to perform regular inspections of G.E.T. and get instant reports.
- » Go online to calculate costs and view production trends of each bucket.
- » Use data to reduce costs and improve production of your G.E.T. system.




# USING BUCKET PRO, YOUR DEALER CAN PROVIDE:

- » **G.E.T. Inspection Reports**  
These instant, on-site reports include % worn, future change out dates, and average life of all your G.E.T. components.



- » **Bucket Cycle Summary**—these monthly summaries show bucket cycle trends of CPT, CPH, and Productivity as well as average life trends.

- » Get real time data on G.E.T. performance and expected life.
- » Plan maintenance
- » Manage Inventory
- » Identify the best G.E.T. solutions
- » Know your CPT



## GET THE FACTS YOU NEED! STOP MANAGING YOUR G.E.T. WITH OPINIONS AND ASSUMPTIONS.

Talk to your Product Support Representative or G.E.T. Specialist today to learn how they can help you simplify your bucket management.

# WEAR PARTS & A.R.M.



# MECHANICALLY ATTACHED WEAR PLATE SYSTEM (MAWPS)

Safeguard wear areas with this hammerless system—available for a wide variety of applications.

## INCREASE YOUR UPTIME

Two minute change-out—no hammer required.



## LOWER YOUR INVENTORY COSTS

Flexible, versatile system welds to flat and curved surfaces.

## SIMPLIFY INSPECTIONS

Wear indicator holes allow for quick and easy inspections, reducing maintenance time.

## EXTEND WEAR LIFE

You can install the system perpendicular to material flow, then rotate it for more wear material.

### RETENTION WITHOUT THE RISK.

Retention components are located within the base plate, where they're shielded from wear and load—eliminating the risk of wear plates falling off.



Solid MAWPS

Skeletal MAWPS

# CHOOSE THE LOWEST-COST WEAR PROTECTION PER HOUR.

## MAWPS VERSUS STEEL PLATES.

When you choose MAWPS instead of steel wear plates, you can see cost savings as high as 44 percent, thanks to significantly lower labor and replacement costs.



TOTAL ANNUAL COSTS WITH STEEL PLATES

	PARTS	LABOR	TOTAL
<b>Installation costs</b>	\$4,000	\$1,200	\$5,200
<b>Replacement costs (2 times per year)</b>	\$8,000	\$2,400	\$10,400
			\$15,600 or \$7.80/hour



TOTAL ANNUAL COSTS WITH MAWPS

	PARTS	LABOR	TOTAL
<b>Installation costs</b>	\$4,000	\$600	\$4,600
<b>Replacement costs (2 times per year)</b>	\$4,000	\$83	\$4,083
			\$8,683 or \$4.34/hour

## EASY INSTALLATION & REMOVAL

Save time and money with MAWPS' two-minute installation and removal.

- 1** Weld the adapter perpendicular to material flow for maximum wear material (or parallel to flow with the Cat logo on top for maximum coverage).



- 2** Position the wear plate over the base plate and slide the wear plate onto the base plate.



- 3** Install one end of the compression retainer with the plug and pry it into place with an 8mm-wide small pry bar.



- 4** Clean, use pry bar to remove the compression retainer, and slide the wear plate off the base plate.



Scan the QR Code to the right to watch the installation video.



Reduce maintenance hours with MAWPS' easy-to-use wear indicator holes. Just look, then rotate or replace.

# SOLID MAWPS

DESIGN SOLUTIONS FOR YOUR BUCKET.

With solid MAWPS, you can enhance protection while keeping machine weight to a minimum. Choose a layout designed by Caterpillar engineers for your specific machine or application to maximize your productivity. Cat dealers can access the global library of MAWPS layouts.



**A.R.M.**  
OPTION  
AVAILABLE



SIZE	MACHINE
50 Series	5230, 994
40 Series	993, 5130, R2900
30 Series (available with A.R.M.)	992, 990, 5080, 374-390
	R1700, R1600
20 Series (available with A.R.M.)	980 and down
	365 and down
	Trucks
10 Series	972 and down
	320-349
	R1300

# SKELETAL MAWPS

STAY COVERED ACROSS YOUR PASS MATCH.

Quick and easy to install, skeletal MAWPS protect the rear portion of truck bodies to help you maximize uptime. A through-hardened DH-2 wear plate slides onto a weld-on base plate and is held in place with a patented compression retainer, trapping materials from any direction.

## TRAP MORE MATERIAL

The skeletal wear plate traps material in and between plates, allowing for material-on-material wear instead of wear on steel body liner products.

## EXTEND WEAR LIFE

Because the compression retainer is positioned low in the base plate, more of the wear plate can be worn away before you need to replace it.

## SIMPLIFY REMOVAL & INSTALLATION

You can typically replace worn wear plates in two minutes or less without hammering or welding.

## INCREASE YOUR FLEXIBILITY

Available in standard and heavy-duty sizes, skeletal MAWPS can be customized to fit virtually any truck body configuration—flat floor or dual slope.



# TOTAL WEAR PROTECTION

INCREASED PRODUCTIVITY. FOR EVERY ENVIRONMENT. FOR EVERY APPLICATION.

Get the best available protection for every product on your site, from wheel loaders to cable shovels, with our Total Wear Protection line.



**Chocky Bars**, available in four shapes, feature a V-groove design that can be bent around a radius. They can be separated or modified in length. The inset of the Cat logo allows for the trapping of fine material in each section, extending the life of the wear material itself. Chocky bars come in four sizes.



**Wear Buttons**, designed for applications that optimize the round profile, trap material to provide material-on-material wear. Wear buttons are available in four sizes.



**Wear Blocks** feature a zigzag inset design that allows for material-on-material wear. They prevent channel wear common in parallel grooves, delivering extended life in extreme operations.



**Roll Bars** protect the leading edge of dozers, loaders, mining shovels and other equipment, providing maximum wear protection while minimizing drag. Roll bars are available in three sizes.



**Bolt Protectors** help prevent hardware wear on cutting edges, top plates, sidebar protectors and more by allowing material to pack. They also allow for easier removal when replacing G.E.T.



Chocky bars in application

# WELD-ON HEEL SHROUDS & HALF ARROW EDGES

## WELD-ON HEEL SHROUDS


Weld-on heel shrouds protect the bottom and side of the bucket, concentrating extra wear material in the corner where it's needed most, and are ~400 Bn in hardness. Straight or curved shrouds come in three sizes, offering up to two inches of corner protection.



---

## WELD-ON HALF ARROW EDGES

Weld-on half arrow edges can be used to customize a bucket with sidebar protection, as side cutters to improve penetration or as segments between teeth to reduce scalloping.



---

## WELD-ON EDGE SHROUDS

Stackable edge shrouds are designed to fit any bucket configuration and extend the life of your excavator bucket edge assembly. Shroud profile is designed to work with K Series vertical pin retainers and horizontal J Series side pins. Tabs allow for easy alignment while installing your edge protection. Two shroud sizes are available per edge thickness to fit any bucket tooth spacing.

# ABRASION RESISTANT MATERIAL (A.R.M.)

Cat Abrasion Resistant Material is a coating made of extremely hard tungsten carbide particles that forms a protective shield over key wear surfaces. Cat G.E.T. with A.R.M. is ideal for high-abrasion, low-to-moderate impact applications—such as working in sand, gravel and other abrasive materials that can severely diminish G.E.T. wear life.

## EXTEND YOUR WEAR LIFE

Tungsten carbide offers three to five times the life of through-hardened G.E.T.

## LOWER YOUR COST PER HOUR


Self-sharpening wear pattern means fewer change-outs in the right applications.



### HARDNESS COMPARISON

MOHS HARDNESS

ROCKWELL "C" HARDNESS



EXAMPLE PARTS WITH A.R.M. APPLIED



Two-Strap K Series Adapter



J Series Penetration Tip



K Series Heavy Duty Tip



**A.R.M.**  
OPTION  
AVAILABLE

**NOTE:** Products available with the A.R.M. option feature this symbol.



PEBJ0078-06

© 2020 Caterpillar. All Rights Reserved.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

