



# Cat<sup>®</sup> S Type

## Excavator Couplers

***Cat<sup>®</sup> S Type Couplers help you get the job done faster while keeping the safety of your people and equipment top of mind. With the ability to easily switch attachments, S Type Couplers bring enhanced versatility and the kind of quality you expect from your Cat products. S Type Couplers are a versatile solution that help your operation run at peak efficiency.***

***Not all attachments are available in all regions. Consult your Cat dealer for specific configurations available in your region.***

### Unmatched Durability

- The most important coupler components are protected inside the cast base
- The coupler is made of cast pieces that sustain force better over time
- Wide contact surface to connect attachments prevents excessive wear
- Low build height maintains consistent breakout force
- Heavy-duty locking wedge keeps attachments secure

### Enhanced Versatility

- Switching attachments is quick and easy
- Attachments can be shared between machines in the same size class
- Lift hook allows for lifting objects with a chain or strap

### Industry-Leading Safety

- SecureLock<sup>™</sup> features and technology lead the industry in safety
  - Pressure relief – limits system to 300 bar (4351 psi) to protect the cylinder or locking wedge from damage
  - Hydraulic lock – check valve prevents hydraulic backflow
  - Sensor – measures the position of the locking wedge and indicates coupling status to the operator
  - Mechanical Spring – keeps the locking wedge in locking position, even in the event of hydraulic pressure loss
- Locking visual on coupler and machine monitor gives operator assurance the attachment is connected
- Operators can switch attachments independently while staying safe in the cab



# Cat® S Type Excavator Couplers

Specifications								
Model	Part Number	Linkage	Width		Weight		Lifting Eye Working Load Limit	
			mm	in	kg	lb	ton	lb
S60	573-3161	M312	340	13.4	174	384	5	10000
	573-3168	312	340	13.4	147	324	5	10000
	573-3166	315	340	13.4	176	388	5	10000
S70	566-2349	B/M320	450	17.7	259	571	8	16000
	566-2351	CB	450	17.7	285	628	8	16000
S80	573-3169	CB	590	23.2	426	939	10	20000
	573-3171	DB	590	23.2	456	1005	10	20000

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

© 2019 Caterpillar  
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

GEHQ9282-01 (10-2019)  
Replaces GEHQ9282-00  
(EU)

