

Cat[®] Extreme Application Grease

For high-load, high-speed applications

NLGI Grade 1, 2



Discover the Difference

Long Life—High-quality calcium sulfonate complex formula with 5% molybdenum disulfide (moly) for long service life in Cat applications.

Moisture Resistance—Resists washout from fresh and salt water.


Reduced Component Wear—Resists softening and continues to protect parts under extreme loads and high-speeds.

Corrosion Protection—Resists oxidation and protects metal against rust. Will not corrode or damage steel, copper bearing alloys or conventional seal materials.



Cat® Extreme Application Grease

Grease Selection Guide



* All temperatures are Operating Temperatures

| Typical Characteristics | | |
|---|-------------------|-------------|
| NLGI | 1 | 2 |
| Color | Gray Black | |
| Molybdenum Disulfide, % | 5 | 5 |
| Operating Temperature Range, °C | -20 to +140 | -15 to +140 |
| Operating Temperature Range, °F | -4 to +284 | +5 to +284 |
| Base Oil Type | Mineral | |
| ASTM D445 Base Oil Viscosity 40°C, mm²/s | 150 | |
| Thickener Type | Calcium Sulfonate | |
| ASTM D2265 Dropping point, °C | > 260 | > 260 |
| ASTM D2266 4 Ball wear, scar diameter, mm | .39 | .39 |
| ASTM D2596 4 Ball weld load, kg | 800 | 800 |
| ASTM D1743 Rust prevention | Pass | Pass |
| ASTM D4048 Copper corrosion | 1A | 1A |
| ASTM D1264 Water wash-out, 79°C, mass % | 0.6 | 0.6 |

The values shown are typical values and should not be used as quality control parameters to either accept or reject product. Specifications are subject to change without notice.

Recommended Use

Cat Extreme Application Greases are formulated for grease fittings and lubrication points in high-load, high-speed applications with operating temperatures ranging from -20°C to +140°C (-4°F to +284°F) for NLGI 1 and -15°C to 140°C (+5°F to +284°F) for NLGI 2.

Health and Safety

Always read and understand the Safety Data Sheet (SDS) before using this product.

For a copy of the SDS, visit us on the web at: www.catmsds.com

CAT DEALERS DEFINE WORLD-CLASS PRODUCT SUPPORT.

We offer you the right parts and service solutions, when and where you need them.

The Cat Dealer network of highly trained experts keeps your fleet up and running to maximize your equipment investment.

LET'S DO THE WORK.™



PEHJ0403
www.cat.com

© 2022 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

