## **Diesel Generator Set**





# **Standby** 3100 ekW 2825 kVA 60 Hz 1800 rpm 4160 Volts

Caterpillar is leading the power generation Market place with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

Image shown may not reflect actual package

### **FUEL/EMISSIONS STRATEGY**

EPA Tier 4 Interim

#### **DESIGN CRITERIA**

 The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

## **FULL RANGE OF ATTACHMENTS**

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

#### SINGLE-SOURCE SUPPLIER

 Fully prototype tested with certified torsional vibration analysis available

## **WORLDWIDE PRODUCT SUPPORT**

- Cat<sup>®</sup> dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries.
- The Cat SOS<sup>SM</sup> program effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by products.

#### **CAT C175-16 DIESEL ENGINE**

- Reliable, rugged, durable design
- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Engine performance optimized for use with Cat clean emissions module (CEM)

## **CAT CLEAN EMISSIONS MODULE (CEM)**

- Diesel oxidation catalyst for particulate matter (PM) and hydrocarbon (HC) control
- Selective catalytic reduction (SCR) with integrated sound attenuation
- Integrated electronics for monitoring, protection, and closed loop NO<sub>x</sub> control.
- Reliable, compact, and lightweight system gives maximum installation flexibility

#### **CAT GENERATOR**

- Matched to the performance and output characteristics of Cat engines
- Single point access to accessory connections

### **CAT EMCP 4 CONTROL PANELS**

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

60 Hz 1800 rpm 4160 Volts



## **Factory Installed Standard & Optional Equipment**

System	Standard	Optional
Air Inlet	Air cleaner; 4 x single element canister with service indicator(s)     Plug group for air inlet shut-off	[ ] Air cleaner; 4 x dual element with service indicator(s) [ ] Air inlet adapters
Cooling	SCAC cooling     Jacket water and AC inlet/outlet flanges	[ ] Remote horizontal SCAC radiator [ ] Remote fuel cooler
Exhaust	Exhaust manifold - dry - dual     Bolted flange (ANSI 6" & SIN 150) with bellow for each turbo (qty 4)     Clean Emissions Module (CEM)     CEM control cabinet     Flanged CEM outlet	[ ] Stainless steel exhaust flex fittings [ ] CEM installation package including support, exhaust connection kit, harness, and heated urea lines.
Fuel	Primary fuel filter with water separator     Secondary fuel filters	
Generator	<ul> <li>3 Phase brushless, Salient pole</li> <li>Cat digital voltage regulator (CDVR) with VAR/PF control, 3-phase sensing</li> <li>Winding temperature detectors</li> </ul>	[ ] Oversize generators [ ] Anti-condensation space heaters
Power	Bus bar (NEMA mechanical lug holes)	[ ] Bottom cable entry
Termination Governor	Top cable entry     ADEM™ A4	[ ] Right or left power termination [ ] Load share module
Control Panel	User interface panel (UIP) - rear mount     EMCP 4.2 Genset Controller     AC & DC customer wiring area (right side)     Emergency Stop Pushbutton	[ ] Local & remote annunciator modules [ ] Digital I/O Module [ ] Generator temperature monitoring & protection
Lube	Lubricating oil Gear type lube oil pump Integral lube oil cooler Oil filter, filler and dipstick Oil drain line and valve Prelube pump Closed crankcase ventilation (CCV) system	
Mounting	<ul> <li>Rails - engine / generator / radiator mounting</li> <li>Rubber anti-vibration mounts (shipped loose)</li> </ul>	[ ] Spring type vibration isolator
Starting / Charging	<ul> <li>24 volt starting motor(s)</li> <li>Batteries with rack and cables</li> <li>Battery disconnect switch</li> </ul>	<ul> <li>[ ] Battery chargers (20, 35, &amp; 50 Amp)</li> <li>[ ] Oversize batteries</li> <li>[ ] Heavy duty starting motors</li> <li>[ ] Barring device (manual)</li> <li>[ ] 75A charging alternator</li> </ul>
General	<ul> <li>Right hand service</li> <li>Paint – Cat Yellow except rails and radiators gloss black</li> <li>SAE standard rotation</li> <li>Flywheel and flywheel housing – SAE No. 00</li> </ul>	

## 60 Hz 1800 rpm 4160 Volts **SPECIFICATIONS**



#### **CAT GENERATOR**

Frame	1846
Excitation	Permanent Magnet
Pitch	0.6667
Number of poles	4
Number of leads	6
Number of bearings	Two Bearing
Insulation	Class H
IP rating	Drip proof IP23
Over speed capability - %	of rated125%
Wave form deviation	2 %
Voltage regulator	3 phase sensing with
	selectable V/Hz regulation
Valtage regulation I ass	then . 1/00/ (atanali, atata)

Voltage regulation....Less than  $\pm 1/2\%$  (steady state) Less than  $\pm 1/2\%$  (3% speed change)

#### **CAT DIESEL ENGINE**

C175, SCAC, V-16, 4 stroke, water-cooled diesel

Bore	175 00 mm (6.89 in)
Stroke	220.00 111111 (0.00111)
Displacement	84.67 L (5166.88 in³)
Compression ratio	15.3:1
Aspiration	TA
Fuel system	Common Rail
Governor Type	ADEM™ A4

#### **CAT EMCP 4 CONTROL PANELS**

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed & Voltage Adjust
- Engine Cycle Crank
- Emergency stop pushbutton

EMCP 4.2 controller features:

- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- Power Factor (per phase & average)
- kW (per phase, average & percent)
- kVA (per phase, average & percent)
- kVAr (per phase, average & percent)
- kW-hr & kVAr-hr (total)

Warning/shutdown with common LED indication of shutdowns for:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32)
- Reverse Reactive Power (kVAr) (32RV)
- Overcurrent (50/51)

### Communications

- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- 6 programmable digital inputs
- 4 programmable relay outputs (Form A)
- 2 programmable relay outputs (Form C)
- 2 programmable digital outputs

Compatible with the following optional modules:

- Digital I/O module
- Local Annunciator
- Remote annunciator
- RTD module
- Thermocouple module

60 Hz 1800 rpm 4160 Volts



## **Technical Data**

Open Generator Set - 1800 rpm/60 Hz/4160 Volts	STAN	DBY
Generator Set Package Perfomance		
Genset Power rating @ 0.8 pf	3875 kVA	
Genset Power Rating without fan	3100 ekW	
Fuel Consumption <sup>1</sup>		
100% Load without fan	790.3 L/hr	208.8 Gal/hr
75% Load without fan	616.2 L/hr	162.8 Gal/hr
50% Load without fan	500.0 L/hr	132.1 Gal/hr
Diesel Exhaust Fluid (DEF) Consumption <sup>2</sup>		
100% Load without fan	50.7 L/hr	13.4 Gal/hr
75% Load without fan	29.5 L/hr	7.8 Gal/hr
50% Load without fan	15.1 L/hr	4.0 Gal/hr
Cooling System <sup>3</sup>		
Engine coolant capacity	303.5 L	80.2 gal
Inlet Air		
Combustion air inlet flow rate	259.3 mm <sup>3</sup> /min	9156 cfm
Exhaust System⁴		
Exhaust stack gas temperature	472 °C	882.2 °F
Exhaust gas flow rate	667 mm³/min	23559 cfm
Exhaust system backpressure (maximum allowable)	6.7 kPA	26.9 in water
Heat Rejection		
Heat rejection to cooolant (total)	1373 kW	78082 Btu/min
Heat rejection to exhaust (total)	3113 kW	176978 Btu/min
Heat rejection to aftercooler	379 kW	21577 Btu/min
Heat rejection to atmosphere from engine	175 kW	9978 Btu/min
Heat rejection to atmosphere from CEM	53 kW	3026 Btu/min
Heat rejection to atmosphere from generator	2.0 kW	116 Btu/min
Alternator <sup>5</sup>		
Motor starting capabiliy @30% voltage dip	7949 skVA	
Frame	1848	
Temperature Rise	150 °C	270 °F
Emissions (Nominal) <sup>7</sup>		
NOx g/hp-hr	0.53 g/hp-hr	
CO g/hp-hr	0.01 g/hp-hr	
HC g/hp-hr	0.00 g/hp-hr	
PM g/hp-hr	0.01 g/hp-hr	

EPA Tier 4 Interim diesel engines required the use of Ultra Low Sulfur Diesel (ULSD) fuel in order to protect emissions control systems, help comply with emissions standards, and meet published maintenance intervals. ULSD fuel will have ≤ 15 ppm (0.0015%) sulfur using the ASTM D5453, ASTM 2622, or SIN 51400 test methods.

<sup>&</sup>lt;sup>2</sup> Diesel Exhaust Fluid (DEF) is 32.5% urea in de-ionized water, defined by ISO-22241

<sup>&</sup>lt;sup>3</sup> For ambient and altitude capabilities consult your Caterpillar dealer. Air flow restriction (system) is added to existing restriction from factory.

<sup>&</sup>lt;sup>a</sup> Backpressure allowance is total backpressure available for the customer excluding the dean emissions module (CEM).

Some packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

<sup>°</sup> Requires the use of CJ4 oil in order to meet published maintenance intervals.

Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

60 Hz 1800 rpm 4160 Volts



## RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC, 98/37/EC, 2004/108/EC

**Standby** - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions

**Fuel Rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

60 Hz 1800 rpm 4160 Volts



## **Dimensions**

Package Dimensions			
Length	6492 mm	255.6 in	
Width	2098 mm	82.6 in	
Height	2208 mm	87.0 in	

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions.

CEM Dimensions		
Length	4580 mm	180.3 in
Width	2361 mm	92.9 in
Height	1714 mm	67.5 in

www.Cat-ElectricPower.com

©2012 Caterpillar All rights reserved.

Materials and specifications are subject to change without notice. The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

Performance No: DM8952 Feature Code: 175DE49

Gen. Arr. Number: 2523976

Sourced: U.S. Sourced

December 2012

EPD0100-B