



Image shown may not reflect actual package.

PRIME 320 kW 400 kVA 50 Hz 1500 rpm 400 Volts

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

- Low Fuel consumption

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

CAT[®] C13 ATAAC DIESEL ENGINE

- Utilizes ACERT[™] Technology
- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic engine control

CAT GENERATOR

- Matched to the performance and output characteristics of Cat engines
- Load adjustment module provides engine relief upon load impact and improves load acceptance and recovery time
- UL 1446 Recognized Class H insulation

CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

| System | Standard | Optional |
|-------------------|--|--|
| Air Inlet | <ul style="list-style-type: none"> • Disposable Air filter • Service indicator | Canister type Air Filter: <input type="checkbox"/> Single element <input type="checkbox"/> Dual element |
| Cooling | <ul style="list-style-type: none"> • Radiator package mounted • Coolant level sight gauge • Low coolant level sensor • Coolant drain line with valve • Fan and belt guards • Cat® Extended Life Coolant | <input type="checkbox"/> Radiator duct flange <input type="checkbox"/> Stone Guard <input type="checkbox"/> Low coolant temperature alarm |
| Exhaust | <ul style="list-style-type: none"> • Dry exhaust manifold • Stainless steel flex fittings • Exhaust flange outlet | <input type="checkbox"/> Industrial <input type="checkbox"/> Residential <input type="checkbox"/> Critical Mufflers <input type="checkbox"/> Manifold and turbocharger guards <input type="checkbox"/> Elbows and flange kits |
| Fuel | <ul style="list-style-type: none"> • Integral narrow single wall fuel tank base • Primary fuel filter with integral water separator • Secondary fuel filters • Fuel priming pump • Engine fuel transfer pump • Fuel cooler integral with cooling system • Flexible fuel lines | <input type="checkbox"/> Fuel level switch <input type="checkbox"/> Manual fuel transfer pump |
| Generator | <ul style="list-style-type: none"> • Class H insulation • Self excited (SE) • Class H temperature rise • IP23 protection • R450 voltage regulator with single phase sensing and load adjustment module | <input type="checkbox"/> Oversize generators <input type="checkbox"/> Permanent magnet excitation (PMG) <input type="checkbox"/> Internal excited (IE) <input type="checkbox"/> Cat digital voltage regulator (Cat DVR) with kVAR/PF <input type="checkbox"/> Anti-condensation space heaters <input type="checkbox"/> Coastal Insulation Protection (CIP) <input type="checkbox"/> Reactive droop <input type="checkbox"/> Three phase sensing |
| Power Termination | <ul style="list-style-type: none"> • Power Center houses EMCP controller and power/control terminations (rear mounted) • Circuit breaker, IEC compliant, 3-4 pole (100% Rated) • Segregated low voltage wiring termination panel • IP22 protection • Bottom cable entry | <input type="checkbox"/> C.B. Shunt trips <input type="checkbox"/> C.B. Auxiliary contacts |
| Governor | <ul style="list-style-type: none"> • ADEM™A4 | |
| Control Panel | <ul style="list-style-type: none"> • EMCP 4.1 (Rear-mounted in Power Center) • Emergency stop pushbutton • AC Voltmeter, Ammeter & Frequency • Engine Speed (rev/min) • Lube Oil pressure | <input type="checkbox"/> EMCP 4.2 <input type="checkbox"/> Local annunciator module (NFPA 99/110) <input type="checkbox"/> Remote annunciator module (NFPA 99/110) <input type="checkbox"/> Digital I/O module <input type="checkbox"/> Speed adjustment <input type="checkbox"/> Voltage adjustment |
| Lube | <ul style="list-style-type: none"> • Lubricating oil • Oil drain line with valves • Oil filter and dipstick • Fumes disposal • Oil cooler | <input type="checkbox"/> Oil temperature sensor <input type="checkbox"/> Manual sump pump |
| Mounting | <ul style="list-style-type: none"> • Integral Narrow 8hr tank base • Linear vibration isolation | <input type="checkbox"/> Narrow skid base <input type="checkbox"/> Integral Dual Wall 8hr tank base* *Available only with enclosed units |
| Starting/Charging | <ul style="list-style-type: none"> • 24 volt starting motor • 24 volt, 45 amp charging alternator • Batteries with rack and cables | <input type="checkbox"/> Jacket water heater <input type="checkbox"/> Battery disconnect switch <input type="checkbox"/> Battery charger – 5 amp |
| General | <ul style="list-style-type: none"> • Paint – Caterpillar Yellow except rails and radiators gloss black (Powder Coated) • Flywheel housing – SAE No.1/2 | <input type="checkbox"/> EU Certificate of Conformance <input type="checkbox"/> Sound attenuated protective enclosure with integral lifting frame <input type="checkbox"/> High Ambient enclosure with integral lifting frame |

SPECIFICATIONS

| STANDARD CAT GENERATOR | |
|--|--|
| Frame size | LC6114C |
| Excitation | Self excitation |
| Pitch | 0.6667 |
| Number of poles | 4 |
| Number of bearings | Single bearing |
| Number of leads | 12 |
| Insulation | Class H |
| IP Rating | IP23 |
| Alignment | Pilot Shaft |
| Overspeed capability (%) | 150 |
| Wave form deviation (%) | 2 |
| Voltage regulator | Single phase sensing (Optional three phase sensing) |
| Voltage regulation | +/- 0.5% (steady state) |
| – Consult your Cat dealer for other available voltages | |
| CAT DIESEL ENGINE | |
| C13 ATAAC, I-6 4-stroke water-cooled diesel | |
| Bore | 130.00 mm (5.12 in) |
| Stroke | 157.00 mm (6.18 in) |
| Displacement | 12.50 L (762.80 in ³) |
| Compression ratio | 16.3:1 |
| Aspiration | Air-to-air aftercooled |
| Fuel system | MEUI |
| Governor type | ADEM™ A4 control system |

CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24 volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- kW, kVA, kVAR, kW-hr, %kW, PF (4.2 only)

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under frequency (81 o/u)
- Reverse power (kW) (32) (4.2 only)
- Reverse reactive power (kVAr) (32RV)
- Overcurrent (50/51)

Communications:

- Four digital inputs (4.1)
- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU) (4.2 only)
- Accessory module data link (4.2 only)
- Serial annunciator module data link (4.2 only)
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local annunciator
- Remote CAN annunciator
- Remote serial annunciator

PRIME 320 ekW 400 kVA
50 Hz 1500 rpm 400 Volts



TECHNICAL DATA

| Open Generator Set – 1500 rpm/50 Hz/400 Volts | EM0432 | |
|--|---|---|
| Low BSFC | | |
| Generator Set Package Performance Genset power rating @ 0.8 pf Genset power rating with fan | 400 kVA 320 ekW | |
| Fuel Consumption 100% load with fan 75% load with fan 50% load with fan | 82.0 L/hr 61.8 L/hr 43.2 L/hr | 21.7 gal/hr 16.3 gal/hr 11.4 gal/hr |
| Cooling System¹ Air Flow Restriction Air Flow (max @ rated speed for radiator arrangement) Engine Coolant Capacity) Radiator Capacity Engine Coolant Capacity w/ Rad | 0.12 kPa 398 m ³ /min 14.2 L 31 L 45.2 L | 0.48 in. water 14055 cfm 3.8 gal 8.2 gal 11.9 gal |
| Inlet Air Combustion air inlet flow rate | 22.7 m ³ /min | 801.6 cfm |
| Exhaust System Exhaust stack gas temperature Exhaust gas flow rate Exhaust flance_size Exhaust system back pressure | 643.6°C 62.2 m ³ /min 127 mm 10 kPa | 1190°F 2196.6 cfm 5 in 40 in. water |
| Heat Rejection Heat rejection to coolant Heat rejection to exhaust Heat rejection from aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere generator | 124 kW 285 kW 57 kW 46.7 kW 23.7 kW | 7052 Btu/min 16208 Btu/min 3242 Btu/min 2655.8 Btu/min 1347.8 Btu/min |
| Alternator² Motor starting capability @ 30% voltage dip Frame Temperature rise | 617 skVA LC6114C 125°C | 225°F |
| Lubrication System Sump refill with filter | 36.0 L | 9.5 gal |
| Emissions (Nominal)³ NO _x CO HC Part matter | 2616.0 mg/nm ³ 710.0 mg/nm ³ 2.7 mg/nm ³ 0.0 mg/nm ³ | |

¹For ambient and altitude capabilities consult your Cat dealer. Airflow restriction (system) is added to existing restriction from factory.

²Generator temperature rise is based on a 40°C (104°F) ambient per NEMA MG1-32. Some packages may have oversized generators with a different temperature rise and motor starting characteristics.

³Emissions data measurement procedures are consistent with those described in EPA CF40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NO_x. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

PRIME 320 ekW 400 kVA

50 Hz 1500 rpm 400 Volts



RATING DEFINITIONS AND CONDITIONS

Applicable Codes and Standards:

IEC60034-1, IEC60034-22, ISO3046, ISO8528, NEMA MG 1-32, NEMA MG 1-33, 2004/108/EC, 2006/42/EC, 2006/95/EC.

Prime – Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated ekW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions.

PRIME 320 ekW 400 kVA

50 Hz 1500 rpm 400 Volts



DIMENSIONS

| Package Dimensions | | |
|--------------------|-----------|-----------|
| Length | 3800.0 mm | 149.61 in |
| Width | 1130.6 mm | 44.51 in |
| Height | 2156.0 mm | 84.88 in |

NOTE: For reference only – do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #4242079).

Performance No.: EM0432

Feature Code: C13DE05

Gen. Arr. Number: 4215197

Source: European Sourced

LEHE0438-00 (05/13)

www.Cat-ElectricPower.com

2013 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.