



DM32E | DM40E | DM48E | DM55E

For messages too important to miss

### DM-E 32"/40"/48"/55" Commercial LED LCD Displays

In public places, restaurants, retail, or other environments where 24/7 operation is mandatory, Samsung delivers reliability. The DM-E Series displays incorporate innovative Samsung cooling technologies, for continuous operation and peace of mind. Images and text will always be sharp, clear and precise, with Full HD 1920 x 1080 resolution and 5000:1 contrast ratio. Lightweight designs ensure installation ease, and an optional touch overlay can enable up to 10 simultaneous touch points for a greater level of interactivity. It's around-the-clock impact and reliability.

#### CONTACT US:

1-866-SAM4BIZ  
[samsung.com/business](http://samsung.com/business)  
[samsung.com/b2bdigitalsignage](http://samsung.com/b2bdigitalsignage)

#### FOLLOW US:

[youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa)  
[@SamsungBizUSA](https://twitter.com/SamsungBizUSA)

**SAMSUNG**  
 BUSINESS

### Key Features



#### Reliable 24/7 Continuous Operation

Samsung DM-E Series commercial displays feature innovative cooling technologies, and are designed from the chassis up to deliver the highest quality images with exceptional reliability, even during 24/7 continuous operation.



#### Enhanced System-on-Chip Performance with Quad-Core CPU

Powered by a System-on-Chip semiconductor and 1GHz quad-core CPU, and featuring 8GB of storage, Samsung's SMART Signage Platform reduces TCO for digital signage deployments, providing savings in hardware, installation and operating costs.



#### Sleek Industrial Design with Thin Bezel

A sleek, stylish look features a 9.5mm bezel width (top and left, 10.5mm on DM32E), with optional customizable bezel trim kits (white, matte black).



#### Ultra-Slim 2.0" Chassis

The stylishly thin chassis looks streamlined, helps simplify installation, and also meets ADA compliance requirements.



#### Slim-Direct LED Backlight

The slim-direct-lit displays of the DM-E Series feature 1920 x 1080 Full HD resolution with 450 nits brightness (400 on DM32E) and 5000:1 contrast ratio for sharp, detail-rich images and crisp, easily legible type.



#### Built-In Wi-Fi

Enjoy the advantages of expanded connectivity to mobile devices and simple mirroring of content on a tablet to the display.



#### Optional Touch Overlay with PC-less Touch Support

Add an optional IR touch overlay accessory to enable up to 10 simultaneous touch points. PC-less touch support means you only need to add the touch overlay accessory to enable touch, and no PC or setback box is required.



#### MagicInfo S3 Digital Signage Software

The software allows you to create playlists, set playback schedules and publish content directly to the display. Most traditional file formats are supported, including RSS feed and live web pages.



# Samsung DM-E 32"/40"/48"/55" Commercial LED LCD Displays



		DM32E	DM40E	DM48E	DM55E	
Display	Screen Size	32"	40"	48"	55"	
	Panel Technology	60Hz Slim D-LED BLU	60Hz Slim D-LED BLU	60Hz Slim D-LED BLU	60Hz Slim D-LED BLU	
	Resolution	1920x1080 (16:9)	1920x1080 (16:9)	1920x1080 (16:9)	1920x1080 (16:9)	
	Brightness	400 nits	450 nits	450 nits	450 nits	
	Contrast Ratio	5000:1	5000:1	5000:1	5000:1	
	Viewing Angle (Horizontal/Vertical)	178° / 178°	178° / 178°	178° / 178°	178° / 178°	
	Orientation	Landscape / Portrait	Landscape / Portrait	Landscape / Portrait	Landscape / Portrait	
	Response Time (G-to-G)	8ms	8ms	8ms	8ms	
Connectivity	Input	VGA (D-Sub 15 Pin), DVI-D (HDMI Common), HDMI1, HDMI2 (thru DVI-D Input, Adapter Not Included), Component/Composite, Stereo Mini Jack, USB 2.0 x 1	VGA (D-Sub 15 Pin), DVI-D (HDMI Common), DisplayPort 1.2, HDMI1, HDMI2 (thru DVI-D Input, Adapter Not Included), Component/Composite, Stereo Mini Jack, USB 2.0 x 1	VGA (D-Sub 15 Pin), DVI-D (HDMI Common), DisplayPort 1.2, HDMI1, HDMI2 (thru DVI-D Input, Adapter Not Included), Component/Composite, Stereo Mini Jack, USB 2.0 x 1	VGA (D-Sub 15 Pin), DVI-D (HDMI Common), DisplayPort 1.2, HDMI1, HDMI2 (thru DVI-D Input, Adapter Not Included), Component/Composite, Stereo Mini Jack, USB 2.0 x 1	
	Output	Stereo Mini Jack	DisplayPort 1.2 (Loop-Out), Stereo Mini Jack	DisplayPort 1.2 (Loop-Out), Stereo Mini Jack	DisplayPort 1.2 (Loop-Out), Stereo Mini Jack	
	External Control	RS232C (In/Out) thru Stereo Jack, RJ45	RS232C (In/Out) thru Stereo Jack, RJ45	RS232C (In/Out) thru Stereo Jack, RJ45	RS232C (In/Out) thru Stereo Jack, RJ45	
	External Sensor	IR, Ambient Light	IR, Ambient Light	IR, Ambient Light	IR, Ambient Light	
Power	Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	
	Power Consumption (Typical/Max)	30W / 77W	44W / 121W	50W / 132W	65W / 176W	
	Power Consumption (Standby)	< 0.5W	< 0.5W	< 0.5W	< 0.5W	
Environmental Conditions	Operating Temperature	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	
	Operating Humidity	10%~80%	10%~80%	10%~80%	10%~80%	
Features	Slim and Light LFD with Built-in MagicInfo Player S3		Slim and Light LFD with Built-in MagicInfo Player S3		Slim and Light LFD with Built-in MagicInfo Player S3	
	Special	Hardware	Super Clear Coating, Temperature Sensor, Pivot Display, Button Lock, Clock Battery (80hrs Clock Keeping), Built in Speaker (10Wx1), Wi-Fi Module Embedded, SD Card Slot		Super Clear Coating, Temperature Sensor, Pivot Display, Button Lock, Clock Battery (80hrs Clock Keeping), Built in Speaker (10Wx1), Wi-Fi Module Embedded, SD Card Slot	
		Software	Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play (DDC2B), PIP/PBP, Image Rotation, Built-in MagicInfo S3, Firmware Update by Network, Predefined Template for Vertical Usage, Multi Channel, Mobile Control, Event Schedule, Backup Player, PC-less Touch		Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play (DDC2B), PIP/PBP, Image Rotation, Built-in MagicInfo S3, Firmware Update by Network, Predefined Template for Vertical Usage, Multi Channel, Mobile Control, Event Schedule, Backup Player, PC-less Touch	
	Tuner	Yes		Yes		
	SMART Signage Platform Compliant	Yes		Yes		
	Internal Media Player	Cortex-A9 1GHz Quad Core, 1.5GB DDR3, 8GB Storage, USB 2.0, Samsung Proprietary OS (VDLinux)		Cortex-A9 1GHz Quad Core, 1.5GB DDR3, 8GB Storage, USB 2.0, Samsung Proprietary OS (VDLinux)		
	VESA Standard Wall Mount Interface	200 x 200mm		400 x 400mm		
	24/7 Operation	Yes		Yes		
	Dimensions	Product Dimensions (without stand)	28.4" x 16.5" x 2.0"		42.3" x 24.4" x 2.0"	
		Packaging Dimensions	32.1" x 19.3" x 5.2"		46.7" x 28.1" x 5.8"	
Bezel Width		10.5mm (Top, Left), 15.0mm (Right, Bottom)		9.5mm (Top, Left), 15.0mm (Right, Bottom)		
Weight	Product Weight	10.7 lbs.		24.5 lbs.		
	Shipping Weight	13 lbs.		30.9 lbs.		
Service	Standard Warranty	3 Years On-Site (Parts / Labor / Backlight)		3 Years On-Site (Parts / Labor / Backlight)		
Accessories	Included	Quick Setup Guide, Warranty Card, D-Sub Cable, Power Cord, Remote Controller, Batteries		Quick Setup Guide, Warranty Card, D-Sub Cable, Power Cord, Remote Controller, Batteries		
	Optional Mount	WMN4070SD, WMN250MD		WMN4270SD, WMN250MD		
	Optional Stand	STN-L3240E		STN-L4655E		
	External Media Player	SBB-DA, SBB-DI, SBB-B32D (Not Attachable)		SBB-DA, SBB-DI, SBB-B32D		
	Optional Touch Overlay	CY-TD32LDAH		CY-TD48LDAH		
	Optional Bezel Trim Kit	CY-BD32BD (Matte Black), CY-BD32WD (White)		CY-BD48BD (Matte Black), CY-BD48WD (White)		
Green Management	Emission Standard	EMC		EMC		
	ENERGY STAR® 6.0 Compliant	Yes		Yes		
	RoHS Compliant	Yes		Yes		
	Packaging Recyclability	Packing Materials Recyclable		Packing Materials Recyclable		

## CONNECTIVITY

- RS232C In
  - RS232C Out
  - IR/Ambient Sensor In
  - Audio In
  - Audio Out
  - SD Card Slot
  - USB
  - DVI In
  - DisplayPort In
  - HDMI In
  - VGA In
  - DisplayPort Out
  - Antenna In
  - AV In
  - IR Out
  - RJ45 In
- Note: 32" model does not have DisplayPort In/Out.



**Learn more** [samsung.com/business](http://samsung.com/business) or [www.samsung.com/b2bdigitalsignage](http://www.samsung.com/b2bdigitalsignage)

**Product support** 1-800-SAMSUNG 1-866-SAM4BIZ

**Follow us** [youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa) [@SamsungBizUSA](https://twitter.com/SamsungBizUSA)

**SAMSUNG**  
BUSINESS

Samsung Electronics has been named 2015 ENERGY STAR Partner of the Year in the product manufacturing category by the U.S. Environmental Protection Agency (EPA).

©2015 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. All brand, product, service names and logos are trademarks and or registered trademarks of their respective manufacturers and companies. See [samsung.com](http://samsung.com) for detailed information. Printed in USA. LFD-DMESERIESB2BDSHT-JUN15T

