



# A clear, simple solution for meeting rooms

## EME Series 65"/75" displays with integrated HDBaseT receivers

Improve the clarity of meetings and huddle rooms with the Samsung EME Series displays. Featuring embedded HDBaseT receivers, they're simple ways of taking advantage of uncompressed content over long distance. Just connect a single Ethernet LAN cable, and you're ready to go. Installation is simple and clean, content is clear and sharp. With nothing lost in the translation, they're the ideal ways to enhance collaboration and communication.

### Contact us

1-866-SAM4BIZ  
[samsung.com/business](http://samsung.com/business)  
[samsung.com/b2bdigitalsignage](http://samsung.com/b2bdigitalsignage)

### Follow us

[youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa)  
 @SamsungBizUSA

## Key features




### Built-in\* HDBaseT receiver

The built-in HDBaseT receiver on the EME Series allows you to take full advantage of HDBaseT, while simplifying installation. Connectivity is simple, and cable clutter is eliminated.



### Connect through a single LAN cable

With an integrated HDBaseT receiver, the EME Series displays receive uncompressed Full HD multimedia content. The AV signal and control signal travel through a single LAN Ethernet cable. Content suffers no degradation, and the single cable allows a clean installation.



### Meeting room console\*

The included meeting room console serves as a table top remote control for volume change, source change and power ON/OFF.



### Full HD and built-in speakers

The EME Series is meeting room-ready with Full HD resolution and built-in 10W x 2 stereo speakers. Images are clear, crisp and colorful. Audio is full and rich.

\*Requires Samsung meeting box: SBB-MT12EA to work properly.


# Samsung EME Series commercial LED LCD displays with integrated HDBaseT receivers



		EM65E	EM75E	
Panel	Diagonal Size	65"	75"	
	Type	60Hz LED BLU	60Hz LED BLU	
	Resolution	1920 x 1080 (16:9)	1920 x 1080 (16:9)	
	Brightness (Typ.)	400 nits	400 nits	
	Contrast Ratio (Typ.)	4000:1	5000:1	
	Viewing Angle (H / V)	178:178	178:178	
	Response Time (G-to-G)	6ms	4ms	
	Orientation	Landscape / Portrait	Landscape / Portrait	
Sound	Speaker Type	Built in Speaker (10W + 10W)	Built in Speaker (10W + 10W)	
Connectivity	Input	RGB	Analog D-SUB, DVI-D	Analog D-SUB, DVI-D
		Video	CVBS, Component, HDMI, HDBT	CVBS, Component, HDMI, HDBT
		Audio	Stereo Mini Jack	Stereo Mini Jack
		USB	USB Player	USB Player
	Output	Audio	Stereo Mini Jack	Stereo Mini Jack
	External Control	RS232C (In / Out) thru Stereo Jack	RS232C (In / Out) thru Stereo Jack	
External Sensor	Yes	Yes		
Power	Type	Internal	Internal	
	Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	
	Power Consumption	Max [W / H]	253	308
		Typical [W / H]	215	260
		Sleep Mode	Less than 0.5W	Less than 0.5W
Off Mode	Less than 0.5W	Less than 0.5W		
Dimensions	Set In. (WxHxD)	57.7" x 33.3" x 2.2"	65.9" x 37.7" x 3.4" (Except Handle 2.2")	
	Package In. (WxHxD)	62.9" x 38.5" x 11.2"	71.2" x 42.7" x 9.8"	
	Bezel Width (mm)	18.0mm (Bottom 23.5mm)	12mm (Bottom 17.3mm)	
Weight	Set	60.4 lbs.	75.1 lbs.	
	Package	78 lbs.	97.2 lbs.	
Features	VESA Mount	400 x 400mm	400 x 400mm	
	Stand Type	Foot Stand (Optional)	Foot Stand (Optional)	
	Special	Built in Speaker (10W + 10W), PIP / PBP, Narrow Bezel, Light Weight, RS232 In / Out, 1 D-Sub, 1 HDMI	Built in Speaker (10W + 10W), PIP / PBP, Narrow Bezel, Light Weight, RS232 In / Out, 1 D-Sub, 1 HDMI	
Environmental Conditions	Operating Temperature	0°C ~ 40°C	0°C ~ 40°C	
	Operating Humidity	10 ~ 80%	10 ~ 80%	
Accessories	Included	Quick Setup Guide, Warranty Card, D-Sub Cable, Power Cord, Remote Controller, Batteries		
	Optional	Stand	STN-L6500E	STN-L7585F
		Mount	WMN6575SD	WMN6575SD
		Media Player	SBB-DA / DI	SBB-DA / DI
Meeting Room Box & Console	SBB-MT12EA	SBB-MT12EA		
Green Management	Emission Standard	EMC	EMC	
	ENERGY STAR Compliant	N/A	N/A	
	RoHS Compliant	Yes	Yes	
	Packaging Recyclability	Packing Materials Recyclable	Packing Materials Recyclable	
Service	Standard Warranty	3 Years Onsite (Parts / Labor / Backlight)	3 Years Onsite (Parts / Labor / Backlight)	

## CONNECTIVITY

1. HBDT In
2. USB (5V, 1.5A)
3. DVI In / MagicInfo In
4. HDMI
5. RGB In
6. RS232C In
7. RS232C Out
8. RGB / DVI / HDMI / AV / Component / Audio In
9. Audio Out
10. AV In / Video / Component In
11. IR / Ambient Sensor In



## MEETING ROOM BOX & CONSOLE (SBB-MT12EA)

Model	Part Number	SBB-MT12EA
Connectivity	Ethernet	10/100Mbps (MDC)
	USB	USB Port x 1 (S/W Update Only)
	Output	DVI Out, RJ-45, RS232 In (Stereo), IR In
	Others	HDMI1, HDMI2, HDBT Out
Power	Type	Adapter
	Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
	Power Consumption	17W (Max) / 10W (Typical) / 15W (Rating)
Dimensions	Set	8.76" x 5.5" x 1.25"
	Package	13.2" x 11.2" x 2.3"
Weight	Set	3.3 lbs.
	Package	8.2 lbs.
Environmental Conditions	Operating Temperature	10°C ~ 40°C
	Operating Humidity	10 ~ 80%
Accessories	Included	User Manual, Adaptor, Power Cord, DVI to HDMI Cable, External IR Sensor, Meeting Console

Learn more [samsung.com/business](http://samsung.com/business) [insights.samsung.com](http://insights.samsung.com) [samsung.com/b2bdigitalsignage](http://samsung.com/b2bdigitalsignage)

Product support 1-866-SAM4BIZ 1-800-SAMSUNG

Follow us [youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa) [@SamsungBizUSA](https://twitter.com/SamsungBizUSA)

**SAMSUNG**