



EZ - In Wire

Specification Sheet



Construction:

Stranded bare copper THHN/THWN conductors with PVC insulation and Nylon jacket cabled together with an aluminum interlocking armor applied over the assembly. A moisture and sunlight resistant, flame retardant PVC jacket is applied over the armor.

Applications:

Armored mini-split cable can be installed without the use of conduit and may be installed indoors and outdoors in wet locations.

Standards:

- ASTM B3, B787
- UL Spec. No. 1569
- Sunlight Resistant
- Direct Burial
- Rated for CT use
- RoHS compliant
- The National Electrical Code®/NFPA 70

Specifications:

| Size (AWG) | # of Cond. | # of Strands | Insulation Thickness (PVC/Nylon) (mils) | Jacket Thickness Over Armor (mil) | Nom. Cable OD (mils) | Nom. Weight (lb/Mft) | Conductor Colors |
|------------|------------|--------------|---|-----------------------------------|----------------------|----------------------|--|
| 14 | 3 | 7 | 15/4 | 40 | 525 | 127 | Black, Red, White |
| 14 | 4 | 7 | 15/4 | 40 | 553 | 148 | Black, Red, Blue, Orange |
| 14 | 7 | 7 | 15/4 | 50 | 636 | 220 | Black, Red, Blue, Orange, Yellow, Brown, Red-Black |

JMF Offers More Line Set Product Options Than Anyone In The Industry.

To View Our Full Product Offering Visit

www.jmfcompany.com