

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATIONS AND OF THE COMPANY UNDERTAKING

Product Name Nashua 324A CW
Product Description Pressure Sensitive Adhesive
Manufacturer/Supplier Berry Plastics Corporation, Tapes and Coatings Division
Address 25 Forge Parkway
 Franklin, MA 02038
Phone Number (800) 248-7659 (Monday – Friday 8:00 am to 5:00 pm)
Chemtrec Number (800) 424-9300
Revision Date: March 23, 2012
MSDS Date: July 10, 2007

Safety Data Sheet according to EC directive 2001/59/EC and OSHA's Hazcom Standard (29 CFR 1910.1200)

2. HAZARDS IDENTIFICATION

EU Main Hazards
 Not classified as hazardous.

Routes of Entry

Inhalation - Skin contact

Carcinogenic Status

Not considered carcinogenic by NTP, IARC, and OSHA.

Target Organs

Skin – Respiratory System – Central Nervous System – Reproductive System

Health Effects - Eyes

Contact may cause irritation due to mechanical abrasion. High concentrations of vapor may cause irritation.

Health Effects - Skin

Prolonged, repeated contact with adhesive may cause irritation and/or allergic sensitization. Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis. Material can be absorbed through the skin and repeated, prolonged contact may cause adverse reproductive effects.

Health Effects - Ingestion

Not an expected route of entry during normal handling and use.

Health Effects - Inhalation

Exposure to vapor may have the following effects:

- irritation of nose, throat and respiratory tract - central nervous system depression - dizziness - drowsiness - headache - mental confusion

Repeated or prolonged exposure to vapor at high concentrations may have the following effects:

- adverse effects to nervous system - lung damage - adverse reproductive effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS#/Codes	Concentration	R Phrases	Classification
Polymers	N.A.	<25%	None	None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS#/Codes	Concentration	R Phrases	Classification
Toluene	108-88-3 203-625-9	0.1 - <1%	R11, R38, R48/20, R63, R65, R67	F, Xn, Repro Cat. 3
Ethyl Acetate	141-78-6 205-500-4	<2.0%	R11,R36,R66,R67	F, Xi

4. FIRST AID MEASURES

Eyes

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Skin

Wash skin thoroughly with soap and water. Obtain medical attention if blistering occurs or redness persists.

Ingestion

Obtain medical attention immediately.

Inhalation

Remove person to fresh air. Seek medical attention if symptoms persist.

Advice to Physicians

Treat symptomatically.

5. FIRE - FIGHTING MEASURES

Extinguishing Media

Water spray, carbon dioxide and dry chemical.

Unusual Fire and Explosion Hazards

May release hazardous vapors during a fire.

Protective Equipment for Fire-Fighting

Wear full protective clothing and self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

No specific measures necessary. Prevent the material from entering drains or watercourses.

7. HANDLING AND STORAGE

Keep away from heat and sources of ignition. Storage area should be: - cool - dry - well ventilated - away from incompatible materials

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards

Exposure limits are listed below, if they exist.

Polymer

None established

Ethyl Acetate

ACGIH: TLV 400 ppm (1440mg/m³) 8h TWA.

OSHA: PEL 400ppm (1400mg/m³) 8h TWA

Toluene

ACGIH: TLV 20 ppm (75mg/m³) 8hTWA.

OSHA:PEL 200 ppm 8h TWA , Ceiling (C) 300 ppm, 500ppm 10-min peak per 8-hr shift

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Control Measures

No specific measures necessary. Good general room ventilation is expected to be adequate to control airborne levels.

Respiratory Protection

Respiratory protection not normally required.

Hand Protection

Not required under normal conditions of use. However, care should be taken to avoid contact with the adhesive.

Eye Protection

Safety glasses

Body Protection

Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Pressure sensitive adhesive coated onto a foil backing with silicone coated paper release liner
Color	Clear adhesive with silver foil backing and white liner
Odor	Slight solvent
pH	Not applicable
Specific Gravity	No data available
Boiling Range/Point (°C/F)	Not applicable
Melting Point (°C/F)	Not applicable
Flash Point (PMCC) (°C/F)	Not known
Explosion Limits (%)	No data available
Vapor Pressure	Not applicable
Density	No data.
VOC (g/l)	<30 g/l
VOC (% by weight)	<2%
Solubility in Water	Not known
Vapor Density (Air = 1)	Not applicable

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Conditions to Avoid

Heat - High temperatures

Materials to Avoid

Strong oxidizing agents - acids - bases

Hazardous Polymerization

Will not occur.

Hazardous Decomposition Products

Oxides of carbon – unknown hydrocarbons

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Toluene: Oral LD50 rat >2,000 mg/kg
Dermal LD50 rabbit >3,000 mg/kg
Inhalation LC50(rat) 28.1 mg/l 4hr

Ethyl Acetate: Oral LD50 (rat) 5,620 mg/kg

Specific Target Organ Systemic Toxicity (single and repeat)

Ethyl acetate: Can cause narcotic effects and respiratory irritation.

Serious Eye damage/Eye Irritation

No relevant studies identified.

Skin Corrosion/Irritation

No relevant studies identified.

Respiratory or Skin Sensitization

No relevant studies identified.

Carcinogenicity

Toluene: No evidence of carcinogenic activity in laboratory animal studies.

Germ Cell Mutagenicity

Toluene: Negative Ames Test with and without metabolic activation.

Toxicity to Reproduction

Toluene: In laboratory studies, birth defects, increased fetal lethality and delayed fetal development have been observed in offspring of female animals exposed during pregnancy. Toluene has been demonstrated to be embryofetotoxic and teratogenic in laboratory animals.

12. ECOLOGICAL INFORMATION

Mobility

No relevant studies identified.

Persistence/Degradability

No relevant studies identified.

Bio-accumulation

No relevant studies identified.

Ecotoxicity

The product may be harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

DOT CFR 172.101 Data	Not Regulated
UN Proper Shipping Name	Not Regulated
UN Class	None.
UN Number	None.
UN Packaging Group	None.
Classification for AIR Transportation (IATA)	Consult current IATA Regulations prior to shipping by air.

15. REGULATORY INFORMATION

EU Label Information

Classification and labelling have been performed according to EU directives 67/548/EEC and 99/45/EC including amendments(2001/60/EC and 2006/8/EC)

EC Annex I Classification

According to EC Commission Directive 67/548/EEC this product is not classified.

R phrases

None.

S phrases

None.

US REGULATIONS (Federal, State) and INTERNATIONAL CHEMICAL REGISTRATION LAWS

TSCA Listing

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Inventory.

EINECS Listing

All ingredients in this product have not been verified for listing on the European Inventory of Existing Commercial Chemical Substances (EINECS).

DSL (Canadian) Listing

All ingredients in this product have not been verified for listing on the Domestic Substance List (DSL).

California Proposition 65

This product contains materials which the State of California has found to cause cancer, birth defects or other reproductive harm.

SARA Title III Sect. 311/312 Categorization

Immediate (acute) Delayed (Chronic)

SARA Title III Sect. 313

This product contains the following chemicals that are listed in Section 313 at or above de minimis concentrations: None

16. OTHER INFORMATION

NFPA Ratings

NFPA Code for Flammability - 0

NFPA Code for Health - 1

NFPA Code for Reactivity - 0

NFPA Code for Special Hazards – 0

HMIS Ratings

HMIS Code for Flammability - 0

HMIS Code for Health - 1

HMIS Code for Reactivity - 0

HMIS Code for Personal Protection - See Section 8

Abbreviations

N/A: Denotes no applicable information found or available

CAS#: Chemical Abstracts Service Number

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit

NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

F: Highly Flammable

Xi: Irritant

16. OTHER INFORMATION

Abbreviations

Xn: Harmful

R: Risk

R11: Highly Flammable.

R36: Irritating to eyes.

R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

S: Safety

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

BOD: Biological Oxygen Demand

KoC: Soil Organic Carbon Partition Coefficient

For further information email: msdstechnical@berryplastics.com

Prepared By: EnviroNet LLC.

The information and recommendations presented in this MSDS are based on sources believed to be accurate. Berry Plastics Corporation, Tapes and Coatings Division assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the **material** for their particular purposes. In particular, we make NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use **or disposal** of the material is in accordance with applicable Federal, State, and local laws and regulations.
