



SCAN WITH SMARTPHONE

FOR INDUSTRY PROFESSIONALS

# 5.5 CFM 2 STAGE - FOR DEEP VACUUM VACUUM PUMP

  
**TAKES OUT  
MOISTURE**

**1/4" AND 3/8" MALE  
FLARE INTAKE  
FITTINGS WITH  
TETHERED CAPS**

**CENTER BALANCED  
HANDLE WITH  
NON-SLIP GRIP**

**LOW  
PROFILE  
ON/OFF  
ROCKER  
SWITCH**

**OIL FILL PORT  
AND EXHAUST  
DOME**



**110V/220V  
POWER  
SELECTOR  
SWITCH**


**LARGE  
SIGHT GLASS  
FOR EASY OIL  
MONITORING**



**6 FT. REMOVABLE  
POWER CORD**




**EASY ACCESS  
OIL DRAIN**



**HEAT  
DISPERSING  
FINS**



**WIDE, STABLE  
BASE**



**HEAT DISPERSING  
MOTOR FINS**



**FAN COOLED  
MOTOR**



## FOR INDUSTRY PROFESSIONALS

Trade Pro's high performance TP-5VP2 Vacuum Pump brings the latest in vacuum pump technology. The 5.5 CFM two stage vacuum pump is built for deep vacuum and long term reliable service on Appliances, Residential A/C and Commercial Refrigeration Systems.

# 5.5 CFM

2 STAGE - FOR DEEP VACUUM

## VACUUM PUMP



**TAKES OUT MOISTURE**

- 2-STAGE
- LIGHTWEIGHT
- POWERFUL
- COOLER RUNNING
- DEEP VACUUM

TradePro by



FOR U.S. JOBS

UNIWELD EMPLOYS OVER 300 WORKERS



**UNIWELD VACUUM PUMP OIL**

Part# 42005  
(1) Quart (946 ml)  
12 per case

Part# 42006  
(1) Gallon (3.78 L)  
6 per case

## PART# TP-5VP2 Vacuum Pump Specifications

Free Air Displacement .....	5.5 cfm, 155 liter/min.
Number of Stages .....	2- Stage Rotary Vane
Factory Micron Rating .....	15 Microns
Intake Fittings (with check valve).....	1/4" and 3/8" M.F.
Thermal Overload Protection.....	1/2 H.P.
Voltage .....	110V/220V-50/60 Hz
Power Cord .....	72" (1.83 m)
Oil Capacity .....	11.1 oz. (350 ml)
Dimensions .....	12.5" x 4" x 9.5" 32.5 cm x 10 cm x 24 cm
Weight.....	20.0 lbs. (9.1 kg)
Shipping Weight.....	22.2 lbs. (10.8 kg)