


# WHITE PAPER

CORROSION OF ALL-ALUMINUM HEAT EXCHANGERS  
USED IN OUTDOOR HVAC APPLICATIONS

## Eco-Last™

DEPENDABLE BY DESIGN.  
PERFORMANCE THAT LASTS.



**ALLIED**™  
Commercial

# WHITE PAPER

## CONTENTS

Summary	P. 2
Overview of Aluminum Corrosion	P. 3
Corrosion Mechanisms of Concern	P. 4
The Outdoor Environment	P. 4
Accelerated Testing	P. 5
Results	P. 7
Conclusion	P. 8
About Allied Commercial	P. 8

---

## SUMMARY

Allied Commercial's Eco-Last™ Coil, an all-aluminum condensing coil, significantly reduces refrigerant charge requirements in select Allied Commercial rooftop units, with proven technology that helps to maximize performance and reliability. By using up to 52% less refrigerant than traditional tube-and-fin condenser coils, the Eco-Last Coil offers users valuable savings. The all-aluminum construction also results in a lighter unit weight, shaving approximately 90 pounds from a 10-ton rooftop unit. Fewer brazed joints—up to 20% fewer compared to traditional coils—decrease the potential of leakage for increased system reliability. Finally, a mounting configuration that uses rubber inserts provides vibration dampening to prevent damage during shipping, as well as isolation to protect against corrosion.

This white paper will detail the effects of corrosion on the Eco-Last Coil as compared to standard industry all-aluminum coils, with specific regard to contributing factors, mechanisms and the outdoor environment.

**Eco-Last™**

DEPENDABLE BY DESIGN.  
PERFORMANCE THAT LASTS.

## OVERVIEW OF ALUMINUM CORROSION

When we process ores from the earth, we add energy to produce metals. Corrosion is simply nature's process of returning a metal to its original, more stable, lower-energy state. We intervene in nature's process by understanding and controlling corrosion drivers.

Corrosion rates are a function of:

### **Time of wetness**

Wetness includes everything from invisible thin films to wet spray. On some surfaces, the presence of high humidity is sufficient for the formation of thin films. At marine sites, winds can carry ocean spray far inland and keep surfaces continually wet. Condensation, another source of wetness, occurs whenever a surface is below the dew point of the surrounding air, and is known to occur even in desert climates. Home lawn sprinkler systems also supply occasional wetness.

### **Presence of ionic contaminants**

Wetness must be accompanied by the presence of some ionic species. Ocean spray is an example of a naturally occurring source of chlorides. Combustion processes are a continuing source of sulfur compounds.

### **pH**

The oxide surface layer that typically naturally protects aluminum is dissolved when the wet surface is sufficiently acidic or basic (i.e., low or high pH). There can be localized shifts in pH as the ionic solution becomes more concentrated while drying out.

### **Temperature**

The rate of chemical reaction (i.e., corrosion) increases with an increase in temperature levels. Temperature cycling often repeatedly evaporates moisture and concentrates contaminants, especially where there is a continual source of wetness.

# WHITE PAPER

## CORROSION MECHANISMS OF CONCERN

General, or uniform, corrosion results in a long-term material loss of the component.


General corrosion is considered a “wear-out” mechanism, which is not likely to significantly affect the unit function during its normal life.

Pitting, or extremely localized corrosion, results in a hole through the wall of the heat exchanger tube, allowing the refrigerant to leak. This failure mode results in a total loss of cooling function.

## THE OUTDOOR ENVIRONMENT

One of the most aggressive outdoor environments for aluminum is the seacoast, as illustrated by Figure 1 which compares wet chloride ion concentrations throughout the United States. Note that time of wetness, temperature and frequency of temperature cycles (from cooling unit cycling) are likely to be relatively higher in many coastal applications.

**Figure 1:** Chloride Ion Concentrations Across the United States



### Sites not pictured:

Alaska 01	0.2 kg/ha
Alaska 03	0.1 kg/ha
Alaska 06	0.1 kg/ha
Puerto Rico 20	87.2 kg/ha
Virgin Islands 01	38.7 kg/ha

### Notes:

- kg/ha (kilogram per hectare) is a surface density measurement unit
- 1 kilogram per hectare = 0.1 gram per meter<sup>2</sup>
- 1 hectare = 10 000 m<sup>2</sup> = 2.47 acre
- 1 kg = 2.2 lb

National Atmospheric Deposition Program/National Trends Network <http://nadp.isws.illinois.edu>

# CORROSION OF ALL-ALUMINUM HEAT EXCHANGERS USED IN OUTDOOR HVAC APPLICATIONS

## ACCELERATED TESTING

Allied Commercial uses a proprietary test protocol that includes:

- Three ASTM\* corrosive solutions
- Testing at high temperature similar to condensing temperatures
- Wet/dry conditions and temperature cycling to concentrate the corrosive solutions
- Stresses that are slightly biased for the pitting failure mode, but also include general corrosion
- Multiple samples tested to leak failure
- Comparison to known customer-accepted all-aluminum product
- Checking for leaks every weekday during testing

*Figure 2: Samples in Test Chamber*



The test protocol is used at the Allied Commercial research and development facility for aluminum product development. In addition, Allied Commercial has been field-testing an all-aluminum product that met the minimum acceptance criteria. Now running nearly fourteen years, the field test has yielded no reports of corrosion leaks from the Allied Commercial all-aluminum coils.

The same protocol was used at an independent test lab to evaluate Allied Commercial's Eco-Last™ Coil. The test included multiple samples of both uncoated and E-coated versions of Allied Commercial's Eco-Last Coils, along with samples of a standard industry all-aluminum coil technology. Figure 2 illustrates the samples in one of two test chambers prior to testing.


*\*The American Society for Testing and Materials*

# WHITE PAPER

## ACCELERATED TESTING

Figures 3, 4 and 5 show the three types of samples before the testing.

**Figure 3:** Standard Industry Sample Before Testing



**Figure 4:** Uncoated Sample Before Testing




**Figure 5:** E-Coated Sample Before Testing



Figures 6, 7 and 8 indicate the condition of the three types of samples after testing.

**Figure 6:** Standard Industry Sample After Testing



**Figure 7:** Uncoated Sample After Testing




**Figure 8:** E-Coated Sample After Testing



## RESULTS

Corrosion test results on leak robustness for the three types of coils are illustrated in Figure 9.

*Figure 9: Corrosion Test Results on Leak Robustness*



As shown in Figure 9, all samples exceeded the test requirements. The standard all-aluminum coil exceeded the test criteria by 28%. The uncoated Eco-Last™ Coil performed 37% above the test requirement and 7% better than the industry standard coil. In contrast, the E-Coated Eco-Last Coil outperformed the industry standard coil by 131% and the test requirement by 197%.

## CONCLUSION

Based on test data from an independent corrosion test lab, Allied Commercial's Eco-Last™ Coil exceeds the test requirements. The data also indicates that the standard Eco-Last Coil is at least equivalent to, and potentially better than, an all-aluminum product that has been generally accepted in coastal applications. In addition, the data shows that the E-Coated Eco-Last Coil shows superior performance to all other options tested.

Previous field testing of Allied Commercial's all-aluminum coil, **started nearly 14 years ago**, has indicated no reports of corrosive leak problems over time. This accelerated test demonstrates that the uncoated Eco-Last Coil has at least 91.8% of the same life as these field-test units.

## ABOUT ALLIED COMMERCIAL

Allied Commercial is a leading provider of high-efficiency packaged rooftop units, split systems, HVAC controls, furnaces and indoor air quality products for the light commercial industry. Committed to helping our customers through advanced products and unsurpassed customer service, Allied Commercial delivers effective HVAC solutions that improve comfort and protect profits.

Visit us online at [www.allied-commercial.com](http://www.allied-commercial.com).



Visit us at [www.allied-commercial.com](http://www.allied-commercial.com) or contact us at 1-800-448-5872.

© 2013 Allied Air Enterprises LLC, a Lennox International Inc. Company



Litho U.S.A.

ACELW-300 01/13 PC73149