## HEAT PUMPS

# **7HP19V**

Variable Capacity | Omniguard® Coil | R-454B | 60HZ

## RESIDENTIAL PRODUCT SPECIFICATIONS

2 to 5 Tons





## MODEL NUMBER IDENTIFICATION



## FEATURE HIGHLIGHTS

- 1. Outdoor Coil Fan
- 2. Omniguard® Coil
- 3. High Capacity Suction Line Drier
- 4. Pressure Transducer
- 5. Four-Way Reversing Valve
- 6. Variable Capacity Rotary Compressor
- 7. DC Inverter Control
- 8. Control Board
- 9. Heavy Gauge Steel Cabinet
- 10. Louvered Coil Protection
- 11. Refrigerant Line Connections and Access



## CONTENTS

Model Number Identification
Approvals And Warranty
Features
Specifications
Optional Accessories - Order Separately
Expanded Sound Data
Field Wiring
Installation Clearances
Dimensions - Unit
TXV Substitution
TXV Ranges

## APPROVALS AND WARRANTY

### APPROVALS

- AHRI Standard 210-240-2023 certified
- · AHRI Certified system match-ups and expanded ratings, visit www.alliedratings.com
- NOTE AHRI certified ratings are based on the following control conditions:
- ENERGY STAR<sup>®</sup> Certified
- · Sound rated to AHRI Standard 270-2008 test conditions
- · Rated According to U.S. Department of Energy (DOE) test procedures
- · Unit and components ETL, NEC and CEC bonded for grounding to meet safety standards for servicing
- ETL certified (U.S. and Canada)
- ISO 9001 Registered Manufacturing Quality System

### WARRANTY

- 10-year limited warranty on all parts, extended warranty available.
- Warranty provides for a total of 10-years of limited warranty.
- · Coverage (Standard 5-year limited parts warranty plus an additional 5-year limited extended parts warranty).
- · Warranty must be registered online within 60 days of installation to qualify for 10-year coverage.
- Unregistered equipment defaults to 5-year coverage.
- See full warranty at www.alliedair.com for terms, conditions, and exclusions.

## FEATURES

### **APPLICATIONS**

- 2 through 5 tons
- Sound levels as low as 61 dBA
- Heating operation down to -15°F
- · Single-phase power supply
- Applicable to indoor air handlers or gas furnaces with indoor add-on coils
- Shipped completely factory assembled, piped and wired
- **NOTE** When heat pumps are used with gas furnaces, a dual-fuel compatible thermostat or zone control system with dual-fuel capabilities must be used (order separately).
- **NOTE** Installer must set outdoor unit, connect refrigerant lines and make electrical connections to complete job.

### **REFRIGERATION SYSTEM**

### **R-454B Refrigerant**

- Low GWP (Global Warming Potential)
- Zero ODP (Ozone Depletion Potential)
- Low Toxicity/Lower Flammability A2L
- · Unit is factory pre-charged
- **NOTE** Total system refrigerant charge is dependent on outdoor unit size, indoor unit size and refrigerant line length.
- **NOTE** Refer to the unit-mounted charging sticker to determine correct amount of charge required.

## Outdoor Coil Fan

- Direct drive fanECM motor
- Vertical air discharge
- Totally enclosed fan motor
- Ball bearings
- · Inherently protected
- PVC (polyvinyl chloride) coated steel fan guard

### 2 Omniguard<sup>®</sup> Coil

- · Enhanced aluminum alloy tube/enhanced fin coil
- · Superior corrosion resistance
- · Ripple-edged aluminum fins
- Aluminum tube construction
- Lanced fins for maximum fin surface exposure
- · Fin collars grip tubing for maximum contact area
- · Flared shoulder tubing connections
- · Factory tested under high pressure
- · Entire coil is accessible for cleaning

### **Expansion Valve - Outdoor Unit**

- Designed and sized specifically for use in heat pump system
- Sensing bulb is located on the line between reversing valve and the coil
- · Senses suction temperature during the heating cycle
- · Factory installed and piped

## FEATURES

### **REFRIGERATION SYSTEM (continued)**

#### **Discharge Temperature Switch**

- Shuts off unit if operating conditions cause the compressor discharge line temperature to rise above setpoint
- Protects compressor from excessive pressure / temperature
- · Automatic reset when temperature drops below setpoint

### 3 High Capacity Suction Line Drier

- Factory installed in the suction line
- Drier traps moisture or dirt that could contaminate the system
- 100% molecular-sieve, bead type drier

### High Pressure Transducer

- · Protects the system from high pressure conditions
- Automatic reset

### Low Pressure Transducer

- Shuts off unit if suction pressure falls below setting
- · Provides loss of charge and freeze-up protection
- Auto-reset

### 5 Four-Way Reversing Valve

- Rapid changeover of refrigerant flow direction from cooling to heating and vice versa
- Operates on pressure differential between outdoor unit and indoor coil
- · Factory installed

### **Optional Accessories**

### **Check/Expansion Valve Kits**

- · Field installed on indoor units (if required)
- See TXV Usage table
- Chatleff-style fitting

### Freezestat

- · Senses suction line temperature
- Cycles compressor off when suction line temperature falls below freezestat setpoint
- Opens at 29°F and closes at 58°F
- Installs on or near the discharge line of the evaporator or on the suction line
- NOTE The 7HP19V is a variable capacity heat pump utilizing variable speed compressor technology. With the variable speed compressor and variable pumping capacity, additional consideration must be given to refrigerant piping sizing and application. Please refer to the Installation Instructions or Service Literature for Line Set Requirements and

## **INDOOR REFRIGERANT DETECTION SYSTEM (RDS)**

- · Complies with UL 60335-2-40 approved standard
- · Required for all systems using R-454B refrigerant
- · Factory or field installed on all indoor units

Refrigerant Piping Guidelines.

- Consists of a RDS refrigerant detection sensor and a mitigation control in the indoor unit
- Ensures safe operation for systems equipped with R-454B refrigerant
- · Indoor sensor will detect any R-454B refrigerant
- If R-454B refrigerant is detected, the refrigerant detection system will stop compressor operation and operate the blower to reduce concentrations in the conditioned space
- Once safe levels are reached the HVAC system will resume normal operation
- Refer to indoor unit Product Specifications documents for additional details

## FEATURES

### Variable Capacity Rotary Compressor

- Rotary compressor
- High volumetric efficiency
- · Uniform suction flow
- · Constant discharge flow
- · Quiet operation
- Low gas pulses during compression reduces operational sound levels
- Compressor motor is internally protected from excessive current and temperature
- Compressor is installed in the unit on resilient rubber mounts for vibration free operation

### **Rotary Compressor Operation**

- · Rotary compressor has a cylindrical chamber
- A roller is mounted to the motor shaft and is offset to rotate in the center of the chamber
- Two spring-loaded vanes sweep the sides of the chamber as the roller rotates
- Roller touches the chamber at a point between the intake and the discharge ports as the roller rotates
- While rotating, the roller draws vapor into the chamber through the intake port
- Vapor is trapped in the space between the chamber wall, the vane, and the point of contact between the roller and the chamber
- As the next vane passes the contact point vapor is compressed
- The space becomes smaller compressing the vapor as the roller rotates
- · Vapor is discharged through the discharge port

### **Compressor Crankcase Heater**

- Protects against refrigerant migration that can occur during low ambient operation
- · Factory Installed

### **Compressor Sound Dampening System**

- Polyethylene compressor
- · 2 inch thick batt fiberglass insulation
- All open edges sealed with one-inch wide hook and loop fastening tape

### **Optional Accessories**

### Compressor Low Ambient Cut-Off Switch

 Non-adjustable switch (low ambient cut-out) prevents compressor operation when outdoor temperature is below 35°F

## CONTROLS

### DC Inverter Control

- Converts AC line voltage into filtered variable DC voltage
- Provides continuous compressor operation, while adjusting the capacity according to indoor temperature
- Adjusts compressor output in increments as small as 1%
- The accurate sensing of the cooling or heating load prevents frequent changes in capacity and ensures efficient, economical operation



- Power Factor Correction (PFC) circuit monitors the DC bus for high, low and abnormal voltage conditions to protect the compressor
- Two LEDS (red and green) indicate inverter operating status and aid in troubleshooting
- Noise filter reduces unwanted electromagnetic interference (EMI)
- The inverter reactor (mounted separately) adds inductance to the line between the inverter and the compressor to limit current rise and protect the compressor

### **CONTROLS** (continued)

### Control Board

- Connections for connecting a conventional heating/cooling thermostat are provided on the control
- Control features:
  - Seven-Segment Display - Shows information about outdoor unit type and



capacity and also displays alerts for common fault conditions (electrical and mechanical)

- Low Voltage Protection Prevents compressor operation when voltage is not within the specified range
- High and low pressure switch monitoring with provisions for lockout
- · Five-Strike lockout protection protects compressor
- · Liquid line temperature and sensor monitoring
- · EEPROM storage of all local configurations
- Non-volatile memory storage of 100 alarm codes with display of last 10 codes for troubleshooting
- · Built-in low-ambient control
- **NOTE** Two RAST connectors for a conventional heating/cooling thermostat are also provided for connecting to the control. A two-stage or singlestage thermostat can be used.

## FEATURES

## Low Ambient Operation

- Cooling Mode The heat pump can operate down to 0°F outdoor air temperature in the cooling mode
- **NOTE** A freezestat is recommended for extra protection during low ambient cooling operation.

## Heating Mode (Low Temperature Protection)

- Outdoor unit will not operate in the heating mode when the outdoor temperature is at or below  $4^\circ\text{F}$
- If the unit is operating and the outdoor temperature drops below  $-4^{\circ}$ F, the unit will continue to operate until the room thermostat is satisfied or the outdoor temperature drops to  $-15^{\circ}$ F

#### Operating Modes: Cooling Mode

- Three climate settings are available:
  - **Comfort** The system supplies higher indoor airflow at all compressor capacities, increasing efficiency by operating at a higher sensible to total ratio
  - **Normal** The system supplies indoor airflow that balances efficiency and comfort
  - Efficiency The system supplies lower indoor airflow at all compressor capacities, improving humidity removal by operating at a lower sensible to total ratio

### **Heating Mode**

- Two climate settings are available:
  - · Normal Heats the home with the highest efficiency
  - Comfort System reduces indoor airflow, increasing supply air temperature
- · All modes are selected on the control board

### **Defrost Mode**

- Enables a demand defrost cycle whenever system heating performance falls below optimum levels
- Clean-sweep defrost provides a more thorough defrost, reducing the number of cycles during heating operation

### **Optional Accessories**

## Indoor Blower Off Delay Relay

Delays the indoor blower-off time during the cooling cycle

## 

- Heavy-gauge steel construction
  - · Pre-painted cabinet finish
  - Louvered heavy gauge steel panels surround unit on all four sides
  - Control box is conveniently located with all controls factory wired
  - Corner patch plate allows access to compressor components
  - Drainage holes are provided in base section for moisture removal

### **Zinc-Coated Steel Unit Base**

Durable zinc-coated base section resists rust and corrosion

### **(1)** Louvered Coil Protection

- Steel louvered panels provides complete coil protection
- Panels may be completely removed

#### Refrigerant Line Connections, Electrical Inlets and Service Valves

- · Sweat connection vapor and liquid lines
- · Located on corner of unit cabinet
- Vapor valve can be fully shut off, while liquid valve may be front seated to manage refrigerant charge while servicing system
- Refrigerant line connections and field wiring inlets are located in one central area of the cabinet
- · See dimension drawing

### **Braze-Free/Press Fitting Flexibility**

Units can accommodate braze-free or press fittings for installation versatility



SPECIFICATIONS							
Size			03	36	060		
Nominal Tonnage			2 Ton Mode	3 Ton Mode	4 Ton Mode	5 Ton Mode	
Sound Rating Number Ran	ge	dBA	62-70	61-72	67-76	66-78	
Connections	Liquid line	(OD) - in.	3/8	3/8	3/8	3/8	
(Sweat)	Vapor line	(OD) - in.	3/4	7/8	7/8	1-1/4	
Compressor Type			Variable Rotary				
Refrigerant	<sup>1</sup> R-454B charge	furnished	7 lbs 1	15 ozs	8 lbs 13 ozs		
Indoor Unit Expansion Valv	e (TXV)		26Z70	26Z70	26Z71	26Z72	
Outdoor	Net face area - ft. <sup>2</sup>	Outer coil	16.	.33	23.36		
Coil		Inner coil	15.	.68	22.76		
	Tube dia	meter - in.	5/*	16	5/16		
		Rows	2	2	2		
		Fins - in.	2	2	22		
Outdoor	Outdoor HP				1/3		
Fan	Dia	meter - in.	2	2	22		
	4	1		4			
		Cfm	26	42	3907		
		Rpm	68	31	941		
		Watts	28	34	425		
Shipping Data - Ibs.			21	15	272		
ELECTRICAL DATA							
Li	ne voltage data (Volts-F	Phase-Hz)		208/23	0-1-60		
<sup>2</sup> Maximum over	current protection (MO	CP) amps	3	5	60		
3	Minimum circuit ampac	city (MCA)	2	3	39.2		
Compressor	16	5.3	28.5				
Fan Motor	Full I	oad amps	2.	.6	3.6		
OPTIONAL ACCES	SORIES - ORDE	ER SEP	ARATELY				
Freezestat	3/8 in.	93G35	•	•	•	•	
Indoor Blower Off Delay Re	lay	58M81	•	•	•	•	

NOTE - Extremes of operating range are plus 10% and minus 5% of line voltage.

<sup>1</sup> Refrigerant charge sufficient for 15 ft. length of refrigerant lines. For longer line set requirements see the Installation Instructions for information about line set length and additional refrigerant charge required.

<sup>2</sup> HACR type breaker or fuse.

<sup>3</sup> Refer to National or Canadian Electrical Code manual to determine wire, fuse and disconnect size requirements.

## **EXPANDED SOUND DATA**

<sup>1</sup> Size	Octave Band Sound Power Levels dBA, re 10 <sup>-12</sup> Watts Center Frequency - HZ						<sup>1</sup> Sound Rating	<sup>2</sup> Estimated Sound Pressure Level at Distance From Unit (dBA at distance in ft.)					
5126	125	250	500	1000	2000	4000	8000	Number (dBA)	3	5	10	15	50
024 Min.	68.1	61.0	60.2	56.2	50.9	46.2	54.5	62	54	50	44	41	28
024 Max.	71.8	68.8	69.3	62.4	58.0	57.5	55.7	70	62	58	52	49	36
036 Min.	68.4	62.2	56.8	53.1	51.7	48.9	54.1	61	53	49	43	40	27
036 Max.	74	68.8	70.2	65.6	60.9	62.8	59.3	72	64	60	54	51	38
048 Min.	68.8	65.9	68.0	58.8	58.0	52.0	52.8	67	59	55	49	46	33
048 Max.	72.4	74.2	74.9	70.5	68.3	66.3	58.5	76	68	64	58	55	42
060 Min.	69.1	63.8	66.1	56.5	54.6	52.0	52.4	66	58	54	48	45	32
060 Max.	82.3	74.3	75.8	73.0	69.8	68.0	58.7	78	70	66	60	57	44

NOTE - The octave sound power data does not include tonal correction.

<sup>1</sup> Tested according to AHRI Standard 270-2008 test conditions. Sound rating Number is the overall A-Weighted Sound Power Level (LwA), dBA (100 Hz to 10,000 Hz). <sup>2</sup> Estimated sound pressure level at distance based on AHRI Standard 275-2010 method for equipment located on the ground, roof, or on side of building wall with no adjacent reflective surface within 9.8 feet. Sound pressure levels will increase based on changes to assumptions. For other applications, refer to AHRI Standard 275.

## FIELD WIRING



#### A- Two Wire Power

B-Two or Three Wire Power (size to heater capacity)

#### **C** - Conventional Thermostat:

- Eight Wire Low Voltage, 18AWG
- Ten Wire Low Voltage, 18AWG with Optional Outdoor Thermostat

#### **D** - Conventional Thermostat:

- Twelve Wire Low Voltage, 18AWG
- Fourteen Wire Low Voltage, 18AWG with Optional Outdoor Thermostat
- NOTE All wiring must conform to NEC or CEC and local electrical codes.

NOTE - Field wiring is not furnished.

## INSTALLATION CLEARANCES

### NOTES:

- Service Clearance 30 in. (762 mm) on one of the sides adjacent to the Control Box.
- One of other three sides must be 36 in. (914 mm).
- One of the two remaining sides may be 12 in. (305 mm).
- The remaining side may be 6 in. (152 mm).
- 48 in. (1219 mm) clearance required on top of unit
- 24 in. (610 mm) required between two units





Model No	D	Shipping Weight (lbs.)		
	A - (Width)	B - (Depth)	C - (Height)	3 ( )
7HP19V36P	29.38	31.25	33.75	215
7HP19V60P	29.38	31.25	43.75	272

## **TXV USAGE**

All coils and air handlers are shipped with a factory installed TXV. In most cases, no substitution is needed. If a different size TXV is required, it will be listed in the "TXV SUBSTITUTION" table by size. The correct TXV must be ordered separately and field installed.

Size	Order Number
024	26Z70
036	26Z70
048	26Z71
060	26Z72

## AHRI STANDARD 210-240-2023

Cooling or heating capacities are net values, including the effects of blower motor heat, and do not include supplementary heat. Power input is the total power input to the compressor(s) and fan(s), plus any controls and other items required as part of the system for normal operation.

Units which do not have an indoor air-circulating blower furnished as part of the model, i.e., split system with indoor coil only, is established by subtracting from the total cooling capacity 1250 Btu/h per 1,000 cfm, and by adding the same amount to the heating capacity.

Total power input for both heating and cooling is increased by 365 W per 1,000 cfm of indoor air circulated.

## **TXV SUBSTITUTION - R-454B**

A general guide for replacing the factory installed R-454B TXV if the indoor unit (coil/air handler) is larger or smaller than the outdoor unit.

Outdo	or Unit	Indoor Unit		Indoor	Indoor
Size	Tons	Size	Tons	TXV	TXV Replacement
				i uninsneu	Replacement
024	2	42	3.5	26Z71	26Z70
024	2	48	4	26Z71	26Z70
024	2	49	4	26Z71	26Z70
024	2	50/60	4/5	26Z71	26Z70
024	2	51/61	4/5	26Z71	26Z70
024	2	60	5	26Z72	26Z70
036	3	42	3.5	26Z71	26Z70
036	3	48	4	26Z71	26Z70
036	3	49	4	26Z71	26Z70
036	3	50/60	4/5	26Z71	26Z70
036	3	51/61	4/5	26Z71	26Z70
036	3	60	5	26Z72	26Z70
048	4	30/36	2.5/3	26Z70	26Z71
048	4	36	3	26Z70	26Z71
048	4	60	5	26Z72	26Z71
060	5	50/60	4/5	26Z71	26Z72
060	5	51/61	4/5	26Z71	26Z72

#### **TXV Ranges:**

<sup>26</sup>Z70 - 1.5 to 3 ton systems - Use on 3 ton (036) and lower systems.

**<sup>26</sup>Z71** - 3.5-4 ton systems - Use on 4 ton (048) and down to 3.5 ton (042) systems.

<sup>26</sup>Z72 - 5 ton systems - Use on 5 ton (060) systems only.









Visit us at <u>www.alliedair.com</u> Contact us at 1-800-448-5872

NOTE - Due to our ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2025 Allied Air Enterprises.