



Cat[®] General Purpose Buckets

950–988 WHEEL LOADERS

Fusion™

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m ³	(yd ³)	kg	(lb)
950H 962H	2,894	(114)	3.10	(4.00)	1,534	(3,382)
	2,894	(114)	3.40	(4.50)	1,610	(3,549)
	2,894	(114)	3.10	(4.00)	1,330	(2,932)
	2,894	(114)	3.40	(4.50)	1,416	(3,122)
	2,894	(114)	3.80	(5.00)	1,498	(3,302)
950K 962K	2,894	(114)	2.70	(3.50)	1,367	(3,014)
	2,894	(114)	2.90	(3.75)	1,430	(3,153)
	2,894	(114)	3.10	(4.00)	1,484	(3,272)
	2,894	(114)	3.20	(4.25)	1,530	(3,373)
	2,894	(114)	3.40	(4.50)	1,554	(3,426)
	2,894	(114)	3.60	(4.75)	1,588	(3,501)
	2,894	(114)	3.80	(5.00)	1,633	(3,600)
IT62G / IT62H	2,894	(114)	3.10	(4.00)	1,359	(2,996)
	2,894	(114)	3.40	(4.50)	1,443	(3,181)
	2,894	(114)	3.80	(5.00)	1,527	(3,367)
966H / 966K	3,201	(126)	3.80	(5.00)	1,965	(4,332)
	3,201	(126)	4.20	(5.50)	2,028	(4,471)
	3,201	(126)	4.60	(6.00)	2,143	(4,721)
972H/ 972K	3,201	(126)	4.20	(5.50)	2,026	(4,467)
	3,201	(126)	4.40	(5.75)	2,068	(4,559)
	3,201	(126)	4.60	(6.00)	2,127	(4,689)
	3,201	(126)	4.80	(6.30)	2,122	(4,678)
	3,201	(126)	5.00	(6.50)	2,212	(4,877)
	3,201	(126)	5.00	(6.50)	2,233	(4,923)

General Purpose Buckets are available with pin-on interface or for use with the Fusion™ Coupler System. GET options available.

Contact your Cat[®] dealer for more information.

All buckets are Performance Series unless shaded.



Americas North



Cat General Purpose Buckets

Pin-on

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m ³	(yd ³)	kg	(lb)
950H	2,921	(115)	2.70	(3.50)	1,347	(2,970)
962H	2,921	(115)	2.90	(3.75)	1,401	(3,089)
	2,921	(115)	3.10	(4.00)	1,483	(3,269)
	2,921	(115)	3.30	(4.25)	1,518	(3,346)
	2,921	(115)	3.40	(4.50)	1,583	(3,490)
	2,921	(115)	3.60	(4.75)	1,381	(3,045)
950K	2,894	(114)	2.70	(3.50)	1,472	(3,245)
962K	2,894	(114)	2.90	(3.75)	1,557	(3,433)
	2,894	(114)	3.10	(4.00)	1,594	(3,514)
	2,894	(114)	3.20	(4.25)	1,663	(3,666)
	2,894	(114)	3.40	(4.50)	1,687	(3,719)
	2,894	(114)	3.60	(4.75)	1,724	(3,801)
	2,894	(114)	3.80	(5.00)	1,778	(3,920)
966H/ 966K	3,201	(126)	3.80	(5.00)	2,112	(4,656)
	3,201	(126)	4.00	(5.25)	2,164	(4,771)
	3,201	(126)	4.20	(5.50)	2,220	(4,894)
	3,201	(126)	4.60	(6.00)	2,260	(4,982)
972H / 972K	3,201	(126)	4.20	(5.50)	2,214	(4,881)
	3,201	(126)	4.40	(5.75)	2,219	(4,892)
	3,201	(126)	4.60	(6.00)	2,274	(5,013)
	3,201	(126)	4.80	(6.25)	2,202	(4,855)
	3,201	(126)	5.00	(6.50)	2,315	(5,104)
	3,201	(126)	5.00	(6.50)	2,383	(5,254)
980H / 980K	3,405	(134)	5.40	(7.00)	2,572	(5,670)
	3,405	(134)	5.70	(7.50)	2,677	(5,902)
	3,405	(134)	6.00	(7.85)	2,726	(6,010)
988H	3,900	(154)	6.90	(9.00)	4,407	(9,716)
	3,900	(154)	7.70	(10.00)	4,653	(10,258)
988K	3,855	(152)	6.90	(9.00)	4,539	(10,007)
	3,855	(152)	7.70	(10.00)	4,779	(10,536)
	3,855	(152)	8.40	(11.00)	4,994	(11,010)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

GEHQ0022 (02-14)

©2014 Caterpillar
All Rights Reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

