



Cat[®] Grapple Buckets

950–972 WHEEL LOADERS

Grapple Buckets are available for use with pin-on interface or for the Fusion™ Coupler System. GET options available.

Contact your Cat[®] dealer for more information.

Fusion™

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m ³	(yd ³)	kg	(lb)
950H / 950K 962H / 962K	3,059	(120)	4.60	(6.00)	2,824	(6,226)
IT62G / IT62H	2,904	(114)	3.30	(4.25)	2,115	(4,663)
966H / 966K 972H / 972K	3,048	(120)	3.80	(5.00)	4,380	(9,656)

Pin-on

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m ³	(yd ³)	kg	(lb)
950K 962K	3,059	(120)	4.60	(6.00)	2,925	(6,449)



Americas North



Cat Grapple Buckets

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

GEHQ0032 (02-14)

©2014 Caterpillar
All Rights Reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

