



# Cat<sup>®</sup> Multi-Purpose Buckets

950–972 WHEEL LOADERS

Multi-Purpose Buckets are available for pin-on interface or for use with the Fusion™ Coupler System.

Contact your Cat<sup>®</sup> dealer for more information.

## Fusion™

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m <sup>3</sup>	(yd <sup>3</sup> )	kg	(lb)
950H 962H	2,943	(116)	2.90	(3.75)	2,087	(4,601)
950K 962K	2,943	(116)	2.90	(3.75)	2,087	(4,601)
IT62G / IT62H	2,927	(115)	2.90	(3.75)	2,080	(4,586)
966H / 966K 972H / 972K	3,220	(127)	3.10	(4.00)	2,785	(6,140)

## Pin-on

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m <sup>3</sup>	(yd <sup>3</sup> )	kg	(lb)
950H 962H	2,929	(115)	2.90	(3.75)	2,014	(4,440)
950K 962K	2,943	(116)	2.90	(3.75)	2,099	(4,628)
IT62G / IT62H	2,938	(116)	2.90	(3.75)	2,009	(4,425)
966H / 966K 972H / 972K	3,226	(127)	3.10	(4.00)	2,721	(5,999)



Americas North



# Cat Multi-Purpose Buckets

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

GEHQ0026 (02-14)

©2014 Caterpillar  
All Rights Reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

