

Forestry Tips – Safe Practices— Hooktender I

SAFETY.CAT.COM™

Discussion Date:

Toolbox Talks are intended to facilitate health and safety discussions on the job site. For additional Toolbox Talks, please visit SAFETY.CAT.COM™.

TOPIC: Safe Practices—Hooktender I

Personal Protective Equipment

- High visibility hard hat and vest.
- Hearing protection.
- Caulk boots and protective gloves.
- Stagged pants.

Safety Responsibilities

The hooktender is responsible for the following:

- Making sure that safety practices are understood and reviewed with everyone in the crew he/she oversees.
- Correcting any unsafe work practices with the crew.
- Implementing a communications plan with the crew; Planning ahead and making sure each person knows his or her role.
- Setting a good example by creating safe work habits.

Notching Stumps

- Make sure tools are in proper condition. Only properly trained workers should use power saws.
- Make a clean work area around guyline stumps.
- Use only vee notch.
- Always wear proper personal protective equipment when using a power saw.

Rigging & Raising A Spar

- Plans must be communicated to crew prior to rigging up the spar.
- Each crew member should know his/her role in rigging.
- The machine must be level and have adequate blocking.
- Guylines must be properly wrapped and shackled around the stump.

Employee Participants:						

The material in this document is provided for informational

purposes only and not as a comprehensive or exhaustive resource on this topic. This material has been compiled from

a multitude of sources believed to be accurate; however, Caterpillar Inc. assumes no responsibility for the accuracy or

currency of this information and encourages you to consult experts in this area for more information. In no event does the content of this document supersede any applicable local, state, or federal statutes or regulations.

SAFETY.CAT.COM™ http://safety.cat.com/toolbox

