


Anmerkung / REMARKS	
b	SPACE REQUIRED FOR MEASURING TORSIONAL VIBRATIONS, AND/OR FOR REMOVAL OF THE VIBRATION DAMPER AND/OR LUBOIL PUMP
e	SPACE REQUIRED FOR REMOVAL OF PISTON AND CYLINDER LINER REDUCED REMOVAL HEIGHT PISTON AND LINER 2300mm
k	SPACE REQUIRED FOR TERMINAL SET
o	SPACE REQUIRED FOR TURBOCHARGER SHAFT
p	SPACE TRQUIRED FOR CHARGE AIR COOLER REMOVING

Gewicht trocken mit flacher Oelwanne
WEIGHT DRY WITH DRY SUMP

CATERPILLAR MOTOREN GmbH & Co. KG RESERVES THE RIGHT TO
MODIFY AND AMEND DATA AT ANY TIME. ANY LIABILITY FOR
ACCURACY OF INFORMATION PROVIDED IS EXCLUDED.
WE WILL SUPPLY FURTHER BINDING DATA IN CONNECTION WITH A CORRESPONDING ORDER.

ALL RIGHTS RESERVED. NO PART OF THIS PUBLICATION
MAY BE REPRODUCED OR COPIED IN ANY FORM,
WITHOUT PRIOR WRITTEN PERMISSION OF CATERPILLAR MOTOREN GmbH & Co. KG.

CATERPILLAR		Model: 9M25E_FWS 1.0 Zeichnung 9M25E_FWS 1.0	
Overhauchen Surfaces ISO 1802	Allgemeintoleranzen General Tolerances ISO 2768 - mK	Draining Control  W 882	Maximale Scale 1:20
		Gewicht / Weight 32.000 kg	
Benennung Name Motor - Einbauzeichnung ENGINE INSTALLATION DRAWING			
Änd.-Stand (Change level) -	Freigabe-Nr. Release No. -	UKZ Doc. Code -	Zeichnungs-Nr. Drawing No. 9M25E_FWS
			Blatt Sheet 1 von of 1