

# UCOM


## Utility Roller

CB14B, CB22, CB24, CB32, CC24,  
CB34, CB34 XW, CC34



### Versatile and Safe

- Foldable ROPS available
  - Provides operator safety
  - Lower transport height
  - Ability to work in low overhead situations
- Single lift point for easy transportability
- Operator Platform access from both sides of machine
- Double-drum and Combi options
- Best-in-class scraper ensures proper drum cleaning



Foldable ROPS Option

### Best-in-Class Comfort

- Platform fully isolated from drum vibration
- Exceptional leg room
- Simple controls
- Sliding seat option
- Suspension seat option
- Wrist rest

### Worry-free Water Spray System

- Up to 5 hours of operation from single fill
- Triple filtration prevents contamination
- Corrosion free water tanks
- Robust water pump provides optimal flow



CB24

Standard ROPS  
with Optional Canopy

Single Lifting Point




CC24

### Smooth Propel System


- Hydrostatic propel joystick
- Reliable Cat® engine
- Two-step speed regulating curve provides smooth operation and better control
- On-demand "traction control" available

Cat Pod-style  
Vibratory System



### Low Environmental Impact

- Bio-oil option
- 500 hour engine oil change - 50% less waste than competitive machines
- Standard ecology drains and hydraulic test ports protect environment from spilled fluids
- Long-life antifreeze



### Virtually Maintenance-free Vibratory System

- Exclusive Cat pod-style vibe system technology
- Maintenance and lubrication free for 3 years/3,000 hours
- Automatic vibration feature shuts off vibration when propel is in neutral



# Specifications

Model	Standard Weight	Drum Width	Static Linear Load	Power
CB14B w/900 mm (35")	1485 kg (3,274 lb)	900 mm (35")	8.3 kg/cm (47 lb/in)	16.8 kW 22.5 hp)
CB14B w/1000 mm (39")	1520 kg (3,351 lb)	1000 mm (39")	7.6 kg/cm (43 lb/in)	16.8 kW 22.5 hp)
CB22	2500 kg (5,512 lb)	1000 mm (39")	12.5 kg/cm (71 lb/in)	24.4 kW (33 hp)
CB24	2700 kg (5,952 lb)	1200 mm (47")	11.3 kg/cm (63 lb/in)	24.4 kW (33 hp)
CB24 XT	3230 kg (7,121 lb)	1200 mm (47")	13.5 kg/cm (79 lb/in)	24.4 kW (33 hp)
CC24	2400 kg (5,291 lb)	1200 mm (47")	10.6 kg/cm (60 lb/in)	24.4 kW (33 hp)
CB32	3230 kg (7,121 lb)	1300 mm (51")	13.0 kg/cm (73 lb/in)	24.4 kW (33 hp)
CB34	3940 kg (8,688 lb)	1300 mm (51")	15.8 kg/cm (89 lb/in)	34.1 kW (46 hp)
CB34 XW	4200 kg (9,259 lb)	1400 mm (55")	15.5 kg/cm (87 lb/in)	34.1 kW (46 hp)
CC34	3670 kg (8,091 lb)	1300 mm (51")	15.6 kg/cm (87 lb/in)	34.1 kW (46 hp)

## Utility Roller Application Guide

			0 - 1.8 Tons		1.8 - 3 Tons				3 - 5 Tons				
Material	Application	Layer Thickness mm (in)	CB14B 900 mm (35")	CB14B 1000 mm (39")	CB22 1000 mm (39")	CB24 1200 mm (47")	CB24 XT 1200 mm (47")	CC24 1200 mm (47")	CB32 1300 mm (51")	CB34 1300 mm (51")	CB34 XW 1400 mm (55")	CC34 1300 mm (51")	
Asphalt	Walking Paths, Driveways, Patchwork	25 - 50 (1 - 2)	Best	Best	Better	Better	Better	Better	Good	Good	Good	Good	
		50 - 100 (2 - 3)	Best	Best	Better	Better	Better	Better	Good	Good	Good	Good	
	Parking Lots, Urban Streets	25 - 50 (1 - 2)	Better	Best	Best	Best	Best	Best	Best	Best	Better	Better	Better
		50 - 100 (2 - 3)	Better	Better	Best	Best	Best	Best	Best	Best	Better	Better	Best
	Roads, Highways	25 - 50 (1 - 2)	Good	Good	Better	Better	Better	Better	Better	Best	Best	Best	Best
		50 - 100 (2 - 3)	Good	Good	Better	Better	Better	Better	Better	Better	Best	Best	Best
Soil	Landscaping	< 100 (4)	Best	Best	Better	Better	Better	Better	Good	Good	Good	Good	
	Small Job Sites	< 100 (4)	Best	Best	Better	Better	Better	Better	Good	Good	Good	Good	
	Medium Job Sites	< 100 (4)	Better	Better	Best	Best	Best	Best	Better	Better	Better	Better	

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

QEXQ1594-03 (2/13)  
© 2013 Caterpillar  
All Rights Reserved

