FOOT & LEG PROTECTION

Toolbox Talks are designed to promote safety discussions and best practices on the jobsite. To see more Toolbox Talks, please visit cat.com/toolboxtalks.

BE PREPARED

- Foot and leg protection should be worn whenever:
 - There is a possibility of foot or leg injuries from falling or rolling objects or from crushing or penetrating materials
 - The work involves exposure to hot or corrosive substances
 - Feet may be exposed to electrical hazards
 - Exposure to static electricity may call for conductive footwear
 - Working with sharp objects such as nails or spikes that could pierce the soles of ordinary shoes
 - Working with molten metal that might splash on feet or legs

TYPES OF FOOT AND LEG PROTECTION

- LEGGINGS Protect the lower legs and feet from heat hazards such as molten metal or welding sparks
- METATARSAL GUARDS Strap to the outside of shoes and protect the instep from impact and compression
- TOE GUARDS Fit over the toes of regular shoes to protect the toes from impact and compression hazards
- **COMBINATION FOOT AND SHIN GUARDS** Protect the lower legs and feet and may be used in combination with toe guards
- SAFETY SHOES Make use of impact-resistant toes and heat-resistant soles that
 protect the feet against hot work surfaces. Some also have metal insoles to protect
 against puncture wounds

The material in this document is provided for informational purposes only and not as a comprehensive or exhaustive resource on this topic. This material has been compiled from a multitude of sources believed to be accurate; however, Caterpillar Inc. assumes no responsibility for the accuracy or currency of this information and encourages you to consult experts in this area for more information. In no event does the content of this document supersede any applicable local, state or federal statutes or regulations.

There are a lot of moving parts on the jobsite. To find a safety topic relevant to your operation, please visit cat.com/toolboxtalks.



Discussion Date: _____

Employee Participants: