



Anmerkung / REMARKS	
b	SPACE REQUIRED FOR MEASURING TORSIONAL VIBRATIONS, AND/OR FOR REMOVAL OF THE VIBRATION DAMPER AND/OR LUBILO PUMP
e	SPACE REQUIRED FOR REMOVAL OF PISTON AND CYLINDER LINER REDUCED REMOVAL HEIGHT FOR CYLINDER LINER 2940mm
k	SPACE REQUIRED FOR TERMINAL SET
o	SPACE REQUIRED FOR TURBOCHARGER SHAFT
p	SPACE REQUIRED FOR CHARGE AIR COOLER REMOVING

Gewicht trocken mit flacher Oelwanne
WEIGHT DRY WITH DRY SUMP

CATERPILLAR		Model: 9M32E-CFWS 1.5 Zeichnung: 9M32E-CFWS 1.4	
Überflachten Surfaces	Allgemeininformanten General Inforances	Drawing Control	W 882
ISO 1302	ISO 2768 - mK	Massstab Scale	1:20
		Werkstoff Material	Gewicht (kg) Weight (kg)
			~52000

CATERPILLAR MOTOREN GmbH & Co. KG RESERVES THE RIGHT TO MODIFY AND AMEND DATA AT ANY TIME. ANY LIABILITY FOR ACCURACY OF INFORMATION PROVIDED IS EXCLUDED. WE WILL SUPPLY FURTHER BINDING DATA IN CONNECTION WITH A CORRESPONDING ORDER.

ALL RIGHTS RESERVED. NO PART OF THIS PUBLICATION
MAY BE REPRODUCED OR COPIED IN ANY FORM,
WITHOUT PRIOR WRITTEN PERMISSION OF CATERPILLAR MOTOREN GmbH & Co. KG.

Motor - Einbauzeichnung
ENGINE INSTALLATION DRAWING

Arnd-Stand Change Level	Freigabe-Nr. Release No.	UK2 Doc. Code	Zeichnungs-Nr. Drawing No.	Blatt Sheet	1
--			9M32E CFWS	von of	1