



Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

Image shown may not reflect actual configuration

## Specifications

Generator Set Specifications	
Rating	320 ekW (400 kVA)
Voltage	415 Volts
Frequency	50 Hz
Speed	1500 rpm

Generator Set Configurations	
Emissions/Fuel Strategy	Meets India CPCB/MoEF Standards

Engine Specifications		
Engine Model	C13 ATAAC, 1-6, 4-Stroke Water-Cooled Diesel	
Bore	130 mm	5.12 in
Displacement	12.5 L	762.8 in <sup>3</sup>
Stroke	157 mm	6.18 in
Compression Ratio	16.6:1	
Aspiration	Air-to-Air-Aftercooled	
Governor Type	ADEM™A4	
Fuel System	MEUI™	

Package Dimensions*		
Length	5500 mm	216.5 in
Width	1800 mm	70.9 in
Height	2275 mm	89.6 in
Weight†	5700 kg	12566 lb

\*Note: For reference only – do not use for installation design. Please contact your local dealer for exact weight and dimensions.

†Weight includes: Oversize generator, skid base, circuit breaker, oil, and coolant.

## **Benefits & Features**

### **Cat® Diesel Engine**

- Uses ACERT™ Technology
- Reliable, rugged, durable design
- Four-stroke cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic engine control

### **Generator**

- Matched to the performance and output characteristics of Cat engines
- Industry-leading mechanical and electrical design
- Industry-leading motor starting capabilities
- High efficiency

### **Cat Noise Enclosure**

- CPCB approved as per India regulations
- Noise Enclosure designed for easy access of all engine parts, and lube oil fumes disposal
- Lockable doors to ensure safety
- Non-igniting, self-extinguishing mineral wool 100 mm thick with resin bonded, used for noise and thermal insulation

### **Cat EMCP Control Panel**

The EMCP controller features the reliability and durability you have come to expect from your Cat equipment. EMCP 4 is a scalable control platform designed to ensure reliable generator set operation, providing extensive information about power output and engine operation. EMCP 4 systems can be further customized to meet your needs through programming and expansion modules.

### **Design Criteria**

- The generator set meets transient response and block loading steps as per ISO8528-5

### **Single-Source Supplier**

Fully prototype tested with certified torsional vibration analysis.

### **Worldwide Product Support**

Cat dealers provide extensive post-sale support including maintenance and repair agreements. Cat dealers have over 1,800 dealer branch stores operating in 200 countries. The Caterpillar S•O•S<sup>SM</sup> program cost-effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products.

## **Standard Equipment**

### **Air Inlet**

- Dual element cannister type air cleaner
- Service indicator

### **Cooling**

- Radiator fan and belt drive
- Fan and belt guard
- Coolant drain line with valve
- Coolant level sensor
- Cat extended life coolant

### **Exhaust**

- Dry exhaust manifold
- Flanged faced outlets
- Exhaust mufflers
- Stainless steel exhaust flex fittings

### **Fuel**

- Primary and secondary fuel filters
- Fuel priming pump
- Flexible fuel lines
- Engine fuel transfer pump
- Integrated fuel cooler
- Enclosure integrated fuel tank

### **Generator**

- Self excited
- Class H insulation
- Class H temperature rise
- Random Wound
- R450M voltage regulator
- Load Acceptance Module (LAM)
- Paralleling kit droop transformer
- Power terminal strip connections
- IP 23 protection

### **Governor**

- Electronic governor – ADEM™A4

## **Standard Equipment**

### **Control Panels**

- EMCP 4.1 Series generator set controller
- Speed adjust
- Emergency stop push button

### **Lube**

- Lubricating oil and filter
- Oil drain line with valves
- Fumes disposal
- Gear type lube oil pump
- Lube oil level indicator (dipstick)

### **Mounting**

- Anti-vibration mounts

### **Starting/Charging**

- 24 volt starting motor
- Batteries with rack and cables
- 45 amp charging alternator

### **General**

- SAE standard rotation
- Flywheel – SAE No.14
- Flywheel housing – SAE No.1
- Paint – Caterpillar Yellow except rails and radiators gloss black

## **Optional Equipment**

### **Control Panels**

- EMCP 4.2

### **Starting System**

- 2nos 12V 200 AH battery
- Disconnect switch

**C13 ACERT™  
320 ekW/ 400 kVA/ 50 Hz/ 1500 rpm/ 415V/ 0.8 Power Factor**

**Rating Type: PRIME**

**Emissions: Meets India CPCB/MoEF Standards**



**C13 ACERT™  
320 ekW/ 400 kVA  
50 Hz/ 1500 rpm/ 415V**

Image shown may not reflect actual configuration

<b>Package Performance</b>	
Generator Set Power Rating with Fan @ 0.8 Power Factor	320 ekW
Generator Set Power Rating	400 kVA

<b>Fuel Consumption</b>		
100% Load With Fan	86.7 L/hr	22.9 g/hr
75% Load With Fan	69.4 L/hr	18.3 g/hr
50% Load With Fan	50.3 L/hr	13.3 g/hr

<b>Cooling System<sup>1</sup></b>		
Engine Coolant Capacity	14.2 L	3.8 gal
Radiator Coolant Capacity	48.0 L	12.7 gal
Engine Coolant Capacity with Radiator/Exp Tank	62.2 L	16.4 gal
Air Flow (Max @ Rated Speed for Radiator Arrangement)	660 m <sup>3</sup> /min	23308 cfm

<b>Inlet Air</b>		
Combustion Air Inlet Flow Rate	25.5 m <sup>3</sup> /min	899.6 cfm

<b>Exhaust System</b>		
Exhaust Stack Gas Temperature	501.9°C	935.4°F
Exhaust Gas Flow Rate	69.7 m <sup>3</sup> /min	2460 cfm
Exhaust System Backpressure (maximum allowable)	10 kPa	40.1 in water

**C13 ACERT™  
320 ekW/ 400 kVA/ 50 Hz/ 1500 rpm/ 415V/ 0.8 Power Factor**

**Rating Type: PRIME**

**Emissions: Meets India CPCB/MoEF Standards**

<b>Heat Rejection</b>		
Heat Rejection to Coolant (total)	122 kW	6940 Btu/min
Heat Rejection to Exhaust (total)	300 kW	17044 Btu/min
Heat Rejection to Atmosphere from Engine	66.5 kW	3783 Btu/min
Heat Rejection to Atmosphere from Generator	23 kW	1308 Btu/min

<b>Alternator<sup>2</sup></b>		
Motor Starting Capability @ 30% Voltage Dip	960 skVA	
Frame	LC6124C	
Temperature Rise	125°C	225°F
Excitation	Self Excited	

<b>Lube System</b>		
Sump Refill with Filter	40 L	10.6 gal

<sup>1</sup> For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to the existing restriction from the factory.

<sup>2</sup> Generator temperature rise is based on a 40°C (104°F) ambient per NEMA MG1-32.

## DEFINITIONS AND CONDITIONS

### Applicable Codes and Standards:

ISO 3046, ISO 8528, IEC60034-1, IS4722

**Prime:** Output available with varying load for an unlimited time. Prime power in accordance with ISO 8528. 10% overload power in accordance with ISO 3046.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO 3046 standard conditions.

**Fuel Rates** are based on fuel oil of 35° API [16°C (60°F)] gravity having an LHV of 42 780 kJ/kg when used at 29°C and weighing 838.9 g/liter.

Additional ratings may be available for specific customer requirements, contact your Cat representative for details.

Performance No.: EMO552-01  
Feature Code: C13DE37  
Generator Arrangement: 4524234  
Date: 14/11/2016  
Source Country: India

LEHE0890-01

[www.Cat-ElectricPower.com](http://www.Cat-ElectricPower.com)

©2015 Caterpillar  
All rights reserved.

Materials and specifications are subject to change without notice.  
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, ADEM, ACERT, MEUI, S•O•S, "Caterpillar Yellow", the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.