



Cat[®] 336D2 L

Hydraulic Excavator

Performance

- Powerful, efficient Cat[®] C9 ACERT[™] engine
- Isochronous engine speed improves fuel efficiency by managing pump and engine speed
- Highly efficient pump delivers superior hydraulic power
- Maximum hydraulic horsepower delivered in high power mode
- Lower fuel consumption in Eco mode
- Boom and stick regeneration reduces fuel consumption
- Robust three stage fuel filtration system increases reliability

Versatility

- Multiple front linkage configurations available to meet all application needs
- Multiple auxiliary hydraulic options can support a large variety of work tools
- Cat buckets and GET are designed and matched to maximize machine performance
- Hydro-mechanical quick coupler options reduce tool change time

Safety

- Hydraulic activation lever safely locks out all hydraulic functions
- Anti-skid plating and countersunk bolts reduce slipping in severe conditions
- Full length firewall separates the pump compartment from the engine
- Ground level fuel cut off switch shuts down the engine in an emergency

Reliability/Durability

- Typically the largest and the most durable structures in the industry
- Modified X-frame structure provides long life and durability
- Robotically welded and stress relieved booms and sticks with internal baffle plates to maximize durability
- Grease Lubricated Tracks (GLT) provides longer life

Ease of Operation

- Ergonomically designed ROPS cab with easy to operate controls
- Multiple seat and joystick adjustment options enhance comfort
- Excellent work site visibility from the cab enhances productivity and safety
- Optimized low effort joystick controls reduce operator fatigue
- Automatic climate control system with 10 vents maximizes comfort

Serviceability

- Most service locations can be accessed at ground level
- Extended service intervals lower owning and operating costs
- Remote mounted filters reduce the time taken to service the machine
- Pressure taps and S-O-SSM ports help maximize uptime

Technology

- Cat Connect technology solutions increase production and minimize operating costs
- Link Technologies wirelessly connects you to your job site providing essential business information (VisionLink[®], Product Link[™])



Cat® 336D2 L Hydraulic Excavator

Engine

Engine Model	Cat C9 ACERT	
Engine Power (ISO 14396)	209 kW	281 hp
Net Power (SAE J1349/ISO 9249)	208 kW	279 hp
Bore	112 mm	4.41 in
Stroke	149 mm	5.87 in
Displacement	8.8 L	537 in ³
<ul style="list-style-type: none"> The Cat C9 ACERT meets U.S. EPA Tier 3, EU Stage IIIA equivalent and Brazil MAR-1 emission standards. 		

Hydraulic System

Main System – Maximum Flow (×2 pumps)	281 L/min	74 gal/min
Swing System – Maximum Flow	265 L/min	70 gal/min
Maximum Pressure – Equipment	35 000 kPa	5,076 psi
Maximum Pressure – Equipment (heavy lift on)	38 000 kPa	5,511 psi
Maximum Pressure – Travel	35 000 kPa	5,076 psi
Maximum Pressure – Swing	28 000 kPa	4,061 psi
Pilot System – Maximum Flow	40 L/min	10.6 gal/min
Pilot System – Maximum Pressure	4000 kPa	580 psi
Boom Cylinder – Bore	150 mm	5.9 in
Boom Cylinder – Stroke	1440 mm	56.7 in
Stick Cylinder – Bore	170 mm	6.7 in
Stick Cylinder – Stroke	1738 mm	68.4 in
Bucket Cylinder – Bore	150 mm	5.9 in
Bucket Cylinder – Stroke	1151 mm	45.3 in

Drive

Maximum Travel Speed	4.6 km/h	2.9 mph
Maximum Drawbar Pull	300 kN	67,375 lbf

Machine Weight

Operating Weight*	37 400 kg	82,500 lb
*Long undercarriage, 2.55 m (8'4") mass stick, 800 mm (31 in) shoes, 6.0 mt (6.6 t) counterweight.		

Swing

Swing Speed	8.3 rpm	
Swing Torque	109 kN·m	80,144 lbf·ft

Service Refill Capacities

Fuel Tank Capacity	620 L	164 gal
Cooling System	40 L	11 gal
Engine Oil	40 L	11 gal
Swing Drive	19 L	5 gal
Final Drive (each)	8 L	2 gal
Hydraulic System Oil Capacity (including tank)	410 L	108 gal
Hydraulic Tank Oil	175 L	46 gal

Dimensions

Boom	Mass Boom 6.18 m (20'3")	
Stick	M2.55 TB	8'4"
Shipping Height*	3600 mm	11'10"
Shipping Length	10 890 mm	35'9"
Tail Swing Radius	3490 mm	11'5"
Length to Center of Rollers	4040 mm	13'3"
Track Length	5020 mm	16'6"
Ground Clearance*	510 mm	1'8"
Ground Clearance**	480 mm	1'7"
Track Gauge	2590 mm	8'6"
Transport Width		
600 mm (24 in) Shoes	3190 mm	10'6"
700 mm (28 in) Shoes	3290 mm	10'10"
800 mm (32 in) Shoes	3390 mm	11'1"
Cab Height	3160 mm	10'4"
Counterweight Clearance**	1220 mm	4'0"
Bucket Type	TB1650HD	
Bucket Capacity	SAE 2.41 m ³ (3.15 yd ³)	
Bucket Tip Radius	1914 mm	6'3"
*Including shoe lug height.		
**Without shoe lug height.		



For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2017 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

AEXQ1980 (03-2017)
Build Number: 1000005423
(Brazil)

