



Cat[®] 120M/ 120M AWD Motor Grader

The Cat[®] 120M/120M AWD Motor Grader is designed to help you get more work done in less time. Unprecedented operator comfort and ease of service help to maximize your return on investment.

Performance

- Programmable Autoshift option simplifies operation by allowing transmission to be programmed to shift at optimal points to match application.
- Power Shift Countershaft Transmission matches to engine, maximizing power to the ground.
- Electronic Throttle Control helps improve productivity by providing best match of horsepower and torque for application demands.

Efficiency

- Aggressive blade angle, optimized moldboard curvature and large throat clearance allow material to roll more freely along blade, increasing efficiency.
- Hydraulic demand fan automatically adjusts speed according to cooling requirements resulting in more power to the ground and improved fuel efficiency.
- Engine idle shutdown is available to shut down engine after a set period of time saving fuel and helping reduce emissions.

Ease of Operation

- Selectable blade lift modes – Fine, Normal, or Coarse – allow you to choose the blade lift modulation mode that best fits your application or operating style.
- Joystick controls with electronically adjustable control pods reduce hand and arm movement by 78%, helping reduce operator fatigue.
- Left joystick controls steering, articulation, return-to-center, wheel lean, gear selection, left moldboard lift cylinder and float.
- Right joystick controls drawbar, circle and moldboard functions as well as electronic throttle control and manual differential lock/unlock.
- Articulation Return-to-Center automatically returns machine to a straight frame position from any angle with the touch of a button.

Safety

- Angled cab doors, tapered engine enclosure and sloped rear window increase visibility.
- Optional rear vision camera enhances sight to rear of machine.

Serviceability

- Convenient access from the top of the circle to the patented top-adjust wear strips and inserts make them easy to add or replace.
- Shimless Moldboard Retention System uses vertical and horizontal adjusting screws to keep moldboard wear strips aligned for reduced blade chatter and precise blade control.

Comfort

- Control pods can be adjusted electronically, making it easy to set to ideal operating position.
- Standard Cat Comfort Series suspension seat is fully adjustable.
- High capacity Heating, Ventilation, and Air Conditioning (HVAC) system dehumidifies and pressurizes cab, sealing out dust, and helps keep windows clear.

Technology

- Shuttle Shift allows smooth, fast direction shifts without requiring you to manipulate the throttle or inching pedal.
- Cat Product Link[™] aids your equipment management with remote monitoring capabilities.
- Optional Stable Blade improves grading precision by decreasing engine speed at 15 percent intervals when machine bounce is detected then increases engine rpm systematically when grader stabilizes.
- Optional Auto Articulation allows you to articulate automatically while steering in tight spaces or around curves, obstacles, and turnarounds.
- Optional Cat GRADE with Cross Slope helps maintain desired cross slope by automatically controlling one side of the blade.
- Optional Cat AccuGrade[™] uses positioning and guidance technologies, machine sensors, and automatic blade control to help get to grade faster, easier and more efficiently.
- Optional Cat Advanced Control Joysticks allow you to control automated grading solutions efficiently and safely without removing your hands from the joysticks.



Cat® 120M/120M AWD Motor Grader

Engine		
Engine Model	Cat C6.6 ACERT™	
Emissions	U.S. EPA Tier 3/EU Stage IIIA equivalent	
Base Power (1st gear) – Net	103 kW	138 hp
Base Power (1st gear) – Net (Metric)	140 hp	
VHP Plus Range – Net	103-136 kW	138-182 hp
VHP Plus Range – Net (Metric)	140-185 hp	
Displacement	6.6 L	403 in ³
Bore	105 mm	4.13 in
Stroke	127 mm	5.0 in
Torque Rise (VHP Plus)	40%	
Maximum Torque (VHP Plus-Net)	906 N·m	668 lbf·ft
Maximum Torque (AWD On)	963 N·m	710 lbf·ft
Speed @ Rated Power	2,000 rpm	
Number of Cylinders	6	
Derating Altitude	3505 m	11,500 ft
Standard Fan Speed – Maximum	1,150 rpm	
Standard Fan Speed – Minimum	600 rpm	
High Ambient Fan Speed – Maximum	1,650 rpm	
High Ambient Fan Speed – Minimum	600 rpm	
High Ambient Capability	50° C	122° F
<ul style="list-style-type: none"> • Maximum torque (VHP Plus) measured at 1,400 rpm. • Net power is tested per ISO 9249, SAE J1349, and EEC 80/1269 Standards in effect at the time of manufacture. • Net power advertised is the power available at rated speed of 2,000 rpm, measured at the flywheel when engine is equipped with fan running at minimum speed, air cleaner, muffler and alternator. • Power as declared per ISO 14396 Rated Speed = 2,000 rpm VHP Plus = 175 kW (234 hp) • No engine derating required up to 3048 m (10,000 ft). 		

Frame		
Circle – Diameter	1530 mm	60.2 in
Drawbar – Height	152 mm	6.0 in
Drawbar – Width	76.2 mm	3.0 in
Front Frame Structure – Height	280 mm	11.0 in
Front Frame Structure – Width	255 mm	10.0 in
Front Axle – Wheel Lean, Left/Right	18°	
Front Axle – Total Oscillation per Side	32°	

Weights			
Gross Vehicle Weight – Base			
Total	16 231 kg	35,783 lb	
Front Axle	4220 kg	9,303 lb	
Rear Axle	12 011 kg	26,479 lb	
Gross Vehicle Weight – Maximum			
Total	22 045 kg	48,601 lb	
Front Axle	6839 kg	15,077 lb	
Rear Axle	15 206 kg	33,523 lb	
Gross Vehicle Weight – Typically Equipped			
Total	18 400 kg	40,565 lb	
Front Axle	5090 kg	11,221 lb	
Rear Axle	13 310 kg	29,343 lb	

Moldboard		
Moldboard – Width	3.7 m	12 ft
Moldboard – Height	610 mm	24.0 in
Arc Radius	413 mm	16.3 in
Throat Clearance	134 mm	5.2 in

Blade Range		
Circle Centershift – Right	656 mm	25.8 in
Circle Centershift – Left	656 mm	25.8 in
Moldboard Sideshift – Right	660 mm	26.0 in
Moldboard Sideshift – Left	510 mm	20.1 in
Blade Tip Range – Forward	40°	
Blade Tip Range – Backward	5°	
Maximum Shoulder Reach Outside of Tires – Right	1905 mm	75.0 in
Maximum Shoulder Reach Outside of Tires – Left	1742 mm	68.6 in
Maximum Lift Above Ground	427 mm	16.8 in
Maximum Depth of Cut	720 mm	28.3 in

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2017 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

AEXQ1758-01 (05-2017)
Replaces AEXQ1758

