



# Cat<sup>®</sup> 962L

## Wheel Loader

**The 962L Wheel Loader applies proven technologies systematically and strategically to meet your high expectations for reliability, productivity, fuel efficiency, and long service life. Meets Brazil MAR-1 emission standards.**

### Reliability

- Cat<sup>®</sup> C7.1 engine offers a combination of proven electronic, fuel, and air systems.
- Utilizing rigorous component design and machine validation processes results in unmatched reliability, durability and high uptime.

### Durability

- Tough countershaft powershift transmission and axles handle extreme applications effectively.
- Improved hydraulic hose routing reduces potential hose wear.
- Full flow hydraulic filtration system with additional loop filtration improves hydraulic system robustness and component life.

### Productivity

- Engine power increased by approximately 10% improves machine performance and response (*compared to H Series*).
- Lock-up clutch torque converter, combined with lock-to-lock shifting, delivers smooth shifts, fast acceleration and speed on grade.
- High capacity torque converter results in greater digging efficiency.
- Z-bar linkage provides high breakout force at ground level.
- Optional high lift linkage offers increased hinge pin height to load more easily in a variety of applications.
- Easy-to-load Performance Series Buckets feature a wider mouth and curved side plates that improve material retention (fill factor) and decrease cycle times.
- Optional fully automatic traction control system (differential locks) improves performance in the pile and poor underfoot conditions.

### Fuel Efficiency

- Up to 10% lower fuel consumption than H Series.\*
- Power dense engine burns less fuel by providing power and torque when needed.
- Performance Series Buckets feature a longer floor that easily digs through the pile resulting in lower fuel consumption.
- Load sensing hydraulics result in proportional flow for implement and steering on demand.
- Standard productive Economy Mode provides maximum fuel savings with minimal productivity impact.

### Ease of Operation

- Best-in-class operator environment provides unmatched comfort, visibility, and efficiency.
- Intuitive, ergonomic controls keep operators focused on their work.
- Optional ride control system with dual accumulators provides excellent ride quality and lowers cab vibrations.

### Safety

- Excellent cab access with wide door and stair-like steps.
- Floor to ceiling windshield, large mirrors with integrated spot mirrors and rear vision camera provide industry leading all-around visibility.
- Robust, repositioned grab bars provide safe access to machine platforms.

### Serviceability

- One-piece tilting hood with side and rear doors; hydraulic and electrical service centers make access fast and easy.
- Convenient access to fuel fill, oil fill, filters and daily maintenance points means less servicing time required.
- Optional, fully integrated Cat Autolube system provides full lube system monitoring and diagnostic test visibility.

### Cat Technology

- Monitor, manage and enhance jobsite operations.
- Cat Link Technologies: VisionLink<sup>®</sup> enables owners to access data wirelessly to monitor machine health, utilization and location.
- Cat Detect Technologies: Integrated rear vision camera enhances visibility behind machine to help operators work safely. Optional Cat Rear Object Detection increases operator awareness of the working environment which enhances site safety.
- Cat Payload Technologies: Optional Cat Production Measurement 2.0 brings simple and accurate on-the-go payload scale allowing operators to deliver exact loads and work more efficiently. Advanced Productivity subscription provides comprehensive actionable information to help you manage and improve the productivity and profitability of your operations.

\*Actual results may vary based on factors such as, but not limited to, machine configuration, operator technique, machine application, climate, etc.



# Cat® 962L Wheel Loader

## Engine

Engine Model	Cat C7.1
Max Gross Power @ 2,000 rpm – ISO 14396:2002 (metric)	195 kW (265 hp)
Max Net Power @ 2,000 rpm – ISO 9249:2007 (metric)	185 kW (252 hp)
Peak Gross Torque (1,400 rpm) – ISO 14396:2002	1050 N·m
Maximum Net Torque (1,400 rpm)	984 N·m
Displacement	7.0 L

- Net power available at the flywheel when the engine is equipped with fan, air cleaner, muffler, and alternator with engine speed at 2,000 rpm.

## Weights

Operating Weight	19 123 kg
------------------	-----------

- Weight based on a machine configuration with Michelin 23.5R25 XHA2 L3 radial tires, full fluids, operator, standard counterweight, cold start, roading fenders, Product Link™, open/open axles (front/rear), power train guard, secondary steering, sound suppression and a 3.4 m³ general purpose bucket with BOCE.

## Bucket Capacities

Bucket Range	2.7-4.4 m³
--------------	------------

## Transmission

Forward 1	6.9 km/h
Forward 2	12 km/h
Forward 3	19.3 km/h
Forward 4	25.7 km/h
Forward 5	39.5 km/h
Reverse 1	6.9 km/h
Reverse 2	12 km/h
Reverse 3	25.7 km/h

- Maximum travel speed in standard vehicle with empty bucket and standard L3 tires with 787 mm roll radius.

## Sound

With Cooling Fan Speed at Maximum Value:

Operator Sound Pressure Level (ISO 6396:2008)	72 dB(A)
Exterior Sound Power Level (ISO 6395:2008)	107 dB(A)
Exterior Sound Pressure Level (SAE J88:2013)	75 dB(A)*

\*Distance of 15 m, moving forward in second gear ratio.

## Operating Specifications

Static Tipping Load – Full 40° Turn – with Tire Deflection	11 700 kg
Static Tipping Load – Full 40° Turn – No Tire Deflection	12 455 kg
Breakout Force	146 kN

- For a machine configuration as defined under “Weight.”
- Full compliance to ISO 14397-1:2007 Sections 1 thru 6, which requires 2% verification between calculations and testing.

## Service Refill Capacities

Fuel Tank	275 L
Cooling System	54 L
Crankcase	20 L
Transmission	43 L
Differentials and Final Drives – Front	43 L
Differentials and Final Drives – Rear	43 L
Hydraulic Tank	125 L

## Hydraulic System

Implement Pump Type	Variable Axial Piston
Implement System:	
Maximum Pump Output (2,150 rpm)	245 L/min
Maximum Operating Pressure	27 900 kPa
Hydraulic Cycle Time – Total	9.5 Seconds

## Dimensions

	Standard Lift	High Lift
Height to Top of Hood	2694 mm	2694 mm
Height to Top of Exhaust Pipe	3412 mm	3412 mm
Height to Top of ROPS	3443 mm	3443 mm
Ground Clearance	365 mm	365 mm
Center Line of Rear Axle to Edge of Counterweight	2147 mm	2186 mm
Center Line of Rear Axle to Hitch	1675 mm	1675 mm
Wheelbase	3350 mm	3350 mm
Overall Length (without bucket)	7129 mm	7543 mm
Hinge Pin Height at Carry Height	642 mm	762 mm
Hinge Pin Height at Maximum Lift	4182 mm	4487 mm
Lift Arm Clearance at Maximum Lift	3624 mm	3791 mm
Rack Back at Maximum Lift	60 degrees	66 degrees
Rack Back at Carry Height	49 degrees	54 degrees
Rack Back at Ground	40 degrees	45 degrees
Maximum Width over Tires (loaded)	2824 mm	2824 mm
Tread Width	2140 mm	2140 mm

- All dimensions are approximate and based on Michelin 23.5R25 XHA2 L3 radial tires.



For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

© 2020 Caterpillar  
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, Product Link, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

AEXQ2183-01  
Replaces AEXQ2183-00  
(Brazil)

